Form 3160-5 (August 2007)	UNITED STATES DEPARTMENT OF THE IN BUREAU OF LAND MANA	NTERIOR MAR	18 2013 •	ORM APPROVED DMB No. 1004-0137 xpires: July 31, 2010	
	BOREAU OF LAND MANY	Farmingt	on Field Office No.		
· •	UNDRY NOTICES AND REPOR	Bureau of L	and Managemen	NM-03560 Tribe Name	
Do not i	use this form for proposals to ed well. Use Form 3160-3 (API	drill or to re-enter an		RCVD MAR 21 '13 OIL CONS. DIV.	
	SUBMIT IN TRIPLICATE - Other instru	ctions on page 2.		ment, Name and/or No 51	
1. Type of Well	X Gas Well . Other		8. Well Name and No.	SAN JUAN 28-7 UNIT	
			Sar	1 Juan 28-7 Unit 98N	
2. Name of Operator ConocoPhillips Cor	mpany		9. API Well No.	30-039-30759	
3a. Address		. Phone No. (include area cod		10. Field and Pool or Exploratory Area	
PO Box 4289, Farmington, NM 87499 4. Location of Well (Footage, Sec., T.R.,M., or Survey Description)		(505) 326-9700		Blanco MV/Basin DK 11. Country or Parish, State	
Surface Unit F (SE	/NW), 2428' FNL & 2062' FWL, V/NW), 1735' FNL & 935' FWL, \$		W Rio Arrib		
12. CHEC	K THE APPROPRIATE BOX(ES) TO	O INDICATE NATURE O	F NOTICE, REPORT OR	OTHER DATA	
TYPE OF SUBMISSION	N	TYPE O	F ACTION		
Notice of Intent	Acidize	Deepen	Production (Start/Resume	Water Shut-Off	
X Subsequent Report	Alter Casing Casing Repair	Fracture Treat New Construction	Reclamation Recomplete	Well Integrity X Other Casing Sundry	
A Subsequent Report	Change Plans	Plug and Abandon	Temporarily Abandon		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal		
	ly for final inspection.) S 920. NU BOPE. <u>PT csg to 600</u>	<u>#/30min @</u> 09:45hrs o		pleted and the operator has	
03/08/13 MIRU AWS Tagged @ 195' & D0 <u>J-55</u> , LT&C csg set.(19sx(57cf-10bbls=3 Pumped Lead w/ 52 Bentonite, 0.4% SM3 Dropped plug & disp to <u>1500#/30min</u> @ 0 TD at 7672'. TD rea Pre-flushed w/ 10bbl celloflake, 0.3% CD- 0.3% CD-32, 6.25pp	ly for final inspection.) 5 920. NU BOPE. <u>PT csg to 600</u> 0 cmt to 234'. Drilled ahead to 4 @ <u>4976'.</u> Pre-flushed w/ 10bbls 3.02yld) Premium Lite w/ 3% Ca(4sx(1116cf-198bbls=2.13yld) P S. Pumped Tail w/ 115sx(159cf - blaced w/ 194bbls FW. Bumped 4:30hrs on 03/15/13. Test -OK ached on <u>03/16/13</u>. Circ. Hole & Is FW, 10bbls GW & 10bbls of F -32, 6.25pps LCM-1, & 1% FL-52	#/30min @ 09:45hrs o 988' - Inter TD reacher of FW, 10bbls GW & 1 Cl2, 0.25 pps celloflake remium Lite w/ 3% Car 28bls=1.38yld) Type I plug @ 20:17hrs on 3/ TIH w/ <u>6 1/4</u> " bit. Tagg RIH w/ 180 jts, <u>4 1/2"</u> W. Pumped scavenge 2. Tail w/ 200sx(396cf plug & displaced w/ 11	ng reclamation, have been com n 03/09/13. Test-OK. d 03/12/13. Circ. Hole 0bbls of FW. Pumped b, 5 pps LCM-1, 0.4% F Cl2, 0.25 pps celloflake II cmt w/ 1% CaCl2, 0.2 14/13. <u>Circ.</u> 70 bbls of ed cmt @ 4931'. Driller <u>11.6#, L-80</u> , LT&C cso r w/ 9sx(28cf-5bbls-3. -70bbls-1.98yId) Prem	Pleted and the operator has PU & TIH w/ <u>8 3/4"</u> bit. & RIH w/ 118jts, <u>7", 23#,</u> Scavenger w/ L-52, 8% Bentonite, 0.4% SMS. 9, 5 pps LCM-1, 0.4% FL-52, 8% 25 pps celloflake, & 0.2% FL-52. cmt to surface. WOC. <u>PT csg.</u> d out cmt & drilled ahead to g <u>set @ 7662'.</u> RU to cmt. 10yId) Premium lite HS FM, 0.25p	
03/08/13 MIRU AWS Tagged @ 195' & DO J-55, LT&C csg set.(19sx(57cf-10bbls=3 Pumped Lead w/ 52 Bentonite, 0.4% SMS Dropped plug & disp to <u>1500#/30min</u> @ O TD at 7672'. TD rea Pre-flushed w/ 10bbl celloflake, 0.3% CD- 0.3% CD-32, 6.25pp WOC. ND BOPE NU	ly for final inspection.) 5 920. NU BOPE. <u>PT csg to 600</u> O cmt to 234'. Drilled ahead to 4 @ 4976'. Pre-flushed w/ 10bbls 3.02yld) Premium Lite w/ 3% Cat 4sx(1116cf-198bbls=2.13yld) P S. Pumped Tail w/ 115sx(159cf- blaced w/ 194bbls FW. Bumped 4:30hrs on 03/15/13. Test -OK* ached on 03/16/13. Circ. Hole & Is FW, 10bbls GW & 10bbls of F -32, 6.25pps LCM-1, & 1% FL-52 Is LCM-1, & 1% FL-52. Dropped J WH RD <u>RR</u> @ 02:00hrs on 03/ 5.1 Completion Rig. Results	#/30min @ 09:45hrs o 988' - Inter TD reacher of FW, 10bbls GW & 1 Cl2, 0.25 pps celloflake remium Lite w/ 3% Car 28bls=1.38yld) Type I plug @ 20:17hrs on 3/ TIH w/ <u>6 1/4</u> " bit. Tagg RIH w/ 180 jts, <u>4 1/2"</u> W. Pumped scavenge 2. Tail w/ 200sx(396cf plug & displaced w/ 11 18/13. YV	ng reclamation, have been com of 03/09/13. Test-OK. <u>03/12/13.</u> Circ. Hole Obbls of FW. Pumped b, 5 pps LCM-1, 0.4% F Cl2, 0.25 pps celloflake II cmt w/ 1% CaCl2, 0.2 14/13. <u>Circ</u> . 70 bbls of t ed cmt @ 4931'. Drilled <u>11.6#, L-80, LT&C csc</u> r w/ 9sx(28cf-5bbls-3 . -70bbls-1.98yId) Pren 9bbls FW. Plug down	Pleted and the operator has PU & TIH w/ <u>8 3/4</u> " bit. & RIH w/ 118jts, <u>7", 23#,</u> Scavenger w/ L-52, 8% Bentonite, 0.4% SMS. e, 5 pps LCM-1, 0.4% FL-52, 8% 25 pps celloflake, & 0.2% FL-52. cmt to surface. WOC. <u>PT csg.</u> d out cmt & drilled ahead to g <u>set @ 7662'.</u> RU to cmt. 10yId) Premium lite HS FM, 0.25p nium lite HS FM, 0.25 pps cellofla	
03/08/13 MIRU AWS Tagged @ 195' & DO J-55, LT&C csg set.(19sx(57cf-10bbls=3 Pumped Lead w/ 52 Bentonite, 0.4% SMS Dropped plug & disp to <u>1500#/30min</u> @ O TD at 7672'. TD rea Pre-flushed w/ 10bbl celloflake, 0.3% CD- 0.3% CD-32, 6.25pp WOC. ND BOPE NU	ly for final inspection.) 5 920. NU BOPE. <u>PT csg to 600</u> O cmt to 234'. Drilled ahead to 4 @ 4976'. Pre-flushed w/ 10bbls 3.02yld) Premium Lite w/ 3% Cat 4sx(1116cf-198bbls=2.13yld) P S. Pumped Tail w/ 115sx(159cf- blaced w/ 194bbls FW. Bumped 4:30hrs on 03/15/13. Test -OK* ached on <u>03/16/13</u>. Circ. Hole & Is FW, 10bbls GW & 10bbls of F -32, 6.25pps LCM-1, & 1% FL-52 Is LCM-1, & 1% FL-52. Dropped J WH RD <u>RR</u> @ 02:00hrs on 03/	#/30min @ 09:45hrs o 988' - Inter TD reacher of FW, 10bbls GW & 1 Cl2, 0.25 pps celloflake remium Lite w/ 3% Car 28bls=1.38yld) Type I plug @ 20:17hrs on 3/ TIH w/ <u>6 1/4</u> " bit. Tagg RIH w/ 180 jts, <u>4 1/2"</u> W. Pumped scavenge 2. Tail w/ 200sx(396cf plug & displaced w/ 11 18/13. YV	ng reclamation, have been com of 03/09/13. Test-OK. <u>03/12/13.</u> Circ. Hole Obbls of FW. Pumped b, 5 pps LCM-1, 0.4% F Cl2, 0.25 pps celloflake II cmt w/ 1% CaCl2, 0.2 14/13. <u>Circ</u> . 70 bbls of t ed cmt @ 4931'. Drilled <u>11.6#, L-80, LT&C csc</u> r w/ 9sx(28cf-5bbls-3 . -70bbls-1.98yId) Pren 9bbls FW. Plug down	PU & TIH w/ <u>8 3/4</u> " bit. & RIH w/ 118jts, <u>7", 23#,</u> Scavenger w/ 5L-52, 8% Bentonite, 0.4% SMS. e, 5 pps LCM-1, 0.4% FL-52, 8% 25 pps celloflake, & 0.2% FL-52. cmt to surface. WOC. <u>PT csg.</u> d out cmt & drilled ahead to g <u>set @ 7662'</u> . RU to cmt. 10yId) Premium lite HS FM, 0.25p hium lite HS FM, 0.25 pps cellofla @ 19:38hrs on 3/17/13. RD Cmt.	
03/08/13 MIRU AWS Tagged @ 195' & DO J-55, LT&C csg set.(19sx(57cf-10bbls=3 Pumped Lead w/ 52 / Bentonite, 0.4% SM3 Dropped plug & disp to <u>1500#/30min</u> @ O <u>TD at 7672'. TD rea</u> Pre-flushed w/ 10bbl celloflake, 0.3% CD- 0.3% CD-32, 6.25pp WOC. ND BOPE NU PT will be conducte 14. Thereby certify that the foregoi	ly for final inspection.) S 920. NU BOPE. <u>PT csg to 600</u> O cmt to 234'. Drilled ahead to <u>4</u> @ <u>4976'.</u> Pre-flushed w/ 10bbls 3.02yld) Premium Lite w/ 3% Cat 4sx(1116cf-198bbls=2.13yld) P S. Pumped Tail w/ 11 5sx(159cf- blaced w/ 194bbls FW. Bumped H4:30hrs on 03/15/13. Test -OK ⁴ ached on 03/16/13. Circ. Hole & Is FW, 10bbls GW & 10bbls of F -32, 6.25pps LCM-1, & 1% FL-52 Is LCM-1, & 1% FL-52. Dropped J WH RD <u>RR</u> @ 02:00hrs on 03/ ed by Completion Rig. Results ing is true and correct. Name (<i>Printed/Typea</i>	#/30min @ 09:45hrs o 988' - Inter TD reacher of FW, 10bbls GW & 1 Cl2, 0.25 pps celloflake remium Lite w/ 3% Car 28bls=1.38yld) Type I plug @ 20:17hrs on 3/ TIH w/ 6 1/4" bit. Tagg a RIH w/ 180 jts, 4 1/2", W. Pumped scavenge 2. Tail w/ 200sx(396cf plug & displaced w/ 11 18/13. r s & TOC will appear of Title	ng reclamation, have been com n 03/09/13. Test-OK. d <u>03/12/13.</u> Circ. Hole 0bbls of FW. Pumped b, 5 pps LCM-1, 0.4% F Cl2, 0.25 pps celloflake Il cmt w/ 1% CaCl2, 0.2 14/13. <u>Circ</u> . 70 bbls of ed cmt @ 4931'. Drilled <u>11.6#, L-80</u> , LT&C csc r w/ 9sx(28cf-5bbls-3 . 70bbls-1.98yId) Pren 9bbls FW. Plug down in n next report.	PU & TIH w/ <u>8 3/4</u> " bit. & RIH w/ 118jts, <u>7", 23#,</u> Scavenger w/ 5L-52, 8% Bentonite, 0.4% SMS. e, 5 pps LCM-1, 0.4% FL-52, 8% 25 pps celloflake, & 0.2% FL-52. cmt to surface. WOC. <u>PT csg.</u> d out cmt & drilled ahead to g <u>set @ 7662'</u> . RU to cmt. 10yId) Premium lite HS FM, 0.25p hium lite HS FM, 0.25 pps cellofla @ 19:38hrs on 3/17/13. RD Cmt.	
03/08/13 MIRU AWS Tagged @ 195' & DO J-55, LT&C csg set.(19sx(57cf-10bbls=3 Pumped Lead w/ 52 Bentonite, 0.4% SM3 Dropped plug & disp to <u>1500#/30min</u> @ O <u>TD at 7672'. TD rea</u> Pre-flushed w/ 10bbl celloflake, 0.3% CD- 0.3% CD-32, 6.25pp WOC. ND BOPE NU PT will be conducte 14. Thereby certify that the foregoi	ly for final inspection.) S 920. NU BOPE. <u>PT csg to 600</u> O cmt to 234'. Drilled ahead to <u>4</u> @ <u>4976'</u> . Pre-flushed w/ 10bbls 3.02yld) Premium Lite w/ 3% Ca(4sx(1116cf-198bbls=2.13yld) P S. Pumped Tail w/ 115sx(159cf - blaced w/ 194bbls FW. Bumped 4:30hrs on 03/15/13. Test -OK ached on <u>03/16/13</u>. Circ. Hole & Is FW, 10bbls GW & 10bbls of F -32, 6.25pps LCM-1, & 1% FL-52 bs LCM-1, & 1% FL-52. Dropped J WH RD <u>RR</u> @ 02:00hrs on 03/ ed by Completion Rig. Results ing is true and correct. Name (<i>Printed/Typed</i> Arleen White	#/30min @ 09:45hrs o 988' - Inter TD reacher of FW, 10bbls GW & 1 Cl2, 0.25 pps celloflake remium Lite w/ 3% Car 28bls=1.38yld) Type I plug @ 20:17hrs on 3/ TIH w/ 6 1/4" bit. Tagg RIH w/ 180 jts, 4 1/2", W. Pumped scavenge 2. Tail w/ 200sx(396cf plug & displaced w/ 11 18/13. Y 5 & TOC will appear of Title	ng reclamation, have been com n 03/09/13. Test-OK. d <u>03/12/13.</u> Circ. Hole Obbls of FW. Pumped 5 pps LCM-1, 0.4% F Cl2, 0.25 pps celloflake II cmt w/ 1% CaCl2, 0.2 14/13. <u>Circ</u> . 70 bbls of ed cmt @ 4931'. Drilled 11.6#, L-80, LT&C csg r w/ 9sx(28cf-5bbls-3. -70bbls-1.98yId) Pren 9bbls FW. Plug down m next report. Staff Regula	PU & TIH w/ <u>8 3/4</u> " bit. & RIH w/ 118jts, <u>7", 23#,</u> Scavenger w/ 5L-52, 8% Bentonite, 0.4% SMS. e, 5 pps LCM-1, 0.4% FL-52, 8% 25 pps celloflake, & 0.2% FL-52. cmt to surface. WOC. <u>PT csg.</u> d out cmt & drilled ahead to g <u>set @ 7662'</u> . RU to cmt. 10yId) Premium lite HS FM, 0.25p hium lite HS FM, 0.25 pps cellofla @ 19:38hrs on 3/17/13. RD Cmt.	
03/08/13 MIRU AWS Tagged @ 195' & DO J-55, LT&C csg set.(19sx(57cf-10bbls=3 Pumped Lead w/ 52 Bentonite, 0.4% SM3 Dropped plug & disp to <u>1500#/30min</u> @ O <u>TD at 7672'. TD rea</u> Pre-flushed w/ 10bbl celloflake, 0.3% CD- 0.3% CD-32, 6.25pp WOC. ND BOPE NU PT will be conducte 14. Thereby certify that the foregoi	ly for final inspection.) S 920. NU BOPE. <u>PT csg to 600</u> O cmt to 234'. Drilled ahead to <u>4</u> @ <u>4976'</u> . Pre-flushed w/ 10bbls 3.02yld) Premium Lite w/ 3% Ca(4sx(1116cf-198bbls=2.13yld) P S. Pumped Tail w/ 115sx(159cf - blaced w/ 194bbls FW. Bumped 4:30hrs on 03/15/13. Test -OK ached on <u>03/16/13</u>. Circ. Hole & Is FW, 10bbls GW & 10bbls of F -32, 6.25pps LCM-1, & 1% FL-52 bs LCM-1, & 1% FL-52. Dropped J WH RD <u>RR</u> @ 02:00hrs on 03/ ed by Completion Rig. Results ing is true and correct. Name (<i>Printed/Typed</i> Arleen White	#/30min @ 09:45hrs o 988' - Inter TD reacher of FW, 10bbls GW & 1 Cl2, 0.25 pps celloflake remium Lite w/ 3% Car 28bls=1.38yld) Type I plug @ 20:17hrs on 3/ TIH w/ 6 1/4" bit. Tagg a RIH w/ 180 jts, 4 1/2", W. Pumped scavenge 2. Tail w/ 200sx(396cf plug & displaced w/ 11 18/13. ⊮√ 5 & TOC will appear of Title Date 3 [ng reclamation, have been com n 03/09/13. Test-OK. ^V d <u>03/12/13.</u> Circ. Hole Obbls of FW. Pumped b, 5 pps LCM-1, 0.4% F Cl2, 0.25 pps celloflake II cmt w/ 1% CaCl2, 0.2 14/13. <u>Circ</u> . 70 bbls of ed cmt @ 4931'. Drilled <u>11.6#, L-80, LT&C csc</u> r w/ 9sx(28cf-5bbls-3. 70bbls-1.98yId) Pren 9bbls FW. Plug down m next report. Staff Regula 8[13] E OFFICE USE	Pleted and the operator has PU & TIH w/ <u>8 3/4</u> " bit. & RIH w/ 118jts, <u>7", 23#,</u> Scavenger w/ 5L-52, 8% Bentonite, 0.4% SMS. 9, 5 pps LCM-1, 0.4% FL-52, 8% 25 pps celloflake, & 0.2% FL-52. Comt to surface. WOC. <u>PT csg.</u> d out cmt & drilled ahead to g <u>set @ 7662'</u> . RU to cmt. 10yld) Premium lite HS FM, 0.25 ps hium lite HS FM, 0.25 pps celloflat @ 19:38hrs on 3/17/13. RD Cmt. atory Tech	
O3/08/13 MIRU AWS Tagged @ 195' & DO J-55, LT&C csg set.(19sx(57cf-10bbls=3 Pumped Lead w/ 52 / Bentonite, 0.4% SMS Dropped plug & disp to <u>1500#/30min</u> @ O <u>TD at 7672'. TD rea</u> Pre-flushed w/ 10bbl celloflake, 0.3% CD- 0.3% CD-32, 6.25pp WOC. ND BOPE NU PT will be conducted 14. Thereby certify that the foregoi Signature Approved by Conditions of approval, if any, are a that the applicant holds legal or equ entile the applicant to conduct oper	All for final inspection.) S 920. NU BOPE. <u>PT csg to 600</u> O cmt to 234'. Drilled ahead to <u>4</u> @ <u>4976'</u> . Pre-flushed w/ 10bbls 3.02yld) Premium Lite w/ 3% Ca(4sx(1116cf-198bbls=2.13yld) P S. Pumped Tail w/ 115sx(159cf-) laced w/ 194bbls FW. Bumped 4:30hrs on 03/15/13. Test -OK ached on <u>03/16/13</u> . Circ. Hole & Is FW, 10bbls GW & 10bbls of F -32, 6.25pps LCM-1, & 1% FL-52 bs LCM-1, & 1% FL-52. Dropped J WH RD <u>RR</u> @ 02:00hrs on 03/ ed by Completion Rig. Results ing is true and correct. Name (<i>Printed/Typed</i> Arleen White THIS SPACE FOR attached. Approval of this notice does not w itable title to those rights in the subject lease rations thereon.	$\frac{#/30min}{2} @ 09:45hrs o 988' - Inter TD reacher of FW, 10bbls GW & 1 Cl2, 0.25 pps celloflake remium Lite w/ 3% Car 28bIs=1.38yId) Type I plug @ 20:17hrs on 3/ TIH w/ 6 1/4" bit. Tagg RIH w/ 180 jts, 4 1/2", W. Pumped scavenge 2. Tail w/ 200sx(396cf plug & displaced w/ 11 18/13. \neq5 & TOC will appear cFEDERAL OR STATE$	ng reclamation, have been com n 03/09/13. Test-OK. ^V d <u>03/12/13.</u> Circ. Hole Obbls of FW. Pumped b, 5 pps LCM-1, 0.4% F Cl2, 0.25 pps celloflake II cmt w/ 1% CaCl2, 0.2 14/13. <u>Circ</u> . 70 bbls of 0 ed cmt @ 4931'. Drilled <u>11.6#, L-80, LT&C csc</u> r w/ 9sx(28cf-5bbls-3. -70bbls-1.98yId) Pren 9bbls FW. Plug down of m next report. Staff Regula 8/13 E OFFICE USE	Pleted and the operator has PU & TIH w/ <u>8 3/4</u> " bit. & RIH w/ 118jts, <u>7", 23#,</u> Scavenger w/ 2L-52, 8% Bentonite, 0.4% SMS. a, 5 pps LCM-1, 0.4% FL-52, 8% 25 pps celloflake, & 0.2% FL-52. Cmt to <u>surface</u> . WOC. <u>PT csg.</u> d out cmt & drilled ahead to <u>a set @ 7662'</u> . RU to cmt. 10yId) Premium lite HS FM, 0.25p nium lite HS FM, 0.25 pps celloflat @ 19:38hrs on 3/17/13. RD Cmt. atory Tech	
O3/08/13 MIRU AWS Tagged @ 195' & DO J-55, LT&C csg set.(19sx(57cf-10bbls=3 Pumped Lead w/ 52 / Bentonite, 0.4% SM3 Dropped plug & disp to <u>1500#/30min</u> @ O <u>TD at 7672'.</u> TD rea Pre-flushed w/ 10bbl celloflake, 0.3% CD- 0.3% CD-32, 6.25pp WOC. ND BOPE NU PT will be conducte 14. Thereby certify that the foregoi Signature Approved by Conditions of approval, if any, are a that the applicant holds legal or equ entile the applicant to conduct oper Title 18 U.S.C. Section 1001 and T	All for final inspection.) S 920. NU BOPE. <u>PT csg to 600</u> O cmt to 234'. Drilled ahead to <u>4</u> @ <u>4976'</u> . Pre-flushed w/ 10bbls 3.02yld) Premium Lite w/ 3% Ca(4sx(1116cf-198bbls=2.13yld) P S. Pumped Tail w/ 115sx(159cf-) laced w/ 194bbls FW. Bumped 4:30hrs on 03/15/13. Test -OK ached on <u>03/16/13</u> . Circ. Hole & Is FW, 10bbls GW & 10bbls of F -32, 6.25pps LCM-1, & 1% FL-52 bs LCM-1, & 1% FL-52. Dropped J WH RD <u>RR</u> @ 02:00hrs on 03/ ed by Completion Rig. Results ing is true and correct. Name (<i>Printed/Typed</i> Arleen White THIS SPACE FOR attached. Approval of this notice does not we induct the subject lease	$\frac{\#/30min}{2} @ 09:45hrs o 988' - Inter TD reacher of FW, 10bbls GW & 1 Cl2, 0.25 pps celloflake remium Lite w/ 3% Car 28bIs=1.38yId) Type I plug @ 20:17hrs on 3/ TIH w/ 6 1/4" bit. Tagg RIH w/ 180 jts, 4 1/2", W. Pumped scavenge 2. Tail w/ 200sx(396cf plug & displaced w/ 11 18/13. FV 5 & TOC will appear c FEDERAL OR STATE $	ng reclamation, have been com n 03/09/13. Test-OK. ^V d <u>03/12/13.</u> Circ. Hole Obbls of FW. Pumped b, 5 pps LCM-1, 0.4% F Cl2, 0.25 pps celloflake II cmt w/ 1% CaCl2, 0.2 14/13. <u>Circ</u> . 70 bbls of 0 ed cmt @ 4931'. Drilled <u>11.6#, L-80, LT&C csc</u> r w/ 9sx(28cf-5bbls-3. -70bbls-1.98yId) Pren 9bbls FW. Plug down of m next report. Staff Regula 8/13 E OFFICE USE	PU & TIH w/ <u>8 3/4</u> " bit. & RIH w/ 118jts, <u>7", 23#,</u> Scavenger w/ 2L-52, 8% Bentonite, 0.4% SMS. a, 5 pps LCM-1, 0.4% FL-52, 8% 25 pps celloflake, & 0.2% FL-52. Cmt to <u>surface</u> . WOC. <u>PT csg.</u> d out cmt & drilled ahead to <u>9 set @ 7662'</u> . RU to cmt. 10yId) Premium lite HS FM, 0.25 pps cellofla @ 19:38hrs on 3/17/13. RD Cmt. atory Tech	