Form 3160-5 (August 2007)	UNITED STATES DEPARTMENT OF THE II	NTERIOR	182013	OMB N	I APPROVED No. 1004-0137	
	BUREAU OF LAND MANA	Farmington	n Field General	No.	: July 31, 2010	
		Bureau of Lar	nd Mahaqeme		6F-078503	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-en abandoned well. Use Form 3160-3 (APD) for such pro			n [6. If Indian, Al	6. If Indian, Allottee or Tribe Name RCUD MAR 21 '13 OIL CONS. DIV.		
	SUBMIT IN TRIPLICATE - Other instru	uctions on page 2.	7. If Unit of C		Name and/or No.	
1. Type of Well Oil Well	X Gas Well Other		8. Well Name		JUAN 29-7 UNIT	····-
			o. wen ivalle		an 29-7 Unit 99C	
2. Name of Operator Burlington Resources Oil & Gas Company LP			9. API Well No. 30-039-31154			
3a. Address		b. Phone No. (include area co	ode) 10. Field and P			
PO Box 4289, Farmington, NM 87499		(505) 326-9700		Blanco MV		
Surface Unit C (Sec., T.,R.,M., or Survey Description) NE/NW), 830' FNL & 1503' FWL, 5 SW/NW), 1470' FNL & 530' FWL, 5			Parish, State Arriba	, New Mexico	
/ 12. CH	ECK THE APPROPRIATE BOX(ES) T	O INDICATE NATURE	OF NOTICE, REPO	RT OR OTH	HER DATA	
TYPE OF SUBMISSI	ON	TYPE	OF ACTION			
Notice of Intent	Acidize	Deepen	Production (Start	/Resume)	Water Shut-Off	
	Alter Casing	Fracture Treat	Reclamation		Well Integrity	Cundar
X Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete	ndon	X Other Casing	Sunary
Final Abandonment Not		Plug Back	Water Disposal	·		
Attach the bond under whit following completion of the Testing has been completed determined that the site is r 03/06/13 MIRU AV	n directionally or recomplete horizontally, give s ch the work will be performed or provide the Bo e involved operations. If the operation results in d. Final Abandonment Notices must be filed on ready for final inspection.) WS 711. NU BOPE. <u>PT csg to 600</u>	subsurface locations and meas ond No. on file with BLM/BL/ n a multiple completion or rec ly after all requirements, inclu D#/30min_@ 19:15hrs	ured and true vertical dep A. Required subsequent r completion in a new interv iding reclamation, have b on 03/07/13. Test	oths of all pertin reports must be al, a Form 316 een completed	nent markers and zones. e filed within 30 days 50-4 must be filed once I and the operator has & TIH w/ <u>8 3/4"</u> bit.	4
If the proposal is to deepen Attach the bond under white following completion of the Testing has been completed determined that the site is r 03/06/13 MIRU AV Tagged @ 192' & <u>J-55</u> , LT&C csg se 19sx(57cf-10bbls Pumped Lead w/ Bentonite, 0.4% S Dropped plug & d to 1500#/30min @ <u>TD at 6015'</u> . TD a Pre-flushed w/ 10 0.3% CD-32, 6.25pps L	a directionally or recomplete horizontally, give s ch the work will be performed or provide the Bo e involved operations. If the operation results in d. Final Abandonment Notices must be filed on ready for final inspection.)	subsurface locations and meas ond No. on file with BLM/BL/ n a multiple completion or rec aly after all requirements, inclu <u>0#/30min</u> @ 19:15hrs <u>4232' - Inter TD</u> read s of FW, 10bbls GW & CI, 0.25 pps celloflake remium Lite w/ 3% Ca 24bls=1.38yId) Type I plug @ 14:30hrs on 3 TIH w/ 6 1/4" bit. Tag & RIH w/ 142 jts, <u>4 1/2</u> scavenger w/ 9sx(280 136sx(269cf-48bbls-1 & displaced w/ 93bbls	A. Required subsequent r completion in a new interv ding reclamation, have b con 03/07/13. Test thed 03/11/13. Cir a 10bbls of FW. Pr b, 5 pps LCM-1, 0. Cl, 0.25 pps celloff II cmt w/ 1% CaCl 3/12/13. <u>Circ.</u> 50 bl ged cmt @ 4174'. ", 11.6#, L-80, LT4 (f-5bbls-3.10yld) f 1.98yld) Premium	this of all pertin reports must be al, a Form 316 een completed t-OK. PU & tro. Hole & umped Sca 4% FL-52, lake, 5 pps 0.25 pps bils of cm <u>t t</u> 0.25 pps Drilled out &C csg <u>set</u> Premium lit lite HS FM	nent markers and zones. e filed within 30 days 50-4 must be filed once and the operator has & TIH w/ <u>8 3/4</u> " bit. RIH w/ 99jts, <u>7", 23</u> ; avenger w/ 8% Bentonite, 0.4% 5 LCM-1, 0.4% FL-5; celloflake, & 0.2% F to surface. WOC. <u>P</u> t cmt & drilled ahead t @ 6012'. RU to cm te HS FM, 0.25pps celloflake	6 SMS. 2, 8% 7L-52. 7 csq 1 to t. cellofla e, 0.3%
If the proposal is to deepen Attach the bond under whit following completion of the Testing has been completed determined that the site is r 03/06/13 MIRU AV Tagged @ 192' & J-55, LT&C csg se 19sx(57cf-10bbls Pumped Lead w/ Bentonite, 0.4% S Dropped plug & d to 1500#/30min @ TD at 6015' . TD f Pre-flushed w/ 10 0.3% CD-32, 6.25 CD-32, 6.25pps L ND BOPE NU WH	a directionally or recomplete horizontally, give s ch the work will be performed or provide the Bo e involved operations. If the operation results in d. Final Abandonment Notices must be filed on ready for final inspection.) WS 711. NU BOPE. <u>PT csg to 600</u> DO cmt to 235'. Drilled ahead to <u>at @ 4220'</u> . Pre-flushed w/ 10bbls 5=3.02yld) Premium Lite w/ 3% Car 439sx(935cf-166bbls=2.13yld) Pre SMS. Pumped Tail w/ 99sx(137cf-2 isplaced w/ 165bbls FW. Bumped 2 22:30hrs on 03/12/13. Test -OK* reached on 03/14/13. Circ. Hole & bbls GW & 2bbls of FW. Pumped s 5pps LCM-1, & 1% FL-52. Tail w/ 1 .CM-1, & 1% FL-52. Dropped plug of the RD <u>RR</u> @ 00:30hrs on 0 <u>3/15/13</u> .	subsurface locations and meas ond No. on file with BLM/BL/ n a multiple completion or rec aly after all requirements, inclu 0#/30min @ 19:15hrs 4232' - Inter TD read s of FW, 10bbls GW 8 (CI, 0.25 pps celloflake emium Lite w/ 3% Ca 24bls=1.38yld) Type I plug @ 14:30hrs on 3 TIH w/ 6 1/4" bit. Tag & RIH w/ 142 jts, <u>4 1/2</u> scavenger w/ 9sx(28c 136sx(269cf-48bbls-1 & displaced w/ 93bbls 1 a b b b b b b c b c c c c c c c c c c	ured and true vertical dep A. Required subsequent r completion in a new interv iding reclamation, have b con 03/07/13. Test ined 03/11/13. Ciri ined 03/11/13. Ciri i 10bbls of FW. Pi is, 5 pps LCM-1, 0 Cl, 0.25 pps celloff II cmt w/ 1% CaCl 3/12/13. <u>Circ.</u> 50 bl iged cmt @ 4174'. <u>", 11.6#, L-80</u> , LT4 if. 5bbls-3.10yld) f 1.98yld) Premium is FW. Plug down @	this of all pertin reports must be al, a Form 316 een completed t-OK. PU & tro. Hole & umped Sca 4% FL-52, lake, 5 pps 0.25 pps bils of cm <u>t t</u> 0.25 pps Drilled out &C csg <u>set</u> Premium lit lite HS FM	nent markers and zones. e filed within 30 days 50-4 must be filed once and the operator has & TIH w/ <u>8 3/4</u> " bit. RIH w/ 99jts, <u>7", 23</u> ; avenger w/ 8% Bentonite, 0.4% 5 LCM-1, 0.4% FL-5; celloflake, & 0.2% F to surface. WOC. <u>P</u> t cmt & drilled ahead t @ 6012'. RU to cm te HS FM, 0.25pps celloflake	6 SMS. 2, 8% 7L-52. 7 csq 1 to t. cellofla e, 0.3%
If the proposal is to deepen Attach the bond under whit following completion of the Testing has been completed determined that the site is r 03/06/13 MIRU AV Tagged @ 192' & J-55, LT&C csg sc 19sx(57cf-10bbls Pumped Lead w/ Bentonite, 0.4% S Dropped plug & d to 1500#/30min @ TD at 6015'. TD Pre-flushed w/ 10 0.3% CD-32, 6.25 CD-32, 6.25ps L ND BOPE NU WH PT will be condu	a directionally or recomplete horizontally, give s ch the work will be performed or provide the Bo e involved operations. If the operation results in d. Final Abandonment Notices must be filed on ready for final inspection.) WS 711. NU BOPE. <u>PT csg to 600</u> DO cmt to 235'. Drilled ahead to <u>at @ 4220'</u> . Pre-flushed w/ 10bbls s=3.02yld) Premium Lite w/ 3% Cat 439sx(935cf-166bbls=2.13yld) Pro- SMS. Pumped Tail w/ 99sx(137cf-2 isplaced w/ 165bbls FW. Bumped 22:30hrs on 03/12/13. Test -OK* reached on 03/14/13. Circ. Hole & bbls GW & 2bbls of FW. Pumped s 50ps LCM-1, & 1% FL-52. Tail w/ 1 .CM-1, & 1% FL-52. Tail w/ 1 .CM-1, & 1% FL-52. Topped plug at t RD <u>RR</u> @ 00:30hrs on 03/15/13.	subsurface locations and meas ond No. on file with BLM/BL/ n a multiple completion or rec aly after all requirements, inclu 0#/30min @ 19:15hrs 4232' - Inter TD read s of FW, 10bbls GW 8 (CI, 0.25 pps celloflake emium Lite w/ 3% Ca 24bls=1.38yld) Type I plug @ 14:30hrs on 3 TIH w/ 6 1/4" bit. Tag & RIH w/ 142 jts, <u>4 1/2</u> scavenger w/ 9sx(28c 136sx(269cf-48bbls-1 & displaced w/ 93bbls 1 a b b b b b b c b c c c c c c c c c c	A. Required subsequent r completion in a new interv ding reclamation, have b con 03/07/13. Test thed 03/11/13. Ciric thed 03/11/13. Ciric thed 03/11/13. Ciric the 03/11/13. Ciric the 03/12/13. Ciric the 03/12/13. Ciric the 03/12/13. Ciric the 04/14 CaCl the 04/	this of all pertin reports must be al, a Form 316 een completed t-OK. PU & tro. Hole & umped Sca 4% FL-52, lake, 5 pps 0.25 pps bils of cm <u>t t</u> 0.25 pps Drilled out &C csg <u>set</u> Premium lit lite HS FM	nent markers and zones. a filed within 30 days 50-4 must be filed once and the operator has & TIH w/ <u>8 3/4</u> " bit. RIH w/ 99jts, <u>7", 23</u> ; avenger w/ 8% Bentonite, 0.4% a LCM-1, 0.4% FL-5; celloflake, & 0.2% F to surface. WOC. <u>P</u> t cmt & drilled ahead t @ 6012'. RU to cm te HS FM, 0.25pps of A, 0.25 pps celloflake s on 3/14/13 RD C	6 SMS 2, 8% 7L-52. 7 csq 1 to t. cellofla e, 0.3%
If the proposal is to deepen Attach the bond under whit following completion of the Testing has been completed determined that the site is r 03/06/13 MIRU AV Tagged @ 192' & J-55, LT&C csg sc 19sx(57cf-10bbls Pumped Lead w/ Bentonite, 0.4% S Dropped plug & d to 1500#/30min @ TD at 6015'. TD Pre-flushed w/ 10 0.3% CD-32, 6.25 CD-32, 6.25ps L ND BOPE NU WH PT will be condu	a directionally or recomplete horizontally, give s ch the work will be performed or provide the Bo e involved operations. If the operation results in d. Final Abandonment Notices must be filed on ready for final inspection.) WS 711. NU BOPE. <u>PT csg to 600</u> DO cmt to 235'. Drilled ahead to et @ 4220'. Pre-flushed w/ 10bbls s=3.02yld) Premium Lite w/ 3% Cai 439sx(935cf-166bbls=2.13yld) Pre SMS. Pumped Tail w/ 99sx(137cf-2 isplaced w/ 165bbls FW. Bumped 22:30hrs on 03/12/13. Test -OK* reached on 03/14/13. Circ. Hole & bbls GW & 2bbls of FW. Pumped s 5pps LCM-1, & 1% FL-52. Tail w/ 1 .CM-1, & 1% FL-52. Dropped plug of t RD <u>RR</u> @ 00:30hrs on 0 <u>3/15/13</u> . Incted by Completion Rig. Results egoing is true and correct. Name (<i>Printed/Types</i> Arleen White	subsurface locations and meas ond No. on file with BLM/BL/ n a multiple completion or rec ily after all requirements, inclu D#/30min @ 19:15hrs 4232' - Inter TD read s of FW, 10bbls GW & CI, 0.25 pps celloflake remium Lite w/ 3% Ca 24bls=1.38yld) Type I plug @ 14:30hrs on 3 TIH w/ 6 1/4" bit. Tag & RIH w/ 142 jts, <u>4 1/2</u> scavenger w/ 9sx(28o 136sx(269cf-48bbls-1 & displaced w/ 93bbls 136s XC69cf-48bbls-1 & displaced w/ 93bbls 136s XC69cf-48bbls-1 & title <u>136s XC69cf-48bbls-1</u>	ured and true vertical dep A. Required subsequent r completion in a new interv iding reclamation, have b on 03/07/13. Test ched 03/11/13. Ciri- ched	this of all pertin reports must be al, a Form 316 een completed t-OK. PU & tro. Hole & umped Sca 4% FL-52, lake, 5 pps 0.25 pps bis of cm <u>t t</u> 0.25 pps bis of cm <u>t t</u> 2 remium lit lite HS FM 18:08 hrs	nent markers and zones. a filed within 30 days 50-4 must be filed once and the operator has & TIH w/ <u>8 3/4</u> " bit. RIH w/ 99jts, <u>7", 23</u> ; avenger w/ 8% Bentonite, 0.4% a LCM-1, 0.4% FL-5; celloflake, & 0.2% F to surface. WOC. <u>P</u> t cmt & drilled ahead t @ 6012'. RU to cm te HS FM, 0.25pps of A, 0.25 pps celloflake s on 3/14/13 RD C	6 SMS. 2, 8% 7L-52. 7 <u>csq</u> 1 to t. cellofla e, 0.3%
If the proposal is to deepen Attach the bond under whit following completion of the Testing has been completed determined that the site is r 03/06/13 MIRU AV Tagged @ 192' & J-55, LT&C csg se 19sx(57cf-10bbls Pumped Lead w/ Bentonite, 0.4% S Dropped plug & d to 1500#/30min @ TD at 6015' . TD a Pre-flushed w/ 10 0.3% CD-32, 6.25 CD-32, 6.25pps L ND BOPE NU WH PT will be condu 14. 1 hereby certify that the fore Signature	a directionally or recomplete horizontally, give s ch the work will be performed or provide the Bo e involved operations. If the operation results in d. Final Abandonment Notices must be filed on ready for final inspection.) WS 711. NU BOPE. <u>PT csg to 600</u> DO cmt to 235'. Drilled ahead to et @ 4220'. Pre-flushed w/ 10bbls s=3.02yld) Premium Lite w/ 3% Cai 439sx(935cf-166bbls=2.13yld) Pre SMS. Pumped Tail w/ 99sx(137cf-2 isplaced w/ 165bbls FW. Bumped 22:30hrs on 03/12/13. Test -OK* reached on 03/14/13. Circ. Hole & bbls GW & 2bbls of FW. Pumped s 5pps LCM-1, & 1% FL-52. Tail w/ 1 .CM-1, & 1% FL-52. Dropped plug of t RD <u>RR</u> @ 00:30hrs on 0 <u>3/15/13</u> . Incted by Completion Rig. Results egoing is true and correct. Name (<i>Printed/Types</i> Arleen White	subsurface locations and meas ond No. on file with BLM/BL/ n a multiple completion or rec ally after all requirements, inclu $\frac{0\#/30min}{24232} - Inter TD readss of FW, 10bbls GW &CI, 0.25 pps celloflakeremium Lite w/ 3% Ca24bls=1.38yld) Type Iplug @ 14:30hrs on 3TIH w/ 6 1/4" bit. Tag& RIH w/ 142 jts, 4 1/2scavenger w/ 9sx(280136sx(269cf-48bbls-1& displaced w/ 93bbls1*** & TOC will appear$	ured and true vertical dep A. Required subsequent r completion in a new interv iding reclamation, have b on 03/07/13. Test ched 03/11/13. Ciri- ched	this of all pertin reports must be al, a Form 316 een completed t-OK. PU & tro. Hole & umped Sca 4% FL-52, lake, 5 pps 0.25 pps bis of cm <u>t t</u> 0.25 pps bis of cm <u>t t</u> 2 remium lit lite HS FM 18:08 hrs	nent markers and zones. a filed within 30 days 50-4 must be filed once and the operator has & TIH w/ <u>8 3/4</u> " bit. RIH w/ 99jts, <u>7", 23</u> ; avenger w/ 8% Bentonite, 0.4% a LCM-1, 0.4% FL-5; celloflake, & 0.2% F to surface. WOC. <u>P</u> t cmt & drilled ahead t @ 6012'. RU to cm te HS FM, 0.25pps of A, 0.25 pps celloflake s on 3/14/13 RD C	6 SMS. 2, 8% 7L-52. 7 <u>csq</u> 1 to t. celloflal e, 0.3%
If the proposal is to deepen Attach the bond under whit following completion of the Testing has been completed determined that the site is r 03/06/13 MIRU AV Tagged @ 192' & J-55, LT&C csg sc 19sx(57cf-10bbls Pumped Lead w/ Bentonite, 0.4% S Dropped plug & d to 1500#/30min @ TD at 6015'. TD Pre-flushed w/ 10 0.3% CD-32, 6.25 CD-32, 6.25ps L ND BOPE NU WH PT will be condu	a directionally or recomplete horizontally, give s ch the work will be performed or provide the Bo e involved operations. If the operation results in d. Final Abandonment Notices must be filed on ready for final inspection.) WS 711. NU BOPE. <u>PT csg to 600</u> DO cmt to 235'. Drilled ahead to et @ 4220'. Pre-flushed w/ 10bbls s=3.02yld) Premium Lite w/ 3% Cai 439sx(935cf-166bbls=2.13yld) Pre SMS. Pumped Tail w/ 99sx(137cf-2 isplaced w/ 165bbls FW. Bumped 22:30hrs on 03/12/13. Test -OK* reached on 03/14/13. Circ. Hole & bbls GW & 2bbls of FW. Pumped s 5pps LCM-1, & 1% FL-52. Tail w/ 1 .CM-1, & 1% FL-52. Dropped plug of t RD <u>RR</u> @ 00:30hrs on 0 <u>3/15/13</u> . Incted by Completion Rig. Results egoing is true and correct. Name (<i>Printed/Types</i> Arleen White	subsurface locations and meas ond No. on file with BLM/BL/ n a multiple completion or rec ally after all requirements, inclu <u>0#/30min</u> @ 19:15hrs <u>4232' - Inter TD</u> read s of FW, 10bbls GW & CI, 0.25 pps celloflake remium Lite w/ 3% Ca 24bls=1.38yId) Type I plug @ 14:30hrs on 3 TIH w/ 6_1/4" bit. Tag & RIH w/ 142 jts, 4_1/2 scavenger w/ 9sx(280 136sx(269cf-48bbls-1 & displaced w/ 93bbls 14 res & TOC will appear ad Title <u>Date</u> 3 [1]	ared and true vertical dep A. Required subsequent r completion in a new interv iding reclamation, have b on 03/07/13. Test ined 03/11/13. Cir a 10bbls of FW. Pr b, 5 pps LCM-1, 0. CI, 0.25 pps celloff II cmt w/ 1% CaCI 3/12/13. <u>Circ.</u> 50 bl iged cmt @ 4174'. ". <u>11.6#, L-80</u> , LT2 if-5bbls-3.10yld) f I.98yld) Premium a FW. Plug down @ on next report. Staff F 8 3 TE OFFICE USE	this of all pertin reports must be al, a Form 316 een completed t-OK. PU & tro. Hole & umped Sca 4% FL-52, lake, 5 pps 0.25 pps bis of cm <u>t t</u> 0.25 pps bis of cm <u>t t</u> 2 remium lit lite HS FM 18:08 hrs	nent markers and zones. e filed within 30 days 50-4 must be filed once and the operator has & TIH w/ <u>8 3/4</u> " bit. RIH w/ 99jts, <u>7", 23</u> ; avenger w/ 8% Bentonite, 0.4% 5 LCM-1, 0.4% FL-5; celloflake, & 0.2% F to surface. WOC. <u>P</u> t cmt & drilled ahead t @ 6012'. RU to cm te HS FM, 0.25pps of A, 0.25 pps celloflake s on 3/14/13 RD C y Tech	6 SMS. 2, 8% 7L-52. 7 <u>csq</u> 1 to t. celloflal e, 0.3%
If the proposal is to deepen Attach the bond under whit following completion of the Testing has been completed determined that the site is r 03/06/13 MIRU AV Tagged @ 192' & J-55, LT&C csg sc 19sx(57cf-10bbls Pumped Lead w/ Bentonite, 0.4% S Dropped plug & d to 1500#/30min @ TD at 6015'. TD a Pre-flushed w/ 10 0.3% CD-32, 6.25 CD-32, 6.25pps L ND BOPE NU WH PT will be condu 14. I hereby certify that the ford Signature Approved by Conditions of approval, if any, a	a directionally or recomplete horizontally, give s ch the work will be performed or provide the Bo e involved operations. If the operation results in d. Final Abandonment Notices must be filed on ready for final inspection.) WS 711. NU BOPE. <u>PT csg to 600</u> DO cmt to 235'. Drilled ahead to <u>at @ 4220'</u> . Pre-flushed w/ 10bbls s=3.02yld) Premium Lite w/ 3% Cau 439sx(935cf-166bbls=2.13yld) Pre SMS. Pumped Tail w/ 99sx(137cf-2 isplaced w/ 165bbls FW. Bumped 22:30hrs on 03/12/13. Test -OK* reached on 03/14/13. Circ. Hole & bbls GW & 2bbls of FW. Pumped s ispps LCM-1, & 1% FL-52. Tail w/ 1 CM-1, & 1% FL-52. Tail w/ 1 CM-1, & 1% FL-52. Dropped plug d RD <u>RR</u> @ 00:30hrs on 03/15/13. Inted by Completion Rig. Results are attached. Approval of this notice does not w cquitable title to those rights in the subject lease	subsurface locations and meas ond No. on file with BLM/BL/ n a multiple completion or rec ally after all requirements, inclu	ured and true vertical dep A. Required subsequent r completion in a new interv iding reclamation, have b on 03/07/13. Test ched 03/11/13. Ciri- ched	ACCENT	nent markers and zones. a filed within 30 days 50-4 must be filed once and the operator has & TIH w/ <u>8 3/4</u> " bit. RIH w/ 99jts, <u>7", 23</u> ; avenger w/ 8% Bentonite, 0.4% a LCM-1, 0.4% FL-5; celloflake, & 0.2% F to surface. WOC. <u>P</u> t cmt & drilled ahead t @ 6012'. RU to cm te HS FM, 0.25pps of A, 0.25 pps celloflake s on 3/14/13 RD C	6 SMS. 2, 8% 1-52. <u>T csq</u> 1 to t. celloflak e, 0.3% mt. W0

RECEIVEN

MMUCUA

Milliam Tambekon

/