Form 3160-5 (August 2007)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB No. 1004-0137 RECLIW S. Ledase Serial No. NMNM 89021 Expires: July 31, 2010

abandoned well. Use Form 3160-3 (APD) for such proposals.					6, If Indian, Allottee or Tribe Name IN/A RCVD MAR 28 '13		
SUBMIT IN TRIPLICATE – Other instructions on page 2 Land Mar					THE TAIL OF CA/Agre	ement,	Name and/or No. L CONS. DIU
1. Type of Well  ☑ Oil Well ☐ Gas Well ☐ Other					8. Well Name and No. Lybrook H32-2306 01H DYST. 3		
2. Name of Operator Encana Oil & Gas (USA) Inc.					9. API Well No. 30-043-21126		
3a. Address       3b. Phone No. (include area code)         370 17th Street, Suite 1700       720-876-3941					10. Field and Pool or Exploratory Area Lybrook Gallup		
4. Location of Well <i>(Footage, Sec., T.,R.,M., or Survey Description)</i> SHL: 1785' FNL and 250' FEL Sec 32, Township 23N, Range 6W BHL: 1785' FNL and 2285' FEL Sec 31, Township 23N, Range 6W					11. Country or Parish, State Sandoval, NM		
12. CHEC	K THE APPROPRIATE BO	X(ES) TO INDI	CATE NATURE	OF NOTIC	E, REPORT OR OTH	ER DA	ATA
TYPE OF SUBMISSION			TYP	E OF ACT	ION		
Notice of Intent	Acidize Alter Casing Casing Repair	_	n re Treat Construction	Recla	nction (Start/Resume) mation mplete		Water Shut-Off  Well Integrity  Other Casing/Cement
✓ Subsequent Report  Final Abandonment Notice	Change Plans Convert to Injection	=	nd Abandon	Temp	orarily Abandon r Disposal		Intermedical
following completion of the involve testing has been completed. Final determined that the site is ready for Set intermediate casing string and of Hole diameter: 8.75", casing diamet 5758'. Stage tool at 2110'. Top of following Stage 1 Cement (Pumped 3/10/13): Sodium Metasilicate. Mixed at 12.1 Yield 1.38 cuft/sk. 40 bbls cement to the string has been supported to the string of	Abandonment Notices must be final inspection.)  emented 3/10/13. Gelled be er: 7", casing weight and cloat collar at 5707'. TOC allowed the second se	be filed only after freshwater muc grade 26# J55 I at surface and I ite FM + 3% Ca iil 257 Type III (	r all requirements I system.  TC. Depth of 8 BOC at 5758'.  ICI2 + 0.25/sk Co	, including .5" hole fro ello Flake	reclamation, have bee om 0 <u>to 5865</u> '. Interi + 5#/sk LCM-1 + 8%	n comp	eleted and the operator has te casing set from surface to onite + 0.4% FL-52A + 0.4%
Started drilling out stage tool at 211	6' on 3/11/13. Tested cas	ing and BOP or	n 3/11/13, pressi	ure held at	1500# for 30 minut	es. No	o pressure drop.
					addeffied for record		
					MAR 2 0 2013		
							HELDOFFICE n Tambeku
14. I hereby certify that the foregoing is t Name (Printed/Typed) Robynn Haden	rue and correct.		Title Engineeri	ng Techno	ologist		
Signature Pobin	Hadin	-	Date 3//	9/13			
, U	THIS SPACE	FOR FEDE	RAL OR STA	TE OFF	ICE USE		
Approved by							
Conditions of approval, if any, are attached that the applicant holds legal or equitable tentitle the applicant to conduct operations	itle to those rights in the subje			,		Date	
Title 18 U.S.C. Section 1001 and Title 43	U.S.C. Section 1212, make it	a crime for any pe	rson knowingly and	d willfully to	o make to any departme	nt or ag	gency of the United States any false.

fictitious or fraudulent statements or representations as to any matter within its jurisdiction