District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

## State of New Mexico Energy Minerals and Natural Resources

Department Oil Conservation Division Form C-144 July 21, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

1000 Die Dresse Dd. Asten MA	1 97410	E- NIM 07505	For permanent pits and exceptions submit to the Santa Fe
1000 Rio Brazos Rd., Aztec, NN <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe		Fe, NM 87505	Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
1220 S. St. Francis St., Sainta Fe		System, Below-Grad	e Tank, or
	Proposed Alternative M		
54			<del></del>
() Type of			ank, or proposed alternative method
		-	tank, or proposed alternative method
	Modification to an ex		W. J
		proposed alternative method	tted or non-permitted pit, closed-loop system,
Instructions: Please su	,	• •	p system, below-grade tank or alternative request
			sult in pollution of surface water, ground water or the
environment. Nor do	es approval relieve the operator of its responsibility	to comply with any other applicable g	governmental authority's rules, regulations or ordinances.
Operator: ConocoPhillip	os Company		OGRID#: 217817
	Farmington, NM 87499		
	AN JUAN 32-7 UNIT 245A		
API Number:	30-045-32465	OCD Permit Number	er:
U/L or Otr/Otr: P(SE/S		<del></del>	7W County: SAN JUAN
Center of Proposed Desig	<del></del>	°N Longitude:	107.349923 °W NAD: X 1927 1983
	Federal State Prive		
2			
<del></del>	G of 19.15.17.11 NMAC		RCVD APR 11'13
Temporary: Drilli	ng Workover		OIL CONS. DIV.
remperary.   Dimi	ing     vvoikovci		
_ =	gency Cavitation P&A		DIST. 3
_ =	gency Cavitation P&A	mil LLDPE	DIST. 3  HDPE PVC Other
Permanent Emer	gency Cavitation P&A	mil LLDPE	, , , , , , , , , , , , , , , , , , ,
Permanent Emer	gency Cavitation P&A Liner type: Thickness	mil LLDPE	, , , , , , , , , , , , , , , , , , ,
Permanent Emer Lined Unlir String-Reinforced Liner Scams: Wel	gency Cavitation P&A Liner type: Thickness		HDPE PVC Other
Permanent Emer Lined Unlir String-Reinforced Liner Scams: Wel	gency Cavitation P&A  led Liner type: Thickness  ded Sactory Other  1: Subsection H of 19.15.17.11 NMAC	Volume:	HDPE PVC Other  bbl Dimensions L x W x D
Permanent Emer Lined Unlir String-Reinforced Liner Scams: Wel	gency Cavitation P&A  led Liner type: Thickness  ded Subsection H of 19.15.17.11 NMAC  P&A Drilling a new well X	Volume:  Workover or Drilling (Applies to	bbl Dimensions L x W x D  activities which require prior approval of a permit or
Permanent Emer Lined Unlir String-Reinforced Liner Scams: Wel   X Closed-loop System Type of Operation:	gency Cavitation P&A  led Liner type: Thickness  ded Factory Other  1: Subsection H of 19.15.17.11 NMAC  P&A Drilling a new well X	Volume:  Workover or Drilling (Applies to	HDPE PVC Other bbl Dimensions L x W x D
Permanent Emer Lined Unlir String-Reinforced Liner Scams: Wel   X Closed-loop System Type of Operation:	gency Cavitation P&A  led Liner type: Thickness  ded Factory Other  a: Subsection H of 19.15.17.11 NMAC  P&A Drilling a new well The subsection H of 19.15.17.11 NMAC  Above Ground Steel Tanks Haul-	Volume:  Workover or Drilling (Applies to notice of intent) Remedial_replace off Bins Other	bbl Dimensions L x W x D  activities which require prior approval of a permit or
Permanent Emer Lined Unlir String-Reinforced Liner Seams: Wel  X Closed-loop System Type of Operation:  X Drying Pad X	gency Cavitation P&A  led Liner type: Thickness  ded Factory Other  a: Subsection H of 19.15.17.11 NMAC  P&A Drilling a new well T  Above Ground Steel Tanks Hauleded Liner type: Thickness 20	Volume:  Workover or Drilling (Applies to notice of intent) Remedial_replace off Bins Other	hdpe PVC Other
Permanent Emer Lined Unlir String-Reinforced Liner Scams: Wel   X Closed-loop System Type of Operation: X Drying Pad X X Lined Unlin- Liner Scams: X Weld	gency Cavitation P&A  led Liner type: Thickness  ded Factory Other  a: Subsection H of 19.15.17.11 NMAC  P&A Drilling a new well T  Above Ground Steel Tanks Hauleded Liner type: Thickness 20	Volume:  Workover or Drilling (Applies to notice of intent) Remedial_replace off Bins Other	hdpe PVC Other
Permanent Emer Lined Unlin String-Reinforced Liner Seams: Wel  X Closed-loop System Type of Operation: X Drying Pad X X Lined Unlin	gency Cavitation P&A  led Liner type: Thickness  ded Factory Other  a: Subsection H of 19.15.17.11 NMAC  P&A Drilling a new well T  Above Ground Steel Tanks Hauleded Liner type: Thickness 20	Volume:  Workover or Drilling (Applies to notice of intent) Remedial_replace off Bins Other	hdpe PVC Other
Permanent Emer Lined Unlir String-Reinforced Liner Seams: Wel   X Closed-loop System Type of Operation: X Drying Pad X X Lined Unlin- Liner Seams: X Weld	gency Cavitation P&A  led Liner type: Thickness  ded Factory Other  1: Subsection H of 19.15.17.11 NMAC  P&A Drilling a new well X  T  Above Ground Steel Tanks Hauled Liner type: Thickness 20  ed X Factory Other	Volume:  Workover or Drilling (Applies to notice of intent) Remedial_replace off Bins Other	hdpe PVC Other
Permanent Emer Lined Unlir String-Reinforced Liner Scams: Wel  X Closed-loop System Type of Operation: X Drying Pad X X Lined Unlin- Liner Scams: X Weld  4 Below-grade tank:	gency Cavitation P&A  led Liner type: Thickness  ded Factory Other  a: Subsection H of 19.15.17.11 NMAC  Above Ground Steel Tanks Haul- ed Liner type: Thickness 20  ed X Factory Other  Subsection I of 19.15.17.11 NMAC  bbl Type of fluid:	Volume:  Workover or Drilling (Applies to notice of intent) Remedial_replace off Bins Other	hdpe PVC Other
Permanent Emer Lined Unlir String-Reinforced Liner Seams: Wel  X Closed-loop System Type of Operation: X Drying Pad X X Lined Unlin- Liner Seams: X Weld  Below-grade tank: Volume:	gency Cavitation P&A  led Liner type: Thickness  ded Factory Other  1: Subsection H of 19.15.17.11 NMAC  Above Ground Steel Tanks Haulded Liner type: Thickness 20  ed X Factory Other  Subsection I of 19.15.17.11 NMAC  bbl Type of fluid:  al:	Volume:  Workover or Drilling (Applies to notice of intent) Remedial_replace off Bins Other	bbl Dimensions Lx Wx D  activities which require prior approval of a permit or ce pump currently in hole.  HDPE PVD Other
Permanent Emer Lined Unlir String-Reinforced Liner Scams: Wel  X Closed-loop System Type of Operation: X Drying Pad X X Lined Unlin Liner Scams: X Weld  4 Below-grade tank: Volume: Tank Construction materia	gency Cavitation P&A  led Liner type: Thickness  ded Factory Other  a: Subsection H of 19.15.17.11 NMAC  P&A Drilling a new well X  T  Above Ground Steel Tanks Haule  ded Liner type: Thickness 20  ed X Factory Other  Subsection I of 19.15.17.11 NMAC  bbl Type of fluid:  al:  t with leak detection Visible sidewalls only	Volume:  Workover or Drilling (Applies to notice of intent) Remedial_replace of the mil X LLDPE I	bbl Dimensions Lx Wx D  activities which require prior approval of a permit or ce pump currently in hole.  HDPE PVD Other
Permanent Emer Lined Unlir String-Reinforced Liner Seams: Wel  X Closed-loop System Type of Operation: X Drying Pad X X Lined Unline Liner Seams: X Weld  Below-grade tank: Volume: Tank Construction materic Secondary containmen	gency Cavitation P&A  ied Liner type: Thickness  ded Factory Other  i: Subsection H of 19.15.17.11 NMAC  Above Ground Steel Tanks Haule  ded Liner type: Thickness 20  ed X Factory Other  Subsection I of 19.15.17.11 NMAC  bbl Type of fluid:  al:  t with leak detection Visible sidewalls only	Volume:  Workover or Drilling (Applies to notice of intent) Remedial_replace of the mil X LLDPE I	bbl Dimensions Lx Wx D  activities which require prior approval of a permit or ce pump currently in hole.  HDPE PVD Other
Permanent Emer Lined Unlir String-Reinforced Liner Seams: Wel   X Closed-loop System Type of Operation: X Drying Pad X X Lined Unlin- Liner Seams: Weld  4 Below-grade tank: Volume: Tank Construction materia Secondary containmen Visible sidewalls and Liner Type: Thicknes	gency Cavitation P&A  led Liner type: Thickness  ded Factory Other  a: Subsection H of 19.15.17.11 NMAC  P&A Drilling a new well X  T  Above Ground Steel Tanks Haule  ded Liner type: Thickness 20  ed X Factory Other  Subsection 1 of 19.15.17.11 NMAC  bbl Type of fluid:  al:  t with leak detection Visible sidewalls only  ss mil HDPE	Workover or Drilling (Applies to notice of intent) Remedial_replace off Bins Other	bbl Dimensions Lx Wx D  activities which require prior approval of a permit or ce pump currently in hole.  HDPE PVD Other
Permanent Emer Lined Unlin String-Reinforced Liner Seams: Wel   X Closed-loop System Type of Operation: X Drying Pad X X Lined Unlin Liner Seams: Weld  4 Below-grade tank: Volume: Tank Construction materic Secondary containmen Visible sidewalls and Liner Type: Thicknes	gency Cavitation P&A  led Liner type: Thickness  ded Factory Other  a: Subsection H of 19.15.17.11 NMAC  P&A Drilling a new well X  T  Above Ground Steel Tanks Haul- ed Liner type: Thickness 20  ed X Factory Other  Subsection 1 of 19.15.17.11 NMAC  bbl Type of fluid: al: t with leak detection Visible sidewalls only ss mil HDPE	Volume:  Workover or Drilling (Applies to notice of intent) Remedial_replace of Bins  Other  mil  X LLDPE  I  lewalls, liner, 6-inch lift and autor Other  PVC  Other	hdder PVC Other

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Alternate. Please specify		
7		
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)		
Signs: Subsection C of 19.15.17.11 NMAC  12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	!	
X Signed in compliance with 19.15.3.103 NMAC		
Administrative Approvals and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration (Fencing/BGT Liner)  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	eration of approval.	
10		
Siting Criteria (regarding permitting) 19.15.17.10 NMAC  Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No	
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)	□NA	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image		
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applied to permanent pits)	☐Yes ☐No ☐NA	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image		
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes No	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	Yes No	
<ul> <li>Written confirmation or verification from the municipality: Written approval obtained from the municipality</li> <li>Within 500 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	Yes No	
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes No	
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	∏Yes ∏No	
Within a 100-year floodplain - FEMA map	Yes No	

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist Subsection B of 19.15.17.9 NMAC		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.		
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC		
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9		
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC		
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC		
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC		
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
Previously Approved Design (attach copy of design)  API  or Permit		
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9  Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC		
String Criteria Compilations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC		
X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC		
X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9  NMAC and 19.15.17.13 NMAC		
Previously Approved Design (attach copy of design)  API		
Previously Approved Operating and Maintenance Plan API		
13		
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.		
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC		
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC		
Climatological Factors Assessment		
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC		
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC		
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC		
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan		
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC		
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC		
Nuisance or Hazardous Odors, including H2S, Prevention Plan		
Emergency Response Plan		
Oil Field Waste Stream Characterization		
Monitoring and Inspection Plan		
Erosion Control Plan		
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
14		
· Proposed Closure: 19.15.17.13 NMAC		
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.		
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank X Closed-loop System  Alternative		
Proposed Closure Method: Waste Excavation and Removal		
X Waste Removal (Closed-loop systems only)		
On-site Closure Method (only for temporary pits and closed-loop systems)		
In-place Burial On-site Trench		
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)		
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.		
Please indicate, by a check mark in the box, that the documents are attached.		
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC		
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC		
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)		
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC		
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC		
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC		

Form C-144 Oil Conservation Division Page 3 of 5

16  Waste Remoyal Closure For Closed-loop Systems That Utilize Above Ground Stee			
Instructions: Please identify the facility or facilities for the disposal of liquids, drilling j facilities are required.	thiids and drill cuttings. Use attachment if more than two		
Disposal Facility Name: Envirotech / JFJ Landfarm % IEI	Disposal Facility Permit #: NM-01-0011 / NM-01-00	010B	
Disposal Facility Name: Basin Disposal Facility	Disposal Facility Permit #: NM-01-005		
Will any of the proposed closed-loop system operations and associated activit  Yes (If yes, please provide the information No	ies occur on or in areas that will nbe used for future	service and	
Required for impacted areas which will not be used for future service and operations:  Soil Backfill and Cover Design Specification - based upon the appropriate Re-vegetation Plan - based upon the appropriate requirements of Subsect  Site Reclamation Plan - based upon the appropriate requirements of Subsect	ion I of 19.15.17.13 NMAC	MAC	
17 Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Receptain siting criteria may require administrative approval from the appropriate district office or no office for consideration of approval. Justifications and/or demonstrations of equivalency are required.	ommendations of acceptable source material are provided below. nay be considered an exception which must be submitted to the Sa	Requests regarding changes to nta Fe Environmental Bureau	
Ground water is less than 50 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS: Data obta	ined from nearby wells	Yes No	
Ground water is between 50 and 100 feet below the bottom of the buried wast	e	☐Yes ☐No	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtain		N/A	
Ground water is more than 100 feet below the bottom of the buried waste.		☐Yes ☐No	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtai	ned from nearby wells	□ N/A	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other signific (measured from the ordinary high-water mark).	ant watercourse or lakebed, sinkhole, or playa lake	Yes No	
- Topographic map: Visual inspection (certification) of the proposed site			
Within 300 feet from a permanent residence, school, hospital, institution, or church in e - Visual inspection (certification) of the proposed site; Aerial photo; satellite image	• •	∐Yes ∐No	
Within 500 horizontal foot of a private domestic fresh water well as apping that less thousand	Gus barrachalda van Gardarracha ar an de arracharracha	∐Yes ∐No	
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existe - NM Office of the State Engineer - iWATERS database; Visual inspection (certific	ence at the time of the initial application.	·	
Within incorporated municipal boundaries or within a defined municipal fresh water well pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obta		Yes No	
Within 500 feet of a wetland  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual insp	. ,	Yes No	
Within the area overlying a subsurface mine.	,	Yes No	
- Written confiramtion or verification or map from the NM EMNRD-Mining and M	lineral Division	] [	
Within an unstable area.  - Engineering measures incorporated into the design: NM Bureau of Geology & Mi Topographic map	neral Resources; USGS; NM Geological Society;	YesNo	
Within a 100-year floodplain FEMA map		Yes No	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each by a check mark in the box, that the documents are attached.	of the following items must bee attached to the clos	sure plan. Please indicate,	
Siting Criteria Compliance Demonstrations - based upon the appropria	te requirements of 19.15.17.10 NMAC		
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC			
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC			
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)  Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
	Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC		
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			

19 Country Annihilation Country Country
Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.
Name (Print): Jamie Gogdwin Title: Regulatory Technician
100
Signature:
e-man address. [amie.i.goodwingeconecommips.com]
20
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)
OCD Representative Signature: Approval Date: 4/11/2013
Title: Con Oliance (Direct DCD Permit Number:
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure
report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an
approved closure plan has been obtained and the closure activities have been completed.
Closure Completion Date:
22
Closure Method:
Waste Excavation and Removal On-site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only)
If different from approved plan, please explain.
23
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:  Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities
were utilized.
Disposal Facility Name: Disposal Facility Permit Number:
Disposal Facility Name: Disposal Facility Permit Number:
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?
Yes (If yes, please demonstrate complilane to the items below)
Required for impacted areas which will not be used for future service and operations:
Site Reclamation (Photo Documentation)   Soil Backfilling and Cover Installation
Re-vegetation Application Rates and Seeding Technique
24 Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in
the box, that the documents are attached.
Proof of Closure Notice (surface owner and division)
Proof of Deed Notice (required for on-site closure)
Plot Plan (for on-site closures and temporary pits)
Confirmation Sampling Analytical Results (if applicable)
Waste Material Sampling Analytical Results (if applicable)
Disposal Facility Name and Permit Number
Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique
Site Reclamation (Photo Documentation)
On-site Closure Location: Latitude: Longitude: NAD 1927 1983
25. grade. 1727 1705
25
Operator Closure Certification:
I hereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that
the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.
Name (Print): Title:
Signature: Date:
Signature: Date:
e-mail address: Telephone:

# **ConocoPhillips Company**

#### **Closed Loop Design:**

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

ConocoPhillips Company may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

### **Closed Loop Operations and Maintenance:**

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- 2. Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

#### **Closed Loop Closure Plan:**

1. Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Industrial Ecosystem Inc. Solids & Sludge Only – No

- Liquids) (Permit # NM-01-0010B) within 6 months from the date that the drilling rig is released.
- 2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. COP shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)
Purity
50 percent
Germination
Percent PLS
20 percent

Source No. two (better quality)
Purity
80 percent
Germination
63 percent
Percent PLS
50 percent

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS