District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office. For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

<u>Pit, Closed-Loop System, Below-Grade Tank, or</u> <u>Proposed Alternative Method Permit or Closure Plan Application</u>
Type of action: Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Modification to an existing permit Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system.
below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: Energen Resources OGRID #: 162928
Address: 2010 Afton Place, Farmington, New Mexico 87401
Facility or well name:Cheney Federal 2
API Number: 3003906441 OCD Permit Number:
U/L or Qtr/Qtr <u>M</u> Section <u>17</u> Township <u>26N</u> Range <u>02W</u> County: <u>Rio Arriba</u> .
Center of Proposed Design: Latitude <u>36.48052</u> Longitude <u>-107.07845</u> NAD: □1927 ⊠ 1983
Surface Owner: 🛛 Federal 🗌 State 🗋 Private 🛄 Tribal Trust or Indian Allotment
2. Pit: Subsection F or G of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A OIL CONS. DIV.
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC OtherDIS1.3 String-Reinforced Liner Seams: Welded Factory OtherVolume:bbl Dimensions: L x W x D 3. Closed-loop System: Subsection H of 19.15.17.11 NMAC Type of Operation: P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or police of the permit
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC OtherDIS1.3 String-Reinforced Liner Seams: Welded Factory OtherVolume:bbl Dimensions: L x W x D 3. Closed-loop System: Subsection H of 19.15.17.11 NMAC Type of Operation: P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent)
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC OtherDIS1.3 String-Reinforced Liner Seams: Welded Factory OtherVolume:bbl Dimensions: L x W x D 3. Closed-loop System: Subsection H of 19.15.17.11 NMAC Type of Operation: P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) Drying Pad Above Ground Steel Tanks Haul-off Bins Other
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC OtherDIST. 3 String-Reinforced Liner Seams: Welded Factory OtherVolume:bbl Dimensions: Lx Wx D 3. Closed-loop System: Subsection H of 19.15.17.11 NMAC Type of Operation: P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) Drying Pad Above Ground Steel Tanks Haul-off Bins Other Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other DIS1.3 String-Reinforced Liner Seams: Welded Retory Gother Other Volume: bbl Dimensions: Lx Wx D Subsection H of 19.15.17.11 NMAC Type of Operation: P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) Drying Pad Above Ground Steel Tanks Haul-off Bins Other Liner Seams: Welded Factory Other Other Difference
□ Lined □ Unlined Liner type: Thicknessmil □ LLDPE □ PVC □ OtherDIS1.3 □ String-Reinforced Liner Seams: □ Welded □ Factory □ OtherVolume:bbl Dimensions: Lx Wx D 3. □ Closed-loop System: Subsection H of 19.15.17.11 NMAC Type of Operation: □ P&A □ Drilling a new well □ Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) □ Drying Pad □ Above Ground Steel Tanks □ Haul-off Bins □ Other □ Lined □ Unlined Liner type: Thicknessmil □ LLDPE □ HDPE □ PVC □ Other Liner Seams: □ Welded □ Factory □ Other 4. ▼ Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume:bbl Type of fluid: Produced Water Tank Construction material: □ Secondary containment with leak detection □ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off □ Visible sidewalls and liner ▼ Visible sidewalls only □ Other
□ Lined □ Unlined Liner type: Thicknessmil □ LLDPE □ HDPE □ PVC □ OtherDIS1.3 String-Reinforced Liner Seams: □ Welded □ Factory □ OtherVolume:bbl Dimensions: Lx Wx D Subsection H of 19.15.17.11 NMAC □ Closed-loop System: Subsection H of 19.15.17.11 NMAC □ Type of Operation: □ P&A □ Drilling a new well □ Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) □ Drying Pad □ Above Ground Steel Tanks □ Haul-off Bins □ Other
Lined Unlined Liner type: Thicknessmil LLDPE PVC OtherDIS1.3 String-Reinforced Liner Seams: Welded Factory OtherNounce:bbl Dimensions: Lx Wx D 3. Closed-loop System: Subsection H of 19.15.17.11 NMAC Type of Operation: P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) Drying Pad Above Ground Steel Tanks Haul-off Bins Other

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

6.

7.

8

Q

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other_

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.3.103 NMAC

Administrative Approvals and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

10. Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system.		
 Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	🗋 Yes 🗌 No	
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks) Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	☐ Yes ☐ No ☐ NA	
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to permanent pits) Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	☐ Yes ☐ No ☐ NA	
 Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🛄 Yes 🗌 No	
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes No	
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No	
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗋 Yes 🗌 No	
Within a 100-year floodplain		

- FEMA map

11. <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 NMAC <u>Instructions</u> : Each of the following items must be attached to the application Please indicate by a check mark in the box, that the documents are
attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:
12. <u>Closed-loop Systems Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.</i> <u>Ceologic and Hydrogeologic Data (only for on-site closure)</u> , based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9
 Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API Number:
Previously Approved Operating and Maintenance Plan API Number: (Applies only to closed-loop system that use
above ground steel tanks or haul-off bins and propose to implement waste removal for closure)
 Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment
 Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan
 Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
^{14.} <u>Proposed Closure</u> : 19.15.17.13 NMAC <i>Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.</i>
Type: Drilling Di Workover Emergency Cavitation P&A Permanent Pit & Below-grade Tank Closed-loop System
Proposed Closure Method: X Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems)
In-place Burial On-site Trench Burial Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
 ^{15.} Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.1 Instructions: Please indentify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if a facilities are required.	D NMAC) more than two	
Disposal Facility Name: Disposal Facility Permit Number:		
Disposal Facility Name: Disposal Facility Permit Number:		
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that <i>will not</i> be used for future service and operations? Yes (If yes, please provide the information below) No		
Required for impacted areas which will not be used for future service and operations: Soil Backfill and Cover Design Specifications based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC	с _.	
17. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate dist considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Just demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.	rce material are rict office or may be fications and/or	
 Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA	
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA	
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA	
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No	
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No	
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗋 Yes 🗌 No	
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No	
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No	
Within a 100-year floodplain. - FEMA map	🗌 Yes 🗌 No	
 Instructions: Each of the following items must be attached to the closure provide the second pr	an. Please indicate, 15.17.11 NMAC not be achieved)	

Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC

Soil Cover Design - based upon the appropriate requirements of Subsection 1 of 19.15.17.15 NMAC
 Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

19. Operator Application Certification:
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.
Name (Print): Title:
Signature: Date:
e-mail address: Telephone:
20. OCD Approval: Permit Application (including closure plan) 🕅 Closure Plan (only) 🔲 OCD Conditions (see attachment)
OCD Representative Signature: 0014HD. Kelly Approval Date: 5702/2013
Title: <u>Complitance</u> Office OCD Permit Number:
 21. <u>Closure Report (required within 60 days of closure completion)</u>: Subsection K of 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 2/26/13
22.
Closure Method: Waste Excavation and Removal On-Site Closure Method If different from approved plan, please explain.
^{23.} <u>Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:</u> Instructions: Please indentify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.
Disposal Facility Name: Disposal Facility Permit Number:
Disposal Facility Name: Disposal Facility Permit Number:
Were the closed-loop system operations and associated activities performed on or in areas that <i>will not</i> be used for future service and operations? Yes (If yes, please demonstrate compliance to the items below) No
Required for impacted areas which will not be used for future service and operations: Site Reclamation (Photo Documentation) Soil Reckfilling and Cover Installation
Re-vegetation Application Rates and Seeding Technique
24. <u>Closure Report Attachment Checklist:</u> Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Mark of Closure Notice (surface owner and division)
Proof of Deed Notice (required for on-site closure)
 Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable)
Waste Material Sampling Analytical Results (required for on-site closure)
Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation
Re-vegetation Application Rates and Seeding Technique
On-site Closure Location: Latitude Longitude NAD: [1927] 1983
Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.
Name (Print): <u>Ed Hasely</u> Title: <u>Sr. Environmental Engineer</u>
Signature: 2/1/22/13
e-mail address: ed.hasely@energen.com Telephone: (505) 324-4131

BELOW-GRADE TANK CLOSURE REPORT

ENERGEN RESOURCES Cheney Federal #2 – Separator BGT

<u>CLOSURE STEPS</u>: (Closure Report information is in **bold**)

(1) Notify the surface owner by certified mail, return receipt requested, of the plans to close the below-grade tank. Attached

(2) Notify the Aztec OCD office (Brandon Powell -334-6178, Ext 15) verbally or by other means at least 72 hours, but not more than one week, prior to the planned closure operation.

Attached

- (3) Remove liquids from the below-grade tank. Dispose of the liquids and sludge in a division-approved facility. No disposal of liquids was required.
- (4) Remove the below-grade tank for re-use in an above-ground setup or for disposal in a division-approved manner. Tank removed.

(5) Unless the equipment is required for some other purpose, remove any on-site equipment associated with the below-grade tank.

All remaining equipment is required for operations.

(6) Test the soils beneath the below-grade tank to determine whether a release has occurred.

- Collect, at a minimum, a five point, composite sample; Composite sample was collected.
- Collect individual grab samples from any area that is wet, discolored or showing other evidence of a release;

No additional sampling was necessary.

Analyze for BTEX, TPH and chlorides to demonstrate:

- Benzene concentration does not exceed 0.2 mg/kg, as determined by EPA SW-846 methods 8021B or 8260B
- Total BTEX concentration does not exceed 50 mg/kg, as determined by EPA SW-846 methods 8021B or 8260B
- TPH concentration does not exceed 100 mg/kg, as determined by EPA method 418.1
- Chloride concentration does not exceed 250 mg/kg, as determined by EPA method 300.1 or the background concentration, whichever is greater.

Constituent	Limit (mg/kg)	Actual Results (mg/kg)
Benzene	0.2	ND
Total BTEX	50.0	ND
TPH (418.1)	100	262 (exceedance)
Chlorides	250	23.5

(7) IF the soil analyses show that the soils meet the concentrations specified in (6) above, backfill the excavation with compacted, non-waste containing, earthen material in a manner that will prevent ponding or erosion. If the area will not be needed for operations, reclaim the area as described in the "RECLAMATION" section. Not applicable.

(8) IF the soil analyses show that the soils exceed one or more of the concentrations specified in (6) above, notify the Aztec OCD office (Brandon Powell - 334-6178, Ext 15) and proceed per 19.15.3.116 NMAC. Attached. Proceeded per 19.15.29 and 19.15.30.

NOTE: If groundwater is encountered at any time during the closure process, the OCD office will be notified and a specific closure plan will be submitted to the Aztec and Santa Fe OCD offices for approval. Not applicable.

FINAL CLOSURE REPORT:

Within 60 days of closure completion, submit a closure report on form C-144, with necessary attachments to document all closure activities including sampling results.

This submittal is the closure report.

RECLAMATION:

If the area is not needed for operations, reclaim the area to a safe and stable condition that blends with the surrounding undisturbed area. Restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover, recontour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate.

(A) Construct the soil cover to the site's existing grade and prevent ponding of water and erosion of the cover material. The soil cover shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater.

(B) Seed or plant the disturbed areas the first growing season after closing the below-grade tank. Drill on the contour whenever practical or by other division-approved methods. The goal is to obtain vegetative cover that equals 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. During the two successive growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

(C) Repeat seeding or planting until it successfully achieves the required vegetative cover.

(D) If conditions are not favorable for the establishment of vegetation, such as periods of drought, contact the Aztec OCD office to discuss possibly delaying seeding or planting until soil moisture conditions become favorable or using additional techniques such as mulching, fertilizing, irrigating, fencing or other practices.

(E) Notify the Aztec OCD office (Brandon Powell – 334-6178, Ext 15) when the area has been seeded or planted and when it successfully achieves re-vegetation.

Area is needed for operations. Upon abandonment, seeding will be deferred to the BLM / Tribal requirements per the BLM / OCD MOU.



November 12, 2012

Bureau of Land Management 6251 College Blvd., Suite A Farmington, New Mexico 87401 Attn: Mr. Jim Lavoto

1	U.S. Postal S CERTIFIEL (Domestic Mail O	Service DMAII nly; No In	™ L™ REC surance Co	EIPT overage Provided)
ЕЭ	JEor delivery information	ation _s visit o	ùr wébsite a	it www.usps.com _@
₽-	OFF		IAL	USE
1,20	Postage	\$		
пл	Certified Fee		1	_
100	Return Receipt Fee (Endorsement Required)			Postmark Here
	Restricted Delivery Fee (Endorsement Required)			-
7 4 0	Total Postage & Fees	\$		
ា	Sent To			
707	Street, Apt. No.; or PO Box No.	••••••		
	City, State, ZIP+4		**********	***************************************
	PSIForm 3800 August 2	0063,	- A.	See Reverse for Instructions

Re: Below Grade Tank Closures Multiple Locations

Dear Mr. Lavoto:

Energen Resources plans to close the below grade tanks located on the well locations listed below. You are on record as the surface owner where these wells are located. New Mexico Oil Conservation Division (NMOCD) rules require notification to the surface owner of our plans to close the below grade tanks. NMOCD rules and guidelines will be followed. The wells are all located in San Juan County, New Mexico.

Cheney Federal #2 - Unit Letter M, Section 17, Township 26N, Range 2W Cheney Federal #2A - Unit Letter D, Section 17, Township 26N, Range 2W

If there are any questions or concerns, please contact me at 505-330-3584.

Sincerely, Hase

Ed Hasely COMPLETE THIS SECTION ON DELIVERY SENDER: COMPLETE THIS SECTION Sr. Environmental Engineer A. Signature Complete items 1, 2, and 3. Also complete **Energen Resources** Agent item 4 if Restricted Delivery is desired. X Print your name and address on the reverse Addressee so that we can return the card to you. C. Date of Delivery R eceived by (Pr Name) Attach this card to the back of the mailpiece, -15-12 or on the front if space permits. C Yes D. Ís de different from item 1? 1. Article Addressed to: Cc: Well File If YES, enter delivery address below: No 🖸 Correspondence BLM 6251 College Blue Ste A Farmington, NM 87402 3. Service Type Attn: Jim Law Express Mail Certified Mail Return Receipt for Merchandise Registered Insured Mail C.O.D. 4. Restricted Delivery? (Extra Fee) C Yes 2. Article Number 7012 0470 0002 1207 6304 (Transfer from service label) Energen Resources Corporation, an En-Domestic Return Receipt 102595-02-M-154 PS Form 3811, February 2004 2

Ed Hasely

From: Sent: To: Subject: Ed Hasely Monday, November 12, 2012 2:25 PM Kelly, Jonathan, EMNRD BGT Closure Notifications

Jonathan – Energen plans to begin the closure process on the below listed BGT's in the near future. Let me know if you have questions. Thanks.

1

Chene y Federal	#2 - Unit Letter M, Section 17, Township 26N, Range 2W
Cheney Federal	#2A - Unit Letter D, Section 17, Township 26N, Range 2W

Ed Hasely Energen Resources Corporation Sr. Environmental Engineer ed.hasely@energen.com[•] Office: (505) 324-4131 Cell: (505) 330-3584

Chency Feel #2 (S. BGT)