Form 3160-5 (August 2007)

UNITED STATES UNITED STATES DEPARTMENT OF THE INTERIOR ADD 1 1 2017

FORM APPROVED OMB No. 1004-0137

(August 2007)	BUREAU OF LAND MAI	NAGEMENT	APR 11		Expires:	July 31, 2010	
		Far	rmington F	ield Tim	se Serial No.	-079367-В	
	IDRY NOTICES AND REPO	ORTS ON WE	Enre Laug	Ma R	dian, Allottee or Tribe I	Vame	
	e this form for proposals t well. Use Form 3160-3 (A			_	•		
SUBMIT IN TRIPLICATE - Other instructions on page 2.					7. If Unit of CA/Agreement, Name and/or No.		
1. Type of Well					SAN JUAN 28-6 UNIT		
Oil Well X Gas Well Other				8. Well Name and No. San Juan 28-6 Unit 110N			
2. Name of Operator	0110000			9. API	Well No.		
Burlington Resources Oil & Gas Company LP 3a. Address 3b. Phone No. (include area code)) 10. Fie	eld and Pool or Explorate	139-30729 Dry Area	
			326-9700		Blanco MV/Basin DK		
4. Location of Well (Footage, Sec., T.,. Surface Unit N (SE/S)	R.,M., or Survey Description) W), 750' FSL & 1700' FWL, 41	, Section 25,	T27N, R6W		untry or Parish, State Rio Arriba	New Mexico	
12. CHECK T	THE APPROPRIATE BOX(ES)	TO INDICATE	NATURE OF	NOTICE,	REPORT OR OTH	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
Notice of Intent	Acidize	Deepen		Production	on (Start/Resume)	Water Shut-Off	
	Alter Casing	Fracture Tre	-	Reclama		Well Integrity	
X Subsequent Report	Casing Repair Change Plans	New Constr	=	Recompl		X Other Casing Sundry	
Final Abandonment Notice	Convert to Injection	Plug and Ab	апооп [Water D	rily Abandon isposal		
13. Describe Proposed or Completed O	<u> </u>		imated starting da	ate of any pro	posed work and approxi	mate duration thereof	
Tagged @ 194' & DO of J-55, ST&C csg set @ 19sx(57cf-10bbls=3.02) Pumped Lead w/ 350sy Bentonite, 0.4% SMS. If Dropped plug & displace to 1500#/30min @ 00:3 TD at 7693'. TD reach Pre-flushed w/ 10bbls If 0.25pps celloflake, 0.3% celloflake, 0.3% CD-32, ND BOPE NU WH RD	, 6.25pps LCM-1, & 1% FL- RR @ 18:00hrs on 04/09/13	to 3421' - Interest of State 1 of FW, 100 cacl2, 0.25 pp. Premium Lite f-20bis=1.38y and 16:14 w/ 6 1/4 e. & RIH w/ 18 s of FW. Pump 3.1% FL-52. 52. Dropped 3.1%	er TD reache bbls GW & 1 os celloflake, w/ 3% CaCl2/Id) Type III of 26hrs on 04/ 4" bit. Tagge 1 jts, 4 1/2", ped scaveng Tail w/ 302s; plug & displa	ed <u>04/01/1</u> lobbls of F , 5 pps LC 2, 0.25 pp: cmt w/ 1% /02/13. <u>Cir</u> ed cmt @ : 11.6#, L-8 ger w/ 9sxl x(598cf-1 aced w/ 11	13. Circ. Hole & F.W. Pumped Sca M-1, 0.4% FL-52, s celloflake, 5 pps CaCl2, 0.25 pps c. 40 bbls of cmt 3356'. Drilled out Q, LT&C csg set (28cf-5bbls-3.10) 9bbls FW. Bump	RIH w/ 80jts, 7", 20#, venger w/ 8% Bentonite, 0.4% SMS. LCM-1, 0.4% FL-52, 8% celloflake, & 0.2% FL-52. to surface. WOC. PT csg cmt & drilled ahead to @ 7682', RU to cmt. VId) Premium lite HS FM, 0.25 pps	
	by Completion Rig. Resu		ııı appear or	n next rep	ort.		
14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) Arleen White			Staff Regulatory Tech				
Signature Welev	r White	Dat	e 41	10/13			
	THIS SPACE FO	R FEDERAL	OR STATE	OFFICE (JSE		
Approved by							
			Title	_ 		Date	
Conditions of approval, if any, are attact that the applicant holds legal or equitab entitle the applicant to conduct operatio	le title to those rights in the subject lea		Office	e	ACCEPTI	ED FOR RECORD	

(Instruction on page 2)

false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department of the United States any