1301 W. Grand Ave., Artesia, NM 88210

1000 Rio Brazos Rd., Aztec, NM 87410

District III

State of New Mexico Energy Minerals and Natural Resources

Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 July 21, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe

District IV 1220 S. St. Francis Dr., Santa Fc. NM 87505	Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
	tem, Below-Grade Tank, or
Proposed Alternative Metho	od Permit or Closure Plan Application
Type of action: X Permit of a pit, closed-loo	p system, below-grade tank, or proposed alternative method
Closure of a pit, closed-loc	op system, below-grade tank, or proposed alternative method
Modification to an existing	g permit
	ed for an existing permitted or non-permitted pit, closed-loop system,
below-grade tank, or prop	osed anemative method idividual pit, closed-loop system, below-grade tank or alternative request
***	of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to cor	mply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: 14538
Address: PO Box 4289, Farmington, NM 87499	
Facility or well name: SAN JUAN 28-4 UNIT 34N	
API Number: 30-039-31123	OCD Permit Number:
	8N Range: 4W County: RIO ARRBA
Center of Proposed Design: Latitude: 36.627827 °	
Surface Owner: X Federal State Private	Tribal Trust or Indian Allotment
Pit: Subsection F or G of 19.15.17.11 NMAC	RCVD AUG 22 '12
Temporary: Drilling Workover	OIL CONS. DIV.
Permanent Emergency Cavita	nter o
Lined Unlined Liner ty	Longitude please result E PVC Other Kelly mit with convention Kelly 122
String-Reinforced String-Reinforced String-Reinforced Donatha	Kelly 234-5178 Ext. 122
Liner Seams: Welded Factory DATE: 612/35	Kelly 334-6178 Ext. 122 Volume: bbl Dimensions L x W x D
3	
X Closed-loop System: Subsection H of 19.15.17.11 NMAC	
	over or Drilling (Applies to activities which require prior approval of a permit or of intent)
X Drying Pad X Above Ground Steel Tanks Haul-off Bit	ns Other
X Lined Unlined Liner type: Thickness 20	mil X LLDPE HDPE PVD Other
Liner Seams: X Welded X Factory Other	
4	
Below-grade tank: Subsection I of 19.15.17.11 NMAC	
Volume:bbl Type of fluid: Tank Construction material:	
	s, liner, 6-inch lift and automatic overflow shut-off
Visible sidewalls and liner Visible sidewalls only	Other
Liner Type: Thicknessmil HDPE	PVC Other
5 Altomotive Methods	
Alternative Method:	
Submittal of an exception request is required. Exceptions must be submitted.	led to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify			
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)			
Signs: Subsection C of 19.15.17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC		1	
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration of approval. (Fencing/BGT Liner) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.			
Siting Criteria (regarding permitting) 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.			
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	No	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	□No	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks)	☐Yes	No	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	LI'''		
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐Yes ☐NA	No	
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	No	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes	No	
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	No	
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	No	
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	No	
Within a 100-year floodplain - FEMA map	Yes	No	

Form C-144 Oil Conservation Division Page 2 of 5

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.			
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC			
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC			
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC			
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of			
19.15.17.9 NMAC and 19.15.17.13 NMAC			
Previously Approved Design (attach copy of design) APIor Permit			
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9			
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC			
X Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC			
X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC			
X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9			
NMAC and 19.15.17.13 NMAC			
Previously Approved Design (attach copy of design) API			
Previously Approved Operating and Maintenance Plan API			
13			
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.			
l 🚗 '			
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
Climatological Factors Assessment			
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC			
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC			
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC			
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC			
Quality Control/Quality Assurance Construction and Installation Plan			
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC			
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC			
Nuisance or Hazardous Odors, including H2S, Prevention Plan			
Emergency Response Plan			
Oil Field Waste Stream Characterization Monitoring and Inspection Plan			
Erosion Control Plan			
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC			
14			
Proposed Closure: 19.15.17.13 NMAC			
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.			
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank X Closed-loop System Alternative			
Proposed Closure Method: Waste Excavation and Removal			
X Waste Removal (Closed-loop systems only)			
On-site Closure Method (only for temporary pits and closed-loop systems)			
In-place Burial On-site Trench			
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)			
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.			
Please indicate, by a check mark in the box, that the documents are attached.			
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)			
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC			
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			

16			
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.D NMAC) Instructions: Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than two			
facilities are required.			
Disposal Facility Name: Envirotech / JFJ Landfarm % IEI Disposal Facility Permit #: NM-01-0011 / NM-01-0	010B		
Disposal Facility Name: Basin Disposal Facility Disposal Facility Permit #: NM-01-005			
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will nbe used for future Yes (If yes, please provide the information No	service and		
Required for impacted areas which will not be used for future service and operations:			
Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 N Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC	MAC		
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			
17 Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.			
Ground water is less than 50 feet below the bottom of the buried waste.	Yes No		
- NM Office of the State Engineer - iWATERS database search; USGS: Data obtained from nearby wells	∐N/A		
Ground water is between 50 and 100 feet below the bottom of the buried waste	Yes No		
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	N/A		
Ground water is more than 100 feet below the bottom of the buried waste.	∏Yes ∏No		
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	N/A		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake	☐Yes ☐No		
(measured from the ordinary high-water mark).			
- Topographic map: Visual inspection (certification) of the proposed site			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	∐Yes ∐No		
- Visual inspection (certification) of the proposed site; Aerial photo; satellite image	☐Yes ☐No		
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application.			
- NM Office of the State Engineer - iWATERS database: Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted			
pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality: Written approval obtained from the municipality	YesNo		
Within 500 feet of a wetland	□Yes □No		
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site			
Within the area overlying a subsurface mine.	Yes No		
- Written confirantion or verification or map from the NM EMNRD-Mining and Mineral Division			
Within an unstable area.	Yes No		
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map			
Within a 100-year floodplain FEMA map	☐Yes ☐No		
18			
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must bee attached to the cloby a check mark in the box, that the documents are attached.	sure plan. Please indicate,		
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC			
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC			
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)			
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC			

Page 4 of 5

19			
Operator Application Certification:			
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief. Name (Print): Jamie Goodwin Title: Regulatory Technician			
Signature: Name (rtill) Date: 8/2//2			
September 1			
e-mail address: jamie.l.goodwin@conocophillips.com Telephone: 505-32649/84			
20			
OCD Approval: Permit Application (including ons (see attachment)			
OCD Approval: Permit Application (including ons (see attachment) OCD Representative Signature: al Date:			
Title:			
21			
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC			
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure			
report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.			
Closure Completion Date:			
22 Closure Method:			
Waste Excavation and Removal On-site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only)			
If different from approved plan, please explain.			
23 Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:			
Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities			
were utilized.			
Disposal Facility Name: Disposal Facility Permit Number: Disposal Facility Permit Number:			
Disposal Facility Permit Number: Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?			
Yes (If yes, please demonstrate complifane to the items below) No			
Required for impacted areas which will not be used for future service and operations:			
Site Reclamation (Photo Documentation)			
Soil Backfilling and Cover Installation			
Re-vegetation Application Rates and Seeding Technique			
24			
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.			
Proof of Closure Notice (surface owner and division)			
Proof of Deed Notice (required for on-site closure)			
Plot Plan (for on-site closures and temporary pits)			
Confirmation Sampling Analytical Results (if applicable)			
Waste Material Sampling Analytical Results (if applicable)			
Disposal Facility Name and Permit Number			
Soil Backfilling and Cover Installation			
Re-vegetation Application Rates and Seeding Technique			
Site Reclamation (Photo Documentation)			
On-site Closure Location: Latitude: Longitude: NAD 1927 1983			
Operator Cleanus Contification			
Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that			
the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.			
Name (Print): Title:			
Time.			
Signature: Date:			
e-mail address: Telephone:			

Form C-144 Oil Conservation Division

Burlington Resources Oil & Gas Company, LP

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

Burlington Resources Oil & Gas Company, LP may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- 2. Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

Closed Loop Closure Plan:

1. Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) within 6 months from the date that the drilling rig is released.

2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. BR shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)

Purity

50 percent

Germination

40 percent

Percent PLS

20 percent

Source No. two (better quality)

Purity

80 percent

Germination

63 percent

Percent PLS

50 percent

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS