

Submit 1 Copy To Appropriate District  
Office  
District I – (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II – (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III – (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV – (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised August 1, 2011

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-043-21129
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Encana Oil & Gas (USA) Inc.		6. State Oil & Gas Lease No.
3. Address of Operator 370 17 <sup>th</sup> Street, Suite 1700 Denver, CO 80202		7. Lease Name or Unit Agreement Name Lybrook 132-2306
4. Well Location SHL: Unit Letter <u>I</u> : 1307 feet from the <u>SOUTH</u> line and 288 feet from the <u>EAST</u> line BHL: Unit Letter <u>L</u> : 1980 feet from the <u>SOUTH</u> line and 330 feet from the <u>WEST</u> line Section 32 Township 23N Range 6W NMPM Sandoval County		8. Well Number 01H
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 7101' GR		9. OGRID Number 282327
		10. Pool name or Wildcat Lybrook Gallup

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Utilized synthetic oil-based mud system from intermediate casing point 5713' to TD of lateral.

Kicked off lateral at 4793' MD on 5/9/13. Landed lateral at 6220' on 5/15/13. Length of lateral 3840'. TD of 10,060' MD/5450' TVD reached 5/18/13. Set production liner 5/19/13.

Hole diameter: 6 1/8" production string diameter, 4 1/2" production string weight and grade: 11.6# SB80 LTC. Depth of 6 1/8" hole from 5800' MD to 10,060' MD. Float shoe at 10,057' MD and float collar at 10,036' MD. Production liner set from 5515' MD to 10,057' MD.

Set 17 external swellable casing packers for isolation of production string at the following depths: (1) 9808' (2) 9537' (3) 9270' (4) 9048' (5) 8782' (6) 8517' (7) 8293' (8) 8025' (9) 7801' (10) 7535' (11) 7268' (12) 7004' (13) 6738' (14) 6518' (15) 6294' (16) 6066' (17) 5832'.

Spud Date: 5/4/13

Rig Release Date: 5/20/13 ✓

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robynn Haden TITLE Engineering Technologist DATE 5/30/13

Type or print name Robynn Haden E-mail address: robynn.haden@encana.com PHONE: 720-876-3941

For State Use Only  
APPROVED BY: Branch Bell TITLE Deputy Oil & Gas Inspector, District #3 DATE 6/3/13  
Conditions of Approval (if any): AV