Form 3160-5

INITED STATES

FORM APPROVED

JUN 2 6 2013

Date

(March 2012)	DEPARTMENT OF THE	HE INTERIOR	JUN 2	6 201 3		JMB No. 1004-0137 pires: October 31, 2014	
	BUREAU OF LAND M			· C	NM-0226792	,	
Do not us	NDRY NOTICES AND RI se this form for propose d well. Use Form 3160-3	is to drill or forg	<i>ยอมใต้กิลภ</i> าเต	i Mana		Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2.					7. If Unit of CA/Agreement, Name and/or No.		
1. Type of Well			*****		La Plata Mancos Un	it	
✓ Oil Well Gas Well Other					8. Well Name and No. LPMU #1 (P-31)		
Name of Operator Benson-Montin-Greer Drilling Corp.					9. API Well No. 30-045-20304		
3a. Address 4900 College Blvd 3b. Phone No. (include are)	10. Field and Pool or Exploratory Area		
Farmington, NM 87402 505-325-88							
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) P-31-T32N-R13W 860' FSL, 900 FEL'				11. County or Parish, State San Juan, NM			
	12. CHECK THE APPROPRIATI	E BOX(ES) TO INDICAT	TE NATURE C	OF NOTIC	E, REPORT OR OTHE	R DATA	
TYPE OF SUBMISS	NON .	TYPE OF AC			FION		
Notice of Intent	Acidize Alter Casing	Deepen Fracture T	reat		ction (Start/Resume)	Water Shut-Off Welf Integrity	
Subsequent Report	Casing Repair	New Cons	truction	Recor	nplete	Other	
Final Abandonment N	Change Plans Office Convert to Inject	ion Plug and A			orarily Abandon Disposal	4 Marries, quantitative que que discriminative de Contra que antique en contra la contra de Cont	
the proposal is to deepe Attach the Bond under following completion o testing has been comple	ompleted Operation: Clearly state along directionally or recomplete horize which the work will be performed of the involved operations. If the operation is ready for final inspection.)	ontally, give subsurface to or provide the Bond No. o eration results in a multip	ocations and me in file with BLN le completion o	asured an WBIA. R or recompl	d true vertical depths of equired subsequent repo etion in a new interval,	orts must be filed within 30 days a Form 3160-4 must be filed once	
	ots to repair casing and return the MU #1 (P-31) will be plugged and			G is requ	esting permission to p	ilug and abandon the well. A rig is	
	of Class B cement from 573'-30				sary.		
	of Class B cement from 300'-0', elihead below surface casing flai				y with regulations. R	D, MOL.	
						OIL CONS. DIV DIST. 3	
				•		JUL 01 2013	
14. Thereby certify that the fo Zach Stradling	regoing is true and correct. Name (Pr		Operations	Manager			
Signature		Date 06/26/2013					
	THIS SDA	TE FOR FEDERAL	OR STAT	TE OFF	CE USE		

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Office Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false,

Title

Original Signed: Stephen Mason

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Approved by

LPMU #1

Proposed Plugged La Plata Gallup

660' FSL, 990' FEL, Section 31, T-32-N, R-13-W,

San Juan County, NM / API #30-045-20304 Lat N36.93829 / Long W108.23822

Today's Date: 8/25/13

Spud: 7/13/68

Comp: 1/13/89

17-1/4" hole

Elevation: 6062' GL

6075' KB

Junk in hole (7-5/8" casing inside of 7-5/8" casing)

Mesaverde @ 380'

Plug #2: 300' - 0' Class B cement, 250 sxs

Parted 7-5/8" Casing at 573'

13-3/8", 48#, Casing set @ 276'

Cement with 330 sxs (Circulated to Surface)

7-5/8" TOC @ 1100' (T.S.)

Plug #1: 573' - 300' Class B cement, 150 sxs

Mancos @ 1648'

Gallup @ 2654'

6-3/4" hole to 3042'

9-7/8" hole to 2700'

TD 3042' PBTD 3014' 5.5" liner top at 2389'

5.5" TOC @ TOL (Calc, 75%) 7-5/8", 26.4#, J-55 Casing set @ 2700' Cement with 500 sxs

Gallup Perforations: 2943' - 2975'

5.5", 15.5", J-55 liner set @ 3042' Cement with 85 sxs

LPMU #1

Current

La Plata Gallup

660' FSL, 990' FEL, Section 31, T-32-N, R-13-W,

San Juan County, NM / API #30-045-20304 Lat N36.93829/ Long W1108.23822

Today's Date: 6/25/13

Spud: 7/13/68

Comp: 1/13/69

17-1/4" hole

Elevation: 6062' GL

6075' KB

Mesaverde @ 380'

Junk in hole (7-5/8" casing inside of 7-5/8" casing)

Mancos @ 1648'

Gallup @ 2654'

9-7/8" hole to 2700'

6-3/4" hole to 3042'

TD 3042' PBTD 3014' 13-3/8", 48#, Casing set @ 276' Cement with 330 sxs (Circulated to Surface)

Parted 7-5/8" Casing at 573"

7-5/8" TOC @ 1100' (T.S.)

5.5" liner top at 2389'

5.5" TOC @ TOL (Calc, 75%)

7-5/8", 26.4#, J-55 Casing set @ 2700' Cement with 500 sxs

Gallup Perforations: 2943' - 2975'

5.5", 15.5", J-55 liner set @ 3042' Cement with 85 sxs