District L 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 CLEZ July 21, 2008 For closed-loop systems that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure, submit to the appropriate NMOCD District Office.
(that only use above ground st	op System Permit or Closure Plan eel tanks or haul-off bins and propose to implo Type of action: Permit X Closur	Application ement waste removal for closure) e
closed-loop system that only use above ground ste Please be advised that approval of this request does not	orm C-144 CLEZ) per individual closed-loop system eel tanks or haul-off bins and propose to implement of t relieve the operator of liability should operations result i f its responsibility to comply with any other applicable go	
Operator: <u>XTO ENERGY INC.</u>	OGRI	D #: <b>5380</b>
Address: 382 CR 3100 AZTEC, NM	· · · · · · · · · · · · · · · · · · ·	
Facility or well name: BRUINGTON GAS		
API Number: <u>30-045-30254</u>		
	21Township Range	1W         County:         SAN JUAN           993483         NAD:         1927         X 1983
Surface Owner: State Sta	_	NAD: 1927 X1983
Operation: Drilling a new well X Workove Above Ground Steel Tanks or Haul-off		ior approval of a permit or notice of intent)
3. Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's n	name, site location, and emergency telephone numb	ers OIL CONS. DIV.
X Signed in compliance with 19.15.3.103 NMA	AC	DIST. 3
Instructions: Each of the following items must attached. Design Plan - based upon the appropriate req Operating and Maintenance Plan - based upo	<b>chment Checklist:</b> Subsection B of 19.15.17.9 No be attached to the application. Please indicate, by unirements of 19.15.17.11 NMAC on the appropriate requirements of 19.15.17.12 NMA d upon the appropriate requirements of Subsection	y a check mark in the box, that the documents are
Previously Approved Design (attach copy of	design) API Number:	
Previously Approved Operating and Mainten	ance Plan API Number:	
Instructions: Please indentify the facility or facil facil facilities are required.	ems That Utilize Aboye Ground Steel Tanks or H ities for the disposal of liquids, drilling fluids and d Disposal Facility Pe	laul_off_Bins_Only:       (19.15.17.13.D NMAC)         lrill cuttings.       Use attachment if more than two         rmit Number:
		mit Number:
	rations and associated activities occur on or in areas	s that will not be used for future service and operations?
Re-vegetation Plan - based upon the approx	ed for future service and operations: tions based upon the appropriate requirements o opriate requirements of Subsection I of 19.15.17.13 ppropriate requirements of Subsection G of 19.15.1	NMAC
<ul> <li>6.</li> <li>Operator Application Certification:</li> <li>I hereby certify that the information submitted w</li> </ul>	ith this application is true, accurate and complete to	o the best of my knowledge and belief.
Name (Print):	Title:	
Signature:	Date:	
e-mail address:	Telephone	:
Form C-144 CLEZ	Oil Conservation Division	Page 1 of 2

<b>OCD Approval:</b> Permit Application (including closure plan) X Closure Plan (only)		
OCD Representative Signature:Kulh Approval Date:		
Title: <u>Compliance Office</u> O OCD Permit Number:		
8.		
<b>Closure_Report (required within 60 days of closure completion)</b> : Subsection K of 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.		
X Closure Completion Date: 7/2/2013		
9. Closure_Report_Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: Instructions: Please indentify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized. Disposal Facility Name:		
Disposal Facility Name: Disposal Facility Permit Number:		
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations? Yes (If yes, please demonstrate compliance to the items below) 🕱 No		
Required for impacted areas which will not be used for future service and operations:           Site Reclamation (Photo Documentation)           Soil Backfilling and Cover Installation           Re-vegetation Application Rates and Seeding Technique		
10.		
<b>Operator Closure Certification:</b> I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.		
Name (Print): SHERRY J. MORROW Title: REGULATORY ANALYST		
Signature: Date: 7/8/2013		
e-mail address: sherry morrow@ctoenergy.com Telephone: 505-333-3630		

•

# XTO Energy Inc. San Juan Basin Closed-Loop System Closure Plan

In accordance with Rule 19.15.17.11 NMAC the following information describes the closure requirements of closed-loop systems on XTO Energy Inc. (XTO) locations. This is XTO's standard procedure for all closed-loop systems. A separate plan will be submitted for any closed-loop system which does not conform to this plan.

### General Plan

XTO will close a drying pad used for a closed-loop system within six months from the date that XTO released the drilling or workover rig. XTO will note the date of the drilling or workover rig's release on form C-105 or C-103, filed with the division, upon the well's or workover's completion.

The closed-loop tank will be closed in accordance with 19.15.17.13 NMAC. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit Number NM01-0011) or IEI (Permit Number NM01-0010B) immediately following rig operations.

All remaining liquids will be transported and disposed of at the Basin Disposal, Inc facility (Permit Number NM01-005). As an alternative (in the event Basin Disposal refused liquids because of capacity considerations, and if proper inventory space is available for liquids transfer while meeting free board requirements), the liquids will be moved forward to a XTO temporary pit constructed in accordance with all specifications in NMAC Rule 19.15.17 for a well yet to be drilled. All specifications, limitations, and rules within the New Mexico Administrative Codes regulating this transfer of liquids will be strictly adhered to. As a third alternative, if Basin Disposal turns away the fluids because of capacity reasons, and the second transfer option is not available, XTO may elect to haul the fluids to IEI (Permit Number NM01-0010B) for final disposition.

The tanks will be removed from the location as part of the rig move. At the time of well abandonment the site will be reclaimed and re-vegetated to pre-existing conditions when possible.

## XTO Energy Inc. San Juan Basin Closed-Loop System Design and Construction Plan

In accordance with Rule 19.15.17.11 NMAC the following information describes the design and construction of closed-loop systems on XTO Energy Inc. (XTO) locations. This is XTO's standard procedure for all closed-loop systems. A separate plan will be submitted for any closed-loop system which does not conform to this plan.

#### General Plan

Our closed-loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will entail an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be of sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

1. Fencing is not required for an above ground closed-loop system.

2. It will be signed in compliance with 19.15.3.103 NMAC.

## XTO Energy Inc. San Juan Basin Closed-Loop Systems Maintenance and Operating Plan

In accordance with Rule 19.15.17.11 NMAC the following information describes the operation and maintenance of closed-loop systems on XTO Energy Inc. (XTO) locations. This is XTO's standard procedure for all closed-loop systems. A separate plan will be submitted for any closed-loop system which does not conform to this plan.

#### **General Plan**

The closed-loop tank will be operated and maintained; to contain liquids and solids, to aid in the prevention of contamination of fresh water sources, in order to protect public health and the environment. To attain the goal the following steps will be followed:

- The liquids will be vacuumed out and disposed of at the Basin Disposal, Inc. facility (Permit Number NM01-005). An alternative if available for liquids disposal, will be to move the liquids forward to a XTO temporary pit constructed in accordance with all specifications in NMAC Rule 19.15.17 for a well yet to be drilled. All specifications, limitations, and rules within the New Mexico Administrative Code regulating this transfer of liquids will be strictly adhered to. As a third alternative, if Basin Disposal turns away the fluids because of capacity reasons, and the second transfer option is not available, XTO may elect to haul fluids to IEI (Permit Number NM01-0010B) for final disposition.
- Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit Number NM01-0011) or IEI (Permit Number NM01-0010B) on a periodic basis to prevent over topping.
- 3. No hazardous waste, miscellaneous solids, waste, or debris will be discharged into, or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 4. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon discovery of the compromised tank, repairs will be enacted immediately.
- 5. All of the above operations will inspected and a log will be signed and dated daily during rig operations.