This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator COP					Lea	ise Name	JICAR	RILLA A	·		Well No10
_ocation of Well	: Unit L	etter _	0	Sec _	23	Twp_	026N	R	ge _	004W AP	I# <u>30-039-20117</u>
	Name of Reservoir or Pool			Pool	Type of Prod				Method of Prod		Prod Medium
Upper Completion	PC				Gas				Flow		Tubing
Lower Completion	MV				Gas				Flow		Tubing
,				Pr	e-Flow	/ Shut-In	Pressu	re Data	3		
Upper	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG		Stabilized?(Yes or No)
Completion	4/16/2013				368 hours				36		Yes
Lower	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG		Stabilized?(Yes or No)
Completion	4/16/2013				320 hours				299		Yes
Commenced a	t: 4/29/				200					or Lower): Lo	OWER
Time Lapsed Time (date/time) Since*				PRESSURE Upper zone Lower zone			1	rod Zone mperature		Remarks	
4/30/2013 8:54:00 AM 24		24		36		26			Checked pressures, flowed lower zone to 26#. Upper zone stayed at 36#.		
5/1/2013 8:55:00 AM 48				36 27				Checked pressures, lower zone flowing at 27#. Upper zone still at 36#.			
Production rate	during to	est			-						
Oil:	BPOD Based on:			Bt	Bbls. In Hrs.				Grav.		GOR
Gas		MC	FPD; Te	est thru (O	rifice or	Meter) _	· –				
				ħ.n	id-Tae	t Shut-In	Praseu	ıre Dat:	a		
Upper Completion	Hour, Date, Shut-In				Mid-Test Shut-In Pressure Length of Time Shut-In			ne Dale	SI Press. PSIG		Stabilized?(Yes or No)
Lower Completion	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG		Stabilized?(Yes or No)

(Continue on reverse side)

ca

Flow Test No. 2

Commenced at:		Zone Producing (Upper or Lower)									
Time	Lapsed Time	PRES	SURE	Prod Zone							
(date/time)	Since*	Upper zone	Lower zone	Temperature	Remarks						
		•		i i							
Draduation rate during	r toot				•						
Production rate during											
Oil: BPOI	D Based on:	Bbls. In	Hrs.		GravGOR						
Gas MCFPD; Test thru (Orifice or Meter)											
		,	,								
Remarks:											
Well flows to A Ridge Compressor.											
I hereby certify that the information herein contained is true and complete to the best of my knowledge.											
			and complete	e to the best of	my knowledge.						
Approved:	9/13	20 13	_ Opera	Operator: COP							
New Mexico Oil Co	onservation Division		By:	By: Travis Chavez							
Ву:			Title:	Title: Multi-Skilled Operator							
U Dep	uty of & Gas Ins District #3	pector,	-								
Title:	y 20, 2013										

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual
 completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.
 Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or
 chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or
 the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when
 requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously change restrictly the rest date.

which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).