This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Page 1 Revised June 10, 2003

W/e11

			wen
Operator	WPX ENERGY_	Lease Name Rosa Unit	No. 117 DK/GL

Location Of Well: Unit Letter D Sec 33 Twp 32N Rge 06W API # 30-0 4526046

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	2050 117 DK	Ga 5	F-100	C 59
Lower Completion	Rosa 117 GL	C-1 a. S	Flow	Tho

Pre-Flow Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	9:00 5-10-13	7 days	691	yes
Lower	Hour, Date, Shut-In	Length of Timé Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	9:00 5-10-13	7 days	405	yes

Flow Test No. 1

			TIOWIC	CBC 1 10.		
Commenced a	t (hour, date)*	8:00 5-1	7-13	Zone	producing (Up	oper or Lower): UPPer
Time (Hour, Date)	Lapsed Time Since*	Pro Upper Compl.	essure Lower Comp	.1	Prod. Zone Temp.	Remarks
9.40 5-18-13		271	406	/1.	Temp,	RCVD MAY 30 '13 OIL CONS. DIV.
5-19-13	48	213	412			DIST. 3
5-20-13	72	259	414			
5-21-13	96	S&2	419			off Cycle
5-22-13	120	267	422			,
5-23-13	144	235	423			

Production rate during test

Oil:	BOPD based on	Bbls. In	Hrs	Grav	GOR
Gas:	MCFPD; Test thru (Orifice or Meter):			

Mid-Test Shut-In Pressure Data

Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion				
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion				

(Continue on reverse side)

Flow Test No. 2

Commenced a	nt (hour, date)**		Zo	ne producing (U	pper or Lower):		
Time	ne Lapsed Time Pressure		essure	Prod. Zone	Remarks		
(Hour, Date)	Since**		Lower Compl.	Temp.			
				<u> </u>			
Production rate	during test						
Oil:	BOPD based	d on	_Bbls. In fice or Meter):	Hrs	Grav	GOR	
	MCFP	D; Test thru (Ori	fice or Meter):				
Remarks:							
I hereby certify	that the informat	tion herein contai	ned is true and com	nlete to the best	of my knowledge		
• •				piete to the oest	Of the knowledge.	·	
Approved		91	2013	Operator 2	WYX ENC	194	
New Mexico O	il Conservation I	Division				1	
				By <u></u> α	SON DIM		
·	1/7/			C.	all Te	ic.L	
By J	5-66	Gas Inspectorict #3		Title // /	wfx Ere Son Su eld Te		
m:41 -	Deputy On &	iot #3	,,,				
11tie	ا ا ا	101 % 0		E-mail Addr	ess		· · · ·
				Date 5	1-28-13		.*

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).