This form is not to be used for reporting packer leakage tests

NEW MEXICO OIL CONSERVATION DIVISION

Page 1

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Revised June 10, 2003

in Southeast Nev	v Mexico	NORTHWEST	142344 14413281		ACKER		We	-11		
Operator	WPX ENERGY Lease Name R					Unit		No. 185B DK/MV		
Location Of W	/ell: Unit Letter _	F Sec <u>16</u> Tv	vp <u>31N</u> R	.ge	06W_AP	I # 30-	-0 <u>4532734</u>			
	Name of Reservoir or Pool		Type of Prod.			Method of Prod.		Prod. Medium		
T.Y.	· · · · · · · · · · · · · · · · · · ·		(Oil or Gas)			(Flow or Art. Lift)		(Tbg. Or Csg.)		
Upper Completion	MesaVe	Gas			Flow		rba			
Lower Completion	Mesaverde Dakota		Source Life long		Flow		* 100			
		Pr	e-Flow Shut-	In P	ressure Da	ta				
Upper Completion	Hour, Date, Shut	Length of Time Shut-In			SI Press. Psig		Stabilized? (Yes or No)			
Lower Completion	Hour, Date, Shut	r, Date, Shut-In		Length of Time Shut-In		SI Press. Psig		Stabilized? (Yes or No)		
Flow Test No. 1										
Commenced				g (Up	g (Upper or Lower): Lowe 1					
Time (Hour, Date)	Lapsed Time Since*	Pre Upper Compl.	ssure Lower Com	sure Prod. Zo Lower Compl. Temp			ne Remarks			
11:10	zuhrs	143.	310			E				
6-4-13		144	162		7	-,	OIL CONS. DIV DIST. 3			
11:07	72 hrs	146	97	7 6			JUN 1 0 2013			
						.				
Production rate	e during test									
Oil:	BOPD based or	nBb	ls. In]	Hrs.		Grav.	GOR		
Gas: 2	O MCFPI	D; Test thru (Orif	ice or Meter):	0	rifi	-				
		Mi	id-Test Shut-	In Pr	essure Da	ta				
Upper Completion	Hour, Date, Shut-	Length of Time Shut-In			SI Press. Psig		Stabilized? (Yes or No)			
Lower Completion	Hour, Date, Shut-In		Length of Time Shut-In			SI Press. Psig		Stabilized? (Yes or No)		

(Continue on reverse side)

Flow Test No.

			riow lest N	(O. Z				
Commenced a	at (hour, date)**		one producing (Upper or Lower):					
Time (Hour, Date)	Lapsed Time Since**	Pressure Upper Compl. Lower Compl		Prod. Zone Temp.	Remarks			
(Hour, Date)	·	opper compi.	Lower Compt.	Temp.	·			
Production rate		don	Rhle In	Urs	Grav GOR			
Gas:	MCFP	D: Test thru (Ori	1115	Glav. GOR				
Remarks:		_, (
			ned is true and com	-	-			
Approved 9/13 20 13				Operator WPX ENERGY				
New Mexico O	oil Conservation I	Division		Operator wpx energy By Mark Glover Title pumper				
By	Deputy Off &	Gas Inspecto	Title pumper					
Title District #3				E-mail Address				
	•			Date /a	-6-13			

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- of a pipeline connection the flow period shall be three hours.

 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).