This form is not to be used for reporting acker leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR			Leas	se Name <u>TRAIL</u>	Well No. 3		
_ocation of We	ell: Unit L	etterI	Sec07	Twp032N	Rge	008W API	# 30-045-24622
	Na	ame of Reservoir or	Pool	Type of Prod		Method of Prod	Prod Medium
Upper Completion	MV		Ga	Gas			Tubing
Lower Completion	DK			Gas			Tubing
•			Pre-Flow	Shut-In Pressu	re Data		
Upper Completion	Hour, Date, Shut-In 5/4/2013			Length of Time Shut-In 180 hours		ss. PSIG 330	Stabilized?(Yes or No) Yes
Lower Completion	Hour, Date, Shut-In 5/4/2013		Length	Length of Time Shut-In 107 hours		ss. PSIG 996	Stabilized?(Yes or No) Yes
	.1,				· · · · · · · · · · · · · · · · · · ·		
			. <u> </u>	low Test No. 1	Mann.	м.	
Commenced	at: 5/8/2	2013 11:13:00 A	M	Zone Pro	oducing (Upper	r or Lower): LC	OWER
Time (date/time)		Lapsed Time		PRESSURE			
		Since*	Upper zone	E Lower zone	Temperature	Remarks	
5/9/2013 11:05:00 AM		24	330	178	57	Temp was taken at meter.	
5/10/2013 11:30:00 AM 48		48	330	175	60	Temp was taken at meter	
5/11/2013 12:02:00 PM 73		332	173	58	Temp was taken at meter		
Production rate	e during te	est					
oil:BPOD Based on:Bb		Bbls. In	ls. In Hrs		Grav.	GOR	
Gas		MCFPD; Te	st thru (Orifice or	Meter)			
	·		Mid-Test	Shut-In Pressu	ıre Data		
	Hour, Date, Shut-In			Length of Time Shut-In		ss. PSIG	Stabilized?(Yes or No)
Upper Completion	Hour, Da	te, ondi-in	Longe		1		·

(Continue on reverse side)

Ca

OIL CONS. DIV DIST. 3

MAY 2 2 2013

Flow Test No. 2

Commenced at:			Zone Pro	Zone Producing (Upper or Lower)							
Time	Lapsed Time	PRESSURE		Prod Zone							
(date/time)	Since*	Upper zone	Lower zone	Temperature	Re	emarks					
						·					
				·							
Production rate during	test .										
Oil:BPOD	Based on:	Bbls. In	Hrs.	(Grav.	GOR					
GasMCFPD; Test thru (Orifice or Meter)											
Remarks:											
						1					
I hereby certify that the information herein contained is true and complete to the best of my knowledge.											
Approved:	9/12	20 13	Onerai	tor: BR							
New Mexico Oil 20			_	By: James Kirby							
1//		-	_								
By: Deputy Oil & Gas Inspector,			riue	Title: Multi-Skilled Operator							
Title:	District #3		Date: _	Date: Monday, May 20, 2013							

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).