State of New Mexico Energy Minerals and Natural Resources Department

Form C-144 July 21, 2008

District II

1301 W. Grand Ave., Artesia, NM 88210

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

Oil Conservation Division

District III	1220 South St. Francis Dr.	•
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the
1220 S. St. Francis Dr., Santa Fe, NM 87505		appropriate NMOCD District Office.
V	Pit, Closed-Loop System, Below-Gr	
·•	osed Alternative Method Permit or C	losure Plan Application
Type of action:	Permit of a pit, closed-loop system, below-grad	le tank, or proposed alternative method
105	X Closure of a pit, closed-loop system, below-gra	ide tank, or proposed alternative method
	Modification to an existing permit	
	Closure plan only submitted for an existing per below-grade tank, or proposed alternative meth	mitted or non-permitted pit, closed-loop system,
Instructions: Please submit one ap		loop system, below-grade tank or alternative request
_	f this request does not relieve the operator of liability should operation	
environment. Nor does approval reli	eve the operator of its responsibility to comply with any other applic	able governmental authority's rules, regulations or ordinances.
Operator: Burlington Resources Oi	1 & Gas Company, LP	OGRID#: 14538
Address: PO Box 4289, Farmingto		
Facility or well name: Huerfano Un	it HZMC 1H	
API Number: 30	0-045-35370 OCD Permit Nu	mber:
U/L or Qtr/Qtr: M(SW/SW) Section	on: 9 Township 26N Range:	10W County: San Juan
Center of Proposed Design: Latitude		107.90843 °W NAD: ### X 1983
Surface Owner: Federal	X State Private Tribal Trust or In	dian Allotment
Permanent Emergency X C Lincd Unlined Li	.11 NMAC kover favitation P&A (MUD Pre-set) ner type: Thickness mil LLDPE	RCVD DEC 6 '13 OIL CONS. DIV. HDPE PVC Other DIST. 3
String-Reinforced Liner Seams: Welded Fa	nctory Other Volume:	bbl Dimensions L x W x D
Ellier Scallis. Weided 172	Citory Other Volume.	
Type of Operation: P&A Drying Pad Above Grou Lined Unlined Line	ion H of 19.15.17.11 NMAC Drilling a new well	s to activities which require prior approval of a permit or HDPE PVD Other
	of 19.15.17.11 NMAC bl Type of fluid: tection Visible sidewalls, liner, 6-inch lift and Visible sidewalls only Other mil HDPE PVC Other	automatic overflow shut-off
5 Alternative Method:		
Submittal of an exception request is req	uired. Exceptions must be submitted to the Santa Fe Envi	ronmental Bureau office for consideration of approval.

Form C-144

Oil Conservation Division

Page 1 of 5



Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks)			
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)			
Four foot height, four strands of barbed wire evenly spaced between one and four feet			
Alternate. Please specify			
7			
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)			
Screen Netting Other			
Monthly inspections (If netting or screening is not physically feasible)			
8 Signs: Subsection C of 19.15.17.11 NMAC			
12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers		ļ	
X Signed in compliance with 19.15.3.103 NMAC			
A Signed in compitance with 17.15.5.105 Notice			
9		ĺ	
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.			
·			
Please check a box if one or more of the following is requested, if not leave blank:	: 1		
X Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for cons (Cavitation pit for Pre-set)	ideration of ap	proval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.		ĺ	
Exception(s). Reducts must be submitted to the Santa Fe Environmental Buleau office for consideration of approval.			
10			
Siting Criteria (regarding permitting): 19.15.17.10 NMAC			
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable			
source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for			
consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria			
does not apply to drying pads or above grade-tanks associated with a closed-loop system.		ĺ	
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.	□Yes	По	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake	Yes	По	
(measured from the ordinary high-water mark).		□.,,	
- Topographic map; Visual inspection (certification) of the proposed site			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial	□Vcs	□No	
application.		[]	
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)	□NA		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	L_1	1	
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	∐ ^{No}	
(Applied to permanent pits)	∐NA		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image			
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering	Yes	∐No	
purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.			
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	Yes	∐No	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality			
Within 500 feet of a wetland.	Yes	□No	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	_		
Within the area overlying a subsurface mine.	Yes	□No	
"- Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	· · · · · · · · · · · · · · · · · · ·		
Within an unstable area.	Yes	No	
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources, USGS; NM Geological			
Society; Topographic map Within a 100-year floodplain	Yes	□No	
- FEMA map		□ ,™	
•	I		

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of
19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API or Permit
12
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9
NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API
Previously Approved Operating and Maintenance Plan API
13
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Climatological Factors Assessment Contified Engineering Design Plans - beset upon the convention requirements of 10.15.17.11.NMAC
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC
Quality Control/Quality Assurance Construction and Installation Plan
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Nuisance or Hazardous Odors, including H2S, Prevention Plan
Emergency Response Plan
Oil Field Waste Stream Characterization Monitoring and Inspection Plan
Erosion Control Plan
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
14
Proposed Closure: 19.15.17.13 NMAC
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type: Drilling Workover Emergency X Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative
Proposed Closure Method: Waste Excavation and Removal
Waste Removal (Closed-loop systems only)
On-site Closure Method (only for temporary pits and closed-loop systems)
In-place Burial On-site Trench
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
15
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.
Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection 1 of 19.15.17.13 NMAC
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

16 Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Instructions: Please identify the facility or facilities for the disposal of liquids, drilling j	Tanks or Haul-off Bins On	ly: (19.15.17.13.D NMAC)		
facilities are required.	nuias una arm cunngs. Ose	инасттет у тоге тип то		
Disposal Facility Name: Envirotech / JFJ Landfarm % IEI E	Disposal Facility Permit #:	NM-01-0011 / NM-01-00	10B	
Disposal Facility Name: Basin Disposal Facility	Disposal Facility Permit #:	NM-01-005		
Will any of the proposed closed-loop system operations and associated activities Yes (If yes, please provide the information No	s occur on or in areas that w	vill not be used for future s	service and	
Required for impacted areas which will not be used for future service and operations: Soil Backfill and Cover Design Specification - based upon the appropriat Re-vegetation Plan - based upon the appropriate requirements of Subsect	•		AC .	
Site Reclamation Plan - based upon the appropraite requirements of Subs	section G of 19.15.17.13 N	MAC		
17 <u>Siting Criteria (Regarding on-site closure methods only:</u> 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan certain siting criteria may require administrative approval from the appropriate district office office for consideration of approval. Justifications and/or demonstrations of equivalency are r	Recommendations of acceptable or may be considered an except	tion which must be submitted to		
Ground water is less than 50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS: Data obtai	ned from nearby wells		Yes N/A	No
Ground water is between 50 and 100 feet below the bottom of the buried waste			Yes	□No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtain	ned from nearby wells		□N/A	
Ground water is more than 100 feet below the bottom of the buried waste.			Yes	No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtain	ned from nearby wells		□ N/A	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significa (measured from the ordinary high-water mark).	nt watercourse or lakebed, sir	ıkhole, or playa lake	Yes	No
- Topographic map; Visual inspection (certification) of the proposed site			-	
Within 300 feet from a permanent residence, school, hospital, institution, or church in ex - Visual inspection (certification) of the proposed site; Aerial photo; satellite image	istence at the time of initial ap	oplication.	∐ Yes	∐No
William Co. L. C.	<i>a</i>		Yes	∐No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than purposes, or within 1000 horizontal fee of any other fresh water well or spring, in exister - NM Office of the State Engineer - iWATERS database; Visual inspection (certification)	nce at the time of the initial ap			
Within incorporated municipal boundaries or within a defined municipal fresh water well pursuant to NMSA 1978, Section 3-27-3, as amended.		pal ordinance adopted	Yes	No
Written confirmation or verification from the municipality; Written approval obtain Within 500 feet of a wetland	ned from the municipality		Yes	□No
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspec	ction (certification) of the prop	posed site		
Within the area overlying a subsurface mine.			Yes	□No
- Written confirantion or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area.			Yes	□No
- Engineering measures incorporated into the design; NM Bureau of Geology & Min Topographic map	eral Resources; USGS; NM C	Geological Society;		
Within a 100-year floodplain. - FEMA map			Yes	□No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of	of the following items mus	t bee attached to the closu	re plan. Plea	se indicate,
by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate	requirements of 10 15 17	IO NMAC		
Proof of Surface Owner Notice - based upon the appropriate requirement	•			İ
Construction/Design Plan of Burial Trench (if applicable) based upon the				
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC				
X Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC				
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
X Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)				
Soil Cover Design - based upon the appropriate requirements of Subsection				
Re-vegetation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subs				

19 Operator Application Certification:
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.
Name (Print): Title:
Signature: Date:
e-mail address: Telephone:
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 12/1/2013
Title: OMPtance Office OCD Permit Number:
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 10/20/2012
Closure Method: Waste Excavation and Removal On-site Closure Method X Alternative Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain.
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.
Disposal Facility Name: Disposal Facility Permit Number:
Disposal Facility Name: Disposal Facility Permit Number:
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations? Yes (If yes, please demonstrate complitane to the items below) No
Required for impacted areas which will not be used for future service and operations: Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique
24
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (if applicable)
Disposal Facility Name and Permit Number
Soil Backfilling and Cover Installation
Re-vegetation Application Rates and Seeding Technique
Site Reclamation (Photo Documentation) On-site Closure Location: Latitude: 36.49729 Longitude: 107.90843 NAD 1927 X 1983
On-site Crosure Education. Latitude. 30.47/29 Longitude. 107.90043 14/LD 1927 A 1983
25
25 Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that
the closure complies with all applicable closure requirements and conditions specified in the approved closure plan
Name (Print): Kenny Davis Title: Staff Regulatory Technician
Signature: Date: 12/5/2013
c-mail address: kenny.r.davis@conocophillips.com Telephone: 505-599-4045

Burlington Resources Oil & Gas Company, LP MUD PRE SET DRILL

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

Burlington Resources Oil & Gas Company, LP may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- 2. Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

Closed Loop Closure Plan:

1. Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) within 6 months from the date that the drilling rig is released.

2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. BR shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

Purity

Source No. two (better quality)

Source No. two (better quality)

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS

Burlington Resources Oil & Gas Company, LP Cavitation Pit for Closed-Loop Locations

Design:

Burlington Resources Oil & Gas Company, LP will use a cavitation pit plan when the surface casing will be pre-set on closed-loop locations. The drill cuttings will be stockpiled on the surface.

Operations and Maintenance:

The cavitation pit will be operated and maintained as follows:

- 1. Only Fresh water and air will be used in the drilling of the surface casing.
- 2. The Cement used will be: Neat Cement with no additives.
- 3. All of the fluids will be removed within 48hrs after drilling.
- 4. A representative five point composite sample will be taken of the drill cuttings, after the setting of the surface casing is complete, using sampling tools and all samples will be tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the testing criteria is not met, all contents will be dug and hauled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

5. The NMOCD will be notified via email of the test results of the cavitation surface as follows:

Components	Tests Method	Limit (mg/Kg)	Results
Benzene	EPA SW-846 8021B or 8260B	0.2	ND
BTEX	EPA SW-846 8021B or 8260B	50	ND
TPH	EPA SW-846 418.1	2500	27.9
GRO/DRO	EPA SW-846 8015M	500	ND
Chlorides	EPA 300.1	500	11.4

Closure Plan:

- 1. The NMOCD will be notified of the sample results and the intent to start the closure process 3-7 days prior to the drill cuttings being transported, moved, or distributed on location.
- 2. In the event the criteria are not met, all solids and liquids will be removed and disposed of at Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B).
- 3. Testing results will be submitted with the Closure Report of the well locations Closed-Loop Permit on Form C-144.

Burlington Resources is aware that approval of this plan does not relieve Burlington Resources of liability should operations result in pollution of surface water, ground water, or the environment. Nor does approval relieve ConocoPhillips of its responsibility to comply with any other applicable governmental authority's rules and regulations.



Report Summary

Client: ConocoPhillips

Chain of Custody Number: 6300

Samples Received: 10-17-12


Job Number: 96052-1706

Sample Number(s): 63464

Project Name/Location: Huerfano Unit HZMC 1H/ MOTE 212

Entire Report Reviewed By: Well Jugge Date: 10-18-12

The analytical results in this report are based upon information supplied by you, the client, and are for your exclusive use. If you have any questions regarding this data package, please do not hesitate to call.





EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	ConocoPhillips	Project #:	96052-1706
Sample ID:	Pre-Set Cuttings	Date Reported:	10-17-12
Laboratory Number:	63464	Date Sampled:	10-16-12
Chain of Custody No:	6300	Date Received:	10-17-12
Sample Matrix:	Sọil	Date Extracted:	10-17-12
Preservative:	Cool	Date Analyzed:	10-17-12
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)	
Gasoline Range (C5 - C10)	ND	0.2	
Diesel Range (C10 - C28)	ND	0.1	
Total Petroleum Hydrocarbons	ND		

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Huerfano Unit HZMC 1H/ MOTE 212





EPA Method 8015 Modified Nonhalogenated Volatile Organics **Total Petroleum Hydrocarbons**

Quality Assurance Report

Client:

QA/QC

Project #:

N/A

Sample ID:

1016TCAL QA/QC

Date Reported:

10-17-12

Laboratory Number:

63463

Date Sampled:

N/A

Sample Matrix:

Methylene Chloride

Date Received:

N/A

Preservative: Condition:

N/A N/A

Date Analyzed: Analysis Requested: 10-17-12 **TPH**

⇒I-Cal Date ∾

I-Cal RF: 9.9960E+02

1.0000E+03

0.04% 0 - 15%

C-Cal RF: % % Difference Accept: Range

Gasoline Range C5 - C10 Diesel Range C10 - C28

10-17-12 10-17-12

9.9960E+02

1.0000E+03

0.04%

0 - 15%

Blank Conc. (mg/L - mg/Kg) Gasoline Range C5 - C10

Concentration ND

Detection Limit 0.2

Diesel Range C10 - C28

ND

0.1

Total Petroleum Hydrocarbons

ND

Duplicate Conc. (mg/Kg) Gasoline Range C5 - C10

Sample Duplicate: ND ND

% Difference: Accept: Range 0.0%

0 - 30%

Diesel Range C10 - C28

ND

ND

0.0%

0 - 30%

Spike Conc. (mg/Kg) Gasoline Range C5 - C10 Diesel Range C10 - C28

Sample ND

ND

Spike Added 250 250

Spike Result 256

257

102% 103% Accept: Range 75 - 125% 75 - 125%

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Was

SW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 63463-63464





EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	ConocoPhillips	Project #:	96052-1706
Sample ID:	Pre-Set Cuttings	Date Reported:	10-17-12
Laboratory Number:	63464	Date Sampled:	10-16-12
Chain of Custody:	6300	Date Received:	10-17-12
Sample Matrix:	Soil	Date Analyzed:	10-17-12
Preservative:	Cool	Date Extracted:	10-17-12
Condition:	Intact	Analysis Requested:	BTEX
	÷	Dilution	50

	Dilution:	50
		Det.
· •	Concentration	Limit
Parameter	(ug/Kg)	(ug/Kg)
Benzene	ND	10.0
Toluene	ND	10.0
Ethylbenzene	ND	10.0
p,m-Xylene	ND	10.0
o-Xylene	ND	10.0
Total BTEX	ND	

ND - Parameter not detected at the stated detection limit.

Parameter	Percent Recovery
Fluorobenzene	85.3 %
1,4-difluorobenzene	97.4 %
Bromochlorobenzene	102 %
	Fluorobenzene 1,4-difluorobenzene

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846.

USEPA, December 1996.

Comments: Huerfano Unit HZMC 1H/ MOTE 212





EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A		Project #:		N/A	
Sample ID:	1017BCAL QA/Q	C	Date Reported:		10-17-12	
Laboratory Number:	63464		Date Sampled:		N/A	
Sample Matrix:	Soil		Date Received:		N/A	
Preservative:	ÑΑ		Date Analyzed:		10-17-12	
Condition:	N/A		Analysis:		BTEX	
			Dilution:		50	
Detection Limits (ug/L) 1.4106E-05	Accept. Range 0-159	0.000	∴ Conc ND	Limit 0.2	23
Toluene	1.1755E-05	1.1755E-05	0.000	ND	0.2	
Ethylbenzene	1.2446E-05	1.2446E-05	0.000	ND	0.2	
p,m-Xylene	8.9996E-06	8.9996E-06	0.000	ND	0.2	
o-Xvlene			0.000			

Duplicate Conc. (ug/Kg)	Sample, Du	plicate	ৣ%Diff.⊹ৣ	Accept Range	Detect: Limit
Benzene	ND	ND	0.00	0 - 30%	10
Toluene	ND	ND	0.00	0 - 30%	10
Ethylbenzene	ND	ND	0.00	0 - 30%	10
p.m-Xylene	ND	ND	0.00	0 - 30%	10
o-Xylene	ND	ND	0.00	0 - 30%	10

Spike Conc. (ug/Kg)	Sample Amo	unt Spiked Spik	ed Sample : % F	Recovery	Accept Range
Benzene	ND	2500	2500	1,00	39 - 150
Toluene	ND	2500	2550	102	46 - 148
Ethylbenzene	ND	2500	2570	103	32 - 160
p,m-Xylene	ND	5000	5180	104	46 - 148
o-Xylene	ND	2500	2600	104	46 - 148

ND - Parameter not detected at the stated detection limit.

Dilution: Spike and spiked sample concentration represent a dilution proportional to sample dilution.

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,


December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using

Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 63463-63464





TOTAL PETROLEUM HYDROCARBONS

Client:	ConocoPhillips	Project #:	96052-1706
Sample ID:	Pre-Set Cuttings	Date Reported:	10-17-12
Laboratory Number:	63464	Date Sampled:	10-16-12
Chain of Custody No:	6300	Date Received:	10-17-12
Sample Matrix:	Soil	Date Extracted:	10-17-12
Preservative:	Cool	Date Analyzed:	10-17-12
Condition:	Intact	Analysis Needed:	TPH-418.1

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

27.9

6.6

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments: Huerfano Unit HZMC 1H/ MOTE 212





EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS QUALITY ASSURANCE REPORT

Client:

QA/QC

Project #:

N/A

Sample ID:

QA/QC

Date Reported:

10-17-12

Laboratory Number:

10-17-TPH.QA/QC 63464

Date Sampled:

N/A

Sample Matrix:

Freon-113

Date Analyzed:

10-17-12

Preservative: Condition:

N/A N/A Date Extracted: Analysis Needed: 10-17-12 **TPH**

Calibration 1-Cal Date

07-11-12

10-17-12

C-Cal Date I-Cal RF: C-Cal RF: % Difference Accept Range

1,660

1,720

3.6%

+/- 10%

Blank Conc. (mg/Kg)

Concentration

Detection Limit

TPH

ND

6.6

Duplicate Conc. (mg/Kg

Sample.

Duplicate % Difference Accept. Range

TPH

TPH

27.9

28.6

2.6%

+/- 30%

Spike Conc. (mg/Kg)

Sample 27.9

Spike Added, Spike Result % Recovery. Accept Range 2,000

1,730

85.3%

80 - 120%

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

QA/QC for Sample 63464.





Chloride

Client: Sample ID: ConocoPhillips

Project #:

96052-1706

Pre-Set Cuttings

Date Reported:

10-17-12

Lab ID#:

63464

Date Sampled:

10-16-12

Sample Matrix:

Soil

Date Received:

10-17-12

Preservative:

Cool

Date Analyzed:

10-17-12

Condition:

Intact

Chain of Custody:

6300

Parameter

Concentration (mg/Kg)

Total Chloride

11.4


Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983.

Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

Huerfano Unit HZMC 1H/ MOTE 212





CHAIN OF CUSTODY RECORD

Client: CONOCOPHILLIPS	. E	ngineer:(etwork #:	/ Rig: Huerfar Cara Blais 10340623	o Unit I	HZMC 1H /	MOTE 212	<u></u>	 112			-			ANAL	YSIS	/ PAR	AME	TERS					
Client Address: RE6. 307# ST. DEP. Client Phone No.: 605-326-953	_	ctivity Cod lant: HZF ser ID: M ignature: ate 10-1	de: -3 CINNSK 	QUO Ross	62-17 ET THO				. ≥	BTEX (Method 8021)	VOC (Method 8260)	RCRA 8 Metals	Cation / Anion		TCLP with H/P		TPH (418.1)	CHLORIDE			-	Sample Cool	Sample Intact
Sample No./ Identification	Sample Date	Sample Time	Lab No.		ample Vatrix	No./Volume of Containers			TPH (BTEX	VOC (RCR/	Cation	PC 1	TCLP	PAH	TPH	CHLC				Samp	Samp
PRE-SET CUTTINGS	10/16/12	1635	63464	Soil) Solid	Sludge Aqueous	1/402.			X	×							X	X				X	X
· 				Soil Solid	Sludge Aqueous																		
				Soil Solid	Sludge Aqueous																		
			•	Soil Solid	Sludge Aqueous												ı						
				Soil Solid	Sludge Aqueous																		
				Soil Solid	Sludge Aqueous																		
				Soil Solid	Sludge Aqueous												_						
				Soil Solid	Sludge Aqueous																		
				Soil Solid	Sludge Aqueous												_						
			1.00 - 1.00	Soil Solid	Sludge Aqueous										-	-							
Relinquished by: Signa	ture)	San			Date 10-/6-12	Time 1744			ed by:				ب <u>د</u>		·				\	10.	1/12	Tin	- 1
Relinquished by: (Signa	ture)						Re	eceive	ed by:	(Signa	ature)	V								·		;	
Relinquished by: (Signal	ture)						Re	eceive	ed by:	(Signa	ature)						•						
Rust - 24	'AR	TURN	AMUDA		EUVI	ROT	E	Cl	\$	N	C	_											

5796 U.S. Highway 64 • Farmington, NM 87401 • Tel 505-632-0615