BURE SUNDRY N Do not use this fo abandoned well.	3b. 1 720-	EMENT S ON WELLS fill or to re-enter ar for such proposal	2013 Icid Offic Rhanaut	5. Lease Serial No. NMNM 118128 6. If Indian, Allottee or N/A 7. If Unit of CA/Agreet N/A 8. Well Name and No. Gallo Canyon Unit M 9. API Well No. 30-043-21179 10. Field and Pool or E: Counselors Gallup/D 11. Country or Parish, S	nent, Name and/or No. 27-2306 01H xploratory Area akota
BHL: Sec 35, T23N, R6W 330' FSL and 335' FWL				Sandoval	
	X THE APPROPRIATE BOX(ES	,,,,,,,,	E OF NOTICI	,	R DATA
TYPE OF SUBMISSION Notice of Intent Subsequent Report Final Abandonment Notice 13. Describe Proposed or Completed Opthe proposal is to deepen directional Attach the Bond under which the worfollowing completion of the involve testing has been completed. Final Address the streng for Set 20" 94# conductor 11/19/13. Set Well spudded 11/22/13. Set surface casing and cemented 11. Hole diameter: 12-25", casing diameters: 19" 519"TVD/MD. On 11/23/13 pumped 185sks Type II to surface. WOC 9.5 hours for surface Float collar at 475"TVD/MD. TOC at set Tested BOP 11/23/13 to 3000# for 30	Ily or recomplete horizontally, giv ork will be performed or provide t ad operations. If the operation res (bandonment Notices must be file final inspection.) depth: 74'. 100sks Type I Nea /22/13. Gelled freshwater mud ter: <u>9.625"</u> , casing weight and s I Cement +1% bwoc CaCl + 0. is casing.	Deepen Fracture Treat New Construction Plug and Abandon Plug Back details, including estimate <i>ve</i> subsurface locations and the Bond No. on file with E sults in a multiple completic ed only after all requiremen at cement mixed at 16ppg system. grade: <u>36ppf J55</u> LTC. D .25 lbs/sk cello flake + 0.	Produc Reclar Recon Tempo Water d starting date measured and BLM/BIA. Re on or recomple ts, including re p.	ction (Start/Resume) mation nplete orarily Abandon Disposal e of any proposed work 1 true vertical depths of equired subsequent repo- etion in a new interval, eclamation, have been of 5" from 0- <u>522</u> 'TVD/M -52A. Yield 1.38 cuft/	all pertinent markers and zones. orts must be filed within 30 days a Form 3160-4 must be filed once completed and the operator has D. <u>Casing set</u> from surface to sk. Mixed at 14.6 ppg. 1 <u>8bbls circ.</u>
Started drilling out float collar (tagged	d at 454') on 11/24/13.				ACCEPTED FOR RECORD
14. Thereby certify that the foregoing is truning (Printed/Typed) Robynn Haden	ie and correct.	Title Enginee			DEC 0 4 2013 FAANSMOTON FIELD ON NOL
Signature 964	Ada	Date /	1/25,	//3	BY_TL_Salvers
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by Conditions of approval, if any, are attached, that the applicant holds legal or equitable til entitle the applicant to conduct operations 11 Title 18 U.S.C. Section 1001 and Title 43 U fictitious or fraudulent statements or repres	tle to those rights in the subject leas hereon. J.S.C. Section 1212, make it a crime	e for any person knowingly a	nd willfully to		or agency of the United States any false,
(Instructions on page 2) NMOCDA					

.