ĺ								
·	Form 3160-5 (February 2005) LIC 23 2013 DEPARTMENT OF THE INTERIO BUREAU OF LAND MANAGEMI	ENT				FORM APPI OMB No. 10 Expires: March	04-0137	
, <b>.</b> 4	Sun Field Office SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an			5. Lease Serial No. NMSF-078360				
Q	abandoned well. Use Form 3160-3 (APD) for such proposals.			6. If Indian, A	llottee or Tribe	e Name		
	SUBMIT IN TRIPLICATE – Other instruction	·····	·	<i>ui</i> 3.	7. If Unit of CA/Agreement, Name and/or No.			
	1. Type of Well							
	Oil Well Gas Well Other			8. Well Name and No. Chaco 2306-19M #191H				
	2. Name of Operator	2. Name of Operator			9. API Well No.			
	WPX Energy Production, LLC       3a. Address     3b. Phone No. (in		irea code)		30-043-21139 10. Field and Pool or Exploratory Area			
	PO Box 640 Aztec, NM 87410 505-333-1822	cinue ur	reu couej		Lybrook Gallup			
	4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. Country or Parish, State			
ρ	SHL:1236' FSL & 287' FWL SEC 19 23N 6W BHL: 382' FSL & 342' FWL SEC 24 23N 7W				Sandoval County, NM			
<b>}</b>	12. CHECK THE APPROPRIATE BOX(ES) TO IN	DICATE	E NATUR	E OF NOTIC	E, REPORT OR	OTHER DAT	`A	······
	TYPE OF SUBMISSION			E OF ACTIO	1			
	Notice of Intent			Production (St	art/Resume)	Water S	hut-Off	
	Alter Casing Fracture Tre			Reclamation		Well In		
	Subsequent Report			Recomplete				<u>)n</u>
	Einel Abandarment	andon		Temporarily A	bandon			
Final Abandonment Convert to Plug Back Water Disposal								
	13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)						f	
	WPX Energy requests a fourth extension to the 30 day flare period per NTL-4A. The current extension is through 12/31/13. This well is dedicated to Beeline and they are in the process of securing Right-of-Way through the BLM FFO and have not yet received authorization for the their 299 application. During the time that we need to continue flaring gas, while waiting on pipeline connection, WPX would propose to temporarily place a trailer mounted refrigeration unit on site to recover natural gas liquids. This would reduce VOCs going to flare approximately 66%. Please see attached proposal.						e	
	Attached is the latest gas analysis for this well with a recap of samples taken since gas was first available. This well is currently flowing at rate on 350 mcf/pd						'pd	
	Authorization granted until Do days following Descance of approved BLM ROW application							
						<u></u>		
14. Thereby certify that the folegoing is true and correct.								
_	Larry Higgins	Title	e Permit	Supervisor		0	IL CONS. DIV	`u
0151.3								
-	Signature THIS SPACE FOR FED		e 12/23/1 OR ST					—
Approved by								
_	Conditions of approval, if any, are attached. Approval of this notice does not wa or certify that the applicant holds legal or equitable title to those rights in the sul lease which would entitle the applicant to conduct operations thereon.	arrant	Title Office	Ketr. E	<u>-nç</u>	Date <b>(</b>	6/14	
-	Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime United States any false, fictitious or fraudulent statements or representations as					any department	or agency of the	

\$

÷

£

(

NMOCD  $\sim$ 

.

-



WPX Energy Production, LLC

In regards to the Mancos/Gallup oil development project WPX Energy currently has underway in Rio Arriba, Sandoval and San Juan counties, WPX Energy would like to propose the following changes in operations as a pilot program to reduce emissions and generate revenue from flare gas:

1) Temporarily place on a well site one 360 Mcf/d trailer mounted mobile refrigeration unit (Shown in Figure 1) downstream of the separator and upstream of the flare stack.




Figure 1: Recapture Solution's trailer mounted mobile refrigeration unit (MRU).

2) Temporarily place a Porta Pak style 18,000 gallon, 108" diameter, ~41' long, 250psi liquids tank with tripod dry breakaway loading valves and ESVs. (Shown in Figure 2)




Figure 2: Recapture Solutions' portable liquids storage tank.

3) One 100kW to 150kW natural gas or propane powered generator to power the MRU.

### **OBJECTIVE:**

WPX Energy would like to deploy Recapture Solutions' systems to reduce the emissions from the flare stack during the approved flaring periods and to generate gross revenue by selling a portion of the well gas to Recapture Solutions, LLC.

Recapture Solutions, LLC estimates a reduction of flare emissions for a 'typical' Mancos/Gallup horizontal oil well as follows:

Estimated VOC reduction (%): 66% Estimated VOC reduction (t / mo, open flare): 1.25 Estimated CO2 reduction (%): 21% Estimated CO2 reduction (t / mo, complete combustion): 240.72

This operation will only take place on well sites that are awaiting pipeline connections and this operation will only take place during the approved flaring period for a specified well site.

## **OPERATIONS:**

Recapture Solutions, LLC will operate all of the equipment in the refrigeration system described above. The mobile refrigeration unit will be monitored continuously via satellite and a trained technician provided by Recapture Solutions, LLC will be onsite once a day to verify correct operations of the refrigeration equipment. The mobile refrigeration unit is equipped with redundant safety systems such as but not limited to: low/high pressure shut down controls, ESD system, dry break away loading valves, pressure relief valves and jersey barriers around the storage trailer. A simplified process flow diagram is shown in figure 4.




Figure 3: Example layout of a well site utilizing Recapture Solutions systems. The three labeled components consist of Recapture Solutions' equipment.

WPX Energy's environmental, health and safety department together with the operations group and Recapture Solutions' engineers have successfully completed a process hazard assessment of Recapture Solutions' refrigeration unit in accordance with WPX Energy's company policy.

The complete Process Hazard Assessment documentation is available upon request.




Figure 4: Process Flow Diagram

## LOCATION

In some instances, WPX Energy will have flow back or production operations before the gas gathering pipeline is tied in to the well site. There are multiple sites that WPX Energy would like to pilot this technology in an effort to reduce the environmental impact of the Mancos/Gallup development project as well as minimize the lost value associated with flaring activity.

WPX Energy has identified the following location as most suitable for testing the effectiveness of this technology:

Chaco 2306-19M #191H, API No. 30-043-21139



2030 Afton Place Farmington, NM 87401 (505) 325-6622

Analysis No: WP130228 Cust No: 85500-10995

# Well/Lease Information

Customer Name:	WPX ENERGY PRODUCTION, LLC	Source:	N/A
Well Name:	CHACO 2306-19M #191H	Pressure:	616 PSIG
County/State:		Sample Temp:	DEG. F
Location:		Well Flowing:	
Field:		Date Sampled:	12/04/2013
Formation:		Sampled By:	ART ALSUP
Cust. Stn. No.:		Foreman/Engr.:	CODY BOYD

#### Remarks:

RUN #04-05; OPERATOR CODE #9024

		Analysis	·	
Component::	Mole%:	**GPM:	*BTU:	*SP Gravity:
Nitrogen	6.057	0.6690	0.00	0.0586
<u>C</u> O2	0.375	0.0640	0.00	0.0057
Methane	65.458	11.1420	661.13	0.3626
Ethane	13.479	3.6190	238.54	0.1399
Propane	9.749	2.6970	245.29	0.1484
Iso-Butane	1.225	0.4020	39.84	0.0246
N-Butane	2.646	0.8380	86.32	0.0531
I-Pentane	0.471	0.1730	18.84	0.0117
N-Pentane	0.349	0.1270	13.99	0.0087
Hexane Plus	0.191	0.0860	10.07	0.0063
Total	100.000	19.8170	1314.02	0.8197

\* @ 14.730 PSIA DRY & UNCORRECTED FOR COMPRESSIBILITY

\*\*@ 14.730 PSIA & 60 DEG. F.

COMPRESSIBLITY FA	CTOR	(1/Z):	1.0043	
BTU/CU.FT (DRY) COP	1322.6			
BTU/CU.FT (WET) CORRECTED FOR (1/Z):				
REAL SPECIFIC GRAV		0.8228		
DRY BTU @ 14.650:	1315.4			
DRY BTU @ 14.696:	1319.5			
DRY BTU @ 14.730:	1322.6			

DRY BTU @ 15.025: 1349.1

# GPM, BTU, and SPG calculations as shown above are based on current GPA factors.

CYLINDER #:	CHACO 12
CYLINDER PRESSURE:	541 PSIG
DATE RUN:	12/5/13 1:01 PM
ANALYSIS RUN BY:	AMANDA ARMENTA