

Form 3160-5 (August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

JAN 08 2014

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS of Land	Àana
Do not use this form for proposals to drill or to re-enter an	

@fffindian, Allottee or Tribe Name

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			Ñ/A	N/A RCVD JAN 15'14	
SUBI	IIT IN TRIPLICATE – Other instruc	7. If Unit of CA/Ag N/A	7. If Unit of CA/Agreement, Name and/or No. N/A DIL CONS. DIU.		
✓ Oil Well Gas Well Other			8. Well Name and N Lybrook E27-230		
2. Name of Operator Encana Oil & Gas (USA) Inc.			9. API Well No. 30-043-21152	the state of a fair	
3a. Address 370 17th Street, Suite 1700 Denver, CO 80202		one No. <i>(include area code)</i> 76-3941	10. Field and Pool of Counselors Gallu		
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) SHL: 1569' FNL and 199' FWL Section 27, T23N, R6W BHL: 700' FNL and 660' FWL Section 28, T23N, R6W			1	11. Country or Parish, State Sandoval County, New Mexico	
12. CH	ECK THE APPROPRIATE BOX(ES)	TO INDICATE NATURE O	F NOTICE, REPORT OR OT	HER DATA	
TYPE OF SUBMISSION		ТҮРЕ	OF ACTION		
Notice of Intent  ✓ Subsequent Report	Acidize Alter Casing Casing Repair Change Plans	Deepen Fracture Treat New Construction Plug and Abandon	Production (Start/Resume) Reclamation Recomplete Temporarily Abandon	Water Shut-Off     Well Integrity     Other Casing Cement Job	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal		
following completion of the invitesting has been completed. Fin determined that the site is ready  Set intermediate casing string and Hole diameter: 8.75", casing diam 5816'MD. Stage tool at 2027'. Top  Cement (pumped 1/5/14): Stage Sodium Metasilicate. Mixed at 12 Yield 1.38 cuft/sk. 10bbls cement	ter: 7". casing weight and grade: 26 of float collar at 5774'MD. TOC at Lead: 331sks Premium Lite FM + 1 ppg. Yield 2.13 cuft/sk. Tail: 261s	ts in a multiple completion of only after all requirements, invater mud system.  8# J55 LTC. Depth of 8.75 surface and BOC at 5816'  3% Cacl2 + 0.25#/sk Cellocks Type III Cement + 1% (	r recompletion in a new intervalending reclamation, have be be from 0-5920'MD. Intermed MD.  offake + 5#/sk LCM-1 + 8% Cacl2 + 0.25#/sk Celloflake	diate casing set from surface to	
Started drilling out stage tool on 1	/6/14.		ومراجعة المحادثة	IAN C 1 2014	
			21.0	Villiam Tambeken	
14. I hereby certify that the foregoing i Name (Printed/Typed) Robynn Haden	s true and correct.	Title Engineering	Technologist		
Signature Solem	Haden	Date 1/7/	4		
	THIS SPACE FOR	FEDERAL OR STAT	E OFFICE USE		
Approved by	ned. Approval of this notice does not war	Title		Date	
	e title to those rights in the subject lease v				

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false,