District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

• •

٩

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

wironamet. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. i. OGRID #:_006515 Address: 709 East_Murray Drive, Parmington, New Mexico_07401 Facility or well name: Flo_Jo #93 API Number: 30-045-34517 OCD Pernit Number:	Pit, Below-Grade Tank, or		
Control of proposed alternative method Control proposed alternative method Control proposed alternative method Control of proposed alternative method Control of proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request case be adved that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the vironment. Nor does approval relieve the operator of liability should operations result in pollution of surface water, ground water or the vironment. Nor does approval relieve the operator of thability should operations result in pollution of surface water, ground water or the vironment. Nor does approval relieve the operator of thability should operations result in pollution of surface water, ground water or the vironment. Nor does approval relieve the operator of thability should operations result in pollution of surface water, ground water or the vironment. Nor does approval relieve the operator of thability should operations result in pollution of surface water, ground water or the vironment. Nor does approval relieve the operator of thability should operations result in pollution of surface water, ground water or the vironment. Plags approved the operator of the responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. vironment: Plags approved the period of the period operator applicable governmental authority's rules, regulations or ordinances vironment: Plags approved the period operator of the surface water approved the period operator of the surface water approved the period operator of the surface water approved the period operator operator of the surface water approved the period operator operatoperator operator operat			
Instructions: Please submit one application (Form C-144) per individual pit, helow-grade tank or alternative request case be advised that approval of this request does not relieve the operator of liability should operations result in politions of surface water, ground water or the vironament. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. 0 Operator: Dugan Production Corp. OGRID #: 006515 Address: 709 EaaGt Murray Drive, Farmington, New Mexico 87401 Facility or well name: Floid 50 #933 API Number: 30-045-34517 OCD Permit Number: County: San Juan Center of Proposed Design: Latitude 36.25998 N Longitude 107,9604 N NAD: [1927 [2] 1983 Surface Owner: El Federal : State : Private : Tribal Trust or Indian Allotment Image: Surface Owner: Section : County: San Juan 2 Pit: Subsection F, G or J of 19.15.17.11 NMAC Trust or Indian Allotment Image: Subsection F, G or J of 19.15.17.11 NMAC Compares: Cold Preament Low Chloride Drilling Fluid : yes : no Image: Subsection 1 of 19.15.17.11 NMAC String-Reinforced Image: Subsection 1 of 19.15.17.11 NMAC RCVD JAN 29 '14 Off. CONS. DIV. DIST. 3 3	 Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, 		
case be advised that approval of this request does not relieve the operator of Hiability should operations result in pollution of surface water, ground water or the vivionment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. It is the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. It is a complexity of the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. It is a complexity of the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. It is a complexity of the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. It is a complexity of the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. It is a complexity of the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. It is a complexity of the order of Processing in the interpret of the operator of the response of the operator of the response of the response of the rule of the rule is a complexity of the rule is a rule in the rule is rule in the rule is a rule in the rule is a rule in th			
Operator: Dugan Production Corp. OGRID #: 006515 Address: 709 East Murray Drive, Farmington, New Mexico 87401 Facility or well name: Flo 30 #93 API Number: 30-045-34517 OCD Permit Number: County: San Juan County: Center of Proposed Design: Latitude 36.25998 N Longitude 107,9604 W NAD: [1927 [2] 1983 Surface Owner: [2] Federal Stringe Counce: [2] Federal Stringe Counce: [2] Federal Stringe Counce: [2] Federal String-Reinforced [] Energency Liner Seams: [] Welded Dial Type of fluid:	Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.		
Address: 709 East Murray Drive, Farmington, New Mexico 87401 Facility or well name: Flo Jo #93 API Number:	L. Operator: Dugan Production Corp. OGRID #: 006515		
Facility or well name: Flo Jo #93 API Number: _30-045-34517 OCD Permit Number: U/L or Qtr/Qtr D Section 1 Township 23N Range 11W County: San Juan Center of Proposed Design: Latitude 36.25998 N Longitude 107.9604 W NAD: [1927 [2] 1983 Surface Owner: [2] Federal State Private Tribal Trust or Indian Allotment a. [2] Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: [2] Orilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no String-Reinforced Liner type: Thickness mil LLDPE HDPE PVC Other			
API Number:			
Center of Proposed Design: Latitude <u>36.25998 N</u> Longitude <u>107.9604 W</u> NAD: [] 1927 [\$] 1983 Surface Owner: [\$] Federal] State] Private] Tribal Trust or Indian Allotment	API Number: 30-045-34517 OCD Permit Number:		
Surface Owner: E Federal E State Private Tribal Trust or Indian Allotment Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: bbl Tank Construction material: Off Off Off Visible sidewalls and liner Visible sidewalls only Other Liner type: Thickness mil HDPE PVC Other Disting Disting Disting Disting Off Disting Disting Disting Off Disting Disting Off Disting Disting <td>U/L or Qtr/QtrDSection _1Township _23NRange _11WCounty: _San_Juan</td>	U/L or Qtr/QtrDSection _1Township _23NRange _11WCounty: _San_Juan		
	Center of Proposed Design: Latitude <u>36.25998 N</u> Longitude <u>107.9604 W</u> NAD: <u>1927 X</u> 1983		
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Dermanent Energency Cavitation P&A Multi-Well Fluid Management Lucy Chloride Drilling Fluidyes no	Surface Owner: 🖾 Federal 🔲 State 🛄 Private 🛄 Tribal Trust or Indian Allotment		
Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume:	Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Volume:bbl Dimensions: Lx Wx D		
Volume:	3.		
Tank Construction material: OIL CONS. DIV. DIST. 3 OIL CONS. DIV. DIST. 3 DIST. 3 Intervalue: <td></td>			
DIST. 3 Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other			
Visible sidewalls and liner Visible sidewalls only Other Liner type: Thickness mil HDPE PVC Other Other Mil HDPE PVC Other Horizout			
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	🗌 Visitu sidemelle end lines 🗇 Visitus sidemelle entre 🖸 Other		
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	Liner type: Thicknessmil HDPE PVC Other		
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	4.		
5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)			
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.		
	5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)		
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital,			
institution or church) T Four foot height, four strands of barbed wire evenly spaced between one and four feet			
	Alternate. Please specify		

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen 🗌 Netting 🗌 Other_

6

7

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

X Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting		
 Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA	
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA	
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗋 Yes 🗌 No	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	🗌 Yes 🗌 No	
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No	
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗋 Yes 🗌 No	
Below Grade Tanks		
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)		
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗍 No	
 Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No	

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🔲 Yes 🗋 No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
 lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.13 and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	cuments are NMAC 15.17.9 NMAC
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of 19.15.17.9 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number:	

•

١

^{12.} <u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are		
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Musiance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.13 NMAC		
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.		
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fl Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	uid Management Pit	
 Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 		
15.	· · · · · · · · · · · · · · · · · · ·	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	ce material are lease refer to	
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA	
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA	
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA	
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No	
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No	
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance		

.

•

•

•

•		
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No	
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes 🗋 No	
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	│ │ │ Yes │ No	
Within a 100-year floodplain. FEMA map	Yes No	
16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.		
17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel Name (Print): Kurt Fagrelius Title: VP-Land & Exploration Signature: KurtFagrelius Date: January 27, 2014	ief. 	
e-mail address: kfagrelius@duganproduction.com Telephone: 505-325-1821		
18. OCD Approval: Image: Constraint of the second sec	2214	
^{19.} <u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:		
20. Closure Method: Waste Excavation and Removal On-Site Closure Method If different from approved plan, please explain.	oop systems only)	
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number	ndicate, by a check	

I Soul Backfulling and Cover Installation	nn.
Soil Backfilling and Cover Installation	UII.

۵

	Re-vegetation Application Rates and Seeding Technique
	Site Declamation (Director Decumentation)

Site Reclamation (Photo Documentation) On-site Closure Location: Latitude

__ Longitude ___

NAD: 1927 1983

Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.			
Name (Print):	Title:		
Signature:	Date:		
e-mail address:	Telephone:		

)

.

8. Variances and Exceptions Attachment:

A variance to change the requirements of the burial marker is requested.

The variance request will read as follows: A steel marker will be set at the center of the on-site burial following onsite-pit closure (see application for administrative approval). The marker will be (24" X 24") and will have the "operator name" and that it designates an "on-site burial" lettering welded on the top side. The marker will be set at ground level and attached to a 4" diameter pipe that is cemented in a hole three feet deep. When the well is abandoned, a steel riser that is 4" in diameter, extending 4' above the ground will be welded to the pipe anchored in cement below the surface. The riser will have lettering welded on side showing the operator name, well number, location (UL, Sec., Twp. and Rge.) and that it designates an on-site burial location.

At all times during the production phase of the well, there will be a well sign showing the following: operator name, well name, lease number, API number, Qtr/Qtr, Sec., Twp., Rge., Latitude, Longitude, county, state and an emergency phone number on location.