nis form is <u>not</u> t ised for reportin backer leakage te	ıg	NE MEXI	CO OIL CONSE	RVATION	I DIVIS	ION	Page 1
Derator XTO Energy			NEW MEXICO PACKER LEAKAGE TEST Lease Name Fee				Revised June 10, 2003 Well No. 008
	ell: Unit Letter	,	8 Twp 301	-			
	Name of Res	ervoir or Pool	Type of Prod. (Oil or Gas)		Method of Prod. (Flow or Art. Lift)		Prod. Medium (Tbg. Or Csg.)
Upper Completion	Dicture	C):FF	Gaz		Flow		TBG
Lower Completion	Mesa Ver		Gas		Art. LiFt		TBG
• •		Pr	e-Flow Shut-In P	ressure Da	ta		
Upper Completion	Hour, Date, Shut-In 3:00 E-28-2013		Length of Time Shut-In		SI Press, Psig		Stabilized? (Sesor No)
Lower Completion	Hour, Date, Shut-In 3:00pm 8-28-2013		Length of Time Shut-In 167 HRS		SI Press. Psig		Stabilized? (Yes)or No
• .		· · ·	Flow Test N	Jo. 1			1. 1.
Commenced	at (hour, date)*	2:30pm (			g (Upper	r or Lower):	
Time (Hour, Date)	Lapsed Time Since*		<u>ssure</u> Lower Compl.	Prod. Z		Remarks	
2:45P 9-4-13	15 m	1412	107		Ī	DIGR AC	rival
3:004 9-4-17	30m	142	104		1		ouer zone
7:15P 9-4-13 7:30P	HSM	142	83			Flow Lo	wet zone
9-4-13 4:30P	1 HR	142	78			Flow La	ower Zone
G-4-13	2 HR	142	70		]_	Flow to	wer Zone
9-11-13 Production rate	3 HR	142	57		Flow		wer Zone
Dil: Dil:	BOPD based o	on — Bb	ls. In	Hrs	- G		GOR
					U	IL CONS. DIV	DIST. 3
Gas:		PD; Test thru (Orif	ice of Meter).		· · ·	SEP 16 2	013
	TI D ( 01		id-Test Shut-In P			Daira	Stabilized? (Yes or No)
Upper Completion	Hour, Date, Shut-In		Length of Time Shut-In Length of Time Shut-In		SI Press. Psig SI Press. Psig		Stabilized? (Yes or No)
Lower Completion	Hour, Date, Shu	Iour, Date, Shut-In		(Continue on reverse side)		55. I SIg	
			(Continue on rev	-		· .	• ••••••
	· ·						
			. · ·				

## NORTHWEST NEW MEXICO PACKER LEAKAC TEST

Flow Test No. 2 Zone producing (Upper or Lower): Commenced at (hour, date)\*\* Prod. Zone Remarks Time Lapsed Time Pressure Since\*\* Temp. Lower Compl. (Hour, Date) Upper Compl. Production rate during test Hrs. GOR BOPD based on Bbls. In Grav. Oil: MCFPD; Test thru (Orifice or Meter): Gas:

Remarks:

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

2014 Operator Approved New Mexico Oil Conservation Division Gas Inspector. District #3 E-mail Address Title Date 9-10-15

Northwest New Mexico Packer Leakage Test Instructions

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division  $G^{(1)}$ ,  $G^{(1)}$ ,  $G^{(2)}$ .

2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.

3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.

4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. <u>Note</u>: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shal remain shut-in while the zone which was previously shut-in is produced.

Page 2

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (a approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).