Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-effect and Field NAME

POINTER 21 14

abandoned well.	Use Form 3160-3 (A	PD) for such propos	sand Managemen	MOALLED TT TA	
SUBMIT IN TRIPLICATE – Other instructions on page 2.			=	eement, Name and/or No.	
1. Type of Well			N/A	OIL CONS. DIV.	
Oil Well Gas W		8. Well Name and No Lybrook H01-2206			
2. Name of Operator Encana Oil & Gas (USA) Inc.		9. API Well No. 30-043-21122			
370 17th Street, Suite 1700		3b. Phone No. (include area of 720-876-3437	10. Field and Pool or Lybrook Gallup	10. Field and Pool or Exploratory Area Lybrook Gallup	
4. Location of Well (<i>Footage, Sec., T</i> SHL: 2323' FNL and 497' FEL, Section 1, T22N BHL: 2080' FNL and 330' FWL, Section 1, T22N)	11. Country or Parish Sandoval, NM	11. Country or Parish, State Sandoval, NM		
12. CHEC	K THE APPROPRIATE BO	X(ES) TO INDICATE NATU	RE OF NOTICE, REPORT OR OTH	HER DATA	
TYPE OF SUBMISSION		r i	YPE OF ACTION		
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production (Start/Resume) Reclamation	☐ Water Shut-Off ☐ Well Integrity	
Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete Temporarily Abandon	Other Casing/Cement	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal		
Attach the Bond under which the water following completion of the involvation testing has been completed. Final adtermined that the site is ready for Set 20" 94# conductor at 60' on 1/24 Well spudded 01/27/2014 Set surface casing string 01/27/2014 Hole diameter: 12.25", casing diameters are from surface to 513.0 TV Pumped 224 sacks of Type III Ceme 01/28/2014. Circulated 5bbls to surface Tested BOP 1/28/2014 to 3000# for Started drilling out cement 1/29/14.	vork will be performed or project operations. If the operation Abandonment Notices must be final inspection.) 4/14. 100sks Type I Neat of the Abandonment Notices must be final inspection.) 4/14. 100sks Type I Neat of the Abandon Street Section (1998) 4. Gelled freshwater mud section (1998) 4. Gelled freshwater mud section (1998) 4. Gelled freshwater mud section (1998) 5. Gelled freshwater mud section (1998) 6. Gelled freshwater mud sect	ovide the Bond No. on file with on results in a multiple complete filed only after all requirements. Sement, 16.6ppg. system. and grade: 36ppf J55 LTC. 5 lbs/sk cello flake + 0.2% b surface casing.	woc FL-52A, yield 1.38 cuft/sk, m	ports must be filed within 30 days al, a Form 3160-4 must be filed once in completed and the operator has RECORD U14 OFFICE Tambe kou IVD/MD. ixed at 14.6 ppg on	
14. I hereby certify that the foregoing is to Name (Printed/Typed) Amanda Cavoto	nue and correct.	Title Engine	ering Technologist		
Signature / Mauda	Card	Date 2/5	-/14		
T	THIS SPACE	FOR FEDERAL OR S	TATE OFFICE USE		
Approved by					
		Γitle		Date	
Conditions of approval, if any, are attached hat the applicant holds legal or equitable t entitle the applicant to conduct operations	itle to those rights in the subjec	s not warrant or certify		Date	

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.