Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

BUR	EAU OF LAND MAN	AGEMENT	f er	3 20 45	'5. Lease Serial No.			
					I NMNM 109385			
SUNDRY N	IOTICES AND REPO	DRTS ON W	ELICSMING	ton Field	offitundian, Allottee	or Tribe Na	ime	
abandoned well.	form for proposals t Use Form 3160-3 (A	(PD) for suc	រម្យាមួយផ្សា h proposa	land Ivian Is.	ayeme			
	7. If Unit of CA/Agreement, Name and/or No.							
SUBMIT IN TRIPLICATE – Other instructions on page 2. 1. Type of Well					N/A			
Oil Well Gas Well Other					8. Well Name and No.			
					Lybrook H01-2206 01H			
2. Name of Operator Encana Oil & Gas (USA) Inc.					9. API Well No. 30-043-21122			
3a. Address 370 17th Street, Suite 1700 3b. Phone No. (include area code)					10. Field and Pool or Exploratory Area			
Denver CO, 80202 720-876-3941					Lybrook Gallup			
4. Location of Well (Footage, Sec., T., SHL: 2323' FNL and 497' FEL, Section 1, T22N BHL: 2080' FNL and 330' FWL, Section 1, T22N)	11. Country or Parish, State Sandoval, NM						
12. CHEC	K THE APPROPRIATE BO	X(ES) TO INDI	CATE NATUR	E OF NOTIC	CE, REPORT OR OTH	IER DATA		
TYPE OF SUBMISSION TYPE OF AC					rion			
Notice of Intent	Acidize	Deepe	n	Produ	uction (Start/Resume)	□ w	ater Shut-Off	
Notice of filterit	Alter Casing	Fractu	re Treat	Recla	mation		ell Integrity	
Subsequent Report	Casing Repair	New C	Construction	Reco	inplete	✓ Ot	her Casing/Cement Job	
	Change Plans	_	nd Abandon		orarily Abandon			
Final Abandonment Notice	Convert to Injection	Plug B	ack	Water	r Disposal			
Attach the Bond under which the w following completion of the involv testing has been completed. Final a determined that the site is ready for	ed operations. If the operati Abandonment Notices must	on results in a mu	altiple completion	on or recompi	letion in a new interva	l, a Form 3	160-4 must be filed once	
Set intermediate casing string 02/6/14. Gelled freshwater mud system. Hole diameter: 8.75", casing diameter: 7", casing weight and grade: 26ppf J-55 LTC. Depth of 8.75" ho					RCVD MAR 4'14 OIL CONS. DIV.			
Hole diameter: 8.75", casing diameter	er: /", casing weight and o	grade: 26ppf J-5	55 LTC. Depth	of 8.75" not	e from 0-5/20 I VD/	WID.)IST. 3	
Casing set from surface to 5720'MD	. Stage tool at 2078'. Top	of float collar at	:5673' MD. TC	OC at surface	e and BOC at 5720'i	MD.	AJI. U	
Cement pumped 2/6/14 Lead: 499sks Premium Lite FM + 39 ppg, yield 2.13 cuft/sk.	% Cacl2 + 0.25#/sk Cellofl	ake + 5#/sk LCl	M-1 + 8% Ben	tonite + 0.49	% FL-52A + 0.4% So	odium Met	asilicate, mixed at 12.1	
Tail: 195sks Type III Cement + 1% b surface. WOC 12.5 hours.	owoc CaCl + 0.25 lbs/sk c	ello flake + 0.2%	6 bwoc FL-52/	A, yield 1.38	cuft/sk, mixed at 14	.6 ppg. 20	bbls <u>circulated</u> to	
Tested BOP 2/7/14 to 3000# for 30n	ninutes. No pressure drop	. Tested casing	2/7/14 to 150	0# for 30 mi	nutes. No pressure	EPTED F	FOR RECORD	
Started drilling out cement 2/7/14							FFR 2 1 2014	
					FAF BY	MINGTON	FIELD OFFICE am Tambekon	
14. I hereby certify that the foregoing is tr Name (Printed/Typed)	rue and correct.							
Robynn Haden			Title Enginee	ering Techno	logist			
Signature Koby	Hadi		Date 2	119/14				
	THIS SPACE	FOR FEDER	RAL OR ST	ATE OFF	ICE USE			
Approved by								

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Title

Office