BUF SUNDRY I	UNITED STATE PARTMENT OF THE REAU OF LAND MAN NOTICES AND REPO form for proposals t	INTERIOR AGEMENT ORTS ON WE	Sington	25 201 1 Field O	5. Lease Serial No. NMNM 109385	FORM APPROVED DMB No. 1004-0137 xpires: July 31, 2010 or Tribe Name	
abandoned well. Use Form 3160-3 (APD) for such proposals.					1		
SUBMIT IN TRIPLICATE – Other instructions on page 2.				7. If Unit of CA/Agreement, Name and/or No. N/A			
Oil Well Gas Well Other					8. Well Name and No. Lybrook H01-2206 01H		
2. Name of Operator Encana Oil & Gas (USA) Inc.				9. API Well No. 30-043-21122			
3a. Address 3b. Phone 1 370 17th Street, Suite 1700 720-876-3 Denver CO, 80202 720-876-3			lude area code	2)	10. Field and Pool or Exploratory Area Lybrook Gallup		
4. Location of Well (<i>Footage, Sec., T.,R.,M., or Survey Description</i>) SHL: 2323' FNL and 497' FEL, Section 1, T22N R6W BHL: 2080' FNL and 330' FWL, Section 1, T22N R6W					11. Country or Parish, State Sandoval, NM		
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA							
TYPE OF SUBMISSION TYPE OF AC					ION		
Notice of Intent	Acidize	Deepen Fracture T	rcat		uction (Start/Resume)	Water Shut-Off	
Subsequent Report	Casing Repair	New Cons			mplete	Other Cemented Liner	
Final Abandonment Notice	Change Plans	Plug and Plug Back		· · · · ·	oorarily Abandon r Disposal		
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) Utilized synthetic oil-based mud system from intermediate casing point (5720'). To TD of lateral. Kicked off lateral at 4515'. Landed lateral at 5989' on 2/7/14 . Length of lateral: 3586'. TD of 9575'MD/5373'TVD. Reached 2/9/14 . Set production liner 2/10/14. Hole diameter: 6.125", casing diameter: 4.5", casing weight and grade: 11.6ppf SB-801_T&C. Depth of 6.125" hole from 5589' to 9575'TVD/MD. Float shoe at 9541'MD. Float collar at 9498'MD. Liner set from 5408'MD to 9537'MD.							
Cement pumped 2/10/14: 329 sks Type III Cement + 0.2% bwoc BA-10A + 0.25lbs/sack Cello Flake + 0.5% bwoc FL-63 + 58.5% fresh water. Yield: 1.37 cf/sk. Density: 14.6ppg. 10bbls circ to surface.							
Rig released 2/11/14.							
					FEB 25 2014		
					FARMIN	STON FIELD OFFICE	
14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) Title Engineering Techr Robynn Haden Title Engineering Techr						uliam Jamberou	
Signature Loby Loder Date 3/34/1					4		
	THIS SPACE	FOR FEDERA	L OR STA				
Approved by							
Title Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would office entitle the applicant to conduct operations thereon.					1	Date	
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.							
(Instructions on page 2) NMOCD A							