

October 13, 2009

Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-031-07025

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Hospah Sand Unit

8. Well Number **#61**

9. OGRID Number

291567

10. Pool name or Wildcat

Hospah

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Dominion Production Co. LLC

3. Address of Operator

1414 W. Swann, Suite 100, Tampa Florida 33606

4. Well Location

Unit Letter E : 3640' feet from the South line and 1000' feet from the West line
Section 01 Township 17N Range 9W NMPM McKinley County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
7073' GR, 7009' KB

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Please see the attached plugging procedure.

Notify NMOCD 24 hrs
prior to beginning
operations

RCVD MAR 5 '14
OIL CONS. DIV.
DIST. 3

Extend Mancos plug down to 700'
Submit CBL for review/approval prior to cementing plug #2

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE President DATE: 2-24-2014

Type or print name David Burns E-mail address: davidburns@dominionproduction.com PHONE: 918-260-7620
For State Use Only

APPROVED BY: [Signature] TITLE Deputy Oil & Gas Inspector, DATE 3/11/14
Conditions of Approval (if any): AV District #3

Plug and Abandonment Plan
Dominion Production Co, LLC.
Hospah Sand Unit #61
3640' FSL & 1000' FWL
Sec. 01 T17N R9W
McKinley County, New Mexico

1. Comply with all OCD, DPC and contractor safety rules and regulations. Hold safety meetings each morning.
2. MIRU, Check Braden head for pressure. Bleed pressure off of well if necessary.
3. **Plug # 1- (Upper Gallup Sand 1715'-1532')** RIH with 2 7/8" 6.5#, WS with mule shoe sub. Wash wellbore to TD of 1715' KB. Mix and Pump 17 Sks, Class B Cement @ 15.5 ppg to cover Gallup with 50' cap and 50' excess.
4. **Plug #2-(Mancos Plug/ Surface Plug, 650'-Surface)** MIRU Wireline Truck, RIH with CBL Tool, from 1500' to Surface. Shoot 3-3/8" squeeze holes at 120 degree at approx. 650' (actual squeeze hole depth will be determined from Bond Log). MIRU Pump Truck, Pump Approx. 20 bbls Fresh Water to establish circulation through Squeeze Holes. At Successful Circulation, Mix and Bullhead 60 Sks, Class B Cement @ 15.5 ppg, for outside annulus, Mancos Surface Plug, followed with 84 Sks of Class B Cement @ 15.5 ppg from 650' or actual depth to surface. Allow well to stabilize overnight. Top Casing off with Cement if necessary.
5. Cut off well 3' below ground and install P&A marker per OCD specifications. RD, cleanup MOL.
6. Restore location to OCD specifications