

\*submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP


3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
Sec., T--N, R--W, NMPM

Unit N (SESW) 1005' FSL & 1880' FWL, Sec. 6, T29N R10W NMPM

2005 SEP 20 AM 8 54

RECEIVED  
070 FARMINGTON NM



5. Lease Number  
NMSF-078717  
6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

8. Well Name & Number

9. Grenier B #5M  
API Well No.

30-045-33201

10. Field and Pool

Blanco Mesaverde/ Basin Dakota

11. County and State  
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment <input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection

☒ Other - 4 1/2" Casing

13. Describe Proposed or Completed Operations

9/2/05 MIRU Bearcat #4. NU BOP. PT csg 600psi for 30 mins, ok. RIH w/7 7/8" bit & tagged cmt @ 324'. 9/10/05 D/O cmt & ahead to 6950'. Circulate hole. 9/11/05 RIH w/162 jts of 4 1/2" 10.5# J55 ST&C csg set @ 6944' w/DV tool set @ 4327'. Cement 1<sup>st</sup> Stage: Pumped preflush of 10bbbls H2O, 10bbbls mud, 10bbbls H2O. Cemented w/18sxs(55cu-10bbbls)scavenger Type 3 cement w/.5pps D29, .3% CD32, 6.25pps LCM1, 1% FL52. Cemented lead w/432sxs(855cu-152bbbls)prem lite w/.25pps Cell-o-Flake, .3% CD32, 6.25pps LCM1, 1% FL52. Pumped # rate of 4bbbls/min. Plug down @0809 hrs. Open weatherford DV tool and circulate out cmt. Circulated 45bbbls cmt to reserve pit. Circulate between stages. Cement 2<sup>nd</sup> Stage: Pumped preflush of 10bbbls H2O, 10bbbls mud, 10bbbls H2O. Cemented w/18sxs(55cu-10bbbls)scavenger Type 3 cement w/.05pps D29, .3% CD32, 6.25pps LCM1, 1% FL52. Cemented lead w/573sxs(1220cu-218bbbls)prem lite w/.3% CaCl2, .3% CD32, 6.25pps LCM1, 1% FL52. Tail in w/90sxs(cu-22bls) prem lite.Pumped @ rate of 4bbbls/min. Plug down @ 1316 hrs. Circulated 35bbbls cmt to reserve pit. ND RD. Rig released @ 1930 hrs on 9/12/05.

14. I hereby certify that the foregoing is true and correct.

Signed Amanda Sandoval Amanda Sandoval Title Regulatory Compliance Assistant

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

SEP 22 2005

FARMINGTON FIELD OFFICE  
BY SD

NMOCED