This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

Page 1

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Revised June 10, 2003

Operator 💋	NOCO	· .' .		*	Lease Nar	ne	AN JUAN 30	No. 12 A		
Location Of W	Vell: Unit Letter _	Sec <u>3</u>	Twp	30	Rge	<u> </u>	_ API # 30-0_ <i>3</i>	9-22729		
	Name of Rese	Type of Prod. (Oil or Gas)			Method of Prod. (Flow or Art. Lift)		Prod. Medium (Tbg. Or Csg.)			
Upper Completion	PC	6AS			NIA		TUBING TUBING			
Lower Completion	MV	6-15			FLOW		TUBING			
		Pre	-Flow Shut-l	n Pr	essure Dat	a				
Upper Completion	Hour, Date, Shut-	-In	Length of Time Shut In		SI	Press. Psig	Stabilized? (Yes or No)			
Lower Completion	Hour, Date, Shut-	-In -ZZ-MAY-ZOH -ZZ-MAY-ZOH	Length of T	ime			Press. Psig	Stabilized? (Yes)or No)		
			Flow To	est N	 o. 1					
Commenced at (hour, date)* Zone producing (Upper or Lower):										
Time (Hour, Date)	Lapsed Time Since*	Pres Upper Compl.		ıl.	Prod. Zo		Remarks			
8:40 27-nas		112.	74		<u> </u>		NO COMMENICATION			
			.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,							
:					:					
Production rate	e during test									
Oil:	BOPD based onBbls. In				In Hrs Gr			GOR		
Gas: _ ·	MCFP	D; Test thru (Orifi	ce or Meter):	<u>. </u>						
	•	Mie	d-Test Shut-	ı İn Pı	essure Da	ta				
Upper Completion	Hour, Date, Shut	Length of Time Shut-In			SI Press. Psig		Stabilized? (Yes or No)			
Lower Completion	Hour, Date, Shut	Length of Time Shut-In			SI Press. Psig		Stabilized? (Yes or No)			
<u> </u>		·	(Continue or	reve	erse side)	<u> </u>		RCVD MAY 28'14		

OIL CONS. DIV.

Flow Test No. 2

Commenced a	at (hour, date)**		Flow Test I		and an I arreal
				one producing (Up	<u></u>
(Hour, Date)	-		essure Lower Compl.	Prod. Zone Temp.	Remarks
(110 uni, 12 unio)	Since	Оррег сопрт.	Lower Compi.	Temp.	
				•	
				• • •	
			:		
Production rate	during test	1			1
Oil:	BOPD base	d on	Bbls. In	Hrs	Grav GOR
Gas:	MCFF	D; Test thru (Ori	fice or Meter):		
Remarks:					•
•				nplete to the best	of my knowledge.
Approved	MA	1 3 0 2014	20	Operator	·
New Mexico O	oil Conservation I	Division			
	/ - /			By Layyo	le
By	m Durgan	7		Title	
Title	eputy Oil & G	as Inspector,	E-mail Addre	ess	
	Distric	i # O	•	Date	

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).