District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

<u>Pit, Below-Grade Tank, or</u>	
Proposed Alternative Method Permit or Closure Plan Ap	<u>plication</u>
Proposed Alternative Method Permit or Closure Plan Ap Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitor proposed alternative method	
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank	or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental	of surface water, ground water or the authority's rules, regulations or ordinances.
I. Operator: BP America Production CompanyOGRID #:778	OIL CONS DIV DIST 3
Address:200 Energy Court, Farmington, NM 87401	
Facility or well name:Gallegos Canyon Unit 72	
API Number:	······································
U/L or Qtr/QtrGSection36Township28NRange13WCounty: _	San Juan
Center of Proposed Design: Latitude36.62100 Longitude108.16685	NAD: 🗌 1927 🔀 1983
Surface Owner: 🖾 Federal 🗌 State 🗌 Private 🗌 Tribal Trust or Indian Allotment	
2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2.	
Liner Seams: Welded Factory Other Volume: bbl Dimension	ons: Lx Wx D
3. Image: Subsection 1 of 19.15.17.11 NMAC Tank A Volume:95.0bbl Type of fluid:Produced water Tank Construction material:Steel Image: Secondary containment with leak detection Image: Visible sidewalls, liner, 6-inch lift and automatic overflow shuter	t-off
□ Visible sidewalls and liner ⊠ Visible sidewalls only □ Other _Single walled/single bottomed	
Liner type: Thicknessmil 🔲 HDPE 🗌 PVC 🗋 Other	······································
4. Alternative Method:	

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

6.

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other_

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

□ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗌 Yes 🗌 No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No

 Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗋 Yes 🗌 No
<u>Temporary Pit Non-low chloride drilling fluid</u>	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
<u>Permanent Pit or Multi-Well Fluid Management Pit</u>	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	cuments are 9 NMAC 15.17.9 NMAC
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.	
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	documents are
 Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment 	
 Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC 	
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan	
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan 	
 Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan 	
 Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	
^{13.} <u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)	
 On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method 	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗍 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	
in the manerparky, which approval obtained non-international	Yes No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes 🗌 No
Within an unstable area.	
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain.	Yes No
- FEMA map	Yes No
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure play a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canned Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
e-mail address: Telephone: <u>OCD Approva</u> l: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:Approval Date:Approval Date:Appr	
18. OCD Approval: Permit Application (including closure plan) Image: Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Image: Closure plan) Image: Closure Plan (only) Image: OCD Conditions (see attachment)	DB14
 18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 650 Title: 670 Compliance Office Offi	DI4

Operator Closure Certification:

22.

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Peace	Date:May 21, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Gallegos Canyon Unit 72</u> <u>API No. 3004507039</u> <u>Unit Letter G, Section 36, T28N, R13W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B. D. or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. **Notice is attached.**
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	110

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT's was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil. This area will be reclaimed with the rest of the site since the well has been plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT will be reclaimed with the rest of the site since the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT will be reclaimed with the rest of the site since the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT will be reclaimed with the rest of the site since the well has been plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation since the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Fia	icis Di., Santa	i re, nivî 8750.)	Sa	anta Fo	e, NM 875	05			
			Rel	ease Notifi	catio	n and Co	orrective A	ction		
						OPERA	ГOR	🔲 Initi	al Report	🛛 Final Repo
Name of Company: BP					Contact: Jef	f Peace		X		
						No.: 505-326-94				
Facility Na	me: Galleg	os Canyon l	Jnit 72			Facility Typ	e: Natural gas v	well		<u></u>
Surface Ow	ner: Federa	al		Mineral (Owner:	Federal		API No	. 30045070)39
				LOC	ATIO	N OF RE	LEASE		-	
Unit Letter G	Section 36	Township 28N	Range 13W	Feet from the 1,730		/South Line	Feet from the 1,650	East/West Line East	County: S	an Juan
L		Lat	itude 3	6.62100		Longitud	e 108.16685			
			_			OF REL				
Type of Rele							Release: N/A	Volume F	Recovered: N	J/A
Source of Re	elease: below	grade tank –	95 bbl			Date and H	lour of Occurrence	ce: Date and	Hour of Dis	covery: N/A
Was Immedi	ate Notice G					If YES, To	Whom?			
			Yes	No 🛛 Not R	equired					
By Whom? Was a Water	D	1 - 10				Date and H	lour Inpacting	the Wetersource		
was a water	course Reac		Yes 🗵	No			nume impacting	ine watercourse,		
If a Waterco	urse was Imr	pacted, Descr	ibe Fully.	k						
	-		-							
Describe Ca	use of Proble	m and Reme	dial Actio	n Taken * Sampli	ing of th	e soil beneath	the BGT was do	ne during removal	o ensure no	soil impacts from
				and chlorides bel					to ensure no	bon impacts from
Describe Are	ea Affected a	and Cleanup /	Action Tal	cen.* BGT was re	emoved a	and the area u	nderneath the BC	T was sampled. T	he excavated	1 area was
backfilled an	id compacted	and will be	reclaimed	with the rest of the	he site si	nce the well I	as been plugged	and abandoned.		
					_					
I hereby cert	ify that the i	nformation g	ven above	e is true and comp	olete to t	he best of my	knowledge and u	inderstand that purs	uant to NM	OCD rules and
regulations a	I operators	are required t	o report a	nd/or file certain i re of a C-141 repu	ort by th	e NMOCD m	nd perform correct arked as "Final R	ctive actions for rel eport" does not rel	eases which eve the oper	may endanger rator of liability
should their	operations h	ave failed to a	dequately	investigate and i	remediat	e contaminati	on that pose a thr	eat to ground water	, surface wa	iter, human health
or the enviro	nment. In a	ddition, NMC	OCD accept	otance of a C-141	report d	loes not reliev	e the operator of	responsibility for c	ompliance w	with any other
federal, state	, or local lav	vs and/or regi	ilations.						DIVICIO	
	۰ ۵۸	Λ.					<u>UIL CON</u>	<u>SERVATION</u>	DIVISIC	<u> IIN</u>
Signature:	YER	Jack								
Dubrate 131		-				Approved by	Environmental S	pecialist:		
Printed Nam	e: Jen Peace						·			
Title: Area E	Environmenta	al Advisor				Approval Da	te:	Expiration	Date:	
E-mail Addr	ess: <u>p</u> eace.je	ffrey@bp.co	n			Conditions o	f Approval:		Attached	П
Date: May	21 2014		Phone: 5	05-326-9479					1 mained	<u> </u>
Date. Way	∠1, ∠VI4		- r none. J	マン・フィロ・ブサイブ					1	

* Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	API #: 3004507039 TANK ID (if applicble): A
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:	PAGE #: <u>1</u> of <u>1</u>
QUAD/UNIT: G SEC: 36 TWP: 1/4-1/4/FOOTAGE: 1,730'N / 1,65		DATE STARTED: 03/31/14 DATE FINISHED: ENVIRONMENTAL
	PROD. FORMATION: PC CONTRACTOR: MBF - T. PETERSON	SPECIALIST(S): NJV
1) 95 BGT (SW/SB) 2) 3)	GPS COORD.: 36.62100 X 108.16685 DISTANCE/BE GPS COORD.: DISTANCE/BE	ARING FROM W.H.:
SAMPLING DATA: 1) SAMPLE ID: 5 PC-TB @ 6' 2) SAMPLE ID:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL (95) SAMPLE DATE: 03/31/14 SAMPLE TIME: 1240 LAB ANALYSIS: 418.1/	/8015B/8021B/300.0(CI)
SOIL COLOR: DARK YELL COHESION (ALL OTHERS): NON COHESIVE/ SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): CO MOISTURE: DRY (SLIGHTLY MOIST) MOIST / W SAMPLE TYPE: GRAB (COMPOSITE) # DISCOLORATION/STAINING OBSERVED: YES (N SITE OBSERVATION	OSE/FIRM/DENSE/VERY DENSE HC ODOR DETECTED: YES NO EXPLANATION OF PTS. 5 OF PTS. 5 OF EXPLANATION ANY AREAS DISPLAYING WETNESS: YES (NO EXPLANATION	COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC / STIFF / VERY STIFF / HARD
SITE SKETCH	EAREST WATER SOURCE: >1,000'NEAREST SURFACE WATER: <1,000'NMC BGT Located : off on site PLOT PLAN circle: attached OW TIME PBGTL T.B. ~6' B.G. X X X X X X X X W DEPRESSION: B.G. = BELOW GRADE: B = BELOW, T.H. = TEST HOLE: ~ = APPROX; W.H. = WELL HEAD;	STIMATION (Cubic Yards) : NA DCD TPH CLOSURE STD: 1,000 ppm MCALIB. READ. = NA ppm MCALIB. GAS = NA ppm PU NISCELL. NOTES MO: N153666670 PO #: Potential Stratege PY: X7-005RN-E Permit date(s): 06/03/10 DCD Appr. date(s): 10/23/13 ank OVM = Organic Vapor Meter ppm = parts per million M A BGT Sidewalls Visible: Y / N BGT Sidewal
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW- SINGLI NOTES: GOOGLE EARTH IMA (WALL, DW - DOUBLE WALL, SB - SINGLE BOTTOM, DB - DOUBLE BOTTOM.	Magnetic declination: 10° E

CLIENT: Blagg Engineering			Client Sa	mple ID: 5P	PC-TB @ '6 (95)	
Project: GCU # 72			Collect	ion Date: 3/.	31/2014 12:40:00 PM	
Lab ID: 1404162-001	Matrix: SOIL Received Date: 4/3/2014 10:30:00 AM					
Analyses	Result	RL	Qual Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	GE ORGANICS	,			Analys	t: BCN
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	4/7/2014 3:03:20 PM	12535
Surr: DNOP	74.5	66-131	%REC	1	4/7/2014 3:03:20 PM	12535
EPA METHOD 8015D: GASOLINE RA	ANGE				Analys	: NSB
Gasoline Range Organics (GRO)	ND	4.9	mg/Kg	1	4/4/2014 12:27:54 PM	12530
Surr: BFB	85.2	74.5-129	%REC	' 1	4/4/2014 12:27:54 PM	12530
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.049	mg/Kg	1	4/4/2014 12:27:54 PM	12530
Toluene	ND	0.049	mg/Kg	1	4/4/2014 12:27:54 PM	12530
Ethylbenzene	ND	0.049	mg/Kg	1	4/4/2014 12:27:54 PM	12530
Xylenes, Total	ND	0.099	mg/Kg	1	4/4/2014 12:27:54 PM	12530
Surr: 4-Bromofluorobenzene	98.4	80-120	%REC	1	4/4/2014 12:27:54 PM	12530
EPA METHOD 300.0: ANIONS					Analyst	: JRR
Chloride	110	30	mg/Kg	20	4/7/2014 3:15:41 PM	12566
EPA METHOD 418.1: TPH					Analyst	JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	4/7/2014 12:00:00 PM	12534

Hall Environmental Analysis Laboratory, Inc.

•

.

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method	od Blank	
	E	Value above quantitation range	Н	Holding times for preparation or analysis exceeded		
	J	Analyte detected below quantitation limits	ND	Not Detected at the Reporting Limit	Page 1 of 6	
	0	RSD is greater than RSDlimit	Р	Sample pH greater than 2.	1 450 1 01 0	
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit		
	S	Spike Recovery outside accepted recovery limits				

Analytical Report Lab Order 1404162 Date Reported: 4/9/2014

Client:Blagg EngineeringProject:GCU # 72

Sample ID MB-12566	SampType: MBLK	TestCode: EPA Method	300.0: Anions		
Client ID: PBS	Batch ID: 12566	RunNo: 17852			
Prep Date: 4/7/2014	Analysis Date: 4/7/2014	SeqNo: 514796	Units: mg/Kg		
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual
Chloride	ND 1.5				
Sample ID LCS-12566	SampType: LCS	TestCode: EPA Method	300.0: Anions		
Sample ID LCS-12566 Client ID: LCSS	SampType: LCS Batch ID: 12566	TestCode: EPA Method RunNo: 17852	300.0: Anions		
			300.0: Anions Units: mg/Kg		
Client ID: LCSS	Batch ID: 12566 Analysis Date: 4/7/2014	RunNo: 17852	Units: mg/Kg	RPDLimit	Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

WO#: 1404162 09-Apr-14

ysis exceeded

Page 2 of 6

Client: Rlago Er .: ering

Client:	Blagg Enginee
Project:	GCU # 72

,

Sample ID MB-12534	SampType: MBLK	TestCode: EPA Method	418.1: TPH	
Client ID: PBS	Batch ID: 12534	RunNo: 17822		
Prep Date: 4/3/2014	Analysis Date: 4/7/2014	SeqNo: 513710	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	ND 20			
Sample ID LCS-12534	SampType: LCS	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS	Batch ID: 12534	RunNo: 17822		
Prep Date: 4/3/2014	Analysis Date: 4/7/2014	SeqNo: 513711	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	92 20 100.0	0 91.6 80	120	
Sample ID LCSD-12534	SampType: LCSD	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS02	Batch ID: 12534	RunNo: 17822		
Prep Date: 4/3/2014	Analysis Date: 4/7/2014	SeqNo: 513712	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	90 20 100.0	0 90.2 80	120 1.52	20

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Value above quantitation range Е
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- s Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- Р Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 6

WO#:

Client:Blagg EngineeringProject:GCU # 72

.

Sample ID MB-12535	SampTyp	be: MB	LK	Tes	tCode: El	PA Method	8015D: Dies	el Range (Organics	
Client ID: PBS	Batch I	D: 125	35	F	RunNo: 1	7817				
Prep Date: 4/3/2014	Analysis Dat	te: 4/7	/2014	S	SeqNo: 5	14212	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Surr: DNOP	7.3		10.00	_	72.6	66	131			
Sample ID LCS-12535	SampTyp	pe: LCS	3	Tes	tCode: El	PA Method	8015D: Diese	el Range C	Organics	
Client ID: LCSS	Batch I	D: 125	35	F	RunNo: 1	7817				
Prep Date: 4/3/2014	Analysis Dat	te: 4/7	/2014	S	SeqNo: 5	14213	Units: mg/K	ζg		
Prep Date: 4/3/2014 Analyte	,			SPK Ref Val	eqNo: 5 %REC	14213 · LowLim <u>it</u>	Units: mg/K HighLimit	(g %RPD	RPDLimit	Qual
	,						Ŭ	0	RPDLimit	Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

WO#: 1404162

09-Apr-14

Client: Blagg Engineering **Project:**

.

GCU # 72

		······································	and the second sec
Sample ID 5ML RB	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Range
Client ID: PBS	Batch ID: R17799	RunNo: 17799	
Prep Date:	Analysis Date: 4/4/2014	SeqNo: 513541	Units: %REC
Analyte	Result PQL SPK va	ue SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Surr: BFB	990 10	00 99.2 74.5	129
Sample ID 2.5UG GRO LCS	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Range
Client ID: LCSS	Batch ID: R17799	RunNo: 17799	
Prep Date:	Analysis Date: 4/4/2014	SeqNo: 513542	Units: %REC
Analyte	Result PQL SPK va	ue SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Surr: BFB	1100 10	00 109 74.5	129
Sample ID MB-12530	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Range
Client ID: PBS	Batch ID: 12530	RunNo: 17816	
Prep Date: 4/3/2014	Analysis Date: 4/4/2014	SeqNo: 513588	Units: mg/Kg
Analyte	Result PQL SPK va	ue SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Gasoline Range Organics (GRO) Surr: BFB	ND 5.0 860 10	00 85.7 74.5	129
Sample ID LCS-12530	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Range
Client ID: LCSS	Batch ID: 12530	RunNo: 17816	
Prep Date: 4/3/2014	Analysis Date: 4/4/2014	SeqNo: 513589	Units: mg/Kg
Analyta	Result PQL SPK va	ue SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Analyte	Result for offer		
Gasoline Range Organics (GRO) Surr: BFB	27 5.0 25	00 0 109 71.7 00 93.2 74.5	134

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Value above quantitation range Е
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank В
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2. Р
- RL

Page 5 of 6

- Reporting Detection Limit

WO#: 1404162 09-Apr-14

WO#: 1404162

09-Apr-14

 Client:
 Blagg Engineering

 Project:
 GCU # 72

				*						
Sample ID 5ML RB	SampT	ype: MB	BLK	Test	tCode: El	PA Method	8021B: Volat	iles		
Client ID: PBS	Batch	n ID: R1	7799	R	RunNo: 1	7799				
Prep Date:	Analysis D	ate: 4/	4/2014	S	SeqNo: 5	13564	Units: %RE	с		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	0.98		1.000		98.1	80	120			
Sample ID 100NG BTEX LCS	SampT	ype: LC	:S	Test	tCode: El	PA Method	8021B: Volat	iles		
Client ID: LCSS	Batch	n ID: R1	7799	R	RunNo: 1	7799				
Prep Date:	Analysis D	ate: 4/	4/2014	S	SeqNo: 5	13565	Units: %RE	с		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	0.71		1.000		71.0	80	120			S
Sample ID MB-12530	SampT	ype: ME	 ЗLК	Test	tCode: El	PA Method	8021B: Volat	iles		
Client ID: PBS	Batch	n ID: 12	530	R	unNo: 1	7816				
Prep Date: 4/3/2014	Analysis D	ate: 4/	4/2014	S	SeqNo: 5	13622	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120			
Sample ID LCS-12530	SampT	ype: LC	:S	Test	tCode: El	PA Method	8021B: Volat	iles		
Client ID: LCSS	Batch	ID: 12	530	R	lunNo: 1	7816				
Prep Date: 4/3/2014	Analysis D	ate: 4/	4/2014	S	eqNo: 5	13623	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	109	80	120			
Toluene	0.99	0.050	1.000	0	99.4	80	120			
Ethylbenzene	1.0	0.050	1.000	0	99.8	80	120			
Xylenes, Total	3.0	0.10	3.000	0	99.1	80	120			
Surr: 4-Bromofluorobenzene	1.1	0.10	1.000	č	109	80	120			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6

	1a11-1	<u></u>	NUUY NECULU	4						ł	łA	LL	E	NV	/IF	20	NF	ME	NT/	AL
Client:	Client: BLAGG ENGR. / BP AMERICA		/ BP AMERICA	Standard	🗌 Rush _		l r	_	_										TO	
				Project Name:					(* 19) (* 19)											
Mailing Ad	dress:	P.O. BO	X 87	GCU # 72			4901 Hawkins NE - Albuguergue, NM 87109										•			
		BLOOM	FIELD, NM 87413	Project #:			1			05-34				-	·	-	-410			
Phone #:		(505) 63	2-1199								*t	-								Ra Vi ^{sk} - S
email or Fa	ax#:			Project Manag	jer:	······			nu											
QA/QC Pac	-		Level 4 (Full Validation)	NELSON VELEZ		's (8021B)	only)	(OUM			S)		04,504	PCB's			er - 300.1)			
Accreditati			<u> </u>	Sampler: NELSON VELEZ			Gas	DRO /	a	ਜ	SIM		0 ₂ ,P	082			water		nple	
		D Other			v Yes			TPH (Gas	\sim	18.	504.	8270SIMS)		3,N	s / 8		A	0.0		e sar
EDD (T	ype)				etature:		E	+	GRC	od 4	3 po	or 8	tals	J'NC	cide	¥)	2	I - 30	<u> </u>	osite
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALNO 1404162	BTEX + -MTB	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0/	Grab sample	5 pt. composite sample
3/31/14	1240	SOIL	5PC - TB @ 6' (95)	4 oz 1	Cool	-001	V		V	V								V		V
											_							-+-		
			· · ·											_				-†	-	
				·		· · · · · · · · · · · · · · · · · · ·														+
																				+
																		+		+
										-										╀─┥
											_								+	┢─┤
					<u> </u>															╈
						÷													+	┼─┤
						 				-							-+			+
		<u> </u>		<u> </u>		<u> </u>														+-+
Date: /	Time:	Relinquish	ed by	Received by:		Date Time	Ren										[
4/2/14	1437	Mu	r Vj	Mister	Walter	4/2/14 1437	BI	L DI	RECT	1Y T(-						
Date:	Time: [749	Relinquish		Received by:	- ruli	Date Time				200 E ::								401 EIRK	<u>SIS</u>	
	If necessa	ry, samples s	submitted to Hall Environmental may be s	subcontracted tolother	accredited laboratorie	es. This serves as notice o	f this p	ossibil	ity. Aı	ny sub	-contr	acted	data v	vill be	clearly	notat	ed on t	he anal	rtical rep	ort.

HALL ENVIRONMENTAL ANALYSIS LABORATORY

Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website; www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Number: 1404	162	RcptNo:	1
Received by/date:	04/03/12			
Logged By: Lindsay Mangin 4	/3/2014 10:30:00 AM	Strenky H	lenger D	1
Completed By: Lindsay Mangin 4	/3/2014 10:51:28 AM	Streeby H	langer	
Reviewed By:	4/05/14			
Chain of Custody				
1. Custody seals intact on sample bottles?	Yes	No No	Not Present 🗹	
2. Is Chain of Custody complete?	Yes	V No ĺ	Not Present	
3. How was the sample delivered?	Cou	rier		
<u>Log In</u>				
4. Was an attempt made to cool the samples?	Yes	No No	NA	
5. Were all samples received at a temperature of	f >0° C to 6.0°C Yes	No [
6. Sample(s) in proper container(s)?	Yes	No		
7. Sufficient sample volume for indicated test(s)?	Yes	No [
8. Are samples (except VOA and ONG) properly	preserved? Yes	No b		
9. Was preservative added to bottles?	Yes	No	NA I	
10.VOA vials have zero headspace?	Yes	No [No VOA Vials 🗸	
11. Were any sample containers received broken	? Yes	. [_] No	# of preserved bottles checked	
12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes	✓ No [for pH:	or >12 unless noted
13 Are matrices correctly identified on Chain of C	ustody? Yes	✓ No [Adjusted?	
14. Is it clear what analyses were requested?	Yes	No No		
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes	M No 🗄	Checked by:	·····
Special Handling (if applicable)				
16. Was client notified of all discrepancies with this	s order? Yes	No 🛛	□ NA 🗹	
Person Notified:	Date	**************************************		-
By Whom:	Via: 🗌 eM	ail 🔲 Phone 🗌 I	Fax []] In Person	

Client Instructions:

17. Additional remarks:

18. Cooler Information

Regarding:

Cooler No	Temp °C	Condition		Seal No	Seal Date	Signed By
1	1.8	Good	Yes			

ł

Page 1 of 1



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

November 21, 2013

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 072

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 2, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

9 P. Vale

Jerry Van Riper Surface Land Negotiator BP America Production Company

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

,

November 21, 2013

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 072 API 30-045-07039 (G) Section 9 – T27N – R12W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Af Peore

Jeff Peace BP Field Environmental Advisor

(505) 326-9479

