District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.
For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

	Pit, Below-Grade Tank, or
	Proposed Alternative Method Permit or Closure Plan Application
11934	Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
	Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised environment. No	that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinan

environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address: _200 Energy Court, Farmington, NM 87401 OIL CONS. DIV DIST. 3
Facility or well name:Atlantic A LS 3A
API Number:3004522507OCD Permit Number:
U/L or Qtr/QtrCSection28 Township31N Range10W County:San Juan
Center of Proposed Design: Latitude36.873885 Longitude107.890824 NAD: ☐1927 ☑ 1983
Surface Owner: ⊠ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed - side walls not visible
Liner type: Thicknessmil
4.
Alternative Method:

Page 1 of 6

5. <u>Fencing</u> : Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital,
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8,	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance of the compliance for each siting criteria below in the application.	otable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	_
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	□ Vas □ Na
from the ordinary high-water mark).	Yes No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	
	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	uments are
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	15.17.9 nmac
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	e documents are
### attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well In Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial	Fluid Management Pit
Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sou provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted presupert to NMCA 1079 Section 2.27.2 or amonded	
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain.	Yes No
- FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	II NMAC 5.17.11 NMAC
07. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:Telephone:	
18. OCD Approval: Permit Application (including closure plan), Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 45/2 Title: OCD Permit Number:	D14
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:6/7/2013	
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-loc ☐ If different from approved plan, please explain.	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please into mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)	licate, by a check

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this belief. I also certify that the closure complies with all applicable closure	closure report is true, accurate and complete to the best of my knowledge and requirements and conditions specified in the approved closure plan.
Name (Print): Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Poace	Date:June 2, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Atlantic A LS 3A Tank A BGT (95 bbl) API No. 3004522507 Unit Letter C, Section 28, T31N, R10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141

Revised August 8, 2011

Santa Fe, NM 87505

Release Notification and Corrective Action

						OPERA'	ГOR		nitial Re	port		Final Report	
Name of Co	mpany: B	Р				Contact: Jeff Peace							
Address: 20	0 Energy (Court, Farmi	ngton, N	M 87401		Telephone No.: 505-326-9479							
Facility Nar	ne: Atlanti	ic A LS 3A				Facility Type: Natural gas well							
Courte on Occ	D. J	-1		M: 10				A Di	200	4500505			
Surface Ow	ner: Feder	aı		Mineral O	wner:	rederai		API	No. 300	4522507			
						OF RE				·			
Unit Letter C	Section 28	Township 31N	Range 10W	Feet from the 1,150	North/ North	South Line	Feet from the 1,500	East/West Li West	ne Cou	inty: San .	Juan		
		Latit	ude36			_	e107.890824_						
				NAT	URE	OF RELI							
Type of Rele			OF LLL T	1- A			Release: N/A		ne Recove				
Source of Release: below grade tank – 95 bbl, Tank A Was Immediate Notice Given?						If YES, To	Our of Occurrenc	e: Date	and Hour	of Discov	ery:		
was militedia	ite Notice C		Yes [No 🛛 Not Re	quired	11 1 E S, 10	whom?						
By Whom?	· · · · · · · · · · · · · · · · · · ·					Date and H	our						
Was a Water	course Reac		Yes 🗵	l No		If YES, Vo	lume Impacting t	he Watercours	e.				
If a Watercou	rse was Im			=			· · · · · · · · · · · · · · · · · · ·						
		, ,											
the BGT. So	il analysis r	esulted in TPI	H, BTEX a	n Taken.* Samplir and chloride below en.* BGT was rer	v standa	rds. Analysis	s results are attach	ned.			-		
backfilled and	d compacted	d and is still w	rithin the	active well area.									
regulations al public health should their o or the enviror	l operators: or the envir perations hament. In a	are required to conment. The ave failed to a	report ar acceptance dequately CD accep	is true and completed of a C-141 repoint investigate and retained for a C-141 repoint investigate and retained of a C-141 repoint investigate and retained for a C-141 retained f	clease no rt by the emediate	otifications ar NMOCD ma contamination	nd perform correct arked as "Final Re on that pose a thre	tive actions for eport" does not eat to ground w	releases v relieve th ater, surfa	which ma ne operato ace water,	y end r of li , hum	anger iability an health	
		0					OIL CONS	SERVATIO	N DIV	ISION			
Signature: 🕻	AR 1	age											
Printed Name	: Jeff Peace	<u> </u>				Approved by	Environmental Sp	pecialist:					
Title: Area Er	vironmenta	al Advisor				Approval Dat	e:	Expirat	Expiration Date:				
E-mail Addre	ss: peace.je	ffrey@bp.con	n			Conditions of	Approval:		Attached				
Date: June 2,	2014	P	hone: 505	-326-9479									

^{*} Attach Additional Sheets If Necessary

ВР		G ENGINEERIN		API#: 3004522507
CLIENT:	P.O. BOX (37, BLOOMFIEL (505) 632-1199		TANK ID (if applicble):
FIELD REPORT:	(circle one): BGT CONFIRI	MATION / RELEASE INVESTIGA	ATION / OTHER:	PAGE#: 1 of 1
SITE INFORMATION		LANTIC A LS # 3		DATE STARTED: 05/29/13
QUAD/UNIT: C SEC: 28 TWP:	31N RNG: 10V	V PM: NM CNTY	SJ ST NM	DATE FINISHED:
1/4 -1/4/FOOTAGE: 1,150'N / 1,50		LEASE TYPE: FEDERAL	KHODN	ENVIRONMENTAL
LEASE #: NM 0606		MV CONTRACTOR: ME	<u> </u>	SPECIALIST(S): NJV
REFERENCE POINT		(H.) GPS COORD.:		OOL NICHIAL
1) 95 BGT (DW/DB) - A 2) 45 BGT (DW/DD) - B	GPS COORD.:	36.873885 X 107.		/BEARING FROM W.H.: 89', N61W
2)	GPS COORD.:	30.073420 X 107.		BEARING FROM W.H.:
4)	GPS COORD.:			/BEARING FROM W.H.:
SAMPLING DATA:	CHAIN OF CUSTODY RECO	PRD(S) # OR LAB USED:	HALL	OVM READING
1) SAMPLE ID: <u>5PC-TB @ 4.5' (9</u>		 05/29/13 SAMPLE TIME:		1/8015B/8021B/300.0(CI) NA
2) SAMPLE ID	•			1/8045B/0024B/300.9(GI) NA
3) SAMPLE ID:			LAB ANALYSIS:	
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:	
SOIL DESCRIPTION	SOIL TYPE: SAN	D / SILT / SILT / SILT	Y CLAY / CLAY / GRAVEL /	OTHER
	DARK YELLOWSH BROV			
COHESION (ALL OTHERS): NON COHESIVE SLIGHTI CONSISTENCY (NON COHESIVE SOILS): L		,	·	C / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC OFT / FIRM / STIFF / VERY STIFF / HARD
MOISTURE: DRY (SLIGHTLY MOIST MOIST / V		· ·		PLANATION -
SAMPLE TYPE: GRAB COMPOSITE				
DISCOLORATION/STAINING OBSERVED	D: YES/[NO] EXPLANATIO	N		
ANY AREAS DISPLAYING WETNESS: YES (NO	EXPLANATION -			
APPARENT EVIDENCE OF A RELEASE (OBSERVED AND/OR OCCU	RRED: YES NO EXPLAN	NATION :	
ADDITIONAL COMMENTS:				
SOIL IMPACT DIMENSION ESTIMATION DEPTH TO GROUNDWATER: <50'	I: NA ft. X NEAREST WATER SOURCE:	NA ft. X NA <1,000' NEAREST SURFACE		STIMATION (Cubic Yards) : NA OCD TPH CLOSURE STD: 100 ppm
	NEAREST WATER SOURCE.			OCD TPH CLOSURE STD: 100 ppm
SITE SKETCH	BERM	PLOT PL		VM CALIB. READ. = NA ppm RF = 0.52
	DEIWII -	1 x		VM CALIB. GAS = <u>NA</u> ppm ME: NA am/om DATE: NA
	SEPARATOR -	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	(95) PBGTL T.B. ~ 4'	
			B.G.	MISCELL. NOTES
	,			WO: N15081455 PO #:
l w.	.н.		İ	PK: ZEVH01BGT2
€)	∠ BERM		PJ#: Z2-00690-C
		DEIM	}	Permit date(s): 06/14/10
PROD.				OCD Appr. date(s): 08/21/12 Tank OVM = Organic Vapor Meter
TANK TANK				ID ppm = parts per million
V 055		\		BGT Sidewalls Visible: Y / N
X - S.P.D. NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVAT	ION DEPRESSION: B.G. = BELOW GF	RADE; B = BELOW; T.H. = TEST HOLE: ^	= APPROX.; W.H. = WELL HEAD:	BGT Sidewalls Visible: Y / N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BE APPLICABLE OR NOT AVAILABLE; SW - SING	LOW-GRADE TANK LOCATION; SPD	= SAMPLE POINT DESIGNATION; R.W.	= RETAINING WALL; NA - NOT	Magnetic declination: 10° E
TRAVEL NOTES: CALLOUT:	LL YVALL, DVV - DOUDLE VVALL, SB - 3	ONSITE:	05/00/40	

Analytical Report Lab Order 1305C03

Date Reported: 6/7/2013

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering
Project: Atlantic A LS #3A

1305C03-002

Lab ID:

Client Sample ID: 5PC-TB@4.5' (95)

Collection Date: 5/29/2013 3:33:00 PM

Received Date: 5/31/2013 10:15:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	2.2.		Analys	t: JME		
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	6/3/2013 12:36:01 PM	7700
Surr: DNOP	91.3	63-147	%REC	1	6/3/2013 12:36:01 PM	7700
EPA METHOD 8015D: GASOLINE RA	NGE				Analys	: NSB
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	6/4/2013 3:24:21 PM	7698
Surr: BFB	86.3	80-120	%REC	1	6/4/2013 3:24:21 PM	7698
EPA METHOD 8021B: VOLATILES					Analys	: NSB
Benzene	ND	0.047	mg/Kg	1	6/4/2013 3:24:21 PM	7698
Toluene	ND	0.047	mg/Kg	1	6/4/2013 3:24:21 PM	7698
Ethylbenzene	ND	0.047	mg/Kg	1	6/4/2013 3:24:21 PM	7698
Xylenes, Total	ND	0.093	mg/Kg	1	6/4/2013 3:24:21 PM	7698
Surr: 4-Bromofluorobenzene	86.9	80-120	%REC	1	6/4/2013 3:24:21 PM	7698
EPA METHOD 300.0: ANIONS					Analys	: JRR
Chloride	ND	7.5	mg/Kg	5	6/5/2013 11:46:31 AM	7759
EPA METHOD 418.1: TPH					Analys	: jmb
Petroleum Hydrocarbons, TR	ND'	20	mg/Kg	1	6/3/2013 12:00:00 PM	7701

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit Page 2 of 9
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1305C03

07-Jun-13

Client:

Blagg Engineering

Project:

Atlantic A LS #3A

MB-7759 Sample ID

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Sample ID LCS-7759

LCSS

6/5/2013

Batch ID: 7759

RunNo: 11115

Prep Date: Analysis Date: 6/5/2013 6/5/2013

SeqNo: 314517

Units: mg/Kg

Analyte

Client ID:

Prep Date:

Result

Result

Result

15

14

SPK value SPK Ref Val **PQL**

HighLimit

RPDLimit

Qual

Chloride

ND 1.5

SampType: LCS

Batch ID: 7759

TestCode: EPA Method 300.0: Anions

%REC LowLimit

RunNo: 11115

90

Units: mg/Kg

110

%RPD

Analyte

Analysis Date: 6/5/2013 PQL

1.5

SeqNo: 314518 SPK value SPK Ref Val

0

15.00

15.00

%REC 92.6

LowLimit HighLimit %RPD **RPDLimit**

Qual

Chloride

Sample ID 1305C03-001BMS 5PC-TB@6.5' (45) SampType: MS

Batch ID: 7759

PQL

7.5

7.5

TestCode: EPA Method 300.0: Anions

RunNo: 11115

Units: mg/Kg

Qual

Analyte

Client ID:

Prep Date: 6/5/2013 Analysis Date: 6/5/2013

2.229

SPK value SPK Ref Val

SeqNo: 314520 %REC

LowLimit HighLimit 109 %RPD

Qual

RPDLimit

Chloride

Sample ID 1305C03-001BMSD Client ID: 5PC-TB@6.5' (45)

SampType: MSD Batch ID: 7759

TestCode: EPA Method 300.0: Anions RunNo: 11115

109

Prep Date:

6/5/2013

Analysis Date: 6/5/2013

SeqNo: 314521

Units: mg/Kg

RPDLimit

Chloride

Analyte

Result POL

14

SPK value SPK Ref Val

15.00

2.229

%REC 81.3

LowLimit 58.8

HighLimit

0.591

%RPD

20

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range E

Analyte detected below quantitation limits J

RSD is greater than RSDlimit 0 RPD outside accepted recovery limits Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded ŀĮ

Sample pH greater than 2 for VOA and TOC only.

ND Not Detected at the Reporting Limit

Reporting Detection Limit

P

Page 3 of 9

Hall Environmental Analysis Laboratory, Inc.

WO#:

1305C03

07-Jun-13

Client: Project: Blagg Engineering Atlantic A LS #3A

Sample ID MB-7701

SampType: MBLK

Result

Client ID:

Analyte

Client ID:

PBS

Batch ID: 7701

RunNo: 11040

TestCode: EPA Method 418.1: TPH

Prep Date:

5/31/2013

Analysis Date: 6/3/2013

PQL

20

SeqNo: 312278

Units: mg/Kg

HighLimit

%RPD **RPDLimit**

Qual

Qual

Petroleum Hydrocarbons, TR

Sample ID LCS-7701

Prep Date: 5/31/2013

LCSS

ND

SampType: LCS

Batch ID: 7701

TestCode: EPA Method 418.1: TPH

RunNo: 11040

SeqNo: 312279

Units: mg/Kg

120

Analyte

Analysis Date: 6/3/2013 **PQL**

LowLimit

SPK value SPK Ref Val Petroleum Hydrocarbons, TR 99 20 99.70 0

%REC 99.1

SPK value SPK Ref Val %REC LowLimit

HighLimit %RPD

RPDLimit Qual

Sample ID LCSD-7701 Client ID: LCSS02

SampType: LCSD

Batch ID: 7701

TestCode: EPA Method 418.1: TPH

RunNo: 11040

80

Units: mg/Kg

Analyte

Prep Date: 5/31/2013 Analysis Date: 6/3/2013

20

SeqNo: 312280

LowLimit HighLimit %RPD

RPDLimit

20

Petroleum Hydrocarbons, TR

99

SPK value SPK Ref Val %REC

99.70

0

99.1

80

120

0

Qualifiers:

0

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range Е
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit RPD outside accepted recovery limits

- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2 for VOA and TOC only. P
- Reporting Detection Limit

Page 4 of 9

Hall Environmental Analysis Laboratory, Inc.

WO#:

Page 5 of 9

1305C03

07-Jun-13

Client:

Blagg Engineering Atlantic A LS #3A

Project:	Atlantic A	A LS #3A									
Sample ID	MB-7700	SampTy	pe: MI	BLK	Tes	tCode: El	PA Method	8015D: Dies	el Range (Organics	
Client ID:	PBS	Batch	ID: 77	00	F	RunNo: 1	1020				
Prep Date:	5/31/2013	Analysis Da	ate: 6/	/3/2013	S	SeqNo: 3	11747	Units: mg/l	≺g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Surr: DNOP	Organics (DRO)	ND 9.3	10	10.00		93.3	63	147			,
Sample ID	LCS-7700	SampTy	pe: LC	s	Tes	tCode: El	PA Method	8015D: Dies	el Range (Organics	
Client ID:	LCSS	Batch	ID: 77	00	F	RunNo: 1	1020				
Prep Date:	5/31/2013	Analysis Da	ate: 6/	3/2013	5	SeqNo: 3	11748	Units: mg/l	K g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
-	Organics (DRO)	45	10	50.00	0	89.8	77.1	128			
Surr: DNOP		4.4		5.000		88.2	63	147			••••
Sample ID	1305C03-001AMS	SampTy	ре: М	3	Tes	tCode: El	PA Method	8015D: Dies	el Range (Organics	
Client ID:	5PC-TB@6.5' (45)	Batch	ID: 77	00	F	RunNo: 1	1020				
Prep Date:	5/31/2013	Analysis Da	ite: 6/	3/2013	8	SeqNo: 3	11868	Units: mg/l	< g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Organics (DRO)	50	10	49.80	0	99.9	61.3	138			
Surr: DNOP		4.7		4.980		93.4	63	147			
Sample ID	1305C03-001AMS	D SampTy	pe: M \$	SD	Tes	tCode: El	PA Method	8015D: Dies	el Range C	Organics	
Client ID:	5PC-TB@6.5' (45)	Batch	ID: 77	00	F	RunNo: 1	1020				
Prep Date:	5/31/2013	Analysis Da	ite: 6/	3/2013	S	SeqNo: 3	11877	Units: mg/k	K g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Organics (DRO)	47	10	50.20	0	94.6	61.3	138	4.70	20	
Surr: DNOP		4.2		5.020		83.1	63	147	0	0	
Sample ID	MB-7743	SampTy	pe: ME	BLK	Tes	tCode: El	PA Method	8015D: Dies	el Range C	rganics	
Client ID:	PBS	Batch	ID: 77	43	F	RunNo: 1	1054				
Prep Date:	6/4/2013	Analysis Da	ite: 6/	4/2013	5	SeqNo: 3	12839	Units: %RE	C		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		9.9		10.00		99.1	63	147			
Sample ID	LCS-7743	SampTy	pe: LC	s	Tes	tCode: El	PA Method	8015D: Dies	el Range (Organics	-
Client ID:	LCSS	Batch	ID: 77	43	F	RunNo: 1	1054				
Prep Date:	6/4/2013	Analysis Da	ite: 6/	4/2013	\$	SeqNo: 3	12840	Units: %RE	:C		
A I- I-				ODK	ODK D-41/-I	0/ DEO	1 1 14	f 10 f- 1 - 1 14	0/ DDD	DDDI imit	Ougl
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual

Qualifiers:

* Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

P Sample pH greater than 2 for VOA and TOC only.

RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1305C03

07-Jun-13

Client:

Blagg Engineering

Project:

Atlantic A LS #3A

Sample ID 1306073-004AMS

SampType: MS Batch ID: 7743 TestCode: EPA Method 8015D: Diesel Range Organics

Client ID: **BatchQC**

PQL

RunNo: 11079

Analyte

Prep Date:

Analysis Date: 6/5/2013

SeqNo: 314233

Units: %REC HighLimit

Result

SPK value SPK Ref Val

%REC LowLimit

Qual

Surr: DNOP

5.0

4.975

101

147

RPDLimit

Qual

Sample ID 1306073-004AMSD

SampType: MSD Batch ID: 7743 TestCode: EPA Method 8015D: Diesel Range Organics RunNo: 11079

%REC

63

Client ID: Prep Date: **BatchQC** 6/4/2013

6/4/2013

Analysis Date: 6/5/2013

PQL

SPK value SPK Ref Val

SeqNo: 314234

Units: %REC HighLimit

RPDLimit

Analyte Surr: DNOP Result 5.7

4.970

115

63

LowLimit

147

%RPD 0

%RPD

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range Е
- Analyte detected below quantitation limits 1
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits

- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit ND
- Sample pH greater than 2 for VOA and TOC only. Reporting Detection Limit

Page 6 of 9

Hall Environmental Analysis Laboratory, Inc.

WO#:

1305C03

07-Jun-13

Client:

Blagg Engineering

Project:

Atlantic A LS #3A

Project:	Atlantic A	A LS #3A 								
Sample ID	MB-7698	SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range								
Client ID:	PBS	Batch ID:	7698	F	tunNo: 1	1056				
Prep Date:	5/31/2013	Analysis Date:	6/4/2013	S	eqNo: 3	13296	Units: mg/h	(g		
Analyte		Result PO	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Rang Surr: BFB	e Organics (GRO)	ND 860	5.0 1000		85.6	80	120			
Sample ID	LCS-7698	SampType:	LCS	Test	Code: El	PA Method	8015D: Gaso	line Rang	e	
Client ID:	LCSS	Batch ID:	7698	R	unNo: 1	1056				
Prep Date:	5/31/2013	Analysis Date:	6/4/2013	S	eqNo: 3	13297	Units: mg/F	(g		İ
Analyte		Result PO	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Rang	e Organics (GRO)		5.0 25.00	0	86.6	62.6	136			
Surr: BFB		900	1000		89.7	80	120			
Sample ID	MB-7744	SampType:	MBLK	Test	Code: El	PA Method	8015D: Gaso	line Rang	e	
Client ID:	PBS	Batch ID:	7744	R	unNo: 1	1113				
Prep Date:	6/4/2013	Analysis Date:	6/5/2013	S	eqNo: 3	14456	Units: %RE	С		
Analyte		Result PC	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: BFB		900	1000		90.4	80	120			
Sample ID	LCS-7744	SampType:	LCS	Test	Code: El	PA Method	8015D: Gaso	line Rang	e	
Client ID:	LCSS	Batch ID:	7744	R	unNo: 1	1113				
Prep Date:	6/4/2013	Analysis Date:	6/5/2013	S	eqNo: 3	14457	Units: %RE	С		
Analyte		Result PC	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: BFB		970	1000		96.9	80	120			
Sample ID	1306073-002AMS	SampType:	MS	Test	Code: EF	PA Method	= 8015D: Gaso	line Rang	е	i
Client ID:	BatchQC	Batch ID:	7744	R	unNo: 1 ′	1113				
Prep-Date:	6/4/2013	Analysis Date:	6/5/2013	S	eqNo: 3	14460	Units: %RE	С		
Analyte		Result PC	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: BFB		950	947.0		100	80	120			
Sample ID	1306073-002AMSI	O SampType:	MSD	Test	Code: EF	PA Method	8015D: Gaso	line Rang	е	
Client ID:	BatchQC	Batch ID:	7744	R	unNo: 1 ′	1113				
Prep Date:	6/4/2013	Analysis Date:	6/5/2013	S	eqNo: 3	14461	Units: %RE	С		
Analyte		Result PC	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: BFB		980	947.0		103	80	120	0	0	

Qualifiers:

* Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

P Sample pH greater than 2 for VOA and TOC only.

RL Reporting Detection Limit

Page 7 of 9

Hall Environmental Analysis Laboratory, Inc.

WO#:

1305C03

07-Jun-13

Client: Project:

Blagg Engineering Atlantic A LS #3A

Sample ID MB-7698	BLK	TestCode: EPA Method 8021B: Volatiles								
Client ID: PBS	Batch ID: 7698 Analysis Date: 6/4/2013			F	RunNo: 1	1056				
Prep Date: 5/31/2013				SeqNo: 313337			Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.89		1.000		88.9	80	120			

Sample ID LCS-7698	TestCode: EPA Method 8021B: Volatiles											
Client ID: LCSS	Batc	h ID: 76 :	98	F								
Prep Date: 5/31/2013	Analysis Date: 6/4/2013			SeqNo: 313338			Units: mg/Kg					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Quai		
Benzene	0.87	0.050	1.000	0	86.8	80	120					
Toluene	0.86	0.050	1.000	0	85.6	80	120					
Ethylbenzene	0.86	0.050	1.000	0	85.6	80	120					
Xylenes, Total	2.6	0.10	3.000	0	86.7	80	120					
Surr: 4-Bromofluorobenzene	0.88		1.000		88.1	80	120					

Sample ID 1305C03-001AMS SampType: MS TestCode: EP.						PA Method	8021B: Vola	tiles					
Client ID: 5PC-TB@6.5' (4	5) Batc	h ID: 76	98	F	RunNo: 1	1056							
Prep Date: 5/31/2013	Analysis [Analysis Date: 6/4/2013			SeqNo: 313340			Units: mg/Kg					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	0.77	0.046	0.9259	0.01403	81.4	67.2	113						
Toluene	0.77	0.046	0.9259	0.01235	81.4	62.1	116						
Ethylbenzene	0.78	0.046	0.9259	0.01590	82.8	67.9	127						
Xylenes, Total	2.4	0.093	2.778	0.02460	84.8	60.6	134						
Surr: 4-Bromofluorobenzene	0.85		0.9259		91.8	80	120						

Sample ID 1305C03-001AMS	D SampType	: MSD		TestCode: EPA Method 8021B: Volatiles								
Client ID: 5PC-TB@6.5' (45)	Batch ID	7698		RunNo: 11056								
Prep Date: 5/31/2013	Analysis Date	6/4/2	:013	S	SeqNo: 3	13341	Units: mg/K	g				
Analyte	Result F	QL S	PK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	0.76 0	.046	0.9259	0.01403	80.7	67.2	113	0.775	14.3			
Toluene	0.76 0	.046	0.9259	0.01235	80.8	62.1	116	0.764	15.9			
Ethylbenzene	0.77 0	.046	0.9259	0.01590	81.4	67.9	127	1.67	14.4			
Xylenes, Total	2.3 0	.093	2.778	0.02460	83.6	60.6	134	1.47	12.6			
Surr: 4-Bromofluorobenzene	0.84		0.9259		90.8	80	120	0	0			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 8 of 9

Hall Environmental Analysis Laboratory, Inc.

WO#: 1305C03

07-Jun-13

Client:

Blagg Engineering

Project:

Atlantic A LS #3A

Sample ID 1306073-001AMS

SampType: MS

TestCode: EPA Method 8021B: Volatiles

LowLimit

80

Client ID: BatchQC Batch ID: 7744

RunNo: 11113

Prep Date: 6/4/2013

SeqNo: 314477

120

Analysis Date: 6/5/2013 PQL

Units: %REC

Analyte

Result

%REC

99.7

Surr: 4-Bromofluorobenzene

0.95

SPK value SPK Ref Val 0.9560

HighLimit

RPDLimit Qual

Sample ID 1306073-001AMSD

SampType: MSD Batch ID: 7744 TestCode: EPA Method 8021B: Volatiles RunNo: 11113

Units: %REC

Analyte

Prep Date: 6/4/2013 Analysis Date: 6/5/2013

SeqNo: 314478

%RPD

Client ID:

%REC SPK value SPK Ref Val

LowLimit

HighLimit

0

Surr: 4-Bromofluorobenzene

BatchQC

Result PQL. 0.96

0.9569

101

80

%RPD

RPDLimit

Qual 0

Sample ID MB-7744

Result

SampType: MBLK

120 TestCode: EPA Method 8021B: Volatiles

Client ID: PBS

Batch ID: 7744

RunNo: 11113

Units: %REC

120

Analyte

Prep Date: 6/4/2013 Analysis Date: 6/5/2013 PQL

SegNo: 314491 SPK value SPK Ref Val %REC

LowLimit HighLimit

80

%RPD

RPDLimit

Qual

Surr: 4-Bromofluorobenzene Sample ID LCS-7744

0.95 SampType: LCS 1.000 95.3

TestCode: EPA Method 8021B: Volatiles

RunNo: 11113

Prep Date:

Client ID:

LCSS 6/4/2013 Batch ID: 7744

Result

0.98

Analysis Date: 6/5/2013

SeqNo: 314492

Units: %REC

Qual

Analyte Surr: 4-Bromofluorobenzene

SPK value SPK Ref Val

1.000

%REC 98.2

80

HighLimit 120 %RPD **RPDLimit**

J

Qualifiers: Value exceeds Maximum Contaminant Level.

Analyte detected below quantitation limits

RPD outside accepted recovery limits

Value above quantitation range

RSD is greater than RSDlimit 0

Analyte detected in the associated Method Blank

Sample pH greater than 2 for VOA and TOC only.

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Reporting Detection Limit

P

Page 9 of 9

Chain-of-Custody Record			Turn-Around Time:				1 1	1 1	ŀ	ł A	LL	E	NV	/TF	2 0	NI	ИF	NT	ΔL		
lient:	BLAG	G ENGR.	/ BP AMERICA	✓ Standard	Rush														TO		
				Project Name:				www.hallenvironmental.com													
/lailing A	ddress:	P.O. BO	X 87	ATLANTIC A LS # 3A				4901 Hawkins NE - Albuguergue, NM 87109													
		BLOOM	FIELD, NM 87413	Project #:			Tel. 505-345-3					5-3975 Fax 505-345-4107									
'hone #: (505) 632-1199			}			13.	5 () () () () () () () () () (- al			Ž	\nal	ysis	Rec	lues	ť		g ver	,		
mail or Fax#:			Project Manag	ger:				mu	_				(T	
⊋A/QC Pa ☑ Stand	C Package: Standard		Level 4 (Full Validation)		NELSON VI	ELEZ	(80218)	TPH (Gas only)	/www			15)		05,50	PCB's			er - 300.1)		a	,
Accreditat	tion:			Sampler:	NELSON VI	ELEZ AV	-\ <u>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</u>	(Gas	/ DRO /	न	Ŧ	SIS		102,1	8082			/ water		au au	
□ NELAF)	□ Other		On Ice	XL Yes		1	TPH		418.1)	504.1)	827	ر ا	03,1	_		द्व	300.0 /		eS a	: :
□ EDD (Type)			Sample Temp	erature: \ 🕡		L	+	(GRO	g	bo	ō	etak	C,N	cide	(A)	j-V(و	ا إ إِنَّا	.
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No	BTEX + WITE	BTEX + MTBE	TPH 8015B	TPH (Method	EDB (Method	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil	Grah camr	5 of composite sample	
5/29/23	1593	SOIL		40z. 2	Cocl	-001	*		V	*								V		4	7
	 	 							_											+	Ť
5/29/13	1538	SOIL	5PC-TB @ 4.5' (95)	4 oz 2	Cool	-002	٧		٧	٧								٧	工	V	1
	ļ	<u> </u>					<u> </u>			_	\dashv			_				-		\bot	\downarrow
	<u> </u>	<u> </u>	·						_	_											\perp
																			\perp		1
																					L
																	,				
																					
																					T
	1																				T
Date:	Time:	Relinquish	ed by:	Received by:		Date Time	Ren	narks	 S:						L			<u>-</u>			_
/30/13	835	Me	holf-	Mustin	بمامه صاعب	5/30/13 835	•	L DIF						_							
Date:	Time:	Relinquish	ed by: U	Received by:	, ,	Date Time	l	f Pea							_				34 B.C.		
3/20/13	11745	Nor Nor	stre 1 Dalley	H	05/31	13 1015	Lw	ork O	rder:		<u>N15</u>	<u>.081</u>	<u>455</u>		Pay	ykey	:Z	<u>.EVHC</u>	01BG1	2	
										١.				:11 ha	doortu	notati	an ha	he ana	lutical re	nort	



Hall Environmental Analysis Laborator) 4901 Hawkins NE Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-410; Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG Work Order N	umber: 1305C03		RcptNo: 1
Received by/date: 05 31	3		
Logged By: Ashley Gallegos 5/31/2013 10:15	S-00 AM	A	
		-A	
Completed By: Ashley Gallegos 5/31/2013 11:47	1:56 AIVI	SAF	
Reviewed By: 15/3///3			
Chain of Custody	_		
1. Custody seals intact on sample bottles?	Yes _	No 🗔	Not Present 🗹
2. Is Chain of Custody complete?	Yes 🗹	No 📙	Not Present 🗔
3. How was the sample delivered?	Courier		
<u>Log In</u>			
4. Was an attempt made to cool the samples?	Yes 🗹	No 🗌	na 🗆
5. Were all samples received at a temperature of >0° C to 6.0°C	C Yes ⊻	No 🗆	NA 🗆
6. Sample(s) in proper container(s)?	Yes 🗸	No 🗌	
7. Sufficient sample volume for indicated test(s)?	Yes 🔽	No 🗆	
8. Are samples (except VOA and ONG) properly preserved?	Yes 🗹	No 🗌	
9. Was preservative added to bottles?	Yes 🗌	No 🗹	NA 🗆
10.VOA vials have zero headspace?	Yes	No 🗆	No VOA Vials
11. Were any sample containers received broken?	Yes	No 🗹	# of preserved
		(7)	bottles checked
12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes 🗹	No ∐	for pH: (<2 or >12 unless noted)
13. Are matrices correctly identified on Chain of Custody?	Yes 🗹	No □	Adjusted?
14. Is it clear what analyses were requested?	Yes 🗹	No 🗆	
15. Were all holding times able to be met?	Yes 🗹	No 🗆	Checked by:
(If no, notify customer for authorization.)		٠ , ,	
Charles Handling (if applicable)			
Special Handling (if applicable) 16. Was client notified of all discrepancies with this order?	Yes 🗌	No 🗆	NA 🗹
A	Date:	ono 🗆 Foy	☐ In Person
The same who have the property of the contract	/ia: ∐ eMail ∐ Pt	none	
Regarding:	,	Maria da Maria de Carrero de Carr	PROTES OF THE CASE OF THE OFFICE OF THE CASE OF THE CA
Client Instructions: 17. Additional remarks:	an endan ter in er er distribuk biskursaksaksaksak es 2 erren	e ar Sadak dan militaran kepada an makada (h. 1821).	and CONTROL of the control of districts of
18. Cooler Information Cooler No Temp °C Condition Seal Intact Seal I	No Seal Date	Signed By	
1 1.0 Good Yes			





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

April 9, 2013

Bureau of Land Management Mark Kelly 1235 La Plata Hwy Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: ATLANTIC A LS 003A

Dear Mr. Kelly

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about April 24, 2013. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper Surface Land Negotiator

AD Van Rien

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

April 8, 2013

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ATLANTIC A LS 003A API 30-045-22507 (G) Section 28 – T31N – R10W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 45 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



