District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-	-Grade Tank, or	•	
Duamagad Altamativa Matha al			<u>n</u>
Type of action: Below grade tank registration	I		
☐ Closure of a pit, below-grade☐ Modification to an existing po		ernative method	
Closure plan only submitted to		ted or non-permitted pit, b	elow-grade tank,
or proposed alternative method			
Instructions: Please submit one application (Form C-1			
Please be advised that approval of this request does not relieve the operator of lia environment. Nor does approval relieve the operator of its responsibility to compare the operator of its responsibility t	bility should operations roly with any other applications.	esult in pollution of surface wa able governmental authority's r	iter, ground water or the ules, regulations or ordinances.
ı. Operator: BP America Production Company	OGRID	#:778	
Address:200 Energy Court, Farmington, NM 87401			
Facility or well name:Gallegos Canyon Unit 527			
API Number:3004529033O			
U/L or Qtr/Qtr P Section 27 Township 29	N Range12W	County:San Ju	ıan
Center of Proposed Design: Latitude36.69282	Longitude108.0813	9	NAD: □1927 ⊠ 1983
Surface Owner: 🗌 Federal 🔲 State 🔀 Private 🔲 Tribal Trust or Indian A			
2.			
Pit: Subsection F, G or J of 19.15.17.11 NMAC			
Temporary: Drilling Workover			
Permanent Emergency Cavitation P&A Multi-Well Flui	d Management	Low Chloride Drilling Fl	luid 🗌 yes 🔲 no
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDP	E 🔲 HDPE 🔲 PVC	Other	·
☐ String-Reinforced			
Liner Seams:  Welded Factory Other	Volume:		
3.		OIL CONS.	DIV DIST, 3
Below-grade tank: Subsection 1 of 19.15.17.11 NMAC	Tank A	AAAV O	0.0044
Volume:95.0bbl Type of fluid:Produced w	vater	MAY 2	U 2014
Tank Construction material: Steel			
Secondary containment with leak detection Visible sidewalls, line	r, 6-inch lift and autom:	atic overflow shut-off	
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other ☐ Do	uble walled/double bot	omed, side walls not visible	
Liner type: Thickness mil  HDPE PVC [		•	
4.			
Alternative Method:			
Submittal of an exception request is required. Exceptions must be submitted.	ed to the Santa Fe Envi	onmental Bureau office for c	consideration of approval.
5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits,	temporary pits, and be	ow-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Require			ce, school, hospital,
institution or church)			•
Four foot height, four strands of barbed wire evenly spaced between one	e and four feet		

Alternate. Please specify\_

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	☐ Yes ☐ No
from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)	☐ Yes ☐ No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached.  Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number:  or Permit Number:	NMAC  15.17.9 NMAC
II.	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Previously Approved Design (attach copy of design) API Number: or Permit Number: or Permit Number:	.15.17.9 NMAC

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached.  ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC  ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  ☐ Climatological Factors Assessment  ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC  ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC  ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  ☐ Quality Control/Quality Assurance Construction and Installation Plan  ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H₂S, Prevention Plan  ☐ Gil Field Waste Stream Characterization  ☐ Monitoring and Inspection Plan  ☐ Erosion Control Plan  ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.  Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC  Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sout provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:Telephone:	
18.  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
OCD Representative Signature: Approval Date:	
Title: OCD Permit Number:	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date:3/20/2014	
20.	
Closure Method:  ☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo ☐ If different from approved plan, please explain.	op systems only)

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure repor	t is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all applicable closure requirements	and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Seff Pare	Date:May 20, 2014
810	
e-mail address:peace.jeffrey@bp.com	Telephone:(503)326-9479

#### BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

# Gallegos Canyon Unit 527 API No. 3004529033 Unit Letter P, Section 27, T29N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

#### General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
  - No notice was sent.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
  - No notice was sent.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	34

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

    Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

#### State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141

Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

	Release Notification and Corrective Action											
						OPERA?	ГOR		nitia	l Report	$\boxtimes$	Final Report
Name of Co			NT	NA 07401		Contact: Jef		170				
		Court, Farmi os Canyon U		M 8/401			No.: 505-326-94 e: Natural gas v					
			71111 327				C. Ivatarar gas v					
Surface Ow	ner: Priva	te		Mineral C	)wner:	Private		AP.	No.	30045290	)33	
, <del></del>	T	<u> </u>				N OF REI	LEASE					
Unit Letter P	Section 27	Township 29N	Range 12W	Feet from the 975	North/ South	South Line	Feet from the 1,150	East/West Last	ine	County: Sa	an Juar	1
		Lat	itude3	6.69282		_ Longitude	e108.08139_		_			
,				NAT	URE	OF RELI						
Type of Rele		v grade tank	05 bbl				Release: N/A our of Occurrence			ecovered: Nour of Disc		, NI/A
Source of Release: below grade tank – 95 bbl				N/A	our of Occurrenc	ie. Date	and r	ioui oi Disi	covery	. IN/A		
Was Immedi	ate Notice (		Yes [	] No 🛛 Not Re	equired	If YES, To	Whom?					
By Whom?					Date and H							
Was a Watercourse Reached? ☐ Yes ☐ No					If YES, Vo	lume Impacting t	the Watercours	e.				
If a Watercou	ırse was Im	pacted, Descri	be Fully.*	<u> </u>								
the BGT. So below the sur	il analysis r rface. Wate	esulted in TPI r analysis resu and Cleanup A	I, BTEX alted in BT	n Taken.* Samplin and chlorides belon TEX below standa ten.* BGT was ren active well area.	ow stand ords. An	ards. A water alysis results	r sample was also are attached.	taken since gr	ound	water was f	found a	nt five feet
regulations al public health should their c or the environ	Il operators or the envir operations h nment. In a	are required to onment. The ave failed to a	report ar acceptanc dequately CD accep	is true and complete of a C-141 repoint is true and complete of a C-141 repoint investigate and retaince of a C-141 repoint in the complete is the complete and retains and retains and retains a complete in the complete is the complete in the complete in the complete in the complete is the complete in	elease no ort by the emediate	otifications and NMOCD made contamination	ed perform correct arked as "Final Roon that pose a three	tive actions for eport" does no eat to ground v	relea relie ater,	uses which is ve the opera surface wat	may en ator of ter, hui	idanger Tiability man health
		)					OIL CONS	SERVATIO	)N I	DIVISIO	N	
Signature:	off 1	gael										
Printed Name	e: Jeff Peace	÷				Approved by	Environmental S <sub>I</sub>	pecialist:				
Title: Area E	nvironment	al Advisor				Approval Date	<del>2</del> :	Expirat	ion D	ate:	····	
E-mail Addre	ess: peace.je	effrey@bp.com	n		(	Conditions of	Approval:			Attached		
Date: May 2	20, 2014		Phone: 50	05-326-9479								

<sup>\*</sup> Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, BL	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199					
FIELD REPORT:	(circle one): BGT CONFIRMATION / R	RELEASE INVESTIGATION / OTHER:		PAGE #: <b>1</b>	of <b>1</b>		
SITE INFORMATION	I: SITE NAME: GCU # 5	27		DATE STARTED: 03	/17/14		
QUAD/UNIT: P SEC: 27 TWP:	29N RNG: 12W PM:	NM CNTY: SJ ST	NM	DATE FINISHED:			
1/4 -1/4/FOOTAGE: 975'S / 1,150	'E SE/SE LEASE TYP	E: FEDERAL/STATE FEE	INDIAN	ENVIRONMENTAL			
LEASE #:	PROD. FORMATION: PC CON			SPECIALIST(S):	JCB		
REFERENCE POINT	: WELL HEAD (W.H.) GPS C	OORD.: 36.69265 X 1	08.08121	GL ELEV.:	5.345'		
1) 95 BGT (DW/DB)	GPS COORD.: 36.0	69282 X 108.08139		RING FROM W.H.: 86',	N48W		
2)	GPS COORD.:		DISTANCE/BEAL	RING FROM W.H.:			
3)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:			
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:			
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR I	LAB USED: <b>HALL</b>			OVM READING (ppm)		
1) SAMPLE ID: 95 BGT 4 pt. S	N @ 4' SAMPLE DATE: 03/17/14	4 SAMPLETIME: 1350 LAB ANA	ysis: <b>418.1/8</b>	3015B/8021B/300.0(C			
2) SAMPLEID: 95 BGT GW				· · · · · · · · · · · · · · · · · · ·	NA		
3) SAMPLEID:	SAMPLE DATE:	SAMPLE TIME: LAB ANAI	YSIS:				
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANA	YSIS:				
SOIL DESCRIPTION	SOIL TYPE: SAND / SILTY SAND SILT	F / SILTY CLAY / CLAY / GRAVEL / OTH	ER				
SOIL COLOR: DARK YELL		LASTICITY (CLAYS): NON PLASTIC / SLIGH		OHESIVE / MEDIUM PLASTIC / HIS	SHLY PLASTIC		
COHESION (ALL OTHERS): NON COHESIVE SLIGHTL		ENSITY (COHESIVE CLAYS & SILTS):					
CONSISTENCY (NON COHESIVE SOILS): LO		C ODOR DETECTED: YES NO EXPLA	IATION -				
SAMPLE TYPE: GRAB / COMPOSITE #		NY AREAS DISPLAYING WETNESS: YES	NO EXPLAN	NATION - GROUNDWATER	@ 5 FT.		
DISCOLORATION/STAINING OBSERVED: YES N							
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER:	D AND/OR OCCURRED : YES NO EXPLAN						
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA f	rt. X NA ft. EXC	AVATION EST	IMATION (Cubic Yards) :	NA		
DEPTH TO GROUNDWATER: <a href="#">&lt;50'</a>	IEAREST WATER SOURCE: >1,000'	NEAREST SURFACE WATER: <1,0	00' NMOC	D TPH CLOSURE STD: 10	) <b>0</b> ppm		
SITE SKETCH	BGT Located: off on site	PLOT PLAN circle: at	tached 0VM	CALIB. READ. = 99.7	ppm RE = 1.00		
		5-11-1			ppm RF = 1.00		
BERM			N TIME	: _ <b>1:55</b> an(pm) DATE: _(	3/17/14		
	PBGTL		··· =	MISCELL. NO	TES		
	T.B. ~ 5' B.G.		l w	/o: <b>N15172963</b>			
	<b>1</b> .6.		P	O #:			
SEPARATOR	W.H.		<u>P</u>	k: ZEVH01BGT	2		
	$\oplus$	PUMP JACK	_	J#: Z2-006Q0	4/40		
		V UNOIN		ermit date(s): 06/1			
		·	Tan		leter		
	COMPRESSOR		<u>ID</u>	ppm = parts per million BGT Sidewalls Visible: Y			
	COMI INCOOK	X - S.P.I		BGT Sidewalls Visible: Y			
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATI	ON DEPRESSION: B.G. = RELOW GRADE: R = RELO	_		BGT Sidewalls Visible: Y	/ N_		
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	OW-GRADE TANK LOCATION; SPD = SAMPLE POIN	NT DESIGNATION; R.W. = RETAINING WALL; N.	NOT NOT	lagnetic declination: 1	<b>0</b> °E		
APPLICABLE OR NOT AVAILABLE; SW - SINGL NOTES:	E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM	w; DB - DOUBLE BOTTOM.  ONSITE: 03/17/14					

#### **Analytical Report**

Lab Order 1403746

Date Reported: 3/20/2014

# Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT GW @ 5'

Project: GCU 527

Collection Date: 3/17/2014 1:40:00 PM

**Lab ID:** 1403746-001

Received Date: 3/18/2014 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8021B: VOLATILES					Analys	: NSB
Benzene	ND	2.0	μg/L	2	3/18/2014 4:46:55 PM	R17409
Toluene	ND	2.0	μg/L	2	3/18/2014 4:46:55 PM	R17409
Ethylbenzene	ND	2.0	μg/L	2	3/18/2014 4:46:55 PM	R17409
Xylenes, Total	ND	4.0	μg/L	2	3/18/2014 4:46:55 PM	R17409
Surr: 4-Bromofluorobenzene	101	82.9-139	%REC	2	3/18/2014 4:46:55 PM	R17409
EPA METHOD 300.0: ANIONS					Analys	: JRR
Chloride	65	5.0	mg/L	10	3/18/2014 9:36:44 PM	R17418

Matrix: AQUEOUS

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 9

- P Sample pH greater than 2.
- RL Reporting Detection Limit

#### **Analytical Report**

#### Lab Order 1403746

Date Reported: 3/20/2014

#### Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Client Sample ID: 95 BGT 4-pt Sidewall @ 4'

**Collection Date:** 3/17/2014 1:50:00 PM

GCU 527 Project: Lab ID: 1403746-002

Received Date: 3/18/2014 10:00:00 AM

Analyses	Result	RL Qu	ual Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	SE ORGANICS				Analyst	:: BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	3/19/2014 12:40:00 PM	12227
Surr: DNOP	97.2	66-131	%REC	1	3/19/2014 12:40:00 PM	12227
EPA METHOD 8015D: GASOLINE R.	ANGE				Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	3/19/2014 11:48:27 AM	12232
Surr: BFB	90.2	74.5-129	%REC	1	3/19/2014 11:48:27 AM	12232
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.047	mg/Kg	1	3/19/2014 11:48:27 AM	12232
Toluene	ND	0.047	mg/Kg	1	3/19/2014 11:48:27 AM	12232
Ethylbenzene	ND	0.047	mg/Kg	1	3/19/2014 11:48:27 AM	12232
Xylenes, Total	ND	0.094	mg/Kg	1	3/19/2014 11:48:27 AM	12232
Surr: 4-Bromofluorobenzene	106	80-120	%REC	1	3/19/2014 11:48:27 AM	12232
EPA METHOD 300.0: ANIONS					Analyst	: JRR
Chloride	34	30	mg/Kg	20	3/18/2014 5:42:21 PM	12222
EPA METHOD 418.1: TPH					Analyst	BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	3/19/2014	12240

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Ε Value above quantitation range
- Analyte detected below quantitation limits J
- O RSD is greater than RSDImit
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- Not Detected at the Reporting Limit ND

Page 2 of 9

- Sample pH greater than 2.
- Reporting Detection Limit RL

#### Hall Environmental Analysis Laboratory, Inc.

WO#: 1403746

20-Mar-14

Client:

Blagg Engineering

Project:

GCU 527

Sample ID MB-12222

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 12222

**PQL** 

RunNo: 17414

Prep Date: 3/18/2014

Analysis Date: 3/18/2014 Result

SeqNo: 501540

Units: mg/Kg

HighLimit

%RPD **RPDLimit** 

Qual

Analyte Chloride

Client ID:

ND 1.5

SampType: LCS Batch ID: 12222 TestCode: EPA Method 300.0: Anions RunNo: 17414

Prep Date: 3/18/2014

Sample ID LCS-12222

LCSS

Analysis Date: 3/18/2014

SeqNo: 501541

Units: mg/Kg

%RPD

Qual

Analyte Chloride

15.00

LowLimit

1.5

SPK value SPK Ref Val %REC

SPK value SPK Ref Val %REC LowLimit

96.0

HighLimit

**RPDLimit** 

14

90

110

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits ı
- RSD is greater than RSDlimit О
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2. Reporting Detection Limit RL

Page 3 of 9

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1403746 20-Mar-14

.....

Client:

Blagg Engineering

Project:	GC	CU 527					
Sample ID	MB	SampType: MBLK	TestCode: EPA Method 3	300.0: Anions			
Client ID:	PBW	Batch ID: R17418	RunNo: 17418				
Prep Date:		Analysis Date: 3/18/2014	SeqNo: 501708	Units: mg/L			
Analyte		Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit 5	%RPD	RPDLimit	Qual
Chloride		ND 0.50					
Sample ID	LCS	SampType: LCS	TestCode: EPA Method 3	300.0: Anions			
Client ID:	LCSW	Batch ID: R17418	RunNo: 17418				
Prep Date:		Analysis Date: 3/18/2014	SeqNo: 501709	Units: mg/L			
Analyte		Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit 9	%RPD	RPDLimit	Qual
Chloride		4.7 0.50 5.000	0 95.0 90	110			
Sample ID	MB	SampType: MBLK	TestCode: EPA Method 3	00.0: Anions			
Client ID:	PBW	Batch ID: R17418	RunNo: 17418				
Prep Date:		Analysis Date: 3/18/2014	SeqNo: 501762	Units: mg/L			
Analyte		Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit 9	%RPD	RPDLimit	Qual
Chloride	_	ND 0.50					
Sample ID	LCS	SampType: LCS	TestCode: EPA Method 3	00.0: Anions			
Client ID:	LCSW	Batch ID: R17418	RunNo: 17418				
Prep Date:		Analysis Date: 3/18/2014	SeqNo: 501763	Units: mg/L			
Analyte		Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %	%RPD	RPDLimit	Qual
Chloride		4.7 0.50 5.000	0 93.1 90	110			

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 9

# Hall Environmental Analysis Laboratory, Inc.

Result

100

20

WO#: 1403746

20-Mar-14

Client:

Analyte

Petroleum Hydrocarbons, TR

Blagg Engineering

GCH 527

Sample ID MB-12240	SampType: MBLK	TestCode: EPA Method	418.1: TPH							
Client ID: PBS	Batch ID: 12240	RunNo: 17411								
Prep Date: 3/18/2014	Analysis Date: 3/19/2014	SeqNo: <b>501513</b>	Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual						
Petroleum Hydrocarbons, TR	ND 20									
Sample ID LCS-12240	SampType: LCS	TestCode: EPA Method	418.1: TPH							
Client ID: LCSS	Batch ID: 12240	RunNo: 17411								
Prep Date: 3/18/2014	Analysis Date: 3/19/2014	SeqNo: 501514	Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual						
Petroleum Hydrocarbons, TR	97 20 100.0	0 97.0 80	120							
Sample ID LCSD-12240	SampType: LCSD	TestCode: EPA Method	418.1: TPH							
Client ID: LCSS02	Batch ID: 12240	RunNo: 17411								

0

%REC

101

LowLimit

80

HighLimit

120

SPK value SPK Ref Val

100.0

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range E
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit O
- RPD outside accepted recovery limits R
- S Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2.
- Reporting Detection Limit RL

Page 5 of 9

**RPDLimit** 

20

%RPD

4.16

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1403746 20-Mar-14

Client:

Blagg Engineering

Project:

GCU 527

Project: GCO													
Sample ID MB-12227	SampTyp	oe: ME	BLK	TestCode: EPA Method 8015D: Diesel Range Organics									
Client ID: PBS	Batch I	D: <b>12</b> 2	227	F	RunNo: 1	7407							
Prep Date: 3/18/2014	Analysis Dat	te: <b>3/</b>	19/2014	8	01466	Units: mg/k	Jnits: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Diesel Range Organics (DRO)	ND	10				_	•						
Surr: DNOP	8.3		10.00		83.2	66	131						
Sample ID LCS-12227	SampTyp	e: LC	s	Tes	tCode: El	PA Method	8015D: Dies	el Range (	Organics				
Client ID: LCSS	Batch II	D: <b>12</b> 2	227	F	RunNo: 1	7407							
Prep Date: 3/18/2014	Analysis Dat	e: <b>3/</b>	19/2014	SeqNo: <b>501518</b>			Units: mg/k	(g					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Diesel Range Organics (DRO)	48	10	50.00	0	96.0	60.8	145						
Surr: DNOP	4.6		5.000		91.5	66	131						

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

P Sample pH greater than 2.

RL Reporting Detection Limit

Page 6 of 9

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1403746

20-Mar-14

Client:

Blagg Engineering

Project:

GCU 527

Sample ID MB-12232	Sampl	Гуре: МЕ	BLK	Tes	tCode: E	PA Method	8015D: Gaso	oline Rang	е				
Client ID: PBS	Batcl	h ID: 12	232	F	RunNo: 1	7430							
Prep Date: 3/18/2014	Analysis [	Date: 3/	19/2014	SeqNo: <b>502301</b> Ur			Units: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Gasoline Range Organics (GRO)	ND	5.0											
Surr: BFB	890		1000		88.9	74.5	129						
Sample ID LCS-12232	SampT	Гуре: <b>L</b> C	s	Tes	tCode: E	PA Method	8015D: Gaso	line Rang	e				
Client ID: LCSS	Batcl	h ID: <b>12</b>	232	F	RunNo: 1	7430							
Prep Date: 3/18/2014	Analysis D	Date: 3/	19/2014	S	SeqNo: <b>5</b>	02302	Units: mg/F	ζg					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Gasoline Range Organics (GRO)	28	5.0	25.00	0	112	71.7	134						
Surr: BFB	960		1000		95.7	74.5	129						

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 7 of 9

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1403746

20-Mar-14

Client:

Blagg Engineering

Project:

GCÙ 527

Sample ID MB-12232	Sampl	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles							
Client ID: PBS	Batcl	h ID: <b>12</b>	232	F	RunNo: 1	7430						
Prep Date: 3/18/2014	Analysis Date: 3/19/2014			SeqNo: <b>502319</b>			Units: mg/K	(g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	ND	0.050										
Toluene	ND	0.050										
Ethylbenzene	ND	0.050										
Xylenes, Total	ND 0.10											
Surr: 4-Bromofluorobenzene	1.1	1.1 1.000			105 80							

Sample ID LCS-12232	Samp	Type: LC	S	Tes	8021B: Volat	tiles								
Client ID: LCSS	Batc	h ID: 12	232	F	RunNo: 1									
Prep Date: 3/18/2014	Analysis [	Date: 3/	19/2014	SeqNo: <b>502320</b> L			Units: mg/Kg							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Benzene	1.1	0.050	1.000	0	111	80	120							
Toluene	1.0	0.050	1.000	0	104	80	120							
Ethylbenzene	1.1	0.050	1.000	0	105	80	120							
Xylenes, Total	3.1	0.10	3.000	0	105	80	120							
Surr: 4-Bromofluorobenzene	1.1		1.000		112	80	120							

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit О
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- Reporting Detection Limit

Page 8 of 9

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1403746

20-Mar-14

Client:

Blagg Engineering

Project:

GCU 527

Sample ID 5ML RB	SampT	ype: ME	BLK	Tes	8021B: Volat	iles				
Client ID: PBW	Batch	n ID: <b>R1</b>	7409	F	RunNo: 1	7409				
Prep Date:	Analysis Date: 3/18/2014			SeqNo: <b>501509</b>			Units: µg/L			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	1.0								
Toluene	ND	1.0								
Ethylbenzene	ND	1.0								
Xylenes, Total	ND	2.0								
Surr: 4-Bromofluorobenzene	20		20.00		99.0	82.9	139			

Sample ID 100NG BTEX LO	CS Samp1	Гуре: <b>LC</b>	s	Tes	8021B: Volat	iles					
Client ID: LCSW	Batcl	h ID: <b>R1</b>	7409	F							
Prep Date:	Analysis [	Date: 3/	18/2014	SeqNo: <b>501510</b> U			Units: µg/L				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	20	1.0	20.00	0	99.2	80	120			-	
Toluene	20	1.0	20.00	. 0	100	80	120				
Ethylbenzene	20	1.0	20.00	0	99.2	80	120				
Xylenes, Total	61	2.0	60.00	0	101	80	120				
Surr: 4-Bromofluorobenzene	19		20.00		93.3	82.9	139				

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 9 of 9

C	Chain-of-Custody Record  Client: BLACK ENGINEERIK INC.  BP AMERICA  Mailing Address: P.O. Box 87			Turn-Around	Time:	By THURSDAY 3-20-2014				H	AL	_L	EN	V	'IR	10	NI	1E	NT	'AI	L
Client:	to B	LAGG E	NOWEEUR INC.	□ Standard		1	.   -		_					_				RA			
	RP	AME	RLC A	Project Name	):		www.hallenvironmental.com														
Mailing	Address	P.O.	Bax 87	GC	U 527		4901 Hawkins NE - Albuquerque, NM 87109														
	Read	NEIELD	NM 87413	Project #:						5-34							4107				
Phone #			2-1199								) - 4	Ar	naly	sis I	Requ	uest	į.	ا المحمد م		4.1.4	
email or	Fax#:			Project Mana	ger:		1_	줉	ହ୍ଲ				- {	3				- [			
QA/QC F	Package:			TR				3270 SIMS) 1982 PCB's 1983 PCB's 1983 PCB's 1983 PCB's 1983 PCB's													
Stan	dard		□ Level 4 (Full Validation)	J- 5CA66					2		•	<u> </u>		욊	Z P			1	. }	Ì	
Accredi		□ Othe	r	J-BLAGE Sampler: J-BLAGE Onlice: XYes X DENO.				TPH	0/0	18.1)		8270		No.	/ 808		क्र	ļ			
□ EDD	(Type)			Sample remorature.					9	4 b	ပို	ö	tals	义	des		Š		į		
Date	Time	Matrix	Sample Request ID		Preservative Type		BTEX + MTBE	BTEX + MTBE + TPH (Gas only)	ТРН 8015B (GRO / DRO / 144BC)	TPH (Method 418.1)	EDB (Method 504.1)	PAH's (8310 or	RCRA 8 Metals	Anions (F,CI,NO <sub>3</sub> ,NO <sub>2</sub> ,PO <sub>4</sub> ,SO <sub>4</sub> )	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHORIDE			
3/1/2014	1340	WATER	95 BET 6W @ 5	ZXVOA	HaClz	-661	×		Ì												$\neg$
14	ч	u	W	L×Soone	- 0-	-001						$\top$						X		$\exists$	$\neg$
. 11	1350	SOIL	4-pt sidewall @ 4	1×402	COUL	-002	×		×	×								×			耳
	<u>.</u>									_	-	$\dashv$	_	_			_	_	$\dashv$	_	_
			·				-		_			+	_	$\dashv$				$\overline{}$	$\dashv$		$\dashv$
							-					$\dashv$	$\dashv$	$\dashv$		-		_	$\dashv$	$\dashv$	$\dashv$
							+		_			$\dashv$	_	$\dashv$		_			$\dashv$		$\dashv$
																					1
																					$\Box$
													_						$\dashv$	_	$\rightarrow$
	<del></del> -			6								$\bot$									
3/11/2014	Time: 15 <i>0</i> 6	Relinquishe	1 B 49	Received by:	Walter	Date Time 3/17/2014 1506	Rer	Remarks: BILL BP PARKEY: ZEVHO1BGT2													
Date:	Time:	Relinquishe	ed by:	Received by:	1	Date Time		Contact: Jeff Reace													
	If necessary, samples submitted to Hall Environmental may be subcontracted to other adcredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report.																				



4901 Hawkins NE Albuquerque, NM 87109

HALL BUYD OUIDCHIM MUNICIPAIA BADOLUIOLY

### Sample Log-In Check List

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com Client Name: **BLAGG** Work Order Number: 1403746 RcptNo: 1 Received by/date: Logged By: Michelle Garcia 3/18/2014 10:00:00 AM 3/18/2014 10:42:12 AM Completed By: Michelle Garcia 03/18 Reviewed By: O E Chain of Custody Yes 🗔 Not Present ✔ 1 Custody seals intact on sample bottles? No 🗓 Yes 🗸 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In 4. Was an attempt made to cool the samples? Yes 🗸 NA No i5. Were all samples received at a temperature of >0° C to 6.0°C Yes 🗸 No NA No 🔡 6. Sample(s) in proper container(s)? Yes 🗸 7. Sufficient sample volume for indicated test(s)? No ... Yes 8. Are samples (except VOA and ONG) properly preserved? Yes . No 🗸 NA 🛄 9. Was preservative added to bottles? 10. VOA vials have zero headspace? No No VOA Vials V Yes 11. Were any sample containers received broken? Yes No 🗸 # of preserved bottles checked No for pH: 12. Does paperwork match bottle labels? Yes (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No 🛄 13. Are matrices correctly identified on Chain of Custody? ~ No 14. Is it clear what analyses were requested? Checked by: 15. Were all holding times able to be met? No 📋 Yes (If no, notify customer for authorization.) Special Handling (if applicable) 16. Was client notified of all discrepancies with this order? Yes Νo NA Y Person Notified: Date: in Person By Whom: Via: Fax eMail Phone ' Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No | Temp °C | Condition | Seal Intact | Seal No

Good

Yes



