District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or	
Proposed Alternative Method Permit or Closure Plan Ap	plication
Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Ap Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-perm or proposed alternative method	
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank	k or alternative request
ease be advised that approval of this request does not relieve the operator of liability should operations result in pollution of vironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental	of surface water, ground water or the authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778Address:200 Energy Court, Farmington, NM 87401	OIL CONS. DIV DIST. 3
Address:200 Energy Court, Farmington, NM 87401	111N 4 0 2018
Pacility or well name:Gallegos Canyon Unit 93	JUN 1 2 2014
API Number:3004507699 OCD Permit Number:	
J/L or Qtr/QtrESection36Township29NRange12WCounty: _	San Juan
Center of Proposed Design: Latitude36.68537 Longitude108.0568	NAD: □1927 ⊠ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment	
Pit: Subsection F, G or J of 19.15.17.11 NMAC	
Semporary: Drilling Workover	
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chlorid	e Drilling Fluid 🔲 yes 🔲 no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other	_
String-Reinforced	
iner Seams: Welded Factory Other Volume: bbl Dimension	ons: Lx Wx D
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A	
Volume: 95.0 bbl Type of fluid: Produced water	
ank Construction material:Steel	
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shu	t-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/Double bottomed, si	de walls not visible
iner type: Thicknessmil	
7 Alternative Method:	

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: •Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
5. Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	
and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents of the state of the	cuments are
attached. □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC □ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	Iuid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sout provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map Within a 100-year floodplain.	Yes No
- FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print):	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 6/16/ Title: OCD Permit Number:	2014
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:4/14/2014	
20. Closure Method: Waste Excavation and Removal □ On-Site Closure Method □ Alternative Closure Method □ Waste Removal (Closed-lo □ If different from approved plan, please explain.	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please incomark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)	dicate, by a check

Operator. Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirements.	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Name (Print):Jeff Peace	Date:June 11, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit 93 API No. 3004507699 Unit Letter E, Section 36, T29N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	34
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and

compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District 1
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

						OPERA:	TOR		Initia	al Report	\boxtimes	Final R	Report
Name of Co	mpany: B	P				Contact: Jef	f Peace						
Address: 20	0 Energy (Court, Farmi	ngton, N	M 87401		Telephone N	No.: 505-326-94	79					.,,,,
Facility Nan							e: Natural gas v					* **	
					•								
Surface Ow	ner: Privat	te		Mineral O	wner:	State_			API No	. 30045076	99		
				LOCA	TIO	N OF DE	TEACE						
*****	6 .:	7D 1:	70			N OF REI		1 22		<u> </u>			
Unit Letter	Section	Township 29N	Range	Feet from the		South Line	Feet from the	1	Vest Line	County: Sa	n Juan		
E	36	29N	12W	1,750	North		890	West					
	<u> </u>	Lat	itude3	36.68537		Longitud	le108.0568	J					
				NAT	URE	OF RELI	EASE						
Type of Relea	ase: none				•	Volume of	Release: N/A		Volume F	Recovered: N	/A		
Source of Rel	lease: belov	v grade tank –	95 bbl			Date and H	lour of Occurrenc	e:	Date and	Hour of Disc	overy:	N/A	
						N/A							
Was Immedia	ate Notice (—	1		If YES, To	Whom?						
			Yes _] No 🛛 Not Re	quired	}							
By Whom?						Date and H							
Was a Watero	course Reac					If YES, Vo	lume Impacting t	he Wate	ercourse.				
		LJ	Yes 🗵] No									
If a Watercou	rse was Im	pacted, Descr	be Fully.	k		<u> </u>							
		, , , , , , , ,											
				n Taken.* Samplir					ig removal	to ensure no	soil im	pacts fro	om
the BGT. So	il analysis r	esulted in TP	H, BIEX	and chlorides belo	w stand	lards. Analys	is results are attac	ched.					
Describe Area	a Affected a	and Cleanup A	Action Tak	cen.* BGT was rer	noved a	and the area u	nderneath the BG	T was s	ampled. T	he excavated	area v	as /as	
				active well area.					1				
	_												
													1
	0 1 1 1	<u> </u>		• • •		C					- CID	1 1	
				is true and completed is true and complete is true and complete is true and complete is true in the interest in the complete is true and complete is true an									1
regulations at	or the envir	ronment The	accentano	ce of a C-141 repo	rt hy the	e NMOCD m	arked as "Final R	enort" c	loes not reli	eve the oner	nay on	liability	
should their o	perations h	ave failed to a	dequately	investigate and re	emediate	e contaminati	on that pose a thre	eat to gi	ound water	, surface wa	ter, hur	nan heal	lth
				otance of a C-141 i									Ì
federal, state,	or local lay	ws and/or regu	lations.										
		Δ					OIL CONS	<u>SERV</u>	<u>ATION</u>	DIVISIO	N		
<u>.</u>	1 20	Leave											
Signature:	YM	pole											
Printed Name	· leff Peace	2			1	Approved by	Environmental Sp	pecialis	t:				
Timited (value, 50) Feder													
Title: Area Et	nvironment	al Advisor				Approval Dat	e:		Expiration .	Date:			
		- "							· · · · · · · · · · · · · · · · · · ·				
E-mail Addre	ss: peace.je	effrey@bp.cor	n			Conditions of	Approval:			Attached			
										/ macricu	ш		
Date: June l	1, 2014		Phone: 50)5-326-9479									

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199 API #:	3
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER: PAGE #: 1 of	1
SITE INFORMATION QUAD/UNIT: E SEC: 36 TWP:	Diffe On William	4
1/4 -1/4/FOOTAGE: 1,750'N / 890 LEASE#: -	D'W SW/NW LEASE TYPE: FEDERAL / STATE / FEE INDIAN ENMRONMENTAL SPECIALIST(S): JCB	
1) 95 BGT (DW/DB) 2) 3)	WELL HEAD (W.H.) GPS COORD.: 36.68524 X 108.05679 GL ELEV.: 5,375 GPS COORD.: 36.68537 X 108.05680 DISTANCE/BEARING FROM WH.: 64', N3E GPS COORD.: DISTANCE/BEARING FROM WH.: DISTANCE/BEARING FROM WH.: GPS COORD.: DISTANCE/BEARING FROM WH.: DISTANCE/BEARING FROM WH.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	DING om)
2) SAMPLE ID:	D 5' SAMPLE DATE: 04/04/14 SAMPLE TIME: 1305 LAB ANALYSIS: 418.1/8015B/8021B/300.0 (CI) 0. SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS: SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS: SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:	.0
SOIL COLOR: DARK YELL COHESION (ALL OTHERS): NON COHESIVE SLIGHTL CONSISTENCY (NON COHESIVE SOILS): COMPOSITE OF A RELEASE OBSERVED: YES OUT OF A RELEASE OBSERVED: YES EQUIPMENT SET OVER RECLAIMED AREA:	DOSE/FIRM / DENSE / VERY DENSE HC ODOR DETECTED: YES NO EXPLANATION- ET / SATURATED / SUPER SATURATED # OF PTS 5	STIC
OTHER: SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <50' N	NA ft. X NA ft. X NA ft. EXCAVATION ESTIMATION (Cubic Yards): NA NA FT. X NA FT. EXCAVATION ESTIMATION (Cubic Yards): NA NA FT. X NA FT. X NA FT. EXCAVATION ESTIMATION (Cubic Yards): NA NA FT. X NA FT. X NA FT. EXCAVATION ESTIMATION (Cubic Yards): NA	ppm
PERI FE NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATI	BGT Located: off on site PLOT PLAN circle: attached NOM CALIB. READ. = 101.0 ppm RF = 00M CALIB. GAS = 100 ppm IME: 7:22 ampm DATE: 04/04/14 WETTER T.B. ~ 5'	4
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	OW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; NA - NOT Magnetic declination: 10° E E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM. ONSITE: 04/04/14	

Analytical Report Lab Order 1404416

Date Reported: 4/14/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Project: GCU 93

Lab ID:

1404416-001

.001 Matrix: SOIL

Client Sample ID: 95 BGT 5-pt @ 5'

Collection Date: 4/4/2014 1:05:00 PM

Received Date: 4/9/2014 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE	ORGANICS				Analys	t: BCN
Diesel Range Organics (DRO)	ND	9.8	mg/Kg	1	4/10/2014 9:18:25 PM	12624
Surr: DNOP	97.4	66-131	%REC	1	4/10/2014 9:18:25 PM	12624
EPA METHOD 8015D: GASOLINE RANG	GE				Analys	t: NSB
Gasoline Range Organics (GRO)	ND	5.0	mg/Kg	1	4/11/2014 12:06:13 AM	1 12623
Surr: BFB	85.0	74.5-129	%REC	1	4/11/2014 12:06:13 AM	1 12623
EPA METHOD 8021B: VOLATILES		•			Analyst	t: NSB
Benzene	ND	0.050	mg/Kg	1	4/11/2014 12:06:13 AM	1 12623
Toluene	ND	0.050	mg/Kg	1	4/11/2014 12:06:13 AM	1 12623
Ethylbenzene	ND	0.050	mg/Kg	1	4/11/2014 12:06:13 AM	1 12623
Xylenes, Total	ND	0.099	mg/Kg	1	4/11/2014 12:06:13 AM	12623
Surr: 4-Bromofluorobenzene	100	80-120	%REC	1	4/11/2014 12:06:13 AM	1 12623
EPA METHOD 300.0: ANIONS					Analyst	t: JRR
Chloride	ND	30	mg/Kg	20	4/10/2014 4:45:22 PM	12646
EPA METHOD 418.1: TPH					Analyst	BCN
Petroleum Hydrocarbons, TR	34	20	mg/Kg	1	4/10/2014	12560

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404416

14-Apr-14

Client:

Blagg Engineering

Project:

GCU 93

Sample ID MB-12646

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 12646

PQL

RunNo: 17936

Prep Date: 4/10/2014 Analysis Date: 4/10/2014

Units: mg/Kg

Result

SeqNo: 517496

HighLimit

RPDLimit %RPD

Qual

Analyte Chloride

ND 1.5

Sample ID LCS-12646

SampType: LCS

TestCode: EPA Method 300.0: Anions

LowLimit

Client ID: LCSS

4/10/2014

Batch ID: 12646

PQL

RunNo: 17936

SPK value SPK Ref Val %REC LowLimit

SeqNo: 517497

Units: mg/Kg

%RPD **RPDLimit**

Analyte

Prep Date:

Analysis Date: 4/10/2014

SPK value SPK Ref Val

93.6

90

HighLimit

110

Chloride

Result 14

1.5 15.00

0

%REC

Qual

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits J

RSD is greater than RSDlimit 0

R RPD outside accepted recovery limits

Spike Recovery outside accepted recovery limits

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н

ND Not Detected at the Reporting Limit

P Sample pH greater than 2. Reporting Detection Limit Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

98

20

100.0

WO#: 1404416

14-Apr-14

Client:

Blagg Engineering

Project:

Petroleum Hydrocarbons, TR

GCU 93

Project: GCU 9				
Sample ID MB-12560	SampType: MBLK	TestCode: EPA Method	I 418.1: TPH	
Client ID: PBS	Batch ID: 12560	RunNo: 17911		
Prep Date: 4/7/2014	Analysis Date: 4/10/2014	SeqNo: 516689	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	ND 20			
Sample ID LCS-12560	SampType: LCS	TestCode: EPA Method	I 418.1: TPH	
Client ID: LCSS	Batch ID: 12560	RunNo: 17911		
Prep Date: 4/7/2014	Analysis Date: 4/10/2014	SeqNo: 516690	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	98 20 100.0	0 97.8 80	120	
Sample ID LCSD-12560	SampType: LCSD	TestCode: EPA Method	I 418.1: TPH	
Client ID: LCSS02	Batch ID: 12560	RunNo: 17911		
Prep Date: 4/7/2014	Analysis Date: 4/10/2014	SeqNo: 516691	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual

97.8

80

120

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 6

20

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404416

14-Apr-14

Client:

Blagg Engineering

Project:

GCU 93

Project: GCU 9				
Sample ID MB-12644	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Organics	
Client ID: PBS	Batch ID: 12644	RunNo: 17898		
Prep Date: 4/10/2014	Analysis Date: 4/10/2014	SeqNo: 516499	Units: %REC	
Analyte	Result PQL SPK value SPK	Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qu	ual
Surr: DNOP	7.5 10.00	74.9 66	131	
Sample ID LCS-12644	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Organics	
Client ID: LCSS	Batch ID: 12644	RunNo: 17898		
Prep Date: 4/10/2014	Analysis Date: 4/10/2014	SeqNo: 516503	Units: %REC	
Analyte	Result PQL SPK value SPK	Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qւ	ual
Surr: DNOP	3.8 5.000	75.5 66	131	
Sample ID MB-12624	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Organics	
Client ID: PBS	Batch ID: 12624	RunNo: 17898		
Prep Date: 4/9/2014	Analysis Date: 4/10/2014	SeqNo: 516973	Units: mg/Kg	
Analyte	Result PQL SPK value SPK	Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qu	ual
Diesel Range Organics (DRO) Surr: DNOP	ND 10 9.5 10.00	95.4 66	131	
Sample ID LCS-12624	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Organics	
Client ID: LCSS	Batch ID: 12624	RunNo: 17898		
Prep Date: 4/9/2014	Analysis Date: 4/10/2014	SeqNo: 516974	Units: mg/Kg	
Analyte	Result PQL SPK value SPK	Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qu	ual
Diesel Range Organics (DRO)	46 10 50.00	0 91.9 60.8	145	
Surr: DNOP	4.4 5.000	87.9 66	131	

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

Result

25

920

PQL

5.0

WO#:

1404416

14-Apr-14

Client:

Blagg Engineering

Project:

Analyte

Surr: BFB

Gasoline Range Organics (GRO)

GCU 93

Sample ID MB-12623	Tes	TestCode: EPA Method 8015D: Gasoline Range										
Client ID: PBS	Batch ID: 12	623	F	RunNo: 1	7906							
Prep Date: 4/9/2014	Analysis Date: 4/	10/2014	S	17100	Units: mg/K							
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Gasoline Range Organics (GRO)	ND 5.0											
Surr: BFB	870	1000		86.6	74.5	129	_					
Sample ID LCS-12623	SampType: LC	SampType: LCS TestCode: EPA Method						е				
Client ID: LCSS	Batch ID: 12	F	RunNo: 17906									
Prep Date: 4/9/2014	Analysis Date: 4/	S	SeaNo: 5	17101	Units: ma/Ka							

0

%REC

102

92.2

LowLimit

71.7

74.5

HighLimit

134

129

%RPD

RPDLimit

Qual

SPK value SPK Ref Val

25.00

1000

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404416

14-Apr-14

Client:

Blagg Engineering

Project:

GCU 93

Sample ID MB-12623 SampType: MBLK			TestCode: EPA Method 8021B: Volatiles									
Client ID: PBS	Batch ID: 12623 Analysis Date: 4/10/2014			F	RunNo: 1	7906						
Prep Date: 4/9/2014				S	SeqNo: 5	17142	Units: mg/F	(g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	ND	0.050	<u> </u>									
Toluene	ND	0.050										
Ethylbenzene	ND	0.050										
Xylenes, Total	ND	0.10										
Surr: 4-Bromofluorobenzene	1.0		1.000		105	80	120					

Sample ID LCS-12623	s	Tes	tCode: El	PA Method	8021B: Vola	tiles				
Client ID: LCSS	Batci	Batch ID: 12623			RunNo: 1	7906				
Prep Date: 4/9/2014	e: 4/9/2014 Analysis Date: 4/10/2014 SeqNo: 517143				17143	Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Quai
Benzene	1.1	0.050	1.000	0	109	80	120			
Toluene	1.0	0.050	1.000	0	102	80	120			
Ethylbenzene	1.0	0.050	1.000	0	102	80	120			
Xylenes, Total	3.0	0.10	3.000	0	100	80	120			
Surr: 4-Bromofluorobenzene	1.1		1.000		107	80	120			

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Work Order Number: 1404413 6 4 4/1/ Client Name: **BLAGG** RcptNo: 1 Received by/date: Logged By: Michelle Garcia 4/9/2014 10:01:00 AM Completed By: 4/9/2014 11:10:00 AM Michelle Garcia Reviewed By: 20 04/09/14 Chain of Custody No 🗌 Not Present Yes 1 Custody seals intact on sample bottles? Yes 🗹 No 🗌 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In No 🗌 NA 🗌 4. Was an attempt made to cool the samples? 5. Were all samples received at a temperature of >0° C to 6.0°C Yes 🔽 NA 🗍 6. Sample(s) in proper container(s)? Yes V No 🗀 Yes 🗹 7. Sufficient sample volume for indicated test(s)? Yes 🗹 8. Are samples (except VOA and ONG) properly preserved? No 🔽 NA 🗆 Yes 9. Was preservative added to bottles? No 🗆 No VOA Vials 10. VOA vials have zero headspace? Yes Yes □ No 🔽 11. Were any sample containers received broken? # of preserved bottles checked Yes 🗹 No 🗌 for pH: 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No \square 13. Are matrices correctly identified on Chain of Custody? Yes 🗸 No 🔲 Yes 🗹 14. Is it clear what analyses were requested? No 🗌 Checked by: 15. Were all holding times able to be met? Yes 🗸 (If no, notify customer for authorization.) Special Handling (if applicable) No 🗌 NA 🗹 16. Was client notified of all discrepancies with this order? Yes 🗌 Person Notified: Date By Whom: Via: ☐ eMail ☐ Phone ☐ Fax In Person Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No Temp °C | Condition Seal Intact | Seal No Seal Date Signed By 1.8 Good Yes

	neada midii	icemy, m	ıc.	Standard	_		_					LAB						
	BP America			Project Name												•		
Mailing Address: P.O. Box 87					www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109													
	Bloomfield, NM 87413				Project #:				Tel 505-345-3975 Fax 505-345-4107									
Phone #:	hone #: (505)320-1183			1										ques				
email or Fax#:			Project Manager:												\top		T	
QA/QC Packs	age:				Jeff Blagg						-			1				
Standard Level 4 (Full Validation))					ତ୍ର	1 1	- 1		Į	i	1 1		- 1		
☐ Other				Sampler: Jeff,Blagg							- 1						-	1=
□ EDD (Typ				On ice: Yo Yes □ No.					8		l		1		1 1		1	5
			.	Sample Temperature: 7 - 🛠					9				ļ					≥
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO. 11	BTEX (8021)		TPH 8015B (GRO / DRO)	TPH 418.1							Chloride	Air Bubbles (Y or N)
04/04/2014	13:05	Soil	95 BGT 5-pt @ 5'	1x 4oz	cool	-001	х		x	x			1			7	x	1
				 			—			_		$\neg \uparrow$	_	+		+	+	十
		 		 			+			-+			+	+-	\vdash	-+	+	+-
		 			 								_			\dashv		+
		 -		 								_¦_	_			-		4-
				ļ														
		1															ł	
																\top	\top	
											_					\neg	\neg	1
	<u> </u>						_		_		_	-+-	\dashv			\neg	_	1-1
		 					+-			-+	_		+	 		-	+-	+-
		+			ļ		-			-+		-	+	+		_	- -	+-
				 					_				-		 	\dashv		
Date	Time:	Palinguish	and by:	Received by:	L	Date Time	Por	205/4						<u> </u>				
Date: 4/8/2014	1821	Relinquished by: July 3 (e.g.G.)		Mestre Waster 4/8/14 821			Remarks: Bill BP Paykey: ZEVH01BGT2								į			
Date:	Time:	Relinquish	ned by:	Received by: Date Time				BP Contact: Jeff Peace Please copy results to: peace.jeffrey@bp.com								io;	Í	
4/8/14	1756	1 Min		1			_											
' If ne	cessary, samples	submitted to I	Hall Environmental may be subcontract	ed to other eccredite	d ∤aboratories. This	OHOGIN 1000 serves as notice of this poss	ibility. A	ny sub-	contra	cted da	sta wil	l be clea	rly note	rted on ti	ne analy	tical re	port.	

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

April 10, 2014

Lonnie Garrison 901 N Auburn #6 Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 093

Dear Mr. Garrison,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about April 11, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9DULKE

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

April 10, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 093 API 30-045-07699 (G) Section 36 – T29N – R29W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

Iff Peace

(505) 326-9479



