District I

1525 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa Fe, NM 87505	to the appropriate NMOCD District Office.									
	t, Below-Grade Tank, Method Permit or Clo	or osure Plan Application									
Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method											
Please be advised that approval of this request does not relieve the environment. Nor does approval relieve the operator of its respons	operator of liability should operation	oit, below-grade tank or alternative request ons result in pollution of surface water, ground water or the olicable governmental authority's rules, regulations or ordinances.									
Operator: BP America Production Company		OGRID #: 778									
Address:200 Energy Court, Farmington, NM _		OIL CONS. DIV DIST. 3									
Facility or well name:Jaquez Gas Com B 1		UIN 12 2014									
API Number:3004508676	OCD Permit Number:	2605									
U/L or Qtr/QtrKSection4Town	nship29N Range	9WCounty:San Juan									
Center of Proposed Design: Latitude36.75110	Longitude107.78	8741 NAD: □1927 ⊠ 1983									
Surface Owner: ☐ Federal ☐ State ☒ Private ☐ Tribal Tru	st or Indian Allotment										
2. Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Mu Lined Unlined Liner type: Thicknessmi String-Reinforced	I LLDPE HDPE PV	C Other									
Liner Seams: Welded Factory Other	Volume:	bbl Dimensions: Lx Wx D									
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC	Tank A										
Volume:95.0bbl Type of fluid: _	Produced water										
Tank Construction material:Steel											
Secondary containment with leak detection Visible si											
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐		•									
Liner type: Thicknessmil	☐ PVC ☐ Other										

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Eencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)								
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,							
Four foot height, four strands of barbed wire evenly spaced between one and four feet								
Alternate. Please specify								
6.								
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)								
☐ Screen ☐ Netting ☐ Other ☐ Monthly inspections (If netting or screening is not physically feasible)								
inspections (if netting of screening is not physically reasible)								
5. Subsection C of 19.15.17.11 NMAC								
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers								
☐ Signed in compliance with 19.15.16.8 NMAC								
8.								
<u>Variances and Exceptions</u> : Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.								
Please check a box if one or more of the following is requested, if not leave blank:								
Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.								
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance of the compliance of the complian	otable source							
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.								
General siting								
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No							
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No							
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No							
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No							
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No							
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No							
Below Grade Tanks								
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)								
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No						
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 							
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Temporary Pit Non-low chloride drilling fluid							
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No						
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No						
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Permanent Pit or Multi-Well Fluid Management Pit							
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image							
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.							
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No						
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No						
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.							
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC							
Previously Approved Design (attach copy of design) API Number: or Permit Number:							
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are						
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC 	.15.17.9 NMAC						
 ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Previously Approved Design (attach copy of design) API Number:							

12.	
<u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Author of the complete of	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well First Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. • - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No									
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No									
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 										
Within a 100-year floodplain FEMA map	Yes No									
- 1 Livit map										
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC									
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.										
Name (Print): Title:										
Signature: Date:										
e-mail address: Telephone:										
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: OCD Permit Number:	2014									
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 4/8/2014										
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo ☐ If different from approved plan, please explain.	op systems only)									
In different from approved plan, please explain.										

22. Operator Closure Certification:						
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.						
Name (Print):Jeff Peace	Title: Area Environmental Advisor					
Signature: Jeff Poses	Date: June 11, 2014					
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479					

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Jaquez Gas Com B 1 API No. 3004508676 Unit Letter K, Section 4, T29N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	51

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1.625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011 Submit 1 Copy to appropriate District Office in

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

accordance with 19.15.29 NMAC.

Release Notification and Corrective Action OPERATOR Initial Report Final Report Name of Company: BP Contact: Jeff Peace Address: 200 Energy Court, Farmington, NM 87401 Telephone No.: 505-326-9479 Facility Name: Jaquez Gas Com B 1 Facility Type: Natural gas well Surface Owner: Private Mineral Owner: Private API No. 3004508676 LOCATION OF RELEASE Unit Letter Section Township Range Feet from the North/South Line Feet from the East/West Line County: San Juan 1.650 South 1.650 West K **Latitude** 36.75110 **Longitude** 107.78741 NATURE OF RELEASE Type of Release: none Volume of Release: N/A Volume Recovered: N/A Source of Release: below grade tank – 95 bbl. Date and Hour of Occurrence: Date and Hour of Discovery: N/A Was Immediate Notice Given? If YES, To Whom? ☐ Yes ☐ No ☒ Not Required By Whom? Date and Hour Was a Watercourse Reached? If YES, Volume Impacting the Watercourse. ☐ Yes ⊠ No If a Watercourse was Impacted, Describe Fully.* Describe Cause of Problem and Remedial Action Taken.* Sampling of the soil beneath the BGT was done during removal to ensure no soil impacts from the BGT. Soil analysis resulted in TPH, BTEX and chlorides below standards. Analysis results are attached. Describe Area Affected and Cleanup Action Taken.* BGT was removed and the area underneath the BGT was sampled. The excavated area was backfilled and compacted and is still within the active well area. I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations. OIL CONSERVATION DIVISION Signature: Approved by Environmental Specialist: Printed Name: Jeff Peace Approval Date: **Expiration Date:** Title: Area Environmental Advisor Conditions of Approval: E-mail Address: peace.jeffrey@bp.com Attached Phone: 505-326-9479 Date: June 11, 2014

^{*} Attach Additional Sheets If Necessary

BP	BLAGG EI	API#: 3004508676						
CLIENT:	P.O. BOX 87, B (50	WI 87413	TANK ID (if applicble):	A				
FIELD REPORT:	OTHER:	PAGE #:	1 of 1					
SITE INFORMATION	SITE INFORMATION: SITE NAME: JAQUEZ GC B # 1							
QUAD/UNIT: K SEC: 4 TWP:		NM CNTY: SJ	st: NM	DATE STARTED:				
1/4 -1/4/FOOTAGE: 1,650'S / 1,65				ENVIRONMENTAL				
	IRE SCHURMAN	SPECIALIST(S):	JCB					
REFERENCE POINT		COORD.: 36.750		GI FI F	=\/· 5 639'			
1) 95 BGT (SW/DB)	GPS COORD.: 3			RING FROM W.H.:				
2)								
3)				RING FROM W.H.:				
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:				
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # C	OR LAB USED: HA	LL		OVM READING (ppm)			
1) SAMPLE ID: 95 BGT 5-pt.	@ 6' SAMPLE DATE: 04/03	/14 SAMPLETIME: 1505	LAB ANALYSIS: 418.1/8	8015B/8021B/30				
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:					
3) SAMPLEID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:					
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:					
SOIL DESCRIPTION	: SOIL TYPE: SAND SILTY SAND / S	SILT SILTY CLAY / CLAY / GRAV	/EL / OTHER					
SOIL COLOR: DARK YEL	LOWISH BROWN	PLASTICITY (CLAYS): NON PLAST	TIC / SLIGHTLY PLASTIC / C					
COHESION (ALL OTHERS): NON COHESIVE SLIGHTL' CONSISTENCY (NON COHESIVE SOILS): LC								
MOISTURE: DRY/SLIGHTLY MOIST MOIST W		HC ODOR DETECTED: YES NO						
SAMPLE TYPE: GRAB COMPOSITE #		ANY AREAS DISPLAYING WETNE	ESS: YES NO EXPLA	NATION -				
DISCOLORATION/STAINING OBSERVED: YES N			IS.					
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE								
EQUIPMENT SET OVER RECLAIMED AREA:	YES NO EXPLANATION -	ANAHUN:						
OTHER:								
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. XNA	ft. X NA ft.	EXCAVATION EST	ΓΙΜΑΤΙΟΝ (Cubic Ya	rds): NA			
DEPTH TO GROUNDWATER: <50' N	EAREST WATER SOURCE: >1,000	NEAREST SURFACE WATER	: <1,000' NMOC	D TPH CLOSURE STE): <u>100</u> ppm			
SITE SKETCH	BGT Located: off on site	PLOT PLAN cir	rcle: attached 0\M	CALIB. READ. = 10 (D.6 ppm RF =1.00			
			↑ ovm	CALIB. GAS =10	00 ppm Rr - 1.00			
			N LTIME		DATE: 04/03/14			
	SEPARATOR		'┌	MISCELL	NOTES			
		BERM	<u> </u>	vo: N15211 0	364			
	PBGTL XXX	\	<u> </u>	O #:				
	T.B. ~ 5'		I	κ: <u>ZEVH01</u>				
	_	J#: Z2-0060						
	ı —	ermit date(s): CD Appr. date(s):	11/10/08 12/08/08					
	Tai	Tank OVM = Organic Vapor Meter						
				BGT Sidewalls Visible: Y (N)				
W.H. ⊕)	(- S.P.D.	BGT Sidewalls Vis	ible: Y / N			
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION TO BE TANK TO BE		ELOW; T.H. = TEST HOLE; ~ = APPROX.	.; W.H. = WELL HEAD;	BGT Sidewalls Vis				
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGL	OW-GRADE TANK LOCATION; SPD = SAMPLE P E WALL; DW - DOUBLE WALL; SB - SINGLE BOT		G WALL; NA - NOT N	Magnetic declinat	ion: 10 ° E			
NOTES:			03/14					

Analytical Report

Lab Order 1404204

Date Reported: 4/8/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT 4-pt@5'

Project: Jaquez GC B 1

Collection Date: 4/3/2014 3:05:00 PM

Lab ID: 1404204-001

Matrix: MEOH (SOIL) Received Date: 4/4/2014 10:00:00 AM

Analyses	Result	RL Qı	ual Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE ORGANICS				·	Analyst:	BCN
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	4/4/2014 6:37:54 PM	12545
Surr: DNOP	82.5	66-131	%REC	1	4/4/2014 6:37:54 PM	12545
EPA METHOD 8015D: GASOLINE RA	ANGE				Analyst:	NSB
Gasoline Range Organics (GRO)	ND	3.1	mg/Kg	1	4/4/2014 11:59:13 AM	R17816
Surr: BFB	90.2	74.5-129	%REC	1	4/4/2014 11:59:13 AM	R17816
EPA METHOD 8021B: VOLATILES					Analyst:	NSB
Benzene	ND	0.031	mg/Kg	1	4/4/2014 11:59:13 AM	R17816
Toluene	ND	0.031	mg/Kg	1	4/4/2014 11:59:13 AM	R17816
Ethylbenzene	ND	0.031	mg/Kg	1	4/4/2014 11:59:13 AM	R17816
Xylenes, Total	ND	0.062	mg/Kg	1	4/4/2014 11:59:13 AM	R17816
Surr: 4-Bromofluorobenzene	105	80-120	%REC	1	4/4/2014 11:59:13 AM	R17816
EPA METHOD 300.0: ANIONS					Analyst:	JRR
Chloride	51	30	mg/Kg	20	4/4/2014 6:10:59 PM	12547
EPA METHOD 418.1: TPH					Analyst:	JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	4/7/2014 12:00:00 PM	12534

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH greater than 2.
- RL Reporting Detection Limit

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404204

08-Apr-14

Client:

Blagg Engineering

Project:

Jaquez GC B 1

Sample ID MB-12547

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PB\$

4/4/2014

Batch ID: 12547

PQL

RunNo: 17824

%REC LowLimit

Prep Date:

Analysis Date: 4/4/2014

SeqNo: 513769

Units: mg/Kg

HighLimit

%RPD **RPDLimit** Qual

Analyte Chloride

ND 1.5

SampType: LCS

Result

PQL

RunNo: 17824

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Sample ID LCS-12547

Batch ID: 12547

SeqNo: 513770

Units: mg/Kg

Prep Date: 4/4/2014

Analysis Date: 4/4/2014

SPK value SPK Ref Val %REC

HighLimit

%RPD

RPDLimit

Qual

1.5

90

110

Chloride

Analyte

Result 14

15.00

SPK value SPK Ref Val

92.5

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range E

Analyte detected below quantitation limits 1

RSD is greater than RSDlimit 0

R RPD outside accepted recovery limits

Spike Recovery outside accepted recovery limits S

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

Sample pH greater than 2. P

Reporting Detection Limit RL

Page 2 of 6

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404204

08-Apr-14

Client:

Blagg Engineering

Project:

Jaquez GC B 1

Sample ID MB-12534

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID: PB\$ Batch ID: 12534

RunNo: 17822

Prep Date: 4/3/2014

Analysis Date: 4/7/2014

SeqNo: 513710

HighLimit

Analyte

SPK value SPK Ref Val %REC LowLimit

Units: mg/Kg

RPDLimit Qual

Petroleum Hydrocarbons, TR

PQL ND 20

Sample ID LCS-12534

SampType: LCS

TestCode: EPA Method 418.1: TPH

Client ID: LCSS

Batch ID: 12534

RunNo: 17822

Prep Date: 4/3/2014 Analysis Date: 4/7/2014

20

Units: mg/Kg

HighLimit

SeqNo: 513711

120

Qual

Analyte Petroleum Hydrocarbons, TR Result

PQL

SPK value SPK Ref Val %REC 100.0 91.6

LowLimit

%RPD

%RPD

RPDLimit

Sample ID LCSD-12534

SampType: LCSD Batch ID: 12534

RunNo: 17822

TestCode: EPA Method 418.1: TPH

Analyte

Client ID:

Prep Date:

4/3/2014

LCSS02

Result

92

Analysis Date: 4/7/2014

SeqNo: 513712

Units: mg/Kg LowLimit HighLimit

%RPD

RPDLimit

Qual

Petroleum Hydrocarbons, TR

PQL 90 20

SPK value SPK Ref Val %REC 100.0

90.2

1.52

20

Qualifiers:

E

Value exceeds Maximum Contaminant Level.

Analyte detected below quantitation limits RSD is greater than RSDlimit O

Ŕ RPD outside accepted recovery limits

Value above quantitation range

Spike Recovery outside accepted recovery limits

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit Sample pH greater than 2.

Reporting Detection Limit RL

Page 3 of 6

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404204

08-Apr-14

Client:

Blagg Engineering

Project:

Jaquez GC B 1

 Sample ID
 MB-12545
 SampType:
 MBLK

 Client ID:
 PBS
 Batch ID:
 12545

 Prep Date:
 4/4/2014
 Analysis Date:
 4/4/2014

Analysis Date: **4/4/2014** SeqNo: **513063** Units: **mg/Kg**

Analyte Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO) ND 10

RunNo: 17793

TestCode: EPA Method 8015D: Diesel Range Organics

Diesel Range Organics (DRO)
Surr: DNOP

Surr: DNOP 7.4 10.00 74.3 66 131

Sample ID LCS-12545 SampType: LCS TestCode: EPA Method 8015D: Diesel Range Organics Client ID: LCSS Batch ID: 12545 RunNo: 17793 Prep Date: 4/4/2014 Analysis Date: 4/4/2014 SeqNo: 513064 Units: mg/Kg Analyte Result **PQL** SPK value SPK Ref Val %REC LowLimit HighLimit %RPD **RPDLimit** Qual

 Diesel Range Organics (DRO)
 46
 10
 50.00
 0
 92.5
 60.8
 145

 Surr: DNOP
 3.8
 5.000
 75.3
 66
 131

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

OC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404204

08-Apr-14

Client:

Blagg Engineering

Project:

Jaquez GC B 1

Sample ID MB-12530

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID: PBS

Batch ID: 12530

RunNo: 17816

Prep Date:

4/3/2014

Analysis Date: 4/4/2014

SeaNo: 513588

Units: %REC

129

HighLimit

Qual

Analyte Surr: BFB

860

930

SPK value SPK Ref Val %REC 85.7

LowLimit 74.5 **RPDLimit**

Sample ID LCS-12530

LCSS

SampType: LCS Batch ID: 12530

SeqNo: 513589

TestCode: EPA Method 8015D: Gasoline Range RunNo: 17816

Units: %REC

129

%RPD

%RPD

Analyte Surr: BFB

Client ID:

Prep Date:

4/3/2014 Result

Analysis Date: 4/4/2014

SPK value

1000

1000

SPK Ref Val %REC

93.2

LowLimit 74.5

HighLimit

RPDLimit

Qual

Sample ID MB-12530 MK PBS

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID: Prep Date:

Batch ID: R17816 Analysis Date: 4/4/2014

Result

Result

27

930

RunNo: 17816 SegNo: 513614

Units: mg/Kg

Qual

Analyte Gasoline Range Organics (GRO)

ND 5.0

PQL

SPK value SPK Ref Val %REC

HighLimit

129

%RPD **RPDLimit**

Qual

Surr: BFB

860

1000

85.7

74.5

LowLimit

Sample ID LCS-12530 MK

SampType: LCS

Analysis Date: 4/4/2014

TestCode: EPA Method 8015D: Gasoline Range

Client ID: Prep Date:

LCSS

Batch ID: R17816

RunNo: 17816 SeqNo: 513615

Units: mg/Kg

%RPD

RPDLimit

Analyte Gasoline Range Organics (GRO)

Surr: BFB

SPK value SPK Ref Val **PQL** 5.0 25.00

1000

%REC 109 93.2 LowLimit 71.7 74.5 HighLimit 134 129

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range E

Analyte detected below quantitation limits

Spike Recovery outside accepted recovery limits

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits R

В Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Sample pH greater than 2.

Reporting Detection Limit

Page 5 of 6

OC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404204

08-Apr-14

Client:

Blagg Engineering

Project:

Jaquez GC B 1

Sample ID MB-12530

SampType: MBLK

TestCode: EPA Method 8021B: Volatiles

LowLimit

80

Client ID:

PBS

Batch ID: 12530

RunNo: 17816

SPK value SPK Ref Val

1.000

Units: %REC

Prep Date: Analyte

4/3/2014

Analysis Date: 4/4/2014

SeqNo: 513622 %REC

102

HighLimit

RPDLimit Qual

Surr: 4-Bromofluorobenzene

Sample ID LCS-12530

1.0

Result

1.1

Result

SampType: LCS

TestCode: EPA Method 8021B: Volatiles

120

Client ID:

LCSS

Batch ID: 12530

Batch ID: R17816

PQL

Analysis Date: 4/4/2014

RunNo: 17816

Units: %REC

120

Prep Date: 4/3/2014 Analysis Date: 4/4/2014

SeqNo: 513623

Analyte

SPK value SPK Ref Val %REC 1.000 109

LowLimit HighLimit 80

%RPD **RPDLimit**

%RPD

Qual

Surr: 4-Bromofluorobenzene

Sample ID MB-12530 MK **PBS**

SampType: MBLK

TestCode: EPA Method 8021B: Volatiles

SPK value SPK Ref Val %REC LowLimit

0

0

0

RunNo: 17816 SeqNo: 513643

Units: mg/Kg

HighLimit

%RPD

Qual

Qual

RPDLimit

Analyte Benzene

Xylenes, Total

Client ID:

Prep Date:

Toluene Ethylbenzene

ND 0.050 ND 0.050 ND 0.050 ND 0.10

Result

Surr: 4-Bromofluorobenzene

1.0

SampType: LCS

TestCode: EPA Method 8021B: Volatiles

80

Sample ID LCS-12530 MK Client ID: LCSS

Batch ID: R17816

RunNo: 17816

102

Prep Date:

Analysis Date: 4/4/2014

SeqNo: 513644

109

99.4

80

80

Units: mg/Kg

120

120

120

Result **PQL** Analyte 1.1 0.050 Benzene 0.99 0.050 1.000 Toluene 1.0 0.050 1.000

SPK value SPK Ref Val 1.000 0

1.000

%REC

LowLimit

HighLimit

%RPD

RPDLimit

Ethylbenzene Xylenes, Total Surr: 4-Bromofluorobenzene

3.0 0.10 3.000 1.1 1.000

99.8 99.1 109 80 80

120 120 80 120

Qualifiers:

Value exceeds Maximum Contaminant Level.

Е Value above quantitation range

Analyte detected below quantitation limits I

Spike Recovery outside accepted recovery limits

RSD is greater than RSDlimit 0

R RPD outside accepted recovery limits Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н

Not Detected at the Reporting Limit ND

Sample pH greater than 2 Р

RL Reporting Detection Limit Page 6 of 6

Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Number:	1404204		RcptNo:	1
Received by/date:	140410				
Logged By: Ashley Gallegos	4/4/2014 10:00:00 AM		A		
Completed By: Ashley Gallegos	4/4/2014 10:17:04 AM		A		;
Reviewed By:	04/04/14		- , 0		
Chain of Custody	0 (104) [14	,	***************************************		
Custody seals intact on sample bottle	s?	Yes 🗌	No 🗆	Not Present 🗹	
2. Is Chain of Custody complete?		Yes 🗹	No 🗌	Not Present	
3. How was the sample delivered?		Courier			
Log In					
4. Was an attempt made to cool the sar	nples?	Yes 🗸	No 🗔	NA L	
5. Were all samples received at a tempe	rature of >0° C to 6.0°C	Yes 🗹	No 🗀	NA 🗆	
6. Sample(s) in proper container(s)?		Yes 🗹	No 🗆		
7. Sufficient sample volume for indicated	test(s)?	Yes 🗹	No 🗌		
8. Are samples (except VOA and ONG)	properly preserved?	Yes 🗹	No 🗌		
9. Was preservative added to bottles?		Yes	No 🗹	NA 🗀	
10.VOA vials have zero headspace?		Yes 🗌	No 🛄	No VOA Vials	
11. Were any sample containers received	I broken?	Yes 🗌	No 🗹	# of preserved bottles checked	
12. Does paperwork match bottle labels? (Note discrepancies on chain of custo	dy)	Yes 🗹	No 🗆	for pH: (<2 (or >12 unless noted
13. Are matrices correctly identified on Ch	nain of Custody?	Yes 🗹	No 🗆	Adjusted?	
14. Is it clear what analyses were request		Yes 🔽	No [] No []	Checked by:	
15. Were all holding times able to be met (If no, notify customer for authorization)		Yes 🗸	No l	Crieckeu by.	
Special Handling (if applicable)					
16. Was client notified of all discrepancies	s with this order?	Yes 🗀	No 🗆	NA 🗹	
Person Notified:	Date:				
By Whom:	Via:	eMail 🗍	Phone 🗌 Fax	In Person	į
Regarding:					
Client Instructions:					
17. Additional remarks:					
18. Cooler Information	interiore de logo 13	Carl Divis	. :Oimina b		
Cooler No Temp % Condition	n Seal Intact Seal No. Yes	Seal Date	Signed By		

Ollerit.	ı. ыаду Engineering, inc.				Standard Rush ANALYSIS LABORAT													
	BP America			Project Name:													•	
Mailing Addr	ess:	P.O. Box	k 87	Jaquez GC B 1			www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109											
		Bloomfie	id, NM 87413	Project #:	roject #:				Tel.	505-3	345-3	975	Fa	x 505	-345-4	4107		
Phone #:		(505)320)-1183					or a		n ja ja ja L	ļ.	inalys	is R	eques	THEN I YOU	e energia. E energia del c		
email or Fax	c#:			Project Mana	ager:					T								
QA/QC Package: Standard Level 4 (Full Validation))	Jeff Blagg	•				<u> </u>									
□ Other			Sampler:	Jeff Blagg				3	5		1			1 1	İ	þ		
□ EDD (Typ	oe)			On Ice:	🖄 Yes	□ No			3	2			- })			1	b
				Sample Tem	perature: \			=	19	의				İ		1	1	\
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO		BTEX (8021)		TPH 418.1							Chloride	Air Bubbles (Y or N)
04/03/2014	15:05	Soil	95 BGT 4-pt @ 5'	1x 4oz	cool	- DC		x	1,	 -							×	+
									-+	1			十			_	+	+
<u></u>							,			+-			\dashv	-		-	+	+
				 						+		-+	-			+	+	+-
						*									 	+		+-
					· ·					+-			┿			+		+-
										-			\dashv	_			+	
		<u> </u>							_	-						_	_	
		<u> </u>	·							<u> </u>					— —		\perp	
							<u></u>		_	_				_				
										_							\bot	
																	上	
Date: /3/2014	Time: 1600	Relinquish	ed by: 1 Blogg	Received by: Mustu	Mela	43/2014 10	-	Remarks: Bill BP Paykey: ZEVH01BGT2 BP Contact: Jeff Peace Please copy results to: peace.jeffrey@bp.com					ta:					
Date: 4/3/14	Time:	Relinquish	, i .	Received by:	A . 11.	Date Ti												
	1729 cessary, samples	submitted to H	all Environmental may be subcontracted	ed to other accredite	d laboratories. This	<u> </u>		lity. An	y sub-co	ntracted	data w	ill be cle	arly not	ated on ti	ne analy	tical re	port.	





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

November 21, 2013

Richard Jacquez 475 Road 4599 Blanco, NM 87421

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: JAQUEZ GC B 001

Dear Mr. Jacquez,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 7, 2013. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

Surface Land Negotiator

97 VaRei

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

November 21, 2013

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

JAQUEZ GC B 001 API 30-045-08676 (G) Section 4 – T29N – R09W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

Joff Peace

(505) 326-9479



