District J 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Proposed Alternative Method Permit or Closure Plan Application Type of action: Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method
Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method
☐ Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID#:778OIL CONS. DIV DIST. 3
Address:200 Energy Court, Farmington, NM
Facility or well name:Nye LS 1
API Number:3004510591OCD Permit Number:
U/L or Qtr/QtrA Section23 Township31N Range11W County:San Juan
Center of Proposed Design: Latitude36.888677 Longitude107.953949 NAD: □1927 ⋈ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
■ Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume: 95.0 bbl Type of fluid: Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/Single bottomed
Liner type: Thicknessmil
4. Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Form C-144

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC 	15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proviously Approved Design (attach conv. of design) - API Number: or Permit Number:	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached.	,
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Remoyal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
Within an unstable area.	
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ief.
Name (Print): Title:	
Signature: Date:	
Signature: Date: e-mail address: Telephone:	
e-mail address:	
e-mail address:	
e-mail address:	/2014
e-mail address:	/2014
e-mail address:	/2014
e-mail address: Telephone:	the closure report.

22. Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closu belief. I also certify that the closure complies with all applicable closure requi	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Name (Print):Jeff Peace	Date: June 11, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Nye LS 1 API No. 3004510591 Unit Letter A, Section 23, T31N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil. The area over the BGT is covered by the LPT and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notifi				ction	
		OPERA			nitial Report 🛛 🖂 Final Repoi
Name of Company: BP		Contact: Jef			
Address: 200 Energy Court, Farmington, NM 87401			No.: 505-326-94		
Facility Name: Nye LS 1	1	acility Typ	e: Natural gas v	vell	
Surface Owner: Federal Mineral	Owner: F	Federal		API	No. 3004510591
	ATION	OF RE	LEASE		
Unit Letter Section Township Range 11W 990 Feet from the	North/S North	South Line	Feet from the 990	East/West Lin East	ne County: San Juan
Latitude 36.888677		Longitud	e_107.953949		
NA	TURE	OF RELI	EASE		
Type of Release: none		,	Release: N/A	Volun	ne Recovered: N/A
Source of Release: below grade tank – 95 bbl,		Date and F N/A	lour of Occurrenc	e: Date a	and Hour of Discovery: N/A
Was Immediate Notice Given? ☐ Yes ☐ No ☒ Not F	Required	If YES, To	Whom?		
By Whom?		Date and H	our		
Was a Watercourse Reached? ☐ Yes ☑ No			lume Impacting t	he Watercourse).
If a Watercourse was Impacted, Describe Fully.*					
the BGT. Soil analysis resulted in TPH, BTEX and chlorides be been backfilled and Cleanup Action Taken.* BGT was rebackfilled and compacted and is still within the active well area.					. The excavated area was
I hereby certify that the information given above is true and compregulations all operators are required to report and/or file certain public health or the environment. The acceptance of a C-141 repshould their operations have failed to adequately investigate and	release no oort by the remediate	tifications ar NMOCD ma contamination	nd perform correct arked as "Final Re on that pose a thre	tive actions for eport" does not eat to ground w	releases which may endanger relieve the operator of liability ater, surface water, human health
or the environment. In addition, NMOCD acceptance of a C-141 federal, state, or local laws and/or regulations.	report do	es not renev	e the operator of r	esponsibility ic	or compliance with any other
Signature: Off Posce			OIL CONS	SERVATIC	N DIVISION
Printed Name: Jeff Peace	A	Approved by	Environmental Sp	pecialist:	
Title: Area Environmental Advisor	A	Approval Dat	e:	Expirati	on Date:
E-mail Address: peace.jeffrey@bp.com	C	Conditions of	Approval:		Attached
Date: June 11, 2014 Phone: 505-326-9479 Attach Additional Sheets If Necessary					

CLIENT: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	API #:
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:	PAGE #:1 of1
SITE INFORMATION QUAD/UNIT: A SEC: 23 TWP: 1/4 -1/4/FOOTAGE: 990'N / 990'E	SITE NAME: NYE LS # 1 31N RNG: 11W PM: NM CNTY: SJ ST: NN NE/NE LEASE TYPE: FEDERAL STATE / FEE / INDIAN	DATE I INIGIALD.
LEASE#: SF080359	PROD. FORMATION: MV CONTRACTOR: MBF - B, SHUMAN	SPECIALIST(S): JCB
1)95 BGT (SW/SB) 2) 3)		E/BEARING FROM W.H.: 132', N10E E/BEARING FROM W.H.: E/BEARING FROM W.H.:
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	OVM READING (ppm)
SAMPLE ID:	Ø 5' SAMPLE DATE: 04/02/14 SAMPLE TIME: 1325 LAB ANALYSIS: 418, SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS: LAB ANALYSIS: SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:	
SOIL COLOR: DARK Y COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LO MOISTURE: DRY SLIGHTLY MOIST MOIST / WE SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED: YES NO	OSE FIRM / DENSE / VERY DENSE T / SATURATED / SUPER SATURATED OF PTS O EXPLANATION HC ODOR DETECTED: YES NO EXPLANATION ANY AREAS DISPLAYING WETNESS: YES NO EXI	RM / STIFF / VERY STIFF / HARD
	LOST INTEGRITY OF EQUIPMENT: YES NO EXPLANATION - D AND/OR OCCURRED: YES NO EXPLANATION: YES NO EXPLANATION -	
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <50' NE		ESTIMATION (Cubic Yards) : NA MOCD TPH CLOSURE STD: 100 ppm
	DOT! !! " [] :	OVAM CALIB READ = QQ Q nom
PERIMETER	*	OWN CALIB. GAS = 100 ppm RF = 1.00 TIME: 7:00 ampm DATE: 04/02/14 MISCELL. NOTES WO: N15426829 PO #:
SECURITY SEF FENCE SEF METER RUN	PARATOR BERM	PK: ZEVH01BGT2 PJ #: Z2-006Q0 Permit date(s): 06/14/10 OCD Appr. date(s): 02/27/14 Tank OVM = Organic Vapor Meter ppm = parts per million A BGT Sidewalls Visible: (Y)/ N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELC	W.H. X - S.P.D. IN DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~ = APPROX.; W.H. = WELL HEAD; DWGRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; NA - NOT WALL; DW-DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM. ON SITE: 04/02/14	BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N Magnetic declination: 10° E

Analytical Report

Lab Order 1404217

Date Reported: 4/11/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Nye LS 1 **Project:**

Lab ID: 1404217-001

Client Sample ID: 95 BGT 5-pt @ 5'

Collection Date: 4/2/2014 1:25:00 PM

Received Date: 4/4/2014 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	GE ORGANICS		<u> </u>		Analyst	:: JME
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	4/8/2014 12:32:28 PM	12557
Surr: DNOP	79.8	66-131	%REC	1	4/8/2014 12:32:28 PM	12557
EPA METHOD 8015D: GASOLINE R.	ANGE				Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.6	mg/Kg	1	4/7/2014 5:55:48 PM	12550
Surr: BFB	85.7	74.5-129	%REC	1	4/7/2014 5:55:48 PM	12550
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.046	mg/Kg	1	4/7/2014 5:55:48 PM	12550
Toluene	ND	0.046	mg/Kg	1	4/7/2014 5:55:48 PM	12550
Ethylbenzene	ND	0.046	mg/Kg	1	4/7/2014 5:55:48 PM	12550
Xylenes, Total	ND	0.092	mg/Kg	1	4/7/2014 5:55:48 PM	12550
Surr: 4-Bromofluorobenzene	101	80-120	%REC	1	4/7/2014 5:55:48 PM	12550
EPA METHOD 300.0: ANIONS					Analyst	: JRR
Chloride	ND	30	mg/Kg	20	4/8/2014 8:56:20 PM	12589
EPA METHOD 418.1: TPH					Analyst	: JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	4/8/2014 12:00:00 PM	12558

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit O
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- Not Detected at the Reporting Limit ND

Page I of 6

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#: 1404217

11-Apr-14

Client:

Blagg Engineering

Project:

Nye LS 1

Sample ID MB-12589

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 12589

RunNo: 17875

Prep Date:

SeqNo: 515443

Units: mg/Kg

4/8/2014

Analysis Date: 4/8/2014

HighLimit

%RPD **RPDLimit**

Qual

Analyte Chloride

Result **PQL** ND 1.5

Sample ID LCS-12589

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Batch ID: 12589

RunNo: 17875

Prep Date: 4/8/2014 Analysis Date: 4/8/2014

SeqNo: 515444

Units: mg/Kg

Analyte

SPK value SPK Ref Val %REC LowLimit

Qual

91.0

90

RPDLimit

14

SPK value SPK Ref Val %REC LowLimit

110

HighLimit

1.5 15.00 Chloride

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range

Analyte detected below quantitation limits J

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits R Spike Recovery outside accepted recovery limits Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

P Sample pH greater than 2.

Reporting Detection Limit

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404217

11-Apr-14

Client:

Blagg Engineering

Project:

Nye LS 1

Sample ID MB-12558

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 12558

PQL

20

RunNo: 17848

Prep Date: 4/7/2014

Analysis Date: 4/8/2014

SeqNo: 514980

Units: mg/Kg

Analyte

Result

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD **RPDLimit**

Qual

Petroleum Hydrocarbons, TR

ND

SampType: LCS

TestCode: EPA Method 418.1: TPH

Sample ID LCS-12558

Batch ID: 12558

RunNo: 17848

Client ID: LCSS Prep Date: 4/7/2014

Analysis Date: 4/8/2014

SeqNo: 514981

Units: mg/Kg

Analyte Petroleum Hydrocarbons, TR Result PQL 92 20 SPK value SPK Ref Val 100.0

%REC 91.5

LowLimit HighLimit 80 120 %RPD **RPDLimit** Qual

Sample ID LCSD-12558

SampType: LCSD

Batch ID: 12558

RunNo: 17848

Client ID: LCSS02 Prep Date: 4/7/2014

Analysis Date: 4/8/2014

SeqNo: 514982

TestCode: EPA Method 418.1: TPH

Units: mg/Kg

RPDLimit

Qual

Analyte

Result

SPK value SPK Ref Val 0

%REC 90.2

LowLimit 80 HighLimit 120

Petroleum Hydrocarbons, TR

90 20

100.0

1.52

%RPD

20

Qualifiers:

S

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

Е Value above quantitation range

Analyte detected below quantitation limits J

RSD is greater than RSDlimit 0

R RPD outside accepted recovery limits

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Sample pH greater than 2.

Reporting Detection Limit

Analyte detected in the associated Method Blank

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1404217

11-Apr-14

Client:

Blagg Engineering

Project:

Nye LS 1

Sample ID MB-12557	SampType: ME	BLK	Tes	tCode: E	PA Method	8015D: Dies	el Range (Organics	
Client ID: PBS	Batch ID: 12	557	F	RunNo: 17	7845				
Prep Date: 4/7/2014	Analysis Date: 4/	/8/2014	S	SeqNo: 5 ′	14590	Units: mg/K	(g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND 10								
Surr: DNOP	7.4	10.00		74.0	66	131			
Comple ID 1 00 40FF7		_		Cada. E					***
Sample ID LCS-12557	SampType: LC	S	ies	(Code: Er	PA Method	8015D: Dies	el Range (Organics	
Client ID: LCSS	SampType: LC Batch ID: 12			RunNo: 1 7		8015D: Dies	el Range (Organics	
,	Batch ID: 12		F		7845	8015D: Diese Units: mg/K	ū	Organics	
Client ID: LCSS	Batch ID: 12	557 /8/2014	F	RunNo: 17	7845		ū	Prganics RPDLimit	Qual
Client ID: LCSS Prep Date: 4/7/2014	Batch ID: 12 Analysis Date: 4/	557 /8/2014	F	RunNo: 17 SeqNo: 5	7845 14592	Units: mg/K	(g	ū	Qual

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

mnle nH greater than ?

P Sample pH greater than 2.

RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

930

WO#: 1404217

11-Apr-14

Client:

Blagg Engineering

Project:

Surr: BFB

Nye LS 1

Sample ID MB-12550	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Range
Client ID: PBS	Batch ID: 12550	RunNo: 17826	
Prep Date: 4/4/2014	Analysis Date: 4/7/2014	SeqNo: 514468	Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Gasoline Range Organics (GRO) Surr: BFB	ND 5.0 860 1000	86.2 74.5	129
Sample ID LCS-12550	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Range
Client ID: LCSS	Batch ID: 12550	RunNo: 17826	
Prep Date: 4/4/2014	Analysis Date: 4/7/2014	SeqNo: 514469	Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Gasoline Range Organics (GRO)	26 5.0 25.00	0 103 71.7	134

93.3

74.5

129

1000

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1404217

11-Apr-14

Client:

Blagg Engineering

Project:

Nye LS 1

Sample ID MB-12550	SampType: MBLK Batch ID: 12550			Tes						
Client ID: PBS				F	RunNo: 1	7826				
Prep Date: 4/4/2014	Analysis [Date: 4/	7/2014	SeqNo: 514510			Units: mg/k	(g		
Analyte	Result PQL SPK value SPK Ref Val %REC LowLim		LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		104	80	120			

Sample ID LCS-12550	TestCode: EPA Method 8021B: Volatiles									
Client ID: LCSS	F									
Prep Date: 4/4/2014	Analysis [Date: 4/	7/2014	SeqNo: 514511			Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	110	80	120			
Toluene	1.0	0.050	1.000	0	101	80	120			
Ethylbenzene	1.0	0.050	1.000	0	101	80	120			
Xylenes, Total	3.0	0.10	3.000	0	101	80	120			
Surr: 4-Bromofluorobenzene	1.1		1.000		108	80	120			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Number	r: 1404217		RcptNo:	1
Received by/date:	04/04/14				
Logged By: Michelle Garcia	4/4/2014 10:00:00 AM	1	Michael Ga	nuie	
Completed By: Michelle Garcia	4/4/2014 11:47:47 AM	1	Microst Ga Microst Ga	٠	
Reviewed By:	rubul 4		, 7		
Chain of Custody	017-17-				
1. Custody seals intact on sample bottles?		Yes 🗌	No 🗌	Not Present	
2. Is Chain of Custody complete?		Yes 🗹	No 🗌	Not Present	
3. How was the sample delivered?		<u>Courier</u>			
<u>Log In</u>			•		
Was an attempt made to cool the samples:	?	Yes 🗹	No 🗌	na 🗆	
5. Were all samples received at a temperature	e of >0° C to 6.0°C	Yes 🗹	No 🗌	na 🗆	
6. Sample(s) in proper container(s)?		Yes 🗹	No 🗆		
7. Sufficient sample volume for indicated test(Yes 🗹	No 🗆			
8. Are samples (except VOA and ONG) prope	Yes 🗹	No 🗌	•		
9. Was preservative added to bottles?		Yes 🗌	No 🗹	, NA 🗆	
10.VOA vials have zero headspace?		Yes 🗌	No 🗌	No VOA Vials 🗹	
11. Were any sample containers received brok	en?	Yes	No 🗹		
		_		# of preserved bottles checked	
12.Does paperwork match bottle labels? (Note discrepancies on chain of custody)		Yes 🗹	No 🗌	for pH: (<2 o	>12 unless noted)
13. Are matrices correctly identified on Chain of	f Custody?	Yes 🗹	No 🗆	Adjusted?	
14. Is it clear what analyses were requested?	·	Yes 🗹	No 🗆		
15. Were all holding times able to be met? (If no, notify customer for authorization.)		Yes 🗹	No 🗆	Checked by:	
(if the inotity design for the inotitorization)					
Special Handling (if applicable)					-
16. Was client notified of all discrepancies with	this order?	Yes 🗌	No 🗆	NA 🗹	
Person Notified:	Date:				
By Whom:	Via:	eMail	Phone Fax	☐ In Person	
Regarding:					
Client Instructions:	<u> </u>				
17. Additional remarks:					
18. <u>Cooler Information</u>			:	ı	
Cooler No Temp °C Condition S		Seal Date	Signed By		
1.0 .000	-				

Client:	ent: Blagg Engineering, Inc.			Standard □ Rush					Ë					•			ATO		
BP America			Project Name		ANALYSIS LABORATORY www.hallenvironmental.com														
Mailing Address: P.O. Box 87		Nye LS 1				4901 Hawkins NE - Albuquerque, NM 87109													
			eld, NM 87413	Project #:						505-345-3975				Fax 505-345-4107					
Phone #:	Phone #: (505)320-1183																		, j.
email or Fax#:			Project Manager:															T	
QA/QC Package: Standard Level 4 (Full Validation)			 	Jeff Blagg				0											
		Sampler: Jeff Blagg					1 6												
	□ Other		On Ice:	∖⊈Yes	□ No		1	ြစ္တ										Z	
				Sample Temperature: /200 6				=	<u> </u>										ح ک
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO		BTEX (8021)	TPH 8015B (GRO / DRO)	TPH 418.1) () () () () () () () () () (Culoride	Air Bubbles (Y or N)
04/02/2014	13:25	Soil	95 BGT 5-pt @ 5'	4oz x 1	cool	-001		x ·	×	×							,	_	+
																十	十	十	T
							寸					H				\dashv	+	+	+
		-							+						\vdash	十	_	+	+
		1			<u> </u>		一十	_							\vdash	\dashv	-		+-
		_							 					\vdash		十		+	+
		-							+							十	+	+	+
<u></u>		+							+-							\dashv	+	+	+
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		1			<u> </u>			_	+						\vdash	\dashv		+	+
 									+							-		+	+
		_					一十	\dashv	+						\vdash	\dashv	+	+	+
							$\neg \dagger$	_	+-							\dashv	\dashv	+	+
Date:	Time:	Relinquish	ped by:	Received by:	<u> </u>	Date Time	F	Remar	ks: B	III BF	>	LI		لــــــا					
Date: 4/3/2014	1600	1 2	off Blogg	Christ	in Was lan	43/2014 160		Paykey					_						
Daie.	Time:	Relinquist	ned by: Hed by:	Received by: Date Time				BP Contact: Jeff Peace Please copy results to: peace.jeffrey@bp.com											
4/3/14	1729	Mister Doctors		Celin	Sun	In 04/04/14 100													

If necessary, samples submitted to Hail Environmental may be subcontracted to other accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report.





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

April 7, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: NYE LS 001 API #: 3004510591

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about April 10, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9D Varka

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

April 10, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

NYE LS 001 API 30-045-10591 (G) Section 23 – T31N – R11W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

Jeff Peace

(505) 326-9479



