District 1
1625 N. Freden Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

	The state of the s
Pit, Below-Grade Tank, or	
Proposed Alternative Method Permit or Closure	Plan Application
Proposed Alternative Method Permit or Closure Proposed Alternative Method Permit or Closure Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternation Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or or proposed alternative method	
Instructions: Please submit one application (Form C-144) per individual pit, below	v-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result nvironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable g	in pollution of surface water, ground water or the overnmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID#:	779
Address:200 Energy Court, Farmington, NM 87401	OIF COMS. D
Facility or well name:Gallegos Canyon Unit 399	
API Number:3004529036 OCD Permit Number:	·
U/L or Qtr/QtrH Section24 Township29N Range13W	County:San Juan
Center of Proposed Design: Latitude36.71309 Longitude108.15138	NAD: □1927 ⊠ 1983
Surface Owner: 🗌 Federal 🔲 State 🔯 Private 🔲 Tribal Trust or Indian Allotment	
2. □ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: □ Drilling □ Workover □ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management □ Lined □ Unlined Liner type: Thicknessmil □ LLDPE □ HDPE □ PVC □ O □ String-Reinforced	
Liner Seams: Welded Factory Other Volume: bb	l Dimensions: L x W x D
3.	
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A	
Volume:95.0bbl Type of fluid:Produced water	
Tank Construction material:Steel	
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic or	verflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/Double bot	ttomed, side walls not visible
Liner type: Thickness mil	
4.	

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Alternative Method:

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC	
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8. Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	otable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
<u>Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.</u> NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application: - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	□ Yes □ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.12 NMAC	
and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	3.17.5
II.	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	uments are
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC 	15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable soun provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
·	
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
·	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain FEMA map	☐ Yes ☐ No ☐ Yes ☐ No
- 1 Divit map	163 110
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:Telephone:	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 6/16/8	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 6/16/66	20(4 the closure report.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: OCD Permit Number: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.

Operator. Closure Certification:	
I hereby certify that the information and attachments submitted with this closu	
belief. I also certify that the closure complies with all applicable closure requi	irements and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Joff Poace	Date: _ June 11, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit 399 API No. 3004529036 Unit Letter H, Section 24, T29N, R13W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 - Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is covered by the LPT.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action OPERATOR Initial Report Final Report Name of Company: BP Contact: Jeff Peace Address: 200 Energy Court, Farmington, NM 87401 Telephone No.: 505-326-9479 Facility Name: Gallegos Canyon Unit 399 Facility Type: Natural gas well Surface Owner: Private Mineral Owner: Private API No. 3004529036 LOCATION OF RELEASE Unit Letter Section Township Feet from the North/South Line Feet from the East/West Line County: San Juan Range 24 29N 13W 2.196 North Н 798 East **Latitude** 36.71309 **Longitude** 108.15138 NATURE OF RELEASE Type of Release: none Volume of Release: N/A Volume Recovered: N/A Source of Release: below grade tank – 95 bbl Date and Hour of Occurrence: Date and Hour of Discovery: N/A Was Immediate Notice Given? If YES, To Whom? ☐ Yes ☐ No ☒ Not Required By Whom? Date and Hour Was a Watercourse Reached? If YES, Volume Impacting the Watercourse. ☐ Yes ☒ No If a Watercourse was Impacted, Describe Fully.* Describe Cause of Problem and Remedial Action Taken.* Sampling of the soil beneath the BGT was done during removal to ensure no soil impacts from the BGT. Soil analysis resulted in TPH, BTEX and chlorides below standards. Analysis results are attached. Describe Area Affected and Cleanup Action Taken.* BGT was removed and the area underneath the BGT was sampled. The excavated area was backfilled and compacted and is covered by the LPT. I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations. OIL CONSERVATION DIVISION Signature: Approved by Environmental Specialist: Printed Name: Jeff Peace Title: Area Environmental Advisor Approval Date: **Expiration Date:** Conditions of Approval: E-mail Address: peace.jeffrey@bp.com Attached | Phone: 505-326-9479 Date: June 11, 2014 * Attach Additional Sheets If Necessary

client: BP	P.O. BOX 87, E	NGINEERING BLOOMFIELD D5) 632-1199	D, NM 8741		API #: 3004! TANK ID (if applicble):	_
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGAT	TION / OTHER:		PAGE #: 1 _	_ of 1
SITE INFORMATION	I: SITE NAME: GCU#	399			DATE STARTED: (04/04/14
QUAD/UNIT: H SEC: 24 TWP:	29N RNG: 13W PM	: NM CNTY:	SJ ST:	NM_	DATE FINISHED:	
1/4-1/4/FOOTAGE: 2,196'N / 798	'E SE/NE LEASE		STATE / FEE IND	DIAN	ENVIRONMENTAL	
	PROD. FORMATION: FT C	ONTRACTOR: MBI	F - P. ALEXANI	DER	SPECIALIST(S):	JCB
REFERENCE POINT			6.71310 X 108.	15146	GL ELEV.:	5,311'
1) 95 BGT (DW/DB)	GPS COORD.:	36.71309 X 108.1	5138 DI	STANCE/BEAF	RING FROM W.H.: 18'	, DUE EAST
2)	GPS COORD.:		DI	STANCE/BEAF	RING FROM W.H.:	
3)	GPS COORD.:		DI	STANCE/BEAF	RING FROM W.H.:	
4)	T			STANCE/BEAF	RING FROM W.H.:	
SAMPLING DATA:	_					OVM READING (ppm)
1) SAMPLE ID: 95 BGT 5-pt. @	5' SAMPLE DATE: 04/04	4/14 SAMPLE TIME:	1210 LAB ANALYSIS:	418.1/8	015B/8021B/300.0	(CI) 0.0
2) SAMPLE ID:	SAMPLE DATÉ:	SAMPLE TIME:	ŁAB ANALYSIS:			
3) SAMPLEID:						
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:			
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND /	SILT / SILTY CLAY / CLAY	// GRAVEL / OTHER			
SOIL COLOR: DARK YELLO		PLASTICITY (CLAYS): NO			DHESIVE / MEDIUM PLASTIC	
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC					STIFF / VERY STIFF / HAR	
MOISTURE: DRY SLIGHTLY MOIST MOIST / WI		HC ODOR DETECTED.	TES <u>VNO</u> EXPLANATIO	JN -		
SAMPLE TYPE: GRAB COMPOSITE #	OF PTS 5	ANY AREAS DISPLAYING	G WETNESS: YES N	O EXPLAN	ATION -	
DISCOLORATION/STAINING OBSERVED: YES N					<u> </u>	
SITE OBSERVATION			IN -			
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:			GT POSITION.			
OTHER:				_		
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA	ft. EXCAVA	TION EST	IMATION (Cubic Yards)	NA
	EAREST WATER SOURCE: >1,000				D TPH CLOSURE STD:	100 ppm
SITE SKETCH	BGT Located: off on si	te PLOT PLA	N circle: attach	ed O\M	CALIB. READ. = 101.0	ppm BE =1.00
_			<u></u>	I	CALIB. GAS = 100	ppm RF =1.00
		BERM	1	_ [[]		04/04/14
	~	_	•	▝╵╞═	MISCELL. N	IOTES
				l _w	o: N1517498	
	$\int (x \hat{x} x)$	x) PBGTL			<u>o: 141317438</u> 0#:	<u> </u>
	W.H.	T,B. ~ 5' B.G.		Pi		GT2
PU JA	_ / /	7		<u>P.</u>	#: Z2-006Q0	
5,0				<u>P</u> e		6/14/10
				O(1/22/13 por Meter
				_ID		illion
✓ TO METER			.,		BGT Sidewalls Visible:	
RUN	ON DEDDEGOION D.O. BELOWORLDE D.	DELOMATIL - TEOT LOVE.	X - S.P		BGT Sidewalls Visible:	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGLI	OW-GRADE TANK LOCATION; SPD = SAMPLE	POINT DESIGNATION; R.W. = 1	RETAINING WALL; NA - NO	DT M	lagnetic declination	
NOTES:		ONSITE:_	04/04/14			
revised: 11/26/13					E	3EI1005E-6.SKF

Analytical Report

Lab Order 1404410

Date Reported: 4/22/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Project:

Lab ID:

GCU 399

1404410-001

Client Sample ID: 95 BGT 5-pt @ 5'

Collection Date: 4/4/2014 12:10:00 PM

Received Date: 4/9/2014 10:00:00 AM

Analyses	Result	RL Qu	ıal Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGI	ORGANICS				Analyst	BCN
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	4/10/2014 8:12:54 PM	12624
Surr: DNOP	100	66-131	%REC	1	4/10/2014 8:12:54 PM	12624
EPA METHOD 8015D: GASOLINE RAI	NGE				Analyst	: RAA
Gasoline Range Organics (GRO)	ND	9.8	mg/Kg	2	4/11/2014 2:41:05 PM	12623
Surr: BFB	88.5	74.5-129	%REC	2	4/11/2014 2:41:05 PM	12623
EPA METHOD 8021B: VOLATILES					Analyst	: RAA
Benzene	ND	0.098	mg/Kg	2	4/11/2014 2:41:05 PM	12623
Toluene	ND	0.098	mg/Kg	2	4/11/2014 2:41:05 PM	12623
Ethylbenzene	ND	0.098	mg/Kg	2	4/11/2014 2:41:05 PM	12623
Xylenes, Total	ND	0.20	mg/Kg	2	4/11/2014 2:41:05 PM	12623
Surr: 4-Bromofluorobenzene	105	80-120	%REC	2	4/11/2014 2:41:05 PM	12623
EPA METHOD 300.0: ANIONS					Analyst	: JRR
Chloride	ND	30	mg/Kg	20	4/10/2014 2:53:41 PM	12646
EPA METHOD 418.1: TPH					Analyst	: BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	4/10/2014	12560

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range Ε
- J Analyte detected below quantitation limits
- О RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#: 1404410

22-Apr-14

Client:

Blagg Engineering

Project:

GCU 399

Sample ID MB-12646

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 12646

RunNo: 17936

4/10/2014 Prep Date:

SeqNo: 517496

Units: mg/Kg

HighLimit

Analyte

Analysis Date: 4/10/2014

%REC LowLimit

RPDLimit %RPD

Qual

Chloride

Result PQL ND 1.5

Sample ID LCS-12646

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS Batch ID: 12646

RunNo: 17936

Prep Date: 4/10/2014

Analysis Date: 4/10/2014

SeqNo: 517497

Units: mg/Kg

%RPD **RPDLimit**

Qual

Analyte

15.00

%REC 93.6

SPK value SPK Ref Val

SPK value SPK Ref Val

90

LowLimit

HighLimit 110

14

1.5

Chloride

PQL

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range Е
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits
- В Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2.
- RLReporting Detection Limit

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1404410

22-Apr-14

Client:

Blagg Engineering

Project:

GCU 399

Sample ID MB-12560 SampType: MBLK TestCode: EPA Method 418.1: TPH Client ID: PBS Batch ID: 12560 RunNo: 17911 Prep Date: 4/7/2014 Analysis Date: 4/10/2014 SeqNo: 516689 Units: mg/Kg Analyte SPK value SPK Ref Val %REC HighLimit %RPD **RPDLimit** Qual LowLimit ND 20 Petroleum Hydrocarbons, TR

Sample ID LCS-12560 SampType: LCS TestCode: EPA Method 418.1: TPH

Client ID: LCSS Batch ID: 12560 RunNo: 17911

Prep Date: 4/7/2014 Analysis Date: 4/10/2014 SeqNo: 516690 Units: mg/Kg

Analyte Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual

Analyte Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit Petroleum Hydrocarbons, TR 98 20 100.0 0 97.8 80 120

SampType: LCSD TestCode: EPA Method 418.1: TPH Sample ID LCSD-12560 Client ID: LCSS02 Batch ID: 12560 RunNo: 17911 Prep Date: 4/7/2014 Analysis Date: 4/10/2014 SeqNo: 516691 Units: mg/Kg %REC Analyte Result SPK value SPK Ref Val LowLimit HighLimit %RPD **RPDLimit** Qual Petroleum Hydrocarbons, TR 98 20 100.0 0 97.8 80 120 0 20

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.

RL Reporting Detection Limit

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404410

22-Apr-14

Client:

Blagg Engineering

Project:

GCU 399

Sample ID MB-12624	SampType: MBLK TestCode: EPA Method 8					8015D: Dies	el Range (Organics		
Client ID: PBS	Batc	h ID: 12	624	F	RunNo: 1	7898				
Prep Date: 4/9/2014	Analysis [Date: 4/	10/2014	SeqNo: 516973		973 Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Surr: DNOP	9.5		10.00		95.4	66	131			
Sample ID LCS-12624	Samp	Гуре: LC	 s	Tes	tCode: El	PA Method	8015D: Dies	el Range (Organics	
Client ID: LCSS	Batc	h ID: 12	624	F	RunNo: 1	7898				
Prep Date: 4/9/2014	Analysis [Date: 4/	10/2014	S	SeqNo: 5	16974	Units: mg/k	ζg		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	46	10	50.00	0	91.9	60.8	145			
Surr: DNOP	4.4		5.000		87.9	66	131			

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1404410

22-Apr-14

Client:

Blagg Engineering

Project:

GCU 399

Sample ID MB-12623	SampT	SampType: MBLK			TestCode: EPA Method 8015D: Gasoline Range					
Client ID: PBS	Batcl	n ID: 12	623	F	RunNo: 1	7906				
Prep Date: 4/9/2014	Analysis E	ate: 4/	10/2014	5	SeqNo: 5	17100	Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	870		1000		86.6	74.5	129			
Sample ID LCS-12623	SampT	ype: LC	s	Tes	tCode: El	PA Method	8015D: Gaso	line Rang	е	
•	Batch	1D: 12	623	F	RunNo: 1	7906				
Client ID: LCSS	Batch Analysis D				RunNo: 1 SeqNo: 5		Units: mg/F	ζg		
Client ID: LCSS Prep Date: 4/9/2014			10/2014				Units: mg/k HighLimit	(g %RPD	RPDLimit	Qual
Client ID: LCSS	Analysis D	ate: 4/	10/2014	5	SeqNo: 5	17101	-	•	RPDLimit	Qual

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1404410 22-Apr-14

Client:

Blagg Engineering

Project:

GCU 399

Sample ID MB-12623	SampT	SampType: MBLK TestCode: EPA Method				8021B: Volat	iles			
Client ID: PBS	Batcl	n ID: 12	623	RunNo: 17906						
Prep Date: 4/9/2014	Analysis D	Analysis Date: 4/10/2014		10/2014 SeqNo: 517142			Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050						· · · · · · · · · · · · · · · · · · ·		
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		105	80	120			
Sample ID LCS-12623	SampT	ype: LC	s	Tes	tCode: El	PA Method	8021B: Volat	iles		
Client ID: LCSS	Batch	ı ID: 12	623	F	RunNo: 1	7906				
Prep Date: 4/9/2014	Analysis D	ate: 4/	10/2014	S	SeqNo: 5	17143	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
·	Result 1.1	PQL 0.050	SPK value 1.000	SPK Ref Val	%REC 109	LowLimit 80	HighLimit 120	%RPD	RPDLimit	Qual
Benzene							-	%RPD	RPDLimit	Qual
Benzene Toluene	1.1	0.050	1.000	0	109	80	120	%RPD	RPDLimit	Qual
Analyte Benzene Toluene Ethylbenzene Xylenes, Total	1.1 1.0	0.050 0.050	1.000 1.000	0 0	109 102	80 80	120 120	%RPD	RPDLimit	Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawking VE Albuquergua, NM 37105 TEL: 505-345-3075 FAX: 505-345-416; Webstter www.ballgavironmental.eum

Sample Log-In Check List

Client Nanie: BLAGG	Work Order Number	1404410		Rootho	1
Received by/date:	04/09/14		- 1111111111111111111111111111111111111	ix law.	
Logged By: Michelle Garcia	4/9/2014 10:00:00 AM		Mirall Ca	(ue)	
Completed By: Michelle Garcia	4/9/2014 10:51:53 AM		Mirie Ga	22.5	
Reviewed By;	104/09/14		4		ļ
Chain of Custody					
1. Custody seats mitact on sample bottles?		Yes 🗍	No∙I⊒	Nột Bresent 🗹	
2. Is Chain of Custody complete?		Yes 🕅	No:	-Not Present 🔲	
3. How was the sample dollypred?		Coine			
Log In					
4. Was an attempt made to cool the samples	7	Yes 🛂	Na 🗌	NA 🗀	
5. Were all samples received at a temperatur	e of >0" C to 6.0"C	Yes 🗹	No 🗀	NA 🗌	
6. Samplé(s) in proper container(s)?		Yes 💆	Ne 🗌		
7: Sufficient sample volume for Indicated test	ś)?	Yes 🗹	Nô 📋		
8. Are samples (except VOA and ONG) prope	rly preserved?	Yes 🗹	No 🗆		
9. Was preservative added to bottles?		Yes 🗌	No 🗹	NA: 🗆	
10. VOA vials have zero headspace?		Yes 🗌	No 🗌	No VOA Vials	
11. Were any sample containers received broken	en?	Yes 🗆	No 🗹	# of preserved	
12. Doe's paperwork match bottle labels? (Note discrepancies on chain of custody)		Yés 🗹	No. □	bollies chieckou for pri	r >12 unless noted)
13. Are malrices correctly identified on Chain o	Yes 🗹	No 🗀	Adjusted?;		
14. Is it clear what analyses were requested?		Yes 📝	No 📙	della sinda in Mario	
45. Were all holding three able to be met? (If no, notify customer for authorization.)		Yes 📈	No 🖭	Checked by.	
Special Handling (if applicable)					
16. Was client notified of all discrepancies with	this order?	yes Li	Nô 🗐	NA 🗹	
Person Natilled:	Dete			de la companya de la	
By Whom:	·Via: [aMail 🔲	Phone 🔲 Fax.	☐ In Person	
Regarding:					
Client Instructions					
17. Additional remarks:					
18. Cooler Information			لا يوني وري		
		Seal Date	Signed By		
1 1/8 Good Vi					· :

Client Blagg Engineering Inc: BP America			Standard Rush Project Name: GCU 399: Project #:			ANALYSIS LABORATORY											
						www.hallenvironmental.com											
Mailing Address: P.O. Box 87		4901 Hawkins NE Albuquerque NM:87109															
Bloomfield, NM 87413 Phone #: (505)320-1183							Tel. 505-345-3975 Fax: 505-345-4107										
							د فرو در در			Ána	ysis	Requ	est				
email or Fax	#.			Project Mana	iger:												
QA/QC Package: Standard D Level 4 (Full Validation)			Jeff Blagg					DRO)	ı						1		
Other				Sampler:	Jeff Blagg				9								19
Other		On los Pres D No					잁	1				l		1 1	0		
			T.	Sample Tem	perature:	<i>7</i> 5	4 🗐		2								<u>\</u>
Date	^{ធ្វីព្រែ} ខំ	Matrix	Sample Request D.	Container Type and #	Preservative Type	HEALNO.	1 BTEX (8021)		TPH 8015B (GROV	TPH 418.1						Chloride	Air Bubbles (Yor N)
04/04/2014	12:10	Soil	95 BGT 5-pt @:5'	1x:4oz	cool	- (x) !	x			x	-				1	×	
		1 1 21 12					1		1			1		\neg	1	11	
-	1				1		1			\dashv	_		\vdash	-	+	++	+
<u></u>		-							-+			+	++		-	+++	-
	_===						-			+	+	-	┼┼	+	+-	++	-
-	i-		-	-			-	-		+		+			+	+	
		<u> </u>	<u>. </u>		·		-		-		_	-	+ +		+	+	
·	<u> </u>	1	1				4			-	4	4			_	++	
						•	 			+		-	-	_		$\stackrel{\downarrow}{\longmapsto}$	
ا بد مدیریس							<u> </u>	-	_		<u>.</u>	<u> </u>				1	
	,						<u> </u> :	; <u>;</u>			_					1-1	
			<u>-</u> -						<u>'</u>	_		<u> </u>				$\downarrow \downarrow \downarrow$	
	-	<u> </u>						البيا				<u> </u>	<u> </u>				
Date:	Time: 87	- 1- 17: C **	1 Deign	Received by: Paykey: ZEVH018GT2 Paykey: ZEVH018GT2 Please copy results to:													
Date:	Time:	Relinquish	w , v v	Received by:		Date Time		ce.jef		·		. :	· • ;=	,FJ	, -, -,		
	lessary samples		totta: MALJUL lat Environmental may be subcomract	ed to other accredition		serves as notice of this poss	iliy. A	ny sub-c	contra	cted cat	ž WII be	cleany	notated	on the r	ariatýtici	i report:	١,

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

April 7, 2014

Beverly and Doyle Newman 5431 Hwy 64 Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 399

Dear Mr. & Mrs. Newman,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about March 31, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9D Va Rja

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

April 10, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 399 API 30-045-29036 (G) Section 24 – T29N – R13W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



