District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Proposed Alternative Method Permit or Closure Plan Application  Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method  Modification to an existing permit/or registration  Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID#:778
Address:200 Energy Court, Farmington, NM
Facility or well name:Storey LS 4A
API Number:3004529050OCD Permit Number:
Center of Proposed Design: Latitude36.62006 Longitude107.67237 NAD: □1927 ⋈ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2.    Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover  Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
■ Below-grade tank: Subsection I of 19.15.17.11 NMAC        Tank A
Volume:95.0bbl Type of fluid:Produced water

Alternative Method:

Liner type: Thickness \_

Tank Construction material: \_\_Steel\_

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off ☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other \_Single walled/double bottomed

\_mil 🔲 HDPE 🗌 PVC 🔲 Other \_

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Alternate. Please specify	, hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC  12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks)  - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
<ul> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	
and 19.15.17.13 NMAC  Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11.  Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	cuments are
attached.  □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  □ A List of wells with approved application for permit to drill associated with the pit.  □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.12 NMAC	.15.17.9 NMAC
and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Form C-144 Oil Conservation Division Page 3 of 6

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC   Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC   Climatological Factors Assessment   Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC   Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC   Quality Control/Quality Assurance Construction and Installation Plan   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC   Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan   Emergency Response Plan   Oil Field Waste Stream Characterization   Monitoring and Inspection Plan   Erosion Control Plan   Erosion Control Plan   Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC   Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	□ Vea□ Ne
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	│

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map Within a 100-year floodplain.	☐ Yes ☐ No
- FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:Telephone:	
18.  OCD Approval: ☐ Permit Application (including closure plan) ☑ Closure Plan (only) ☐ OCD Conditions (see attachment)	
OCD Representative Signature: Approval Date:	2014
	the closure report.
19.  Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure requi	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Posse	Date:June 12, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

# BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

## BELOW-GRADE TANK CLOSURE PLAN

## Storey LS 4A API No. 3004529050 Unit Letter F, Section 34, T28N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

## General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
  - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

#### Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.** 

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District 1</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

\* Attach Additional Sheets If Necessary

# State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

**Release Notification and Corrective Action** 

Form C-141 Revised August 8, 2011

						<b>OPERA</b>	ΓOR		☐ Initi	al Report	$\boxtimes$	Final Repor
Name of Co						Contact: Jef						
		Court, Farmi	ngton, N	M 87401			No.: 505-326-94					
Facility Na	me: Storey	LS 4A				Facility Typ	e: Natural gas v	vell				
Surface Ow	ner: Feder	al		Mineral (	)wner: 1	Federal			API No	. 30045290	50	
				LOCA	ATIO	N OF REI	LEASE					
Unit Letter F	Section 34	Township 28N	Range 8W	Feet from the 1,790		South Line	Feet from the 1,570	East/V West	Vest Line	County: Sa	an Juan	
	<u> </u>	Lati	itude3	6.62006		_ Longitud	e107.67237			<b>L</b>		
				NAT	URE	OF REL	EASE					
Type of Rele	ase: none					Volume of	Release: N/A		Volume F	Recovered: N	l/A	
Source of Re	lease: belov	v grade tank –	95 bbl, T	ank A		Date and H N/A	lour of Occurrenc	e:	Date and	Hour of Dis	covery:	N/A
Was Immedia	ate Notice (		Yes [	No ⊠ Not Re	equired	If YES, To	Whom?	-				
By Whom?						Date and F	lour					
Was a Water	course Read	ched?	Yes 🗵	] No			olume Impacting t	he Wate	ercourse.			
If a Watercon	ırse was Im	pacted, Descri	be Fully.*	*		<u> </u>						
		r ,										
							the BGT was dor is results are attac		g removal 1	to ensure no	soil im	pacts from
				en.* BGT was re active well area.	moved a	nd the area u	nderneath the BG	T was s	ampled. Ti	he excavated	area w	vas
regulations al public health should their or or the environ	I operators or the envir operations homent. In a	are required to ronment. The ave failed to a	report an acceptanc dequately CD accep	nd/or file certain rece of a C-141 repo investigate and re	elease no ort by the emediate	otifications are NMOCD made contamination	knowledge and und perform correctarked as "Final Room that pose a threet the operator of restriction."	tive acti eport" d eat to gr	ons for rele oes not reli ound water	eases which eve the oper , surface wa	may en ator of ter, hur	danger liability nan health
OIL CONSERVATION DIVISION												
Signature:	all	Page										
Printed Name	U ·		<u>, , , , , , , , , , , , , , , , , , , </u>			Approved by	Environmental S <sub>I</sub>	oecialist	::			
Title: Area E		<del>-</del>			1	Approval Dat	e:	I	Expiration I	Date:		
		effrey@bp.com	n			Conditions of		<u> </u>	Attached			
Date: June 1	2, 2014		Phone: 50	5-326-9479							-	

CLIENT: BP	P.O. BOX 87, BL	GINEERING, INC. OOMFIELD, NM 87 632-1199	'413	API #: 3004529050  TANK ID (if applicble): A & B
FIELD REPORT:	(circle one): BGT CONFIRMATION / R	·		PAGE #: 1 of 1
	28N RNG: 8W PM:	NM CNTY: SJ ST		DATE STARTED: 04/14/14  DATE FINISHED:
1/4 - 1/4/FOOTAGE: 1,790'N / 1,57 LEASE #: SF078566 REFERENCE POINT	PROD. FORMATION: MV CON	ELKHORN TRACTOR: MBF - B. SCHL	JMAN	ENVIRONMENTAL SPECIALIST(S): JCB
	GPS COORD.: <b>36.6</b>	36,62005 X · 62006 X 107.67237	_ DISTANCE/BEAR	GL ELEV.: 5,859' RING FROM W.H.: 94', S64W RING FROM W.H.: 99', 94W
3)			_ DISTANCE/BEAF	RING FROM W.H.:
SAMPLING DATA:  1) SAMPLE ID: 5PC - TB @ 5		SAMPLETIME: 1115 LABANA		
<ul> <li>2) SAMPLE ID:</li></ul>		SAMPLE TIME: LAB ANA	LYSIS:	
SOIL DESCRIPTION  SOIL COLOR: DARK YELL  COHESION (ALL OTHERS): NON COHESIVE) SLIGHTLY  CONSISTENCY (NON COHESIVE SOILS): LC  MOISTURE: DRY SLIGHTLYMOIST MOIST / WE  SAMPLE TYPE: GRAB (COMPOSITE) #  DISCOLORATION/STAINING OBSERVED: YES N	COMSH ORANGE  COHESIVE / COHESIVE / HIGHLY COHESIVE   DE  COSE / FIRM / DENSE / VERY DENSE   HC  ET / SATURATED / SUPER SATURATED   OF PTS. 5   AN  O EXPLANATION -	ASTICITY (CLAYS): NON PLASTIC / SLIGHENSITY (COHESIVE CLAYS & SILTS): ODOR DETECTED: YES NO EXPLAINT WETNESS: YES	TLY PLASTIC / CO SOFT / FIRM / S NATION -	
SITE OBSERVATION  APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:  OTHER: TANK B ACTUALLY 95 BBL BGT	DAND/OR OCCURRED : YES NO EXPLANA YES NO EXPLANATION - <b>T-BLOCK L</b>	ITION: IFT TO BE SET ATOP TANK A.	DENCE OF A	RELEASE).
	EAREST WATER SOURCE: >1,000'	NEAREST SURFACE WATER: <1,0		IMATION (Cubic Yards) : NA DEPTH CLOSURE STD: 100 ppm
SITE SKETCH	BGT Located: off on site	PLOT PLAN circle: a    W.H.	_ A OVM	CALIB. READ. =         NA         ppm         RF = 1.00           CALIB. GAS =         NA         ppm           NA         am/pm         DATE:         NA
CONTA RI  NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO	SEPARATOR  WOODEN R.W. PROD. TANK BERM  EEL JINMENT NG  W DEPRESSION; B.G. = BELOW GRADE; B = BELOW	V, T.H. = TEST HOLE; ~ = APPROX.; W.H. = W	W PC PI P. Pe OC Tan ID A B ELL HEAD;	J#: Z2-006Q0  ermit date(s): 06/14/10  CD Appr. date(s): 02/28/14  k OVM = Organic Vapor Meter ppm = parts per million  BGT Sidewalls Visible: Y/ N  BGT Sidewalls Visible: Y / N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELC APPLICABLE OR NOT AVAILABLE; SW-SINGLE	DW-GRADE TANK LOCATION; SPD = SAMPLE POINT WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM DV DATE - 11/17/2013	DESIGNATION; R.W. = RETAINING WALL; N ; DB - DOUBLE BOTTOM. ONSITE: <b>04/14/14</b>	A-NOI M	agnetic declination: 10° E

revised: 11/26/13 BEI1005E-6.SKF

## **Analytical Report**

## Lab Order 1404814

Date Reported: 4/23/2014

## Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering Project: Storey LS #4A

Lab ID:

1404814-001

mg/Kg

Client Sample ID: 5PC - TB @ 5' (95) - A

Collection Date: 4/14/2014 11:15:00 AM Received Date: 4/17/2014 10:10:00 AM

**Analyses** Result **RL Qual Units** DF Date Analyzed Batch **EPA METHOD 8015D: DIESEL RANGE ORGANICS** Analyst: JME Diesel Range Organics (DRO) ND 10 mg/Kg 4/18/2014 10:23:41 AM 12758 Surr: DNOP %REC 103 57.9-140 4/18/2014 10:23:41 AM 12758 **EPA METHOD 8015D: GASOLINE RANGE** Analyst: RAA Gasoline Range Organics (GRO) ND 5.0 mg/Kg 4/19/2014 12:41:00 AM 12765 1 Surr: BFB 85.2 %REC 4/19/2014 12:41:00 AM 12765 74.5-129 **EPA METHOD 8021B: VOLATILES** Analyst: RAA Benzene ND 0.050 4/19/2014 12:41:00 AM 12765 mg/Kg Toluene 0.050 ND mg/Kg 4/19/2014 12:41:00 AM 12765 Ethylbenzene ND 0.050 mg/Kg 4/19/2014 12:41:00 AM 12765 Xylenes, Total ND 0.10 ma/Ka 4/19/2014 12:41:00 AM 12765 Surr: 4-Bromofluorobenzene 100 80-120 %REC 4/19/2014 12:41:00 AM 12765 **EPA METHOD 300.0: ANIONS** Analyst: JRR 4/18/2014 4:42:34 PM 12780 Chloride ND 30 mg/Kg **EPA METHOD 418.1: TPH** Analyst: JME Petroleum Hydrocarbons, TR ND 20 4/18/2014 12:00:00 PM 12725

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit

Page 1 of 7

- Sample pH greater than 2.
- Reporting Detection Limit RL

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1404814 23-Apr-14

Client:

Blagg Engineering

Project:

Storey LS #4A

Sample ID MB-12780

SampType: MBLK

TestCode: EPA Method 300.0: Anions

LowLimit

PBS Client ID:

Batch ID: 12780

RunNo: 18105

%RPD

Prep Date:

4/18/2014

Analysis Date: 4/18/2014

SeqNo: 522731

Units: mg/Kg

Analyte

%REC

HighLimit

**RPDLimit** 

Qual

Chloride

Result PQL ND 1.5

Sample ID LCS-12780

**LCSS** 

SampType: LCS

TestCode: EPA Method 300.0: Anions

RunNo: 18105

Prep Date: 4/18/2014

SeqNo: 522732

Units: mg/Kg

Analyte

Client ID:

Analysis Date: 4/18/2014

Batch ID: 12780

PQL

1.5

%REC

HighLimit

%RPD **RPDLimit**  Qual

Result

0

Chloride

14

SPK value SPK Ref Val

SPK value SPK Ref Val

92.8

90

15.00

LowLimit

110

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

Spike Recovery outside accepted recovery limits

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits R

В Analyte detected in the associated Method Blank

Η Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Sample pH greater than 2. P

Reporting Detection Limit RL

Page 3 of 7

# Hall Environmental Analysis Laboratory, Inc.

WO#: 1404814

23-Apr-14

Client:

Blagg Engineering

Project:

Analyte

Storey LS #4A

Sample ID MB-12725

SampType: MBLK

TestCode: EPA Method 418.1: TPH

**PBS** Client ID:

Batch ID: 12725

RunNo: 18086

Prep Date: 4/15/2014 Analysis Date: 4/18/2014

SeqNo: 522085

Units: mg/Kg

**PQL** 

%REC

HighLimit

**RPDLimit** 

Qual

Petroleum Hydrocarbons, TR

ND 20

Result

Result

Result

99

SampType: LCS

TestCode: EPA Method 418.1: TPH

LowLimit

Sample ID LCS-12725 Client ID:

LCSS

Batch ID: 12725

RunNo: 18086

SPK value SPK Ref Val

Analysis Date: 4/18/2014

SeqNo: 522086

Units: mg/Kg

120

Qual

Analyte Petroleum Hydrocarbons, TR

Prep Date:

PQL

SPK value SPK Ref Val 100.0

%REC

LowLimit

HighLimit

**RPDLimit** 

91 20

90.9

%RPD

%RPD

Qual

Sample ID LCSD-12725

Client ID: LCSS02

4/15/2014

SampType: LCSD

TestCode: EPA Method 418.1: TPH

RunNo: 18086

Units: mg/Kg

**RPDLimit** 

Analyte Petroleum Hydrocarbons, TR

Prep Date: 4/15/2014

Analysis Date: 4/18/2014 **PQL** 

Batch ID: 12725

SPK value SPK Ref Val 20

100.0

%REC 99.1

SeqNo: 522087

80

120

%RPD 8.61

20

0

LowLimit

HighLimit

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

RSD is greater than RSDlimit 0 R RPD outside accepted recovery limits

Analyte detected below quantitation limits

S Spike Recovery outside accepted recovery limits Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н ND Not Detected at the Reporting Limit

Sample pH greater than 2.

RLReporting Detection Limit

Page 4 of 7

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1404814

23-Apr-14

Client:

Blagg Engineering

Project:

Storey LS #4A

	L3 #4A		
Sample ID MB-12758	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Organics
Client ID: PBS	Batch ID: 12758	RunNo: 18068	
Prep Date: 4/17/2014	Analysis Date: 4/18/2014	SeqNo: <b>521273</b>	Units: mg/Kg
Analyte	Result PQL SPK value S	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO)	ND 10		
Surr: DNOP	10 10.00	102 57.9	140
Sample ID LCS-12758	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Organics
Client ID: LCSS	Batch ID: 12758	RunNo: 18068	
Prep Date: 4/17/2014	Analysis Date: 4/18/2014	SeqNo: <b>521275</b>	Units: mg/Kg
Analyte	Result PQL SPK value S	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO)	46 10 50.00	0 91.4 60.8	145
Surr: DNOP	4.4 5.000	88.6 57.9	140
Sample ID MB-12781	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Organics
Client ID: PB\$	Batch ID: 12781	RunNo: 18068	
Prep Date: 4/18/2014	Analysis Date: 4/18/2014	SeqNo: <b>521276</b>	Units: %REC
Analyte	Result PQL SPK value S	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Surr: DNOP	9.6 10.00	96.0 57.9	140
Sample ID LCS-12781	SampType: <b>LCS</b>	TestCode: EPA Method	8015D: Diesel Range Organics
Client ID: LCSS	Batch ID: 12781	RunNo: 18068	
Prep Date: 4/18/2014	Analysis Date: 4/18/2014	SeqNo: <b>521898</b>	Units: %REC
Analyte	Result PQL SPK value S	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Surr: DNOP	4.6 5.000	91.5 57.9	140

## Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 7

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1404814

23-Apr-14

Client: Project: Blagg Engineering

Storey LS #4A

Sample ID	MB-12765 MK	
• · · · · · · · · · · · · · · · · · · ·		•

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID: **PBS** 

Batch ID: R18084

RunNo: 18084

Prep Date:

Analysis Date: 4/18/2014

SeqNo: 522566

Units: %REC

Analyte

PQL

Result

SPK value SPK Ref Val %REC

HighLimit LowLimit

%RPD

Qual

Surr: BFB

860

1000

85.6

74.5

**RPDLimit** 

Sample ID LCS-12765 MK

SampType: LCS Batch ID: R18084

PQL

TestCode: EPA Method 8015D: Gasoline Range RunNo: 18084

129

Client ID: Prep Date:

LCSS

Units: %REC

Analyte

Analysis Date: 4/18/2014

SeqNo: 522567

Qual

Client ID:

1000

SPK value SPK Ref Val

%REC LowLimit 91.5

HighLimit

%RPD **RPDLimit** 

Surr: BFB

910

Result

ND

Result

74.5

129

Sample ID MB-12765

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range RunNo: 18084

HighLimit

Prep Date: 4/17/2014

**PBS** 

Batch ID: 12765

Analysis Date: 4/18/2014

SeqNo: 522600

Units: mg/Kg

Analyte

**PQL** 5.0 SPK value SPK Ref Val

%REC

LowLimit

%RPD

**RPDLimit** 

Qual

Gasoline Range Organics (GRO) Surr: BFB

860

85.6

74.5

129

Sample ID LCS-12765

SampType: LCS

1000

1000

TestCode: EPA Method 8015D: Gasoline Range

HighLimit

134

129

Client ID: Prep Date:

**LCSS** 4/17/2014

Batch ID: 12765 Analysis Date: 4/18/2014

RunNo: 18084

SeqNo: 522601

Units: mg/Kg

%RPD

**RPDLimit** Qual

Analyte

Surr: BFB

Gasoline Range Organics (GRO)

Result 24

910

PQL SPK value SPK Ref Val 5.0 25.00

0

%REC LowLimit 97.9 91.5

71.7 74.5

# Qualifiers:

S

- E Value above quantitation range Analyte detected below quantitation limits
- Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

- 0 RSD is greater than RSDlimit
- RPD outside accepted recovery limits R

- В Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2. RLReporting Detection Limit

Page 6 of 7

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1404814

23-Apr-14

Client:

Blagg Engineering

Project:

Storey LS #4A

Sample ID MB-12765	SampT	уре: <b>М</b> Е	BLK	Tes	tCode: El	PA Method	8021B: Vola	tiles		
Client ID: PBS	Batch ID: 12765			RunNo: 18084						
Prep Date: 4/17/2014	Analysis Date: 4/18/2014			SeqNo: <b>522634</b>			Units: mg/F	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								•
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120			

Sample ID LCS-12765	TestCode: EPA Method 8021B: Volatiles												
Client ID: LCSS	765	RunNo: 18084											
Prep Date: 4/17/2014	Analysis Date: 4/18/2014			5	SeqNo: 5	22635	Units: mg/h						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	1.1	0.050	1.000	0	109	80	120	·	•				
Toluene	1.0	0.050	1.000	0	103	80	120						
Ethylbenzene	1.0	0.050	1.000	0	104	80	120			•			
Xylenes, Total	3.1	0.10	3.000	0	103	80	120						
Surr: 4-Bromofluorobenzene	1.1		1.000		106	80	120						

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 7 of 7



## Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

# Sample Log-In Check List

Client Name: BLAGG	GG Work Order Nun			814			RcptNo	: 1
Received by/date:	49	01/17/14)						
Logged By: Michelle	e Garcia	ia 4/17/2014 10:10:00			Michael	ь Ga	nui	
Completed By: Michelle	e Garcia	4/17/2014 11:56	:14 AM		Mital	ι UCn	(ue)	
Reviewed By:	Cs	04/17/14			•	7		
Chain of Custody	- <del></del>							
1. Custody seals intact or	sample bottles?		Yes		No		Not Present	
2. Is Chain of Custody co	mplete?		Yes	V	No [		Not Present	
3. How was the sample d	elivered?		Cou	rier				
<u>Log In</u>								
4. Was an attempt made	to cool the samples	?	Yes	$\checkmark$	No		na 🗆	
5. Were all samples recei	ived at a temperature	e of >0° C to 6.0°C	Yes	<b>~</b>	No [		NA 🗆	
6. Sample(s) in proper co	ontainer(s)?		Yes	V	No			
7. Sufficient sample volun	Yes	V	No [					
8. Are samples (except V	OA and ONG) prope	rly preserved?	Yes	V	No [			
9. Was preservative adde	d to bottles?		Yes		No (	<b>✓</b>	NA 🗆	
10.VOA vials have zero headspace?					No [		No VOA Vials 🗹	
11. Were any sample containers received broken?					No l	<b>v</b>	# of	
						_,	# of preserved bottles checked	
12. Does paperwork match (Note discrepancies on			Yes	$\checkmark$	No L		for pH: (<2	or >12 unless noted)
13, Are matrices correctly identified on Chain of Custody?				<b>✓</b>	No [		Adjusted?	•
14. Is it clear what analyses were requested?				$\checkmark$	No [	□ ¦		
15. Were all holding times (If no, notify customer f			Yes	$\checkmark$	No [		Checked by:	
Special Handling (if a	oplicable)							
16. Was client notified of al	<del></del>	this order?	Yes		No [		NA 🗹	
Person Notified:	<u> </u>	D:	ate:		4.4			
By Whom:	<u> </u>		ia: ∏ eMa	il 🗀 F	Phone 🗍 F	ax	☐ In Person	
Regarding:	<del></del>	f						
Client Instructions	s:		<del></del>	<del> </del>			- 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 1-12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12	:
17. Additional remarks:		<del></del>	•		,,,	•		· <del>-</del>
18. Cooler Information  Cooler No Temp  1 1.0	°C Condition S	eal Intact   Seal N	o   Seal Da	ite	Signed By	<u></u>		

enam-or-custody Record			4			Ι,	4	T. 1		H 8	d I	F	ŃΊ	/T		MI	ME	:MI	ra i	li i	
Client: BLAGG ENGR. / BP AMERICA			Standard				HALL ENVIRONMENTAL ANALYSIS LABORATORY														
				Project Name	2																<b>≱.</b> ■
Mailing Address: P.O. BOX 87			STOREY LS # 4A.					www.hallenvironmental.com 4901 Hawkins NE - Albuquerque), NM 87109													
BLOOMFIELD, NM-87413				Project #:				леі. 505-345-3975 — ғах.: 505-345-4107													
Phone #:		(505) 63	2-1199		المالية المستعدد	_	Analysis Request														
emaillor Fax#:-		Project Manager					171							I		1			-		
QA/QC Peckage:  [2] Standard:   [3] Level 4 (Full Validation)		NELSON VELEZ				(Ajuo s	1			S		04,50	/ 8082 PCB's			(1:000:1)					
Accreditation:			Sämpler: NELSON VELEZ 770			T K	IPH (Gas only)	ORO A	13	9	ZOSIMS)	,	Q'20	8082	'		/water	 	-	mple	
NELAP		□:Other		Onlice: WYes E No					10	418.1)	504.1)	827	: ::w/2	1,60			)A)	300.0	i l	- I.,	e s
EDD((Type)).		Sample Temperature: 100				jų.	89			6	etai	N	cide	₹	J-VC	, ,	, 1	힐	ž į		
Date	Time	Matrix	Sample/Request ID	Container Type and #	Preservative Type:	HEALNO:	BTEX +-MITE	BYEX + MTBE +	TPH 8015B (GRO / DRO	TPH (Method	EDB (Method	PAH (8310 or	RCRA 8 Metals	Anions (F,Cl,NO3,NO2,PO4,SO4)	8081 Pesticides	8250B (VOA)	\$270 (Semi-VOA)	Chloride (soil			5 pt. composite sample
4/14/14	1115	SOIL	SPC - TB @ 5' (95) - A	4 ož 1	Cool	-Co.)	V	_	٧		,				ω,		- W.	٧.	+	-	<u>,                                    </u>
į	]		_	:					1.	•	1		-		,				+		
4/14/14	1033	sou	SPC TP @ 5' (AC) 0	1 00 1	Giel					-1	,	-	. <del>-</del>	-			_	)		<u>                                     </u>	_
· · · -	1				1		-	,	. •				-						$\dashv$	平	丁-
				<del> </del>	•	:	-							$\vdash$				_		_	4
	· · ·			<u> </u>			_			<u> </u>	,		L							_	$\bot$
	n Te					. <u>.                                   </u>			·	j		t		. ,	;						
			,							•	"				- 4		- 1				
		·			<u></u>							,							1		T
		ا ـــال	<u> </u>	,	,	1	,	,	;	1									7	Ť	1
			t .	£.			,				,	il			•			-	<del></del>	+	+
				1					•	-				-	一	$\dashv$	-	$\dashv$	-	-	┪
			<u> </u>						, <b>.</b> .	-				-				<del>-  </del> ;	, .	-	+
Date:	<u> </u>	Relinquishe	d by:	Received by:	<u>:</u>	Date Time	Ren	harks	<u> </u>	i i	!	لــــا	'							1	<u> </u>
1/10/14 1505 Man of		Milotin la make Hundey 1505 BILL DIRECTLY. TO BP:						<b>.</b>													
Date: Time: Relinquished by:		Received by:	D. Double	Date Time	Jeff Peace, 200 Energy Court, Farmington, NM 87401  Work Order:N15451481: Paykey:ZEVH0180						<u> (Ż:</u>	_									
	If recesse	ry; samples si	ibmiliteo to Háll Environmental maý be s	ubconfracted to diner	accredited laboratories	This serves as notice of	this po	issipil	ty, An	ly sub	contra	acta <b>c</b>	jata w	III be c	early.	notate	d on u	re snn	lytical t	eport.	





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

April 7, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

#### VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: STOREY LS 004A

API#: 3004529050

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about April 29, 2014. If there aren't any unforescen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper Surface Land Negotiator

90 de Rje

**BP America Production Company** 

#### **BP America Production Company**

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

## SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

April 10, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

STOREY LS 004A API 30-045-29050 (G) Section 34 – T28N – R08W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

**BP Field Environmental Advisor** 

(505) 326-9479

If leave



