District 1

1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application
Type of action:  Below grade tank registration  Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method  Modification to an existing permit/or registration  Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request  Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: WPX Energy Production LLC
API Number:30-043-21161
2.
Below-grade tank: Subsection I of 19.15.17.11 NMAC  Volume:
4.  Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Alternate. Please specify As per BLM specifications

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other	
☐ Monthly inspections (If netting or screening is not physically feasible)	
7.  Signs: Subsection C of 19.15.17.11 NMAC  ☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  ☐ Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
5. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptant are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  -   NM Office of the State Engineer - iWATERS database search;   USGS;   Data obtained from nearby wells	☐ Yes ☒ No ☐ NA
<u>Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.</u> NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. ( <b>Does not apply to below grade tanks</b> )  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☑ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☑ No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ⊠ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☒ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☑ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☑ No
Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ⊠ No
Within 100 feet of a wetland.	

- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes 🛛 No		
Temporary Pit Non-low chloride drilling fluid			
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No		
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Permanent Pit or Multi-Well Fluid Management Pit			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).			
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No		
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of			
initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC			
Previously Approved Design (attach copy of design) API Number: or Permit Number:			
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.10 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
Previously Approved Design (attach copy of design) API Number: or Permit Number:			
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.  Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Climatological Factors Assessment  Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC	uments are		
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC			

Lane Specifications and Computability Assessment - based upon the approprial exequirements of 19.15.17.11 NMAC   Outside Control Quality Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC   Proceed of Description of the Overland Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Proceeding the Control Plan - Based upon the appropriate requirements of 19.15.17.11 NMAC   Proceeding the Control Plan   Process of Contr		
Operating and Maintonance Plan - hosed upon the appropriate requirements of 19.15.17.12 NMAC   Percentage of Maintonance of Hazandous Oftens, including Has, Prevention Plan   Eurogeney Response Unit   Percentage of Hazandous Oftens, including Has, Prevention Plan   Eurogeney Response Unit   Percentage of Hazandous Oftens, including Has, Prevention Plan   Eurogeney Response Unit   Percentage of Hazandous Oftens, including Has, Prevention Plan   Eurogeney Cartain   Percentage of Hazandous Oftens (Percentage Oftens of Hazandous Oftens of Hazandous Oftens (Percentage Oftens of Hazandous Oftens of Hazandous Oftens (Percentage Oftens of Hazandous Oftens (Percentage Oftens of Hazandous Oftens (Percentage Oftens of Hazandous Oftens of Hazandous Oftens (Percentage Oftens of Hazandous Oftens (Percentage Oftens of Hazandous Oftens of Hazandous Oftens (Percentage Oftens of Hazandous Oftens of Hazandous Oftens of Hazandous Oftens (Percentage Oftens of Hazandous Oftens (Percentage Oftens of Hazandous Oftens of Hazandous Oftens of Hazandous Oftens of Hazandous Oftens (Percentage Oftens of Hazandous Oftens	Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC	
Precloserd and Overcopting Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Nationates of Plan   Characteristics (including 11,5, Prevention Plan   Prevention   P		
Nationace or Plazandous Olders, including HS, Peveration Plan	Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Grisfold Wasts Stream Characterization   Monitoring and Inspection   Plan   Boston Control Plan   Colsure Plan - Insect appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan	
Monitoring and inspection Plan   Person Corton Plan   Court of Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
Closure Plan		
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC     Proposed Closure: 91.51.71.13 NMAC     Internative Proposed Closure Plan.		
Proposed Cleasure: 19.15.17.13 NMAC   Instructions: Please complete the applicable baxes, Baxes 14 through 18, in regards to the proposed closure plan.		
Proposed Cleasure:   91,157,13 NMAC   Instructions: Place complete the applicable baxes, Boxes 14 through 18, in regards to the proposed closure plan.		
Instructions: Please complete the applicable baxes, Boxes 14 through 18, to regards to the proposed closure plan.   Type:   Drilling   Worknown   Emergency   Cavitation   P&A   Permanent Pit   Below-grade Tank   Multi-well Fluid Management Pit   Alternative   Maste Emonotal (Closard-loop systems only)   Waste Emonotal (Closard-loop systems)   Provent Closard (Closard-loop systems)   Provent Closard (Closard-loop systems)   Waste Emonotal (Closard-loo		
Alternative   Proposed Closure Method:   Waste Excavation and Removal   Closed-loop systems only   On-site Closure Method (Only for temporary pits and closed-loop systems)   In-place Burial   On-site Trench Burial   On-s		
Alternative   Proposed Closure Method:   Waste Excavation and Removal   Closed-loop systems only   On-site Closure Method (Only for temporary pits and closed-loop systems)   In-place Burial   On-site Trench Burial   On-s	Type: \(\sim \) Drilling \(\Gamma\) Workover \(\Gamma\) Emergency \(\Gamma\) Cavitation \(\Gamma\) P&A \(\Gamma\) Permanent Pit \(\Gamma\) Below-grade Tank \(\Gamma\) Multi-well F	luid Management Pit
Waste Removal (Closed-loop systems only)   Donite Closure Method (Only for temporary pits and closed-loop systems)   Donite Closure Method (Only for temporary pits and closed-loop systems)   Donite Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.   Proteotos and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC   Donite Plan Proteotos and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC   Donite Plan Proteotos   Donite Plan Private   Donite Plan Private   Donite Plan Private   Donite Plan Private   Donite   Donite Plan Private   Donite   Donit		rara management i k
So   Back   Excavation and Removal Closure Method   Only for temporary pits and closed-loop systems		•
	Waste Removal (Closed-loop systems only)	
Maste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the doture plan. Please influence, by a check mark in the box, that the documents are attached.   Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC     Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC     Sold Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC     Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC     Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC     Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC     Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC     Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC     Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC     Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC     String Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC     String Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC     String Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC     String Criteria (regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC     String Criteria (regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC     String Criteria (regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC     String Criteria (regard	On-site Closure Method (Only for temporary pits and closed-loop systems)	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Plants indicate, by a check nurk in the box, that the documents are attached.		
Maste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.   Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC   Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC   Solar Backfill and Cover Posing Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the bottom of the buried waste.   NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   NA   NM Office of the State Engineer - iWATERS database; Visual inspe		
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC   Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)   Sola Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Steep Leading Name and Permit Number (for liquids, drilling fluids and drill cuttings)   Sola Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Steep Leading Name and upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Six Recelamation Plan - based upon the upon series of Six Recelamation Plan - based upon the six Rec		attached to the
Confirmation Sampling Plan (if applicable)- based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC    Disposal Facility Name and Permit Number (for liquids, cfilling fluids and drill cuttings)   Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC   Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC   Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Piecase refer to 19.15.17.10 NMAC for guidalace.    Ground water is less than 25 feet below the bottom of the buried waste.   NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   Ground water is hetween 25-50 feet below the bottom of the buried waste.   NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   Ground water is more than 100 feet below the bottom of the buried waste.   NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   Yes   No   NA		
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)   Solf Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Site Reclamation Plan - based upon the appropriate requirements of Automation of Plan Plan Plan Intervilence in the Intervilence of Intervilence of Plan Plan Intervilence of Inte		
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC    Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC   Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC   Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance.    Ground water is less than 25 feet below the bottom of the buried waste.		
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC   Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance.    Ground water is less than 2.5 feet below the bottom of the buried waste.		
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC   Instructions: Each stifing criteria requires a demonstration of compilance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance.    Ground water is less than 25 feet below the bottom of the buried waste.		
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each stiling criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance.    Ground water is less than 25 feet below the bottom of the buried waste.	Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each stiling criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance.    Ground water is less than 25 feet below the bottom of the buried waste.	T 15	
Provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance.    Ground water is less than 25 feet below the bottom of the buried waste.		
Ground water is less than 25 feet below the bottom of the buried waste.  NM Office of the State Engineer - i WATERS database search; USGS; Data obtained from nearby wells  Oround water is between 25-50 feet below the bottom of the buried waste.  NM Office of the State Engineer - i WATERS database search; USGS; Data obtained from nearby wells  Oround water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - i WATERS database search; USGS; Data obtained from nearby wells  Oround water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - i WATERS database search; USGS; Data obtained from nearby wells  Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary) high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Within an unstable area.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resourc	Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable south	
Ground water is less than 25 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 25-50 feet below the bottom of the buried waste  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site, Aerial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map		Please refer to
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	19.15.17.10 NMAC for guidance.	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	Ground water is less than 25 feet below the bottom of the buried waste.	☐ Yes ☒ No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map    Yes   No   Yes   No		
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map    Yes   No   Yes   No	Ground water is between 25-50 feet below the bottom of the buried waste	☐ Yes ☒ No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Acrial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Acrial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	Ground water is more than 100 feet below the bottom of the buried waste.	N Ves D No
lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Within the area overlying a subsurface mine.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Within the area overlying a subsurface mine.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakehed, sinkhole, or playa	D Ves M No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Written confirmation or verification map; Topographic map; Visual inspection (certification) of the proposed site  We within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Witten confirmation or verification or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☑ No
at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
- NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		☐ Yes ☑ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  □ Yes □ No  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  □ Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  □ Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  □ Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.  □ Yes □ No  □ Yes □ No	Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☑ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☑ No
adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	
Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.  □ Yes □ No	- Written confirmation or verification from the municipality; Written approval obtained from the municipality	∐ Yes ∐ No
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.  □ Yes □ No		
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.  □ Yes□ No		Yes No
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.  □ Yes □ No	·	
Society; Topographic map  Within a 100-year floodplain.  Yes No		
Within a 100-year floodplain.		☐ Yes ☐ No
	Within a 100-year floodplain.  - FEMA map	Yes No

			•	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requiremer Construction/Design Plan of Burial Trench (if applicable) based upon to Construction/Design Plan of Temporary Pit (for in-place burial of a dryill Protocols and Procedures - based upon the appropriate requirements of Confirmation Sampling Plan (if applicable) - based upon the appropriate Waste Material Sampling Plan - based upon the appropriate requirement Disposal Facility Name and Permit Number (for liquids, drilling fluids a Soil Cover Design - based upon the appropriate requirements of Subsect Re-vegetation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate Plan - based upon the appropriate Plan - based upon the appropriate Plan - based	e requirements of 19.1 nts of Subsection E of the appropriate requireing pad) - based upon 19.15.17.13 NMAC e requirements of 19.1 ts of 19.15.17.13 NM and drill cuttings or intion H of 19.15.17.13 ction H of 19.15.17.13	15.17.10 NMAC 19.15.17.13 NMAC ements of Subsection K of 19.15.17.1 the appropriate requirements of 19.1 15.17.13 NMAC AC case on-site closure standards canno NMAC NMAC	II NMAC  5.17.11 NMAC	
Operator Application Certification:  I hereby certify that the information submitted with this application is true, according to the control of the control	curate and complete to	o the best of my knowledge and belie	ef.	
Name (Print): Mark Heil	Title:	Regulatory Specialist		
Signature:	Date:	6/24/14		
e-mail address: mark.heil@wpxenergy.com	Telephone:	505-333-1806		
18. OCD Approval: ☑ Permit Application (including closure pl n) ☐ Closure	e Plan (only) 🔲 O	CD Conditions (see attachment)		
OCD Representative Signature:		Approval Date: 7/2/	1204	
Title: Compliance Office	OCD Permit Nu	,		
19.  Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report.  The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date:				
The closure report is required to be submitted to the division within 60 days of	of the completion of t e closure activities ha	ve been completed.		
The closure report is required to be submitted to the division within 60 days of	of the completion of t e closure activities ha Closure Co	ve been completed. ompletion Date:	complete this	
The closure report is required to be submitted to the division within 60 days of section of the form until an approved closure plan has been obtained and the closure Method:  Waste Excavation and Removal On-Site Closure Method Alter	of the completion of the closure activities had Closure Commercative Closure Method items must be attack	ompletion Date:od	op systems only)	
The closure report is required to be submitted to the division within 60 days a section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the following mark in the box; that the documents are attached.    Proof of Closure Notice (surface owner and division)     Proof of Deed Notice (required for on-site closure for private land only)     Plot Plan (for on-site closures and temporary pits)     Confirmation Sampling Analytical Results (if applicable)     Waste Material Sampling Analytical Results (required for on-site closure     Disposal Facility Name and Permit Number     Soil Backfilling and Cover Installation     Re-vegetation Application Rates and Seeding Technique     Site Reclamation (Photo Documentation)     On-site Closure Location: Latitude     Lor	of the completion of the closure activities had Closure Commercative Closure Method items must be attack	ompletion Date:od	op systems only)	
The closure report is required to be submitted to the division within 60 days a section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the following mark in the box approved plan, please explain.  21.  Closure Report Attachment Checklist: Instructions: Each of the following mark in the box, that the documents are attached.  Proof of Closure Notice (surface owner and division)  Proof of Deed Notice (required for on-site closure for private land only)  Plot Plan (for on-site closures and temporary pits)  Confirmation Sampling Analytical Results (if applicable)  Waste Material Sampling Analytical Results (required for on-site closure)  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique  Site Reclamation (Photo Documentation)  On-site Closure Location: Latitude  Lor	cof the completion of the closure activities had Closure Compensative Closure Method in the compensative Closure Closu	ompletion Date:od   Waste Removal (Closed-located to the closure report. Please incomplete and complete to the best of my k	op systems only)  dicate, by a check	
The closure report is required to be submitted to the division within 60 days a section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the following mark in the Example of the following mark in the box, that the documents are attached.  Proof of Closure Notice (surface owner and division)  Proof of Deed Notice (required for on-site closure for private land only)  Plot Plan (for on-site closures and temporary pits)  Confirmation Sampling Analytical Results (if applicable)  Waste Material Sampling Analytical Results (required for on-site closure)  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique  Site Reclamation (Photo Documentation)  On-site Closure Location: Latitude  Lor	cof the completion of the closure activities had Closure Completed	ompletion Date:od   Waste Removal (Closed-located to the closure report. Please incomplete and complete to the best of my k	op systems only)  dicate, by a check  1983  nowledge and plan.	
The closure report is required to be submitted to the division within 60 days a section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the form until an approved closure plan has been obtained and the section of the form until an approved closure Method      Alte	cof the completion of the closure activities had Closure Completed	not waste Removal (Closed-located by Maste Removal (Closed-located	op systems only)  dicate, by a check  1983  nowledge and olan.	

## WPX Energy Production, LLC San Juan Basin: New Mexico Assets

WPX Energy would like to modify the current temporary pit permit to reflect the changes to the location and size of the pit. The pit size as permitted is 50'x 70' and 15' deep and changed to 150' x 50' and 15' deep. The pit's center location changed from 36.13457 N and 107.46654W to a 36.13524N and 107.46621W.

