Form 3160- 5		D STATES		FORM APPROVED OMB No. 1004-0137
(March 2012)		or manathered	الحالية المريا فتتنافأ	Expires: October 31, 2014
		ND MANAGEMENT		Jicarilla Contract 110
	SUNDRY NOTICES AN	ND REPORTS ON WEL	LS	6. If Indian, Allottee, or Tribe Name
а	Do not use this form for pro	posals to drill or to re-ente	ran"	Jicarilla Apache
				Jitaima Apathe
SUBMI	SUNDRY NOTICES AN Do not use this form for pro abandoned well. Use Form 3 T IN TRIPLICATE - Other X Gas Well	Instructions on page	· · ·	7. If Unit or CA/Agreement Name and/or No.
1. Type of Well			Ne	1
Oil Well	X Gas Well	· Other	·DIV	8. Well Name and No. Jicarilla A #1M
2. Name of Operator			0, 57	9. API Well No.
EnerVest Operating, L.L.C.		· · · · ·	201, 3	30-039-31172
3a. Address 1001 Fannin Street, Suite 80	0 Houston TX 77002	3b. Phone No. (inc 713-659-3500	lude areâ code)	10. Field and Pool, or Exploratory Area Blanco Mesaverde/Basin Dakota
4. Location of Well (Footage; Sec.,	0 110uston, 12x 77002	[715-057-5500	· · · · · · · · · · · · · · · · · · ·	11. County or Parish, State
1807' FSL & 2527' FWL (U				Rio Arriba, NM
12. CHECK THE APPI	ROPRIATE BOX(ES) TO IN	DICATE NATURE OF NO	TICE, REPORT, OR	OTHER DATA
TYPE OF SUBMISSION	<u> </u>	· · · · · · · · · · · · · · · · · · ·	TYPE OF ACTION	
Notice of Intent	Acidize	Deepen	Production (Start/ Resume) Water Shut-Off
	Alter Casing	. Fracture Treat	Reclamation	Well Integrity
X Subsequent Report	Casing Repair	New Construction	Recomplete	X Other
	Change Plans	Plug and Abandon	Temporarily	Abandon Drilling Operations
Final Abandonment Notice	Convert to Injectio	·	Water Dispo	
3. Describe Proposed or Completed	• 🛄		· · ·	
Attach the Bond under which the following completion of the invol	work will be performed or provid lved operations. If the operation r	give subsurface locations and m de the Bond No. on file with the esults in a multiple completion of	easured and true vertica BLM/BIA. Required su or recompletion in a new	I depths or pertinent markers and zones. ubsequent reports must be filed within 30 days w interval, a Form 3160-4 must be filed once
Attach the Bond under which the following completion of the invo testing has been completed. Final determined that the site is ready f 5/14-20/2014: Drill and s tool at 4432' with mechan ppg, 2.01 cu ft/sk, 40 bbls cmt. Pumped 50 sks, typ 20 bbls good cmt to surfa	work will be performed or provid lyed operations. If the operation r l Abandonment Notice must be fil for final inspection.) survey from 509' to TD of nical DV tool at 2532'. C s good cmt back to surfac be III cmt w/additives, 1.3 acce. Mxd and pumped 34 ppg, 1.39 cu ft/sk yld, SD.	give subsurface locations and m de the Bond No. on file with the esults in a multiple completion of led only after all requirements, in <u>f 7615'</u> . Run 180 jts <u>4-1</u> / Cemented first stage w/50 g. Followed w/277 sks p 9 cu ft/sk yld & 14.6 ppg 4 sks prem lite w/additin , drop plug, bumped plu	easured and true vertica BLM/BIA. Required st or recompletion in a new netuding reclamantion, <u>2" N-80 L</u> T&C c: 06 sks premium li orem lite w/additiv g density tail cmt. ves, mxd at 12.1 p	I depths or pertinent markers and zones. Josequent reports must be filed within 30 days winterval, a Form 3160-4 must be filed once have been completed, and the operator has sg, set at 7615'. FC @ 7571, Hydraulic DV te high strength w/additives, mixed at 12.5 yes mixed at 12.1 ppg, 2.13 cu ft/sk yield lea Open stage tool @ 500 psi, shut down, circ
Attach the Bond under which the following completion of the invo testing has been completed. Final determined that the site is ready f 5/14-20/2014: Drill and s tool at 4432' with mechan ppg, 2.01 cu ft/sk, 40 bbls cmt. Pumped 50 sks, typ 20 bbls good cmt to surfa type III cmt mxd at 14.6 p	work will be performed or provid lyed operations. If the operation r l Abandonment Notice must be fil for final inspection.) survey from 509' to TD of nical DV tool at 2532'. C s good cmt back to surfac be III cmt w/additives, 1.3 acce. Mxd and pumped 34 ppg, 1.39 cu ft/sk yld, SD.	give subsurface locations and m de the Bond No. on file with the esults in a multiple completion of led only after all requirements, in <u>f 7615'</u> . Run 180 jts <u>4-1</u> / Cemented first stage w/50 g. Followed w/277 sks p 9 cu ft/sk yld & 14.6 ppg 4 sks prem lite w/additin , drop plug, bumped plu	easured and true vertica BLM/BIA. Required st or recompletion in a new netuding reclamantion, <u>2" N-80 L</u> T&C c: 06 sks premium li orem lite w/additiv g density tail cmt. ves, mxd at 12.1 p	I depths or pertinent markers and zones. Josequent reports must be filed within 30 days winterval, a Form 3160-4 must be filed once have been completed, and the operator has sg, set at 7615'. FC @ 7571, Hydraulic DV te high strength w/additives, mixed at 12.5 ves mixed at 12.1 ppg, 2.13 cu ft/sk yield lea Open stage tool @ 500 psi, shut down, circ pg, 2.13 cu ft/sk yld for lead & tail w/50 sks
Attach the Bond under which the following completion of the invo testing has been completed. Final determined that the site is ready f 5/14-20/2014: Drill and s tool at 4432' with mechan ppg, 2.01 cu ft/sk, 40 bbls cmt. Pumped 50 sks, typ 20 bbls good cmt to surfa type III cmt mxd at 14.6 p Baker Hughes. <u>RD</u> and	work will be performed or provid lyed operations. If the operation r l Abandonment Notice must be fil for final inspection.) survey from 509' to TD of nical DV tool at 2532'. C s good cmt back to surfac be III cmt w/additives, 1.3 acce. Mxd and pumped 34 ppg, 1.39 cu ft/sk yld, SD l relsd rig at 06:00 5/20/14	give subsurface locations and m de the Bond No. on file with the esults in a multiple completion of led only after all requirements, in <u>f 7615'</u> . Run 180 jts <u>4-1</u> / Cemented first stage w/50 g. Followed w/277 sks p 9 cu ft/sk yld & 14.6 ppg 4 sks prem lite w/additin , drop plug, bumped plu	easured and true vertica BLM/BIA. Required st or recompletion in a new netuding reclamantion, <u>2" N-80 L</u> T&C c: 06 sks premium li orem lite w/additiv g density tail cmt. ves, mxd at 12.1 p	I depths or pertinent markers and zones. Josequent reports must be filed within 30 days winterval, a Form 3160-4 must be filed once have been completed, and the operator has sg, set at 7615'. FC @ 7571, Hydraulic DV te high strength w/additives, mixed at 12.5 ves mixed at 12.1 ppg, 2.13 cu ft/sk yield lea Open stage tool @ 500 psi, shut down, circ pg, 2.13 cu ft/sk yld for lead & tail w/50 sks
Attach the Bond under which the following completion of the invo testing has been completed. Final determined that the site is ready f 5/14-20/2014: Drill and s tool at 4432' with mechan ppg, 2.01 cu ft/sk, 40 bbls cmt. Pumped 50 sks, typ 20 bbls good cmt to surfa type III cmt mxd at 14.6 p Baker Hughes. <u>RD</u> and	work will be performed or provid lved operations. If the operation r l Abandonment Notice must be fil or final inspection.) survey from 509' to TD or nical DV tool at 2532'. C s good cmt back to surfac be III cmt w/additives, 1.3 ace. Mxd and pumped 34 opg, 1.39 cu ft/sk yld, SD l relsd rig at 06:00 5/20/14 ACCEF	give subsurface locations and m de the Bond No. on file with the results in a multiple completion of led only after all requirements, in <u>f 7615'</u> . Run 180 jts <u>4-1</u> , Cemented first stage w/5 ⁶ g. Followed w/277 sks p 9 cu ft/sk yld & 14.6 ppg 44 sks prem lite w/additiv , drop plug, bumped plu 4. PTED FOR RECORD UN 1 6 2014	easured and true vertica BLM/BIA. Required su or recompletion in a new neluding reclamantion, 2" N-80 LT&C c 06 sks premium li orem lite w/additiv g density tail cmt. ves, mxd at 12.1 p g at 3110 psi, <u>circ</u>	I depths or pertinent markers and zones. Josequent reports must be filed within 30 days winterval, a Form 3160-4 must be filed once have been completed, and the operator has sg, set at 7615'. FC @ 7571, Hydraulic DV te high strength w/additives, mixed at 12.5 ves mixed at 12.1 ppg, 2.13 cu ft/sk yield lea Open stage tool @ 500 psi, shut down, circ pg, 2.13 cu ft/sk yld for lead & tail w/50 sks
Attach the Bond under which the following completion of the invo testing has been completed. Final determined that the site is ready f 5/14-20/2014: Drill and s tool at 4432' with mechan ppg, 2.01 cu ft/sk, 40 bbls cmt. Pumped 50 sks, typ 20 bbls good cmt to surfa type III cmt mxd at 14.6 p Baker Hughes. <u>RD</u> and	work will be performed or provid lved operations. If the operation r l Abandonment Notice must be fil or final inspection.) survey from 509' to TD or nical DV tool at 2532'. C s good cmt back to surfac be III cmt w/additives, 1.3 ace. Mxd and pumped 34 opg, 1.39 cu ft/sk yld, SD l relsd rig at 06:00 5/20/14 ACCEF	give subsurface locations and m de the Bond No. on file with the esults in a multiple completion of led only after all requirements, in <u>f 7615'</u> . Run 180 jts <u>4-1</u> , Cemented first stage w/5 g. Followed w/277 sks p 9 cu ft/sk yld & 14.6 ppg 9 cu ft/sk yld & 14.6 ppg 4 sks prem lite w/additiv , drop plug, bumped plu 4.	easured and true vertica BLM/BIA. Required su or recompletion in a new neluding reclamantion, 2" N-80 LT&C c 06 sks premium li orem lite w/additiv g density tail cmt. ves, mxd at 12.1 p g at 3110 psi, <u>circ</u>	I depths or pertinent markers and zones. Josequent reports must be filed within 30 days winterval, a Form 3160-4 must be filed once have been completed, and the operator has sg, set at 7615'. FC @ 7571, Hydraulic DV te high strength w/additives, mixed at 12.5 ves mixed at 12.1 ppg, 2.13 cu ft/sk yield lea Open stage tool @ 500 psi, shut down, circ pg, 2.13 cu ft/sk yld for lead & tail w/50 sks
Attach the Bond under which the following completion of the invo testing has been completed. Final determined that the site is ready f 5/14-20/2014: Drill and s tool at 4432' with mechan ppg, 2.01 cu ft/sk, 40 bbls cmt. Pumped 50 sks, typ 20 bbls good cmt to surfa type III cmt mxd at 14.6 µ Baker Hughes. <u>RD</u> and WO completion.	work will be performed or provid lved operations. If the operation r l Abandonment Notice must be fil for final inspection.) survey from 509' to TD of nical DV tool at 2532'. C s good cmt back to surfac be III cmt w/additives, 1.3 ince. Mxd and pumped 34 opg, 1.39 cu ft/sk yld, SD l relsd rig at 06:00 5/20/14 ACCEF	give subsurface locations and m de the Bond No. on file with the results in a multiple completion of led only after all requirements, in <u>f 7615'</u> . Run 180 jt <u>s</u> 4-1 <i>1</i> . Cemented first stage w/50 ge. Followed w/277 sks p 9 cu ft/sk yld & 14.6 ppg 4 sks prem lite w/additiv , drop plug, bumped plu 4. PTED FOR RECORD UN 1 6 ZU14 NGTON FIELD OFFICE Net State of State of State of State of State NGTON FIELD OFFICE	easured and true vertica BLM/BIA. Required su or recompletion in a new neluding reclamantion, 2" N-80 LT&C c 06 sks premium li orem lite w/additiv g density tail cmt. ves, mxd at 12.1 p g at 3110 psi, <u>circ</u>	I depths or pertinent markers and zones. Josequent reports must be filed within 30 days winterval, a Form 3160-4 must be filed once have been completed, and the operator has sg, set at 7615'. FC @ 7571, Hydraulic DV te high strength w/additives, mixed at 12.5 ves mixed at 12.1 ppg, 2.13 cu ft/sk yield lea Open stage tool @ 500 psi, shut down, circo pg, 2.13 cu ft/sk yld for lead & tail w/50 sks culated 20 bbls good cmt to surface. RD
Attach the Bond under which the following completion of the invo testing has been completed. Final determined that the site is ready f 5/14-20/2014: Drill and s tool at 4432' with mechan ppg, 2.01 cu ft/sk, 40 bbls cmt. Pumped 50 sks, typ 20 bbls good cmt to surfa type III cmt mxd at 14.6 p Baker Hughes. <u>RD</u> and WO completion.	work will be performed or provid lved operations. If the operation r l Abandonment Notice must be fil for final inspection.) survey from 509' to TD of nical DV tool at 2532'. C s good cmt back to surfac be III cmt w/additives, 1.3 ince. Mxd and pumped 34 opg, 1.39 cu ft/sk yld, SD l relsd rig at 06:00 5/20/14 ACCEF	give subsurface locations and m de the Bond No. on file with the results in a multiple completion of led only after all requirements, in <u>f 7615'</u> . Run 180 jt <u>s</u> 4-1 <i>1</i> . Cemented first stage w/50 ge. Followed w/277 sks p 9 cu ft/sk yld & 14.6 ppg 4 sks prem lite w/additiv , drop plug, bumped plu 4. PTED FOR RECORD UN 1 6 ZU14 NGTON FIELD OFFICE Net State of State of State of State of State NGTON FIELD OFFICE	easured and true vertica BLM/BIA. Required su or recompletion in a new neluding reclamantion, 2" N-80 LT&C c 06 sks premium li orem lite w/additiv g density tail cmt. ves, mxd at 12.1 p g at 3110 psi, <u>circ</u>	I depths or pertinent markers and zones. Josequent reports must be filed within 30 days winterval, a Form 3160-4 must be filed once have been completed, and the operator has sg, set at 7615'. FC @ 7571, Hydraulic DV te high strength w/additives, mixed at 12.5 ves mixed at 12.1 ppg, 2.13 cu ft/sk yield lea Open stage tool @ 500 psi, shut down, circ pg, 2.13 cu ft/sk yld for lead & tail w/50 sks
Attach the Bond under which the following completion of the invo testing has been completed. Final determined that the site is ready f 5/14-20/2014: Drill and s tool at 4432' with mechan ppg, 2.01 cu ft/sk, 40 bbls cmt. Pumped 50 sks, typ 20 bbls good cmt to surfa type III cmt mxd at 14.6 p Baker Hughes. <u>RD</u> and WO completion.	work will be performed or provid lved operations. If the operation r Abandonment Notice must be fil for final inspection.) survey from 509' to TD of nical DV tool at 2532'. C is good cmt back to surface be III cmt w/additives, 1.3 ace. Mxd and pumped 34 opg, 1.39 cu ft/sk yld, SD relsd rig at 06:00 5/20/14 ACCEF JI FARMIN BY:	give subsurface locations and m de the Bond No. on file with the results in a multiple completion of led only after all requirements, in <u>f 7615'</u> . Run 180 jts <u>4-1</u> , Cemented first stage w/5' g. Followed w/277 sks p 9 cu ft/sk yld & 14.6 ppg 94 sks prem lite w/additiv , drop plug, bumped plu 4. PTED FOR RECORD UN 1 6 ZU14 NGTON FIELD OFFICE William Taimbeka	easured and true vertica BLM/BIA. Required su or recompletion in a new neluding reclamantion, 2" N-80 LT&C c: 06 sks premium li orem lite w/additiv g density tail cmt. ves, mxd at 12.1 p g at 3110 psi, <u>circ</u>	A depths or pertinent markers and zones. Josequent reports must be filed within 30 days winterval, a Form 3160-4 must be filed once have been completed, and the operator has sg, set at 7615'. FC @ 7571, Hydraulic DV te high strength w/additives, mixed at 12.5 wes mixed at 12.1 ppg, 2.13 cu ft/sk yield lea Open stage tool @ 500 psi, shut down, circo pg, 2.13 cu ft/sk yld for lead & tail w/50 sks culated 20 bbls good cmt to surface. RD Sr. Regulatory Analyst May 30, 2014
Attach the Bond under which the following completion of the invo testing has been completed. Final determined that the site is ready f 5/14-20/2014: Drill and s tool at 4432' with mechan ppg, 2.01 cu ft/sk, 40 bbls cmt. Pumped 50 sks, typ 20 bbls good cmt to surfa type III cmt mxd at 14.6 p Baker Hughes. <u>RD</u> and WO completion.	work will be performed or provid lved operations. If the operation r Abandonment Notice must be fil for final inspection.) survey from 509' to TD of nical DV tool at 2532'. C is good cmt back to surface be III cmt w/additives, 1.3 ace. Mxd and pumped 34 opg, 1.39 cu ft/sk yld, SD relsd rig at 06:00 5/20/14 ACCEF JI FARMIN BY:	give subsurface locations and m de the Bond No. on file with the results in a multiple completion of led only after all requirements, in <u>f 7615'</u> . Run 180 jts <u>4-1</u> , Cemented first stage w/5' g. Followed w/277 sks p 9 cu ft/sk yld & 14.6 ppg 44 sks prem lite w/additiv , drop plug, bumped plu 4. PTED FOR RECORD UN 1 6 ZU14 NGTON FJELD OFFICE WILLIAM Tambeks a) Title Date <u>CE FOR FEDERAL OR S</u>	easured and true vertica BLM/BIA. Required su or recompletion in a new neluding reclamantion, 2" N-80 LT&C c: 06 sks premium li orem lite w/additiv g density tail cmt. ves, mxd at 12.1 p g at 3110 psi, <u>circ</u>	A depths or pertinent markers and zones. Josequent reports must be filed within 30 days winterval, a Form 3160-4 must be filed once have been completed, and the operator has sg, set at 7615'. FC @ 7571, Hydraulic DV te high strength w/additives, mixed at 12.5 wes mixed at 12.1 ppg, 2.13 cu ft/sk yield lea Open stage tool @ 500 psi, shut down, circo pg, 2.13 cu ft/sk yld for lead & tail w/50 sks culated 20 bbls good cmt to surface. RD Sr. Regulatory Analyst May 30, 2014
Attach the Bond under which the following completion of the invo testing has been completed. Final determined that the site is ready f 5/14-20/2014: Drill and s tool at 4432' with mechan ppg, 2.01 cu ft/sk, 40 bbls cmt. Pumped 50 sks, typ 20 bbls good cmt to surfa type III cmt mxd at 14.6 p Baker Hughes. <u>RD</u> and WO completion.	work will be performed or provid lved operations. If the operation r Abandonment Notice must be fil for final inspection.) survey from 509' to TD of nical DV tool at 2532'. C is good cmt back to surface the III cmt w/additives, 1.3 ace. Mxd and pumped 34 opg, 1.39 cu ft/sk yld, SD relsd rig at 06:00 5/20/14 ACCEF JU FARMIN BY:	give subsurface locations and m de the Bond No. on file with the results in a multiple completion of led only after all requirements, in <u>f 7615'</u> . Run 180 jts <u>4-1</u> , Cemented first stage w/50 ge. Followed w/277 sks p 99 cu ft/sk yld & 14.6 ppg 14 sks prem lite w/additin , drop plug, bumped plu 4. PTED FOR RECORD UN 1 6 ZU14 NGTON FIELD OFFICE MILLICIAN Tombe for CE FOR FEDERAL OR S rant or certify which would Office	easured and true vertica BLM/BIA. Required si por recompletion in a new neluding reclamantion, (2" N-80 LT&C cc 06 sks premium li prem lite w/additiv g density tail cmt. ves, mxd at 12.1 p g at 3110 psi, circ Mathematical contents (circ)	A depths or pertinent markers and zones. Josequent reports must be filed within 30 days winterval, a Form 3160-4 must be filed once have been completed, and the operator has sg, set at 7615'. FC @ 7571, Hydraulic DV te high strength w/additives, mixed at 12.5 yes mixed at 12.1 ppg, 2.13 cu ft/sk yield lea Open stage tool @ 500 psi, shut down, circ pg, 2.13 cu ft/sk yld for lead & tail w/50 sks culated 20 bbls good cmt to surface. RD Sr. Regulatory Analyst May 30, 2014 E Date