State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

986 <u>Pit, Below-Grade Tank, or</u>									
Proposed Alternative Method Permit or Closure Plan Application									
Type of action: Below grade tank registration									
Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method									
Modification to an existing permit/or registration									
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method									
LIS - Oleg 35 Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request									
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the									
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.									
Decrator: BP America Production CompanyOGRID #:778									
Address:200 Energy Court, Farmington, NM 87401									
Facility or well name:Gallegos Canyon Unit 194									
API Number:3004506935 OCD Permit Number:									
U/L or Qtr/Qtr									
Center of Proposed Design: Latitude36.60914 Longitude108.14122 NAD: []1927 [X] 1983									
Surface Owner: 🗌 Federal 🔲 State 🗌 Private 🖾 Tribal Trust or Indian Allotment									
2									
Pit: Subsection F, G or J of 19.15.17.11 NMAC									
Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes									
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other									
String-Reinforced									
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D									
³ ÔIL CONS. DIV DIST. 3									
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A									
Volume: 95.0bbl Type of fluid: Produced water JUL/ 0 1 2014									
Tank Construction material:Steel									
Secondary containment with leak detection 🔲 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off									
Usible sidewalls and liner Visible sidewalls only Other _Double walled/double bottomed side walls not visible									
Liner type: Thicknessmil									
4.									
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Burcau office for consideration of approval.									

22

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify_

5.

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other_

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	
<u>Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.</u> - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗋 Yes 🗌 No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	🗌 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map 	Yes No
<u>Below Grade Tanks</u>	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No								
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 									
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗋 Yes 🗌 No								
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 									
Temporary Pit Non-low chloride drilling fluid									
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).									
- Topographic map; Visual inspection (certification) of the proposed site	🔲 Yes 🗌 No								
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗋 Yes 🗋 No								
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No								
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No								
Permanent Pit or Multi-Well Fluid Management Pit									
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).									
- Topographic map; Visual inspection (certification) of the proposed site	🗋 Yes 🗌 No								
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No								
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of									
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No								
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No								
^{10.} <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc									
 attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 	NMAC								
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 	15.17.9 NMAC								
Previously Approved Design (attach copy of design) API Number: or Permit Number:									
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	cuments are								
 attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. 	15.17.9 NMAC								
and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC									
Previously Approved Design (attach copy of design) API Number: or Permit Number:									

12.	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. <u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
 ^{14.} <u>Waste Excavation and Removal Closure Plan Checklist</u>: (19.15.17.13 NMAC) <i>Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached.</i> Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	
15. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗋 Yes 🗋 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 								
written commutation of vermeation from the municipality, written approval obtained from the municipality	Yes 🗍 No							
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	Yes 🗌 No							
Within an unstable area.								
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No							
Within a 100-year floodplain. - FEMA map								
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure play a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canned Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC							
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef.							
Name (Print): Title:								
Signature: Date:	:							
e-mail address: Telephone:								
e-mail address:								
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:	VDDK							
 18. OCD Approval: Permit Application (including closure plan) (Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 7/22 Title: OCD Permit Number: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. 	the closure report. complete this							

Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name	(Print):	J
------	----------	---

Signature:

22.

eff Peace

asce

Title: Area Environmental Advisor_____

 Date: _	_June 30, 2014_

e-mail address:__peace.jeffrey@bp.com_____

Telephone: ___(505) 326-9479_____

.

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Gallegos Canyon Unit 194</u> <u>API No. 3004506935</u> <u>Unit Letter D, Section 5, T27N, R12W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. No notice was sent. The surface at this site is allotment land. BP requested a list of surface owners from FIMO so notices could be sent, but a response from FIMO was never received.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)
 All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.
- 4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

- BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.
 All equipment associated with the BGT has been removed.
- 6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil. The area over the BGT is covered by the LPT and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Frar	ncis Dr., Sant	a Fe, NM 8750	5			e, NM 875						
			Rel	ease Notifi				ctior				
						OPERA	ГOR		🔲 Initia	al Report	\boxtimes	Final Report
Name of Co	ompany: B	Р				Contact: Jef	f Peace			<u> </u>		
		Court, Farm		M 87401			No.: 505-326-94					
Facility Na	me: Galleg	os Canyon	Jnit 194			Facility Typ	be: Natural gas	well	·			
Surface Ow	ner: Triba	1		Mineral (Owner: '	Tribal			API No	. 30045069	935	
				LOCA	ATIO	N OF REI	LEASE					
Unit Letter D	Section 5	Township 27N	Range 12W	Feet from the 850	North/ North	South Line	Feet from the 920	East/V West	Vest Line	County: S	an Juan	
	J	Lat	itude3	6.60914		_Longitud	e108.14122_					
				NAT	URE	OF REL	EASE					
Type of Rele				•			Release: N/A			Recovered: N		
Source of Re	lease: belov	v grade tank -	- 95 bbl			Date and H N/A	lour of Occurrent	ce:	Date and	Hour of Dis	covery:	N/A
Was Immedi	ate Notice C				<u> </u>	If YES, To	Whom?					
		L	Yes _	No 🛛 Not R	equired						- <u>-</u>	
By Whom? Was a Water	December December	hod9				Date and I		the Wet				
was a water	course Read	ned?	Yes 🛛] No		IT YES, VC	olume Impacting	the wate	ercourse.			
If a Watercou	urse was Im	pacted, Desci	ibe Fully.'	k	<u> </u>							_ <u></u>
				n Taken.* Sampli					g removal 1	o ensure no	soil im	pacts from
the BGT. So	oil analysis r	esulted in TP	H, BTEX	and chlorides bel	ow stand	ards. Analys	is results are atta	ched.				
D	A CC+1		A ati a Tal	ten.* BGT was re			- down and the DC		anaulad T			
				active well area.	moved a	ind the area u	nderneath the BC	1 Was s	ampled. I	ne excavated	i area v	/as
,	F											
hereby certi	fy that the i	nformation g	iven above	is true and comp	lete to th	ne best of my	knowledge and u	Indersta	d that purs	uant to NM	OCD ru	les and
egulations al	ll operators	are required t	o report ar	nd/or file certain i	elease no	otifications a	nd perform correc	ctive act	ions for rele	eases which	may en	danger
				ce of a C-141 repo								
				investigate and r stance of a C-141								
		vs and/or reg						r				
		0					OIL CON	SERV	ATION	DIVISIC	<u>N</u>	
Signature:	loff,	Pool	•									
	200					Approved by	Environmental S	pecialis	:			
Printed Name	e: Jeff Peace	<u> </u>										·
l'itle: Area E	nvironment	al Advisor				Approval Dat	ie:		Expiration	Date:		
						Conditions	f Approval:					
-mail Addre	ess: peace.je	effrey@bp.co			—— '	Conditions of	п Арргомат:			Attached		
Date: June 3	30, 2014		Phone: 5	05-326-9479	1							

 Date:
 June 30, 2014
 Phc

 * Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENG P.O. BOX 87, BLG (505)	7413	API #:	_	
FIELD REPORT:	(circle one): BGT CONFIRMATION / RE	632-1199 ELEASE INVESTIGATION / OTHER	:	PAGE #:	
SITE INFORMATION QUAD/UNIT: D SEC: 5 TWP: 1/4 -1/4/FOOTAGE: 850'N / 920'W LEASE #: -	27N RNG: 12W PM:	NM CNTY: SJ S E FEDERAL / STATE / FEE	1	DATE STARTED: DATE FINISHED: ENVIRONMENTAL SPECIALIST(S):	
REFERENCE POINT	WELL HEAD (W.H.) GPS CO GPS COORD.: 36.6 GPS COORD.:	DORD.: <u>36.60915 X</u> 0914 X 108.14122	108.14093 DISTANCE/BEAR DISTANCE/BEAR DISTANCE/BEAR	RING FROM W.H.:7 RING FROM W.H.: RING FROM W.H.:	78.5', S83.5W
SAMPLING DATA: 1) SAMPLE ID: 2) SAMPLE ID: 3) SAMPLE ID: 4) SAMPLE ID:	SAMPLE DATE: 04/18/14 SAMPLE DATE:	SAMPLE TIME: LAB AN SAMPLE TIME: LAB AN SAMPLE TIME: LAB AN LAB AN	IALYSIS:		• • •
SOIL DESCRIPTION SOIL COLOR: GRAYIS COHESION (ALL OTHERS): NON COHESIVE) SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): [LO MOISTURE: DRY SLIGHTLY MOIST / WE SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED: YES [N SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVED EQUIPMENT SET OVER RECLAIMED AREA: N OTHER: SITE'S SURFACE EQUIPMENT E	Image: Contestive / Contestive / Highly contestive / December / December / December / Contestive / December / Contestive / December / Contestive / December	ASTICITY (CLAYS): NON PLASTIC / SLIG NSITY (COHESIVE CLAYS & SILTS) ODOR DETECTED: YES NO EXPLA Y AREAS DISPLAYING WETNESS: YE S NO EXPLANATION - TION:	GHTLY PLASTIC / CC): SOFT / FIRM / S ANATION -	STIFF / VERY STIFF / H	IARD
SITE SKETCH	BGT Located : off fon site	NEAREST SURFACE WATER:	000' NMOCI attached 0VM (↑ 0VM (IMATION (Cubic Yard D TPH CLOSURE STD: CALIB. READ, = CALIB. GAS = NA	100 ppm ppm <u>RF = 1.00</u> ppm
SEPARATO PBGTL T.B. ~ 5' B.G. STEEL COMTAINMENT	BERM	₩.⊓. ⊕ GALLEGOS WASH		MISCELL. O: D#: C: ZDCS01(J#: X5-COSM ermit date(s): CD Appr. date(s): NM = Organic	GEN1 WR-C 06/10/10 06/03/13 Vapor Meter million
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELC	W-GRADE TANK LOCATION; SPD = SAMPLE POINT WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM;	/; T.H. = TEST HOLE; ~ = APPROX.; W.H. = \ DESIGNATION; R.W. = RETAINING WALL;	S.P.D. MELL HEAD; NA- NOT	BGT Sidewalls Visib BGT Sidewalls Visib agnetic declinatic	ole: Y / N ole: Y / N

Hall Environmental Analys	is Labora	itory, Ii	ic.			Analytical Report Lab Order 1404929 Date Reported: 4/30/20	14
CLIENT: Blagg Engineering Project: GCU #194				Collection I	Date: 4/1	C-TB@5'(95) 8/2014 11:45:00 AM	
Lab ID: 1404929-001 Analyses	Matrix: Result		Qual	Units		22/2014 10:00:00 AM Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE	ORGANICS					Analyst	BCN
Diesel Range Organics (DRO)	ND	9.9		mg/Kg	1	4/24/2014 3:51:44 PM	12796
Surr: DNOP	102	57.9-140		%REC	1	4/24/2014 3:51:44 PM	12796
EPA METHOD 8015D: GASOLINE RAN	IGE					Analyst	NSB
Gasoline Range Organics (GRO)	ND	4.7		mg/Kg	1	4/24/2014 3:56:39 PM	12823
Surr: BFB	83.7	74.5-129		%REC	1	4/24/2014 3:56:39 PM	12823
EPA METHOD 8021B: VOLATILES						Analyst	NSB
Benzene	ND	0.047		mg/Kg	1	4/24/2014 3:56:39 PM	12823
Toluene	ND	0.047		mg/Kg	1	4/24/2014 3:56:39 PM	12823
Ethylbenzene	ND	0.047		mg/Kg	1	4/24/2014 3:56:39 PM	12823
Xylenes, Total	ND	0.095		mg/Kg	1	4/24/2014 3:56:39 PM	12823
Surr: 4-Bromofluorobenzene	97.2	80-120		%REC	1	4/24/2014 3:56:39 PM	12823
EPA METHOD 300.0: ANIONS						Analyst	JRR
Chloride	ND	30		mg/Kg	20	4/23/2014 3:03:36 PM	12841
EPA METHOD 418.1: TPH						Analyst	JME
Petroleum Hydrocarbons, TR	ND	20		mg/Kg	1	4/25/2014 12:00:00 PM	12824

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Metho	od Blank		
Qualifiers:		Varue exceeds Maximum Containmant Level.	D	<u>,</u>			
	Е	Value above quantitation range	Н	Holding times for preparation or analysis exceeded			
	J	Analyte detected below quantitation limits	ND	Not Detected at the Reporting Limit	Page 1 of 6		
	0	RSD is greater than RSDlimit	Р	Sample pH greater than 2.			
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit			
	S	Spike Recovery outside accepted recovery limits					

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

Client:Blagg EngineeringProject:GCU #194

Sample ID LCS-12841	SampT	ype: LC	s	Tes	tCode: El	PA Method	300.0: Anion	s		
Client ID: LCSS	Batch	n ID: 12	2841 RunNo: 18179							
Prep Date: 4/23/2014	Analysis D	Analysis Date: 4/23/2014 SeqNo: 52476				24769	Units: mg/M	٢g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Chloride	14	1.5	15.00	0	91.1	90	110			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - P Sample pH greater than 2.
 - RL Reporting Detection Limit

Page 2 of 6

1404929 *30-Apr-14*

WO#:

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

Client:	Blagg Engineering
Project:	GCU #194

Sample ID MB-12824	SampType: MBLK	TestCode: EPA Method	418.1: TPH		
Client ID: PBS	Batch ID: 12824	RunNo: 18209			
Prep Date: 4/22/2014	Analysis Date: 4/25/2014	SeqNo: 525508	Units: mg/Kg		
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual
Petroleum Hydrocarbons, TR	ND 20				
Sample ID LCS-12824	SampType: LCS	TestCode: EPA Method	418.1: TPH		
Client ID: LCSS	Batch ID: 12824	RunNo: 18209			
Prep Date: 4/22/2014	Analysis Date: 4/25/2014	SeqNo: 525509	Units: mg/Kg		
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual
Petroleum Hydrocarbons, TR	87 20 100.0	0 87.3 80	120		
Sample ID LCSD-12824	SampType: LCSD	TestCode: EPA Method	418.1: TPH		
Client ID: LCSS02	Batch ID: 12824	RunNo: 18209			
Prep Date: 4/22/2014	Analysis Date: 4/25/2014	SeqNo: 525510	Units: mg/Kg		
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual
Petroleum Hydrocarbons, TR	89 20 100.0	0 88.7 80	120 1.52	20	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - P Sample pH greater than 2.
 - RL Reporting Detection Limit

Page 3 of 6

1404929

WO#:

30-Apr-14

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.
--

Client:	Blagg Engineering
Project:	GCU #194

Sample ID	MB-12796	SampTy	/pe: ME	BLK	Tes	tCode: El	PA Method	8015D: Dies	el Range (Drganics	
Client ID:	PBS	Batch	ID: 12	796	R	RunNo: 1	8181				
Prep Date:	4/22/2014	Analysis Da	ate: 4/	24/2014	S	SeqNo: 5	24863	Units: mg/ł	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
•	Organics (DRO)	ND	10								
Surr: DNOP		9.6		10.00		96.1	57.9	140			
Sample ID	LCS-12796	Test	tCode: El	PA Method	8015D: Dies	el Range (Drganics				
Client ID:	LCSS	Batch	ID: 12	796	R	RunNo: 1	8181				
Prep Date:	4/22/2014	Analysis Da	ate: 4/	24/2014	S	SeqNo: 5	24864	Units: mg/k	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Organics (DRO)	47	10	50.00	_0	93.1	60.8	145			
Our DNIOD		47		5.000		02.0	E7 0	4.40			
Surr: DNOP		4.7		5.000		93.9	57.9	140			
	1404916-001AMS	4.7 SampTy	/pe: MS		Test			8015D: Dies	el Range (Drganics	
Sample ID	1404916-001AMS BatchQC	SampTy	pe: MS	 5			PA Method		el Range (Drganics	
Sample ID Client ID:		SampTy	iD: 12	 3 796	R	Code: EF	PA Method 3181		-	Organics	<u></u>
Sample ID Client ID:	BatchQC	SampTy Batch	iD: 12	5 796 24/2014	R	Code: EF IunNo: 18 SeqNo: 52	PA Method 3181	8015D: Dies	-	Organics RPDLimit	Qual
Sample ID Client ID: Prep Date: Analyte	BatchQC	SampTy Batch Analysis Da	ID: 12 ate: 4/	5 796 24/2014	R	Code: EF RunNo: 18 SeqNo: 52	PA Method 3181 24870	8015D: Dies Units: mg/k	(g	-,	Qual
Sample ID Client ID: Prep Date: Analyte	BatchQC 4/22/2014	SampTy Batch Analysis Da Result	ID: 12 ate: 4 / PQL	5 796 24/2014 SPK value	R S SPK Ref Val	Code: EF RunNo: 18 SeqNo: 53 %REC	PA Method 3181 24870 LowLimit	8015D: Dies Units: mg/H HighLimit	(g	-,	Qual
Sample ID Client ID: Prep Date: Analyte Diesel Range (Surr: DNOP	BatchQC 4/22/2014	SampTy Batch Analysis Da Result 51 5.1	ID: 12 ate: 4 / PQL 9.9	5 796 24/2014 SPK value 49.31 4.931	R S SPK Ref Val 0	Code: EF SunNo: 18 SeqNo: 52 %REC 104 103	PA Method 3181 24870 LowLimit 47.4 57.9	8015D: Diese Units: mg/F HighLimit 148	(g %RPD	RPDLimit	Qual
Sample ID Client ID: Prep Date: Analyte Diesel Range (Surr: DNOP Sample ID	BatchQC 4/22/2014 Drganics (DRO)	SampTy Batch Analysis Da Result 51 5.1 SampTy	ID: 12 ate: 4 / PQL 9.9	5 796 24/2014 SPK value 49.31 4.931 SD	R S SPK Ref Val 0 Test	Code: EF SunNo: 18 SeqNo: 52 %REC 104 103	PA Method 3181 24870 LowLimit 47.4 57.9 PA Method	8015D: Dies Units: mg/F HighLimit 148 140	(g %RPD	RPDLimit	Qual
Sample ID Client ID: Prep Date: Analyte Diesel Range G Surr: DNOP Sample ID Client ID:	BatchQC 4/22/2014 Drganics (DRO) 1404916-001AMSE	SampTy Batch Analysis Da Result 51 5.1 SampTy	ID: 12 ate: 4/ PQL 9.9 pe: MS ID: 12	5 796 24/2014 SPK value 49.31 4.931 5D 796	R S SPK Ref Val 0 Test R	Code: EF RunNo: 18 BeqNo: 52 %REC 104 103 Code: EF	PA Method 3181 24870 LowLimit 47.4 57.9 PA Method 3181	8015D: Dies Units: mg/F HighLimit 148 140	(g %RPD el Range (RPDLimit	Qual
Sample ID Client ID: Prep Date: Analyte Diesel Range G Surr: DNOP Sample ID Client ID:	BatchQC 4/22/2014 Drganics (DRO) 1404916-001AMSE BatchQC	SampTy Batch Analysis Da Result 51 5.1 SampTy Batch	ID: 12 ate: 4/ PQL 9.9 pe: MS ID: 12	5 796 24/2014 SPK value 49.31 4.931 5D 796 24/2014	R S SPK Ref Val 0 Test R	Code: EF SunNo: 18 SeqNo: 52 %REC 104 103 Code: EF SunNo: 18 SeqNo: 52	PA Method 3181 24870 LowLimit 47.4 57.9 PA Method 3181	8015D: Diese Units: mg/F HighLimit 148 140 8015D: Diese	(g %RPD el Range ((g	RPDLimit	Qual
Sample ID Client ID: Prep Date: Analyte Diesel Range (Surr: DNOP Sample ID Client ID: Prep Date: Analyte	BatchQC 4/22/2014 Drganics (DRO) 1404916-001AMSE BatchQC	SampTy Batch Analysis Da Result 51 5.1 SampTy Batch Analysis Da	ID: 12: ate: 4/ PQL 9.9 Ppe: MS ID: 12: ate: 4/	5 796 24/2014 SPK value 49.31 4.931 5D 796 24/2014	R S SPK Ref Val 0 Test R S	Code: EF SunNo: 18 SeqNo: 52 %REC 104 103 Code: EF SunNo: 18 SeqNo: 52	PA Method 3181 24870 LowLimit 47.4 57.9 PA Method 3181 24872	8015D: Diese Units: mg/k HighLimit 148 140 8015D: Diese Units: mg/k	(g %RPD el Range ((g	RPDLimit	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- Analyte detected below quantitation limits J
- 0 RSD is greater than RSDlimit
- RPD outside accepted recovery limits R۰
- S Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank В
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - Sample pH greater than 2. Р
 - RL Reporting Detection Limit

Page 4 of 6

1404929

WO#:

30-Apr-14

QC SUMMARY REPORT

Hall	Environmental	Analysis	Laboratory,	Inc.
------	---------------	----------	-------------	------

Client:	Blagg Engineering
Project:	GCU #194

Sample ID MB-12823	SampT	ype: ME	BLK	Tes	TestCode: EPA Method 8015D: Gasoline Range						
Client ID: PBS	Batch	h ID: 12	823	F	RunNo: 18182						
Prep Date: 4/22/2014	Analysis D	Date: 4/	/24/2014	S	SeqNo: 5	25363	Units: mg/k	۲g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Gasoline Range Organics (GRO)	ND	5.0			_						
Surr: BFB	830		1000		82.9	74.5	129				
Sample ID LCS-12823	ID LCS-12823 SampType: LCS					PA Method	8015D: Gaso	line Rang	e		
Client ID: 1 LCSS	Batch ID: 12823			F	RunNo: 1	8182					
Prep Date: 4/22/2014	Analysis D	is Date: 4/24/2014 SeqNo:			BeqNo: 5	25364	Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Gasoline Range Organics (GRO)	24	5.0	25.00	0	94.9	71.7	134				
Surr: BFB	910		1000		91.1	74.5	129				
•••		ype: MS		Tes			129 8015D: Gasc	line Rang	e		
Surr: BFB	I S SampT	ype: M DID: 12	<u></u>			PA Method		bline Rang	e		
Surr: BFB	I S SampT	n ID: 12	5 823	F	tCode: EI	PA Method 8182		0	e		
Surr: BFB Sample ID 1404916-001AM Client ID: BatchQC	S SampT Batch	n ID: 12	5 823 /24/2014	F	tCode: El RunNo: 1 SeqNo: 5	PA Method 8182	8015D: Gasc	0	e RPDLimit	Qual	
Surr: BFB Sample ID 1404916-001AM Client ID: BatchQC Prep Date: 4/22/2014	S SampT Batch Analysis D	n ID: 12 Date: 4 /	5 823 /24/2014	ਸ S	tCode: El RunNo: 1 SeqNo: 5	PA Method 8182 25366	8015D: Gasc Units: mg/K	(g		Qual	
Surr: BFB Sample ID 1404916-001AM Client ID: BatchQC Prep Date: 4/22/2014 Analyte	S SampT Batch Analysis D Result	n ID: 12 Date: 4 /	5 823 /24/2014 SPK value	R S SPK Ref Val	tCode: El RunNo: 1 SeqNo: 5 %REC	PA Method 8182 25366 LowLimit	8015D: Gasc Units: mg/K HighLimit	(g		Qual	
Surr: BFB Sample ID 1404916-001AM Client ID: BatchQC Prep Date: 4/22/2014 Analyte Gasoline Range Organics (GRO)	S SampT Batch Analysis D Result 22 900	n ID: 12 Date: 4 /	S 823 /24/2014 SPK value 24.25 969.9	F S SPK Ref Val 0	tCode: EI RunNo: 1 SeqNo: 5 %REC 92.0 93.1	PA Method 8182 25366 LowLimit 69.5 74.5	8015D: Gaso Units: mg/K HighLimit 145	5 59 %RPD	RPDLimit	Qual	
Surr: BFB Sample ID 1404916-001AM Client ID: BatchQC Prep Date: 4/22/2014 Analyte Gasoline Range Organics (GRO) Surr: BFB	S SampT Batch Analysis D Result 22 900 SD SampT	Date: 4 / PQL 4.8	S 823 /24/2014 SPK value 24.25 969.9 SD	F S SPK Ref Val 0 Tes	tCode: EI RunNo: 1 SeqNo: 5 %REC 92.0 93.1	PA Method 8182 25366 LowLimit 69.5 74.5 PA Method	8015D: Gaso Units: mg/K HighLimit 145 129	5 59 %RPD	RPDLimit	Qual	
Surr: BFB Sample ID 1404916-001AM Client ID: BatchQC Prep Date: 4/22/2014 Analyte Gasoline Range Organics (GRO) Surr: BFB Sample ID 1404916-001AM	S SampT Batch Analysis D Result 22 900 SD SampT	PQL 4.8 7ype: MS	5 823 /24/2014 SPK value 24.25 969.9 5D 823	F S SPK Ref Val 0 Tes F	tCode: EI RunNo: 1 SeqNo: 5 %REC 92.0 93.1 tCode: EI	PA Method 8182 25366 LowLimit 69.5 74.5 PA Method 8182	8015D: Gaso Units: mg/K HighLimit 145 129	Sg %RPD bline Rang	RPDLimit	Qual	
Surr: BFB Sample ID 1404916-001AM Client ID: BatchQC Prep Date: 4/22/2014 Analyte Basoline Range Organics (GRO) Surr: BFB Sample ID 1404916-001AM Client ID: BatchQC	S SampT Batch Analysis D Result 22 900 ISD SampT Batch	PQL 4.8 7ype: MS	S 823 24/2014 SPK value 24.25 969.9 SD 823 24/2014	F S SPK Ref Val 0 Tes F	tCode: EI RunNo: 1 SeqNo: 5 %REC 92.0 93.1 tCode: EI RunNo: 1 SeqNo: 5	PA Method 8182 25366 LowLimit 69.5 74.5 PA Method 8182	8015D: Gasc Units: mg/K HighLimit 145 129 8015D: Gasc	Sg %RPD bline Rang	RPDLimit	Qual	
Surr: BFB Sample ID 1404916-001AM Client ID: BatchQC Prep Date: 4/22/2014 Analyte Basoline Range Organics (GRO) Surr: BFB Sample ID 1404916-001AM Client ID: BatchQC Prep Date: 4/22/2014	S SampT Batch Analysis D Result 22 900 SD SampT Batch Analysis D	PQL 4.8 7ype: MS 1D: 12 4.8 7ype: MS 1D: 12 0ate: 4/	S 823 24/2014 SPK value 24.25 969.9 SD 823 24/2014	F S SPK Ref Val 0 Tes F S	tCode: EI RunNo: 1 SeqNo: 5 %REC 92.0 93.1 tCode: EI RunNo: 1 SeqNo: 5	PA Method 8182 25366 LowLimit 69.5 74.5 PA Method 8182 25367	8015D: Gaso Units: mg/K HighLimit 145 129 8015D: Gaso Units: mg/K	Sg %RPD Nine Rang	RPDLimit e		

Qualifiers:

* Value exceeds Maximum Contaminant Level.

E Value above quantitation range

- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

,

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 6

30-Apr-14

1404929

WO#:

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

Client:Blagg EngineeringProject:GCU #194

Sample ID MB-12823	Samp1	ype: ME	BLK	Tes	tCode: El	PA Method	8021B: Vola	tiles
Client ID: PBS	Batcl	h ID: 12	823	F	RunNo: 1	8182		
Prep Date: 4/22/2014	Analysis D	Date: 4/	24/2014	S	SeqNo: 5	25386	Units: mg/H	٢g
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%R
Benzene	ND	0.050						
Toluene	ND	0.050						
Ethylbenzene	ND	0.050						
Xylenes, Total	ND	0.10						
Surr: 4-Bromofluorobenzene	0.98		1.000		97.7	80	120	
Sample ID LCS-12823	SampT	ype: LC	S	Tes	tCode: El	PA Method	8021B: Volat	tiles
Client ID: LCSS	Batch	n ID: 12	823	R	RunNo: 1	8182		

Prep Date: 4/22/2014	Analysis [Analysis Date: 4/24/2014			eqNo: 525388 Units: mg/Kg					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.0	0.050	1.000	0	100	80	120			
Toluene	0.97	0.050	1.000	0	96.9	80	120			
Ethylbenzene	0.98	0.050	1.000	0	97.6	80	120			
Xylenes, Total	2.9	0.10	3.000	0	96.3	80	120			
Surr: 4-Bromofluorobenzene	1.1		1.000		106	80	120			

Sample ID 1404929-001AMS SampType: MS				TestCode: EPA Method 8021B: Volatiles							
Client ID: 5PC-TB@5'(95)	Batch	n ID: 12	823	RunNo: 18182							
Prep Date: 4/22/2014	Analysis Date: 4/24/2014			5	SeqNo: 525391 Units: mg/			<g< th=""></g<>			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	1.0	0.047	0.9497	0	105	67.4	135				
Toluene	0.91	0.047	0.9497	0	95.5	72.6	135				
Ethylbenzene	0.90	0.047	0.9497	0	95.3	69.4	143				
Xylenes, Total	2.7	0.095	2.849	0	94.4	70.8	144				
Surr: 4-Bromofluorobenzene	0.97		0.9497		103	80	120				

Sample ID 1404929-001AM	SD SampT	уре: М S	SD	Tes	tCode: E	PA Method	8021B: Vola	tiles		
Client ID: 5PC-TB@5'(95)	Batch	Batch ID: 12823 RunNo: 18182								
Prep Date: 4/22/2014	Analysis D	Analysis Date: 4/24/2014			SeqNo: 5	25393	Units: mg/k	ίg		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.98	0.048	0.9524	0	102	67.4	135	2.04	20	
Toluene	0.89	0.048	0.9524	0	93.7	72.6	135	1.72	20	
Ethylbenzene	0.90	0.048	0.9524	0	94.0	69.4	143	1.08	20	
Xylenes, Total	2.7	0.095	2.857	0	92.9	70.8	144	1.31	20	
Surr: 4-Bromofluorobenzene	0.98		0.9524		103	80	120	0	0	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - Sample pH greater than 2.
- RL Reporting Detection Limit

Р

Page 6 of 6

1404929

Qual

WO#:

RPDLimit

%RPD

30-Apr-14

Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Name: BLAGG Work Order Number					RcptNo:	1
Received by/date: C.S.	04/22/14						
Logged By: Ashley Gallegos	4/22/2014 10:00:00 A	М		Stof			
Completed By: Ashley Gallegos 4/22/2014 12:57:43 PM				Ay			
Reviewed By:	04/2=	2/1L	ł	V			
Chain of Custody		V.	1				
1. Custody seals intact on sample bottles?		Yes		No		Not Present 🗸	
2. Is Chain of Custody complete?		Yes	~	No		Not Present	
3. How was the sample delivered?		<u>Cour</u>	ier			ť	
<u>Log In</u>							
4. Was an attempt made to cool the sample	s?	Yes	•	No		NA	
5. Were all samples received at a temperatu	re of >0° C to 6.0°C	Yes	✓	No		NA	
6. Sample(s) in proper container(s)?		Yes	y	No			<u> </u>
7. Sufficient sample volume for indicated tes	t(s)?	Yes	V	No			
8. Are samples (except VOA and ONG) prop	erly preserved?	Yes	~	No			
9. Was preservative added to bottles?		Yes		No	✓	NA	
10.VOA vials have zero headspace?		Yes		No		No VOA Vials 🗸	
11. Were any sample containers received bro	ken?	Yes		No	~	# of preserved	
12. Does paperwork match bottle labels?		Yes	~	No		bottles checked for pH:	
(Note discrepancies on chain of custody)							>12 unless noted)
13. Are matrices correctly identified on Chain	of Custody?	Yes	✓	No		Adjusted?	
14. Is it clear what analyses were requested?		Yes	V	No		Checked by:	
15. Were all holding times able to be met? (If no, notify customer for authorization.)		Yes	v	No		Checked by.	
Special Handling (if applicable)							
16. Was client notified of all discrepancies wit	h this order?	Yes		No		NA 🗸	
Person Notified:	Date:			<u> </u>			
By Whom:	Via:	eM	ail	Phone	Fax	In Person	
Regarding:				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
Client Instructions:							
17. Additional remarks:							
18. <u>Cooler Information</u> Cooler No Temp °C Condition	Seal Intact Seal No	Seal D	ata	Signed E	av		

Chain-of-Custody Record							ы. Эл	1 -1		łÁ	i.	(کو ا	Ňľ	/ T E	2 n		ME	INT	AI	1	
Client: BLAGG ENGR / BP AMERICA			Standard,			6	-						•			ATC	-				
				Project Name	1				8:724		ww	w.h:	allèn	viro	nme	ntal	соп	n'			
Mailing Address: P.O. BOX 87			GCU:#194				www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109														
BLOOMFIELD, NM 87413				Project #:			Tél. 505-345-3975 Fax 505-345-4107														
Phone #: (505) 632-1199)							•					Vnal	ysis	Rec	jues	it					
email or Fax#:			Project Manager,					9	\int_{-}^{-}	Ť			-				-	ŀ			
QA/QC Rečkaĝe: 교 Standard □ lievel 4 (Full Validățión)		NELSON VELEZ			, (80218)	+ TPH (Gas only)				5)		09"SO	PCB's			(Thoise Hig	н т. -		a		
Accreditation			Sampler: NELSON VELEZ				(Gas	DRO /	÷	÷	NIS(021	1082			/ watêr		1-	Ē	
INELAP _ II Other			On Ice					\sim	118	Š.	3270		N N	ŝ / ŝ		F	0.005			IP S	
D EDD (Type)			Sample Temperature: 2,5				+ 	GRC	pō.	pio	ja 1	tals	J'NC	cide	A)	NON-			<u>v</u> :	E SO	
Ďáte	Time	i Mātříx.	Sample Request ID	Gontainer Type and #	Preservative Type	HEAL No.	BTEX + WITB	BTEX'+ MTBE	IPH BOISB (GRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 of 827051M5)	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (<u>Semi-VOA</u>)	Chloride (sail		Grap sample	5, pt. composite sample Afr builther Actual Str
4/18/14	1145	SOIL	'SPC - TB @'S' (95)	4 öz 1	Cool	-:001	V		۷	۷								V			V
			- .	·				ł ,		1	,		1		1						1
			-			(1						-	<u> </u>		-	-	
		`				. 1	1		 :				•								+
		<u></u>		+		· · · · · · · · · · · · · · · · · · ·		1	`			<u>.</u>	ł	-					-		╉
				· ·	<u> </u>		, ,		• <u>·</u>	•		·			·				<u> </u>		
	 	· · · · · · · · · · · · · · · · · · ·	7	· ·		1		•	,					¹					-+-		╇
<u> </u>									<u></u>	·· ·	·			1						<u> </u>	<u> </u>
					<u> </u>								·····	<u></u>	·;				<u> </u>	-	<u>-</u>
<u> </u>				<u> </u>	<u> </u>		<u> </u>		·;	·									<u> </u>	- -	+-
	ļ			<u> </u>	<u> </u>	<u> </u>				· ·		<u> </u>								_ <u> </u>	.
	: 									· .		L	.*.			· · ·	·		<u></u>		_ <u> </u>
				mark at his				Ļ					'			. ·	ļ				<u> </u>
4/21/14	Time SZS	Relinquish	lary	Received by: Date: Time. Mustu Davitus 1/2/1.4.825 Received by: Date: Time.				Rémarks: BILL DIRECTLY, TO BP: Jeff Peace, 200 Energy Court, Farmington, NM 87401													
1/21/11/1740 Phrister Walter			Cela S	2-11- O	1/22/14 1000	Work Order: Paykey:ZDCS01GEN1															

.

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

May 7, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 194 API 30-045-06935 (G) Section 05 – T27N – R12W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

for Posel

Jeff Peace BP Field Environmental Advisor

(505) 326-9479



