District 1
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

·
Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address: _200 Energy Court, Farmington, NM 87401
Facility or well name:Gallegos Canyon Unit 55
API Number:3004507044 OCD Permit Number:
U/L or Qtr/QtrGSection35Township28NRange12WCounty:San Juan
Center of Proposed Design: Latitude36.62128 Longitude108.07777 NAD: ☐1927 ☒ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2. □ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: □ Drilling □ Workover □ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined Liner type: Thickness mil □ LLDPE □ HDPE □ PVC □ Other □ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
☑ Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A OIL CONS. DIV DIST. 3
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/Single bottomed
Liner type: Thicknessmil
4. Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No

Form C-144 Oil Conservation Division

Page 2 of 6

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC	5.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. 	15.17.9 NMAC
and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	e documents are
☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
 □ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC □ Quality Control/Quality Assurance Construction and Installation Plan 	
 □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Nuisance or Hazardous Odors, including H₂S, Prevention Plan □ Emergency Response Plan 	
Oil Field Waste Stream Characterization Monitoring and Inspection Plan	
☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	Fluid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial	
Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
e-mail address:	the closure report.
e-mail address: Telephone:	the closure report.

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure require	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Pase	Date:June 30, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit 55 API No. 3004507044 Unit Letter G, Section 35, T28N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil. The area over the BGT is covered by the LPT and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District 1
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

		_	Rele	ease Notific	ation	and Co	rrective A	ction	· -		=
						OPERA	ΓOR	In	tial Report	\boxtimes	Final Report
Name of Co						Contact: Jef					
		Court, Farm	·	M 87401			No.: 505-326 - 94				
Facility Nar	ne: Galleg	gos Canyon I	Jnit 55			Facility Typ	e: Natural gas v	vell			
Surface Ow	ner: Feder	al		Mineral C	wner:	Federal		API	lo. 300450	7044	
				LOCA	OITA	N OF REI	LEASE				
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/West Line	County:	San Juai	n
G	35	28N	12W	1,650	North		1,650	East			
L	<u> </u>	Lat	itude3	6.62128		_ Longitud	e108.07777_				
				NAT	URE	OF RELI	EASE				
Type of Relea						· · · · · · · · · · · · · · · · · · ·	Release: N/A	Volum	Recovered:	N/A	
Source of Re	lease: belov	w grade tank -	- 95 bbl			Date and I-I	our of Occurrenc	e: Date ar	d Hour of Di	scovery	r: N/A
Was Immedia	ate Notice (Yes [No ⊠ Not Re	quired	If YES, To	Whom?				
By Whom?						Date and H					
Was a Watero	course Read		Yes ⊠	No		If YES, Vo	lume Impacting t	he Watercourse.			
If a Watercou	rse was Im	pacted, Descr	ibe Fully.	S		·		 			
the BGT. So	il analysis i	esulted in TP	H, BTEX	n Taken.* Samplin and chlorides belo en.* BGT was rea active well area.	w stand	ards. Analys	is results are attac	ched.			
regulations al public health should their o	l operators or the envi- perations h nment. In a	are required to a ronment. The rave failed to a reddition, NMC	o report ar acceptance adequately OCD accep	is true and comp id/or file certain re e of a C-141 repo investigate and re tance of a C-141	elease no rt by the emediate	otifications are NMOCD made contamination	nd perform correct arked as "Final Roon that pose a thre	tive actions for r eport" does not r eat to ground wa	eleases which elieve the ope er, surface w	n may en erator of eater, hu	ndanger f liability man health
0	10	0					OIL CONS	SERVATIO	<u> DIVISI</u>	<u>NC</u>	
Signature: Printed Name	: Jeff Peac	e				Approved by	Environmental Sp	pecialist:			
Title: Area Eı						Approval Dat	e:	Expiratio	n Date:		
E-mail Addre	ess: peace.jo	effrey@bp.co	m			Conditions of	Approval:		Attache	d 🔲	
Date: June 3	0 2014		Phone: 50)5-326-9479							

^{*} Attach Additional Sheets If Necessary

CLIENT: BP		NGINEERING, INC. BLOOMFIELD, NM 87	7/13	API#: 300	450704	14
CLICIVI.	•	05) 632-1199	7413	TANK ID (if applicble):	Α	
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTHER:		PAGE#:	o f _	1
SITE INFORMATION				DATE STARTED: _	04/17/	14
QUAD/UNIT: G SEC: 35 TWP:				DATE FINISHED: _		
1/4 -1/4/FOOTAGE: 1,650'N / 1,65 LEASE #: SF078903		TYPE: FEDERAL / STATE / FEE ELKHORN ONTRACTOR: MBF - S. GLYN		ENVIRONMENTAL SPECIALIST(S):	NJV	ı
REFERENCE POINT	: WELL HEAD (W.H.) GPS	S COORD.: 36.62142 X	108.07773	GL ELE	√: 5,96	i1'
1) 95 BGT (SW/SB)	GPS COORD.:3	6.62128 X 108.07777	DISTANCE/BEAR	RING FROM W.H.:	66', S25	W
2)	GPS COORD.:	11- 3	_ DISTANCE/BEAF	RING FROM W.H.:		
3)	GPS COORD.:		_ DISTANCE/BEAF	RING FROM W.H.:		
4)	GPS COORD.:		_ DISTANCE/BEAF	RING FROM W.H.:		
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # 0	OR LAB USED: HALL			RE	OVM EADING (ppm)
1) SAMPLE ID:	95) SAMPLE DATE: 04/17	1/14 SAMPLE TIME:	alysis: 418.1/8	015B/8021B/300	.0 (CI)	NA
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANA	ALYSIS:			
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB AN/	ALYSIS:			
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANA	ALYSIS:			
SOIL DESCRIPTION	SOIL TYPE: SAND / SILTY SAND	SILT / SILTY CLAY / CLAY / GRAVEL / OT	HER			
SOIL COLOR: GRAYISH		PLASTICITY (CLAYS): NON PLASTIC / SLIG		DHESIVE / MEDIUM PLAST	TIC / HIGHLY PL	_ASTIC
COHESION (ALL OTHERS): NON COHESIVE/ SLIGHTLY		DENSITY (COHESIVE CLAYS & SILTS)				
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY (SLIGHTLY MOIST) MOIST / WE		HC ODOR DETECTED: YES NO EXPLA	NATION -			
SAMPLE TYPE: GRAB COMPOSITE #		ANY AREAS DISPLAYING WETNESS: YE	S NO EXPLAN	ATION -		
DISCOLORATION/STAINING OBSERVED: YES N						
SITE OBSERVATION						
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:			ON.			
OTHER: BGT - 15 FT. LOW PROFILE WIT						
SOIL IMPACT DIMENSION ESTIMATION:	NA	ft. X NA ft. EXC	CAVATION EST	IMATION (Cubic Yard	is): N A	Δ
	EAREST WATER SOURCE: >1,000'	NEAREST SURFACE WATER: <1,0		D TPH CLOSURE STD:	100	ppm
SITE SKETCH	BGT Located: off on sit	e PLOT PLAN circle: a	attached O\M	CALIB. READ. = NA	nnm	
				CALIB. GAS = NA		= 0.52
	PUI JAC		N TIME:			
	⊕ W.H.	>r\	 	MISCELL.		\equiv
	BERM		l w			3
PBGTL T.B. ~ 4'				0. 141333120 D#:	00	
B.G.			Pł		BGT2	
(x	× × × SEPARATOR		P.	#: Z2-006Q (
	SEPARATOR		Pe		06/08/10	-
			O(12/11/13 /apor Meter	-
COMPRESSOR ──➤	METER		ID.	ppm = parts per	million	
	RUN		. <u>-</u> _ A	BGT Sidewalls Visib		
NATES. DOT - DELOWADADE TANK ED. EVOLUTIO	NI DEDDECCIONI D. O DEL CIMODADE D. D.		S.P.D.	BGT Sidewalls Visib		
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELO	OW-GRADE TANK LOCATION; SPD = SAMPLE F	POINT DESIGNATION; R.W. = RETAINING WALL; N	VELL MEAU; L	agnetic declinatio		
APPLICABLE OR NOT AVAILABLE; SW - SINGLE	E WALL; DW - DOUBLE WALL; SB - SINGLE BOT	TOM; DB - DOUBLE BOTTOM.			··· · · · · · · · · · · · · · · · · ·	
NOTES:		ONSITE: 04/17/14				

'Analytical Report

Lab Order 1404930

Date Reported: 4/29/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering Client Sample ID: 5PC-TB@4'(95)

 Project:
 GCU #55
 Collection Date: 4/17/2014 1:30:00 PM

 Lab ID:
 1404930-001
 Matrix: SOIL
 Received Date: 4/22/2014 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	E ORGANICS			,	Analyst	BCN
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	4/24/2014 4:22:43 PM	12796
Surr: DNOP	101	57.9-140	%REC	1	4/24/2014 4:22:43 PM	12796
EPA METHOD 8015D: GASOLINE RA	NGE				Analyst	NSB
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	4/24/2014 5:22:20 PM	12823
Surr: BFB	83.7	74.5-129	%REC	1	4/24/2014 5:22:20 PM	12823
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.048	mg/Kg	1	4/24/2014 5:22:20 PM	12823
Toluene	ND	0.048	mg/Kg	1	4/24/2014 5:22:20 PM	12823
Ethylbenzene	ND	0.048	mg/Kg	1	4/24/2014 5:22:20 PM	12823
Xylenes, Total	ND	0.095	mg/Kg	1	4/24/2014 5:22:20 PM	12823
Surr: 4-Bromofluorobenzene	97.6	80-120	%REC	1	4/24/2014 5:22:20 PM	12823
EPA METHOD 300.0: ANIONS					Analyst	JRR
Chloride	ND	30	mg/Kg	20	4/23/2014 3:16:02 PM	12841
EPA METHOD 418.1: TPH					Analyst	JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	4/25/2014 12:00:00 PM	12824

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#: 1404930

29-Apr-14

Client:

Blagg Engineering

Project:

GCU #55

Sample ID LCS-12841

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Batch ID: 12841

RunNo: 18179

Prep Date: 4/23/2014

Analysis Date: 4/23/2014

SeqNo: 524769

Units: mg/Kg

Analyte

PQL

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD **RPDLimit**

Qual

Result

Chloride

15.00

91.1

14

1.5

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits S
- В Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded H
- Not Detected at the Reporting Limit
- Sample pH greater than 2. Reporting Detection Limit

P

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

Result

89

20

WO#:

1404930

29-Apr-14

Client:

Blagg Engineering

Project:

Analyte

Petroleum Hydrocarbons, TR

GCU #55

Sample ID MB-12824	SampType: MBLK	TestCode: EPA Method	418.1: TPH	
Client ID: PBS	Batch ID: 12824	RunNo: 18209		
Prep Date: 4/22/2014	Analysis Date: 4/25/2014	SeqNo: 525508	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit	Qual
Petroleum Hydrocarbons, TR	ND 20			
Sample ID LCS-12824	SampType: LCS	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS	Batch ID: 12824	RunNo: 18209		
Prep Date: 4/22/2014	Analysis Date: 4/25/2014	SeqNo: 525509	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit	Qual
Petroleum Hydrocarbons, TR	87 20 100.0	0 87.3 80	120	
Sample ID LCSD-12824	SampType: LCSD	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS02	Batch ID: 12824	RunNo: 18209		
Prep Date: 4/22/2014	Analysis Date: 4/25/2014	SeqNo: 525510	Units: mg/Kg	

SPK value SPK Ref Val %REC

100.0

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank

LowLimit

80

88.7

HighLimit

120

%RPD

1.52

RPDLimit

20

Qual

- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404930

29-Apr-14

Client:

Blagg Engineering

Project:

GCU #55

Sample ID MB-12796	SampType: MBLK			SampType: MBLK TestCode: EPA Method 8015D: Diesel Range C					Organics	
Client ID: PBS	D: PBS Batch ID: 12796 RunNo: 18181									
Prep Date: 4/22/2014	Analysis E	Date: 4/	24/2014	\$	SeqNo: 5	24863	Units: mg/h	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Surr: DNOP	9.6		10.00		96.1	57.9	140			
Sample ID LCS-12796	SampT	Гуре: LC	s	Tes	Code: El	PA Method	8015D: Dies	el Range (Organics	
Client ID: LCSS	Batcl	h ID: 12	796	F	RunNo: 1 :	8181				
Prep Date: 4/22/2014	Analysis E	Date: 4/	24/2014	5	SeqNo: 5	24864	Units: mg/F	(g	•	
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	47	10	50.00	0	93.1	60.8	145			
Surr: DNOP	4.7		5.000		93.9	57.9	140			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

910

WO#:

1404930

29-Apr-14

Client:

Blagg Engineering

Project:

Surr: BFB

GCU #55

Sample ID MB-12823	SampType	: MBLK	Tes	A Method	8015D: Gaso	line Rang	е,		
Client ID: PB\$	Batch ID:	12823	F	RunNo: 18	3182				
Prep Date: 4/22/2014	Analysis Date:	4/24/2014	SeqNo: 525363			Units: mg/F			
Analyte	Result P	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO) Surr: BFB	ND 830	5.0 1000		82.9	74.5	129			
Sample ID LCS-12823	SampType	: LCS	Tes	tCode: EP	A Method	8015D: Gaso	line Rang	e	<u> </u>
Client ID: LCSS	Batch ID:	12823	R	lunNo: 18	182				
Prep Date: 4/22/2014	Analysis Date:	4/24/2014	S	SeqNo: 525364		Units: mg/K	(g		
Analyte	Result Po	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	24	5.0 25.00	0	94.9	71.7	134			

91.1

74.5

129

1000

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.

RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404930

29-Apr-14

Client:

Blagg Engineering

Project:

GCU #55

Sample ID MB-12823	Samp ⁻	BLK	Tes	tCode: El										
Client ID: PBS	Batc	823	F	RunNo: 1										
Prep Date: 4/22/2014	Analysis [Date: 4/	24/2014	S	SeqNo: 5	25386	Units: mg/Kg							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	: HighLimit %RI		RPDLimit	Qual				
Benzene	ND	0.050								-				
Toluene	ND	0.050												
Ethylbenzene	ND	0.050												
Xylenes, Total	ND	0.10												
Surr: 4-Bromofluorobenzene	0.98		1.000		97.7	80	120							
Sample ID LCS-12823	SampType: LCS TestCode: EPA Method							tiles						
Client ID: LCSS	Batc	h ID: 12	823	R	RunNo: 1	8182								
Prep Date: 4/22/2014	Analysis [Date: 4/	24/2014	S	SeqNo: 5	25388	Units: mg/K	(g						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Donzeno	1.0	0.050	1.000	0	100	80	120							
Benzene	1.0	0.000												
	0.97	0.050	1.000	0	96.9	80	120							
Toluene				0		80 80	120 120							
Benzene Toluene Ethylbenzene Xylenes, Total	0.97	0.050	1.000	_	96.9									

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6

Hall Environmental Analysis Laboratory

4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name:	BLAGG		Work Order	Number: 1	14049:	30			RoptNe	o: 1
Received by/da	te: <i>C</i> -S		24/22/14	7	<u>.</u> .					··· · · · · · · · · · · · · · · · · ·
Logged By:	Ashley Gall	iegos	4/22/2014 10:0	0:00 AM			A	7		
Completed By:	Ashley Gall	_	4/22/2014 1;08	:39 PM			A	V }-		:
Reviewed By:	10	cs	04/22/1	u				J		:
Chain of Cus	stody		01 00	l .!		••		-	ü	
	als intact on sa	nnle hottles?			Yes	-;	No		Not Present ✓	
	Custody compl	-			Yes			: :	Not Present	
	3. How was the sample delivered?				Courie		•			
Log In										
4. Was an atte	empt made to o	cool the samples	?		Yes	Y	No		NA i.	•
5. Were all samples received at a temperature of >0° C to 6.0°C				°C '	Yes 🤄	/ i	No	<u>!</u> . i	NA .	
6. Sample(s) in proper container(s)?					Yes	V	No	٠,		
7. Sufficient sa	ample volume f	for indicated test(s)?	•	Yes :	Ä	No	: .: : .:	•	
8. Are samples	s (except VOA	and ONG) prope	rly preserved?	,	Yes :	7	No	: :!		
9. Was preser	vative added to	bottles?			Yes		No	✓	NA 🗀	
10.VOA vials h	ave zero heads	space?		,	Yes :]	No	i. J	No VOA Vials 🗸	
11. Were any s	sample containe	ers received brok	en?		Yes	<u>:</u>	No	V		-
					_				# of preserved bottles checked	
12 Does paper	work match bo epancies on cha			,	Yes :		No		for pH;	or >12 unless noted)
		ntified on Chain o	f Custody?	,	Yes :	/ .	No	. : .	Adjusted?	
14 Is it clear wi					Yes 2		No			
15. Were all holes (If no. notify	lding times able customer for a			•	Yes i	į.	No	il	Checked by:	
(,		,								
Special Hand	dling (if app	licable)								
16. Was client r	notified of all di	screpancies with	this order?	,	Yes	:	No	:::	NA 🗸	
Perso	n Notified:	and the second district the second	THE PARTY OF	Date:	TOTAL COLUMN TRANSPORT		The state of the s	PARTITION OF THE PARTIT		
By Wi	hom:	THE CO. T. ST. W. C. LANS CO.	CONTRACTOR CONTRACTOR	Via: É	eMail	[]]	Phone : :	Fax	In Person	
Regai	rding:	1:								
Client	Instructions:									
17. Additional	remarks:									
18. Cooler Info										•
Cooler N			eal Intact Seal	No: Se	al Date	•	Signed I	3у		
17	2.5	Good Ye	S :			<u>İ</u>	and the state of t			

Chain-of-Custody Record			Turn-Around	HALL ENVIRONMENTAL																		
Client: BLAGG ENGR. / BP AMERICA			✓ Standard	ANALYSIS LABORATOR																		
·				Project Name	:						ww	w.h	aller	viro	nme	ental	.con	1				
Mailing Address: P.O. BOX 87				GCU # 55	5		49	01 H	ławk	kins	NE ·	- All	ouqu	ıerq	ue, 1	MI	3710	9				
BLOOMFIELD, NM 87413		Project #:				Tel. 505-345-3975 Fax 505-345-4107																
Phone #: (505) 632-1199								,	 -	77	Anal	ys is	Red	ques	t	ب ا	- Janeary		34.4 34.4			
email or F	ax#:			Project Manag	ger:				ħ√					4)				ਜ਼				
QA/QC Package: Standard Level 4 (Full Validation)				NELSON VI	ELEZ	HMB's (8021B)		wite)			(S)		04,50	PCB's			er - 300.1)			ره		
Accreditation:			Sampler:	NELŞON VE	ELEZ 925	\ \{\frac{8}{3}}	(Gas	80,	1)	1)	SIS		02,5	087			wat			ם		
□ NELAP □ Other		On ice 15 ib yes 3 to No.			1 ₹	IPH (0/0	118.	504.	22		Z,	8/8		A)	0.00	İ		e sa			
□ EDD (Type)			Sample Temp	erature. 2 (70	ŀ	E +]	GRC	po ,	po	5 5	tals	Ž	cide	ব	٠] <u>-</u>		<u>a</u>	osit		
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALNO	BTEX +-NATE	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 / water		Grab sample	5 pt. composite sample	
4/17/14	1330	SOIL	5PC - TB @ 4' (95)	4 oz 1	Cool	-001	٧		٧	٧					-			V			٧	
																						•
																						•
																					一	
							 													\dashv	\neg	
							 									-			\dashv	-	$\neg \uparrow$	•
															-							
														-					\dashv	\dashv	\dashv	
													-			-						
											-					\vdash		 	\dashv	\dashv	\rightarrow	•
							-						-		-			┝─┪		-	\rightarrow	
					<u> </u>													\square	\dashv	\dashv		
Deter	Times	Polinguish	ad har	Received by:		Date Time	<u> </u>			-,			<u> </u>				لـــا					-
Date:	Time: \$25	Relinquish	in y	Mustu Walter 4/21/14825			Remarks: BILL DIRECTLY TO BP: Jeff Peace, 200 Energy Court, Farmington, NM 87401															
Date:	Date: Time: Relinquished by:		Received by: Date Time Cellin Srm 04/22/14 1000				Work Order: N15391263 Paykey: 7FVH01BGT2															





BP.America Production Company (200/Energy Court Farmington, NM 87401 (Phone: (505) 326-9200

January 30, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 055

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closume Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about February 25, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

Surface Land Negotiator

9D Ven Rin

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

January 30, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 055 API 30-045-07044 (G) Section 35 - T28N - R12W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



