District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

.*

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or	
Proposed Alternative Method Permit or Closure Plan A	pplication
1/994 Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-per or proposed alternative method Below grade tank registration	
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tan	ik or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable government.	of surface water, ground water or the al authority's rules, regulations or ordinances.
Deperator: BP America Production Company OGRID #:778	
Address:200 Energy Court, Farmington, NM 87401	OIL CONS. DIV DIST. 3
Facility or well name:Gallegos Canyon Unit 213	JUN 2 4 2014
API Number:	
U/L or Qtr/QtrJ Section8 Township28N Range12W County:	San Juan
Center of Proposed Design: Latitude36.67297 Longitude108.13439	NAD: 1927 🛛 1983
Surface Owner: 🛛 Federal 🗌 State 🗌 Private 🗌 Tribal Trust or Indian Allotment	······
 2. Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chlorid Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced 	
Liner Seams: Welded Factory Other Volume: bbl Dimension	ons: Lx Wx D
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A Volume: 95.0 bbl Type of fluid: bbl Type of fluid:	
Tank Construction material:Steel	
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shi	ut-off
□ Visible sidewalls and liner □ Visible sidewalls only ⊠ Other _Single walled/Single bottomed, sid	
Liner type: Thicknessmil	
4. Alternative Method:	

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (*Required if located within 1000 feet of a permanent residence, school, hospital, institution or church*)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify_

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other_

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

□ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks. **General siting** Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. 🗌 Yes 🗌 No NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells □ NA 🗌 Yes 🗌 No Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. \square NA NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells. Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance Yes No adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality Within the area overlying a subsurface mine. (Does not apply to below grade tanks) \square Yes \square No Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. (Does not apply to below grade tanks) Yes No Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map ☐ Yes ☐ No Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map **Below Grade Tanks** Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured Yes No from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Yes No Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter) Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, Yes No or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	
	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗍 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗍 No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🛄 No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
 initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
^{10.} <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 NI <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc</i> <i>attached.</i>	
 Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 	NMAC
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC 	5.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doct	uments are
 attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15 	15 17 9 NMAC
and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

٠

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
13. Demonst Channes 10 15 17 12 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Managamant Dit
Alternative	fund Management i ft
Proposed Closure Method: 🔲 Waste Excavation and Removal	
Waste Removal (Closed-loop systems only)	
 On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial 	
Alternative Closure Method	
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

•

.

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	🗋 Yes 🗌 No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain.	Yes No
- FEMA map	Yes No
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure play a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canned Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	· · · · · · · · · · · · · · · · · · ·
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
e-mail address: Telephone:	
e-mail address: Telephone:	
e-mail address:	
e-mail address:	2014 the closure report.
e-mail address: Telephone:	2014 the closure report.
e-mail address:	2014 the closure report. complete this

٠

22. Operator Closure Certification:

.

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Joff Parce	Date:June 23, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Gallegos Canyon Unit 213</u> <u>API No. 3004511618</u> <u>Unit Letter J, Section 8, T28N, R12W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil. The area over the BGT is covered by the LPT and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

•

Oil Conservation Division 1220 South St. Enousin D.

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Frai	ncis Dr., Sant	a Fe, NM 8750	5			i St. France, NM 875						
			Rele		_		orrective A	ction				
						OPERA				al Report		Final Repor
Name of Co	ompany: B	Р				Contact: Jef						i mai reepoi
		Court, Farm	ington, N	M 87401			No.: 505-326-94	79				
		os Canyon I					e: Natural gas v					
									1			
Surface Ow	/ner: Feder			Mineral (Jwner:	Federal		·	API No	. 30045110	618	
						N OF REI		1				
Unit Letter J	Section 8	Township 28N	Range 12W	Feet from the 1,450	North/ South	South Line	Feet from the 2,370	East/W East	est Line	County: S	an Juan	
	L	Lat	itude3	5.67297		Longitud	e108.13439_					
				NAT	FURE	OF RELI	EASE					
Type of Rele						Volume of	Release: N/A			lecovered: N		
Source of Re	lease: belov	v grade tank -	- 95 bbl			Date and H	lour of Occurrenc	e:	Date and	Hour of Dis	covery:	N/A
Was Immedi	ate Notice (Yes 🗌	No 🛛 Not R	equired	If YES, To	Whom?					
By Whom?					,	Date and H	our					
Was a Watercourse Reached?						If YES, Vo	lume Impacting t	he Water	course.			· · · · · · · · · · · · · · · · · · ·
If a Watercou	urse was Im	pacted, Descr	ibe Fully.*			<u>.</u>				<u></u>		
							the BGT was do is results are attac		, removal t	o ensure no	soil im	pacts from
the BO1. 30	ni analysis i		n, di ca a		ow stand	alus. Allalys		incu.				
											, .	
				en.* BGT was re , and is still with			nderneath the BG	T was sa	mpled. Tł	ne excavated	l area w	as
	•		-									
							knowledge and u					
							id perform correc arked as "Final R					
							on that pose a thr					
							e the operator of i					
		vs and/or regu			•		•	•	·			
	all al) eace					OIL CON	SERV	ATION	DIVISIC	<u>DN</u>	
Signature:						Approved by	Environmental S	pecialist:				
Printed Name Title: Area E						Approval Dat	e:	E	xpiration l	Date:		
E-mail Addre			n			Conditions of			<u>, r</u>			
					`		PF- 3 . WII			Attached		
Date: June 2	23 2014		Phone: 50)5-326-9479						1		

* Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, BLO	GINEERING, INC. OMFIELD, NM 87413 632-1199	API #: 3004511618 TANK ID (if applicble): A
FIELD REPORT:	(circle one): BGT CONFIRMATION / REL	LEASE INVESTIGATION / OTHER:	PAGE #:1 of1
	28N RNG: 12W PM: N 0'E NW/SE LEASE TYPE:		ENVIRONMENTAL
REFERENCE POINT 1) 95 BGT (SW/SB) 2)	WELL HEAD (W.H.) GPS COOR GPS COORD.: 36.67 GPS COORD.: GPS COORD.:	ORD.: 36.67339 X 108.134	16 GL ELEV.: 5,676' /BEARING FROM W.H.: 168', S35W /BEARING FROM W.H.:
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAI	· · · · · · · · · · · · · · · · · · ·	OVM READING (ppm)
 2) SAMPLE ID: 3) SAMPLE ID: 	SAMPLE DATE: SAMPLE DATE:		
SOIL COLOR: DARK YE COHESION (ALL OTHERS): NON COHESIVE SUIGHTLY CONSISTENCY (NON COHESIVE SOILS): LO MOISTURE: DRY SLIGHTLY MOIST / WE SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED: YES NO SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVED EQUIPMENT SET OVER RECLAIMED AREA: O OTHER: BGT 15 FT. DIAMETER LOW PRO	LLOWISH ORANGE PLAS COHESIVE / COHESIVE / HIGHLY COHESIVE DEN OSE/ FIRM / DENSE / VERY DENSE HC O T / SATURATED / SUPER SATURATED HC O OF PTS. 5 D EXPLANATION - ANY S: LOST INTEGRITY OF EQUIPMENT: YES AND/OR OCCURRED : YES NO EXPLANATION - LP AGT TO E	ON:	C / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC M / STIFF / VERY STIFF / HARD
SOIL IMPACT DIMENSION ESTIMATION:			ESTIMATION (Cubic Yards) : NA
	BGT Located : off on site	PLOT PLAN circle: attached	MOCD TPH CLOSURE STD:100 ppm DVM CALIB. READ. =52.2ppm RF = 0.52
	PBGTL T.B. ~ 4' B.G. (x x x) VDEPRESSION; B.G. = BELOW GRADE; B = BELOW; WGRADE TANK LOCATION; SPD = SAMPLE POINT D	N.H. N WASH CHANNEL DD. NK X - S.P.D. T.H. = TEST HOLE; ~ = APPROX.; W.H. = WELL HEAD; JESIGNATION; R.W. = RETAINING WALL; NA- NOT	DW CALIB. GAS = 100 ppm IME: 6:30 mpm DATE: 04/25/14 IMISCELL. NOTES WO: N15386076 PO #: PK: ZEVH01BGT2 PJ #: Z2-006Q0 Permit date(s): 06/09/10 OCD Appr. date(s): 11/25/13 Tank OVM = Organic Vapor Meter JD ppm = parts per million A BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N Magnetic declination:
	WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; D		
NUTES.		UNSITEUTILUIT	

revised: 11/26/13

,

BEI1005E-6.SKF

						Date Reported: 5/7/201	4
CLIENT: Blagg Engineering Project: GCU 213 Lab ID: 1405045-001	Matrix:	SOIL	C	Collection	Date: 4/2	BGT 5-pt @ 4' 25/2014 12:55:00 PM /2014 10:03:00 AM	
Analyses	Result	RL	Qual L	Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE	EORGANICS					Analysi	BCN
Diesel Range Organics (DRO)	ND	9.9		mg/Kg	1	5/5/2014 1:46:03 PM	12982
Surr: DNOP	98.9	57.9-140		%REC	1	5/5/2014 1:46:03 PM	12982
EPA METHOD 8015D: GASOLINE RAI	NGE					Analyst	NSB
Gasoline Range Organics (GRO)	ND	5.0		mg/Kg	1	5/3/2014 1:21:53 AM	12961
Surr: BFB	86.9	74.5-129		%REC	1	5/3/2014 1:21:53 AM	12961
EPA METHOD 8021B: VOLATILES						Analyst	NSB
Benzene	ND	0.050		mg/Kg	1	5/3/2014 1:21:53 AM	12961
Toluene	ND	0.050		mg/Kg	1	5/3/2014 1:21:53 AM	12961
Ethylbenzene	ND	0.050		mg/Kg	1	5/3/2014 1:21:53 AM	12961
Xylenes, Total	ND	0.099		mg/Kg	1	5/3/2014 1:21:53 AM	12961
Surr: 4-Bromofluorobenzene	101	80-120		%REC	1	5/3/2014 1:21:53 AM	12961
EPA METHOD 300.0: ANIONS						Analyst	JRR
Chloride	ND	30		mg/Kg	20	5/2/2014 4:28:04 PM	12983
EPA METHOD 418.1: TPH						Analyst	BCN
Petroleum Hydrocarbons, TR	ND	20		mg/Kg	1	5/6/2014	12981

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method Blank	
	Е	Value above quantitation range	Н	Holding times for preparation or analysis	s exceeded
	3	Analyte detected below quantitation limits	ND	Not Detected at the Reporting Limit	Page 1 of (
	0	RSD is greater than RSDlimit	Р	Sample pH greater than 2.	1 4 50 1 01 1
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit	
	S	Spike Recovery outside accepted recovery limits			

Analytical Report Lab Order 1405045

Date Reported: 5/7/2014

Hall Environmental Analysis Laboratory, Inc.

• •

•

QC SUMMARY REPORT

1405045 *07-May-14*

Client:	Blagg Engineering
Project:	GCU 213

Sample ID MB-12983	SampType: MBLK	TestCode: EPA Method	300.0: Anions		
Client ID: PBS	Batch ID: 12983	RunNo: 18386			
Prep Date: 5/2/2014	Analysis Date: 5/2/2014	SeqNo: 530932	Units: mg/Kg		
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual
Chloride	ND 1.5				
Chloride Sample ID LCS-12983	ND 1.5 SampType: L CS	TestCode: EPA Method	300.0: Anions		
		TestCode: EPA Method RunNo: 18386	300.0: Anions		
Sample ID LCS-12983 Client ID: LCSS	SampType: LCS		300.0: Anions Units: mg/Kg		
Sample ID LCS-12983 Client ID: LCSS	SampType: LCS Batch ID: 12983 Analysis Date: 5/2/2014	RunNo: 18386		RPDLimit	Qual

Qualifiers:

- . * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 2 of 6

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.	

WO#: 1405045

07-May-14

Client: Blagg Engineering GCU 213 **Project:** Sample ID MB-12981 SampType: MBLK TestCode: EPA Method 418.1: TPH Client ID: PBS Batch ID: 12981 RunNo: 18411 Prep Date: 5/2/2014 Analysis Date: 5/6/2014 SeqNo: 531748 Units: mg/Kg Analyte Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual Petroleum Hydrocarbons, TR ND 20 Sample ID LCS-12981 SampType: LCS TestCode: EPA Method 418.1: TPH Client ID: LCSS Batch ID: 12981 RunNo: 18411 Prep Date: 5/2/2014 Analysis Date: 5/6/2014 SeqNo: 531749 Units: mg/Kg PQL SPK value SPK Ref Val %REC Analyte Result LowLimit HighLimit %RPD RPDLimit Qual 100 Petroleum Hydrocarbons, TR 20 100.0 0 104 80 120 Sample ID LCSD-12981 SampType: LCSD TestCode: EPA Method 418.1: TPH Client ID: LCSS02 Batch ID: 12981 RunNo: 18411 Prep Date: 5/2/2014 Analysis Date: 5/6/2014 SeqNo: 531751 Units: mg/Kg SPK value SPK Ref Val %REC LowLimit Analyte Result PQL HighLimit %RPD RPDLimit Qual 99 100.0 Petroleum Hydrocarbons, TR 20 0 98.6 80 120 5.72 20

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 6

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

WO#: 1405045

07-May-14

_

Client: Blagg Project: GCU 2	Engineering 213								
Sample ID MB-12982	SampType	e: MBLK	Tes	tCode: El	PA Method	8015D: Dies	el Range (Organics	
Client ID: PBS	Batch ID): 12982	F	RunNo: 1	8356				
Prep Date: 5/2/2014	Analysis Date	e: 5/2/2014	5	SeqNo: 5	30268	Units: mg/H	ζg		
Analyte	Result F	PQL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10							
Surr: DNOP	8.4	10.00		84.4	57.9	140			
Sample ID LCS-12982	SampType	e: LCS	Tes	tCode: EF	PA Method	8015D: Diese	el Range (Drganics	
Client ID: LCSS	Batch ID	12982	F	RunNo: 18	3356				
Prep Date: 5/2/2014	Analysis Date	: 5/2/2014	S	SeqNo: 5	30310	Units: mg/K	g		
Analyte	Result F	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	49	10 50.00	0	97.9	60.8	145			
Surr: DNOP	4.4	5.000		88.8	57.9	140			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

QC SUMMARY REPORT

WO#: 1405045

07-May-14

.....

Hall Environmental Analysis Laboratory, Inc.

Client:	Blagg Engineering
Project:	GCU 213

Sample ID MB-12961	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Range
Client ID: PBS	Batch ID: 12961	RunNo: 18363	
Prep Date: 5/1/2014	Analysis Date: 5/2/2014	SeqNo: 530504	Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Gasoline Range Organics (GRO)	ND 5.0		
Surr: BFB	840 1000	84.0 74.5	129
Sample ID LCS-12961	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Range
Client ID: LCSS	Batch ID: 12961	RunNo: 18363	
Prep Date: 5/1/2014	Analysis Date: 5/2/2014	SeqNo: 530505	Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Gasoline Range Organics (GRO)	25 5.0 25.00	0 99.3 71.7	134
Surr: BFB	920 1000	91.9 74.5	129
Sample ID MB-12990 MK	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Range
Client ID: PBS	Batch ID: R18376	RunNo: 18376	
Prep Date:	Analysis Date: 5/5/2014	SeqNo: 531630	Units: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Surr: BFB	840 1000	84.2 74.5	129
Sample ID LCS-12990 MK	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Range
Client ID: LCSS	Batch ID: R18376	RunNo: 18376	
Prep Date:	Analysis Date: 5/5/2014	SeqNo: 531635	Units: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Surr: BFB	930 1000	92.6 74.5	129

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 6

QC SUMMARY REPORT

GCU 213

Client: Blagg Engineering

Project:

Sample ID MB-12961	Samp	Гуре: М	BLK	Tes	TestCode: EPA Method 8021B: Volatiles					
Client ID: PBS	Batch ID: 12961			F	RunNo: 18363					
Prep Date: 5/1/2014	Analysis [Date: 5	/2/2014	S	SeqNo: 5	30547	Units: mg/k	٢g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.99		1.000		98.9	80	120			
Sample ID LCS-12961	Samp1	Type: LC	:s	Tes	tCode: E	PA Method	8021B: Vola	tiles		
Client ID: LCSS	Batci	h ID: 12	961	F	RunNo: 1	8363				
Prep Date: 5/1/2014	Analysis D)ate: 5/	2/2014	S	SeqNo: 5	30548	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	111	80	120			
Toluene	1.0	0.050	1.000	0	104	80	120			
Ethylbenzene	1.0	0.050	1.000	0	102	80	120			
Xylenes, Total	3.1	0.10	3.000	0	102	80	120			
Surr: 4-Bromofluorobenzene	1.1		1.000	-	106	80	120			
Sample ID MB-12990 MK	SampT	ype: MI	BLK	Tes	tCode: El	PA Method	8021B: Volat	iles		
Client ID: PBS	Batch	n ID: R1	8376	R	RunNo: 1	B376				
Prep Date:	Analysis D)ate: 5/	5/2014	S	SeqNo: 5	31665	Units: %RE	с		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	0.99		1.000		99.1	80	120			
Sample ID 100NG BTEX LC	s SampT	ype: LC	S	Test	tCode: EI	PA Method	8021B: Volat	iles		
Client ID: LCSS	Batch	n ID: R1	8376	R	RunNo: 1	3376				
Prep Date:	Analysis D	ate: 5/	5/2014	S	eqNo: 5	31666	Units: %RE	С		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	1.1		1.000		108	80	120			

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Value above quantitation range Ε
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank В
- Н Holding times for preparation or analysis exceeded

Page 6 of 6

- ND Not Detected at the Reporting Limit
- Sample pH greater than 2. Р
- RL Reporting Detection Limit

WO#: 1405045



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Number:	1405045		RcptNo:	1
Received by/date: CS	05/01/14				
Logged By: Celina Sessa	5/1/2014 10:03:00 AM				
Completed By: Celina Sessa	5/1/2014 1:59:42 PM				
Reviewed By: MA	05/0/01				
Chain of Custody			•		i
1. Custody seals intact on sample bottles?		Yes 🗌	No 🗌	Not Present 🗹	
2. Is Chain of Custody complete?		Yes 🗹	No 🗌	Not Present	
3. How was the sample delivered?		Courier			
<u>Log In</u>					
4. Was an attempt made to cool the sampl	es?	Yes 🗹	No 🗌	NA 🗌	
5. Were all samples received at a temperat	ure of >0° C to 6.0°C	Yes 🗹	No 🗌	NA 🗌	
6. Sample(s) in proper container(s)?		Yes 🗹	No 🗌		
7. Sufficient sample volume for indicated te	st(s)?	Yes 🗹	No 🗌		
8. Are samples (except VOA and ONG) pro	perly preserved?	Yes 🗹	No 🗔		
9. Was preservative added to bottles?		Yes 🗌	No 🗹	· NA 🗌	
10.VOA vials have zero headspace?		Yes 🗌	No 🗌	No VOA Vials 🗹	
11. Were any sample containers received br	oken?	Yes 🗆	No 🗹 .	# of preserved	
12.Does paperwork match bottle labels?		Yes 🗹	No 🗂	bottles checked for pH:	
(Note discrepancies on chain of custody)			N. 🗖	(<2 or Adjusted?	>12 unless noted)
13, Are matrices correctly identified on Chair		Yes 🗹			
14 Is it clear what analyses were requested?15. Were all holding times able to be met?	1	Yes 🗹	No 🗌	Checked by:	
(If no, notify customer for authorization.)		Yes 🗹			, , · · · · · · · · · · · · · · · ·
Special Handling (if applicable)					
16. Was client notified of all discrepancies w	ith this order?	Yes 🗌	No 🗌	NA 🗹	
Person Notified:	Date		·····		
By Whom:	Via:	eMail 🛛 F	hone 🗌 Fax	In Person	
Regarding:					
Client Instructions:					
17. Additional remarks:					

18. <u>Cooler Information</u>

Cooler No	Temp ^o C	Condition	Seal Intact	Seal No	Seal Date	Signed By
1	2.2	Good	Yes			

Client	Blagg Engineering, Inc.			Standard 🗆 Rush				ANALYSIS LABORATORY											
BP America				Project Name: GCU 213					<u>.</u> .						nenta				
Mailing Address: P.O. Box 87								4901 Hawkins NE - Albuquerque, NM 87109											
Bloomfield, NM 87413				Project #.				Tel. 505-345-3975 Fax 505-345-4107											
Phone #: (505)320-1183								të nga. Nga s			Ana	lysis	Req	uest	17 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1. 5	ادرینے میں ا ۲۰		
email or Fax#:				Project Manager:															
QA/QC Package:				Jeff Blagg						ĝ									
				Sampler: Jeff Blagg				1										19	
🗆 EDD (Type)				On Ice: 🖄 Yes 🖾 No Sample Temperature: 📿 🎗 🧟						GRO								ر or ∧	
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	heal n 140504		BTEX (8021)		1PH 8015B (GRO / DRO)	IPH 418.1						Chloride	Air Bubbles (Y or N)	
04/25/2014	12:55	Soil	95 BGT 5-pt @ 4'	1x 4oz	cool	-001		×			×						x		
·····										-+-	+		1			-+	1-1		
				<u> </u>				┼╌┼		+	-+-	-	+	╏──┤			++	·	
							··· · ·	┼╌┧	-+	╧	+-	-	+	┝──╽			╂━┤		
	+	+						╉╼┽	-+-	-+-			+			_{	╀╼┥	<u>-</u> +-	
	+	+					_ <u>. </u>	╋╼┦	-+	+	-+-	+	╉──	┝─┤	-+-		╁╾┥	┝─┼╍	
								┟╌┤	-+	+			+				<u> </u>	┢╼╍┨╌┙	
<u></u>	·		·					- +	-+-				+	┝─┦			┿╾┥	┝━╋╼	
	<u> </u>				<u> </u>			┞╺┥			-+-		+	┟╌╽			╁━━┥	┝─┼╸	
<u> </u>				<u> </u>				┝─┤	-+-								\downarrow	┝─┼─	
				<u> </u>				+ + + + + + + + + + + + + + + + + + +					<u> </u>					┝━┠╧	
	ļ				L						4	-						┟──┟┙	
Date:	Time:	Relinquished by:		Received by: Date Time			Remarks: Bill BP Paykey: ZEVH01BGT2												
³⁰ /2014 Date:	Time: Relinquished by:			Received by: Date Time				BP Contact: Jeff Peace Please copy results to: peace.jeffrey@bp.com											
4130/14	1735	11 IN	holden Walles	Celar	- due	05/01/14	10:03											<u> </u>	
lf ne	ecessary, samples	s submitted to I	all Environmental may be subcontract	ed to other accredite	d laboratories. This	s serves as notice of	this possib	illity. An	iy sub-o	ontrac	ed dat	a will be	clearly	notated	d on the	analytics	al report	ι. ·	

.

S



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

January 30, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 213

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about February 20, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

9] Jakk

Jerry Van Riper Surface Land Negotiator BP America Production Company

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

January 30, 2014

. •

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 213 API 30-045-11618 (G) Section 8 – T28N – R12W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Teacl

Jeff Peace BP Field Environmental Advisor

(505) 326-9479



