District 1
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

	Pit, Below-Grade Tank, or
	Proposed Alternative Method Permit or Closure Plan Application
11990 45-25202	Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
	or proposed alternative method
	Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
	at approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the

environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. Operator: BP America Production Company______ OGRID #:___778____ Address: 200 Energy Court, Farmington, NM 87401_____ Facility or well name: Gallegos Canyon Unit 174E API Number: 3004525202 U/L or Qtr/Qtr ___E___ Section ____28__ Township 28N Range 12W County: San Juan Center of Proposed Design: Latitude ____36.63652 _____ Longitude __-108.12438 _____ NAD: ☐1927 ☑ 1983 Surface Owner: ☐ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover ☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined Liner type: Thickness _____mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other ☐ String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A Volume: 95.0 bbl Type of fluid: Produced water Tank Construction material: Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off ☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other Double walled/double bottomed side walls not visible Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church)	', hospital,
☐ Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	·- <u>-</u>
6. Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	·
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Ycs ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	uments are
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	uments are
□ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	e documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	Fluid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.	☐ Yes ☐ No
- NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	·
Within a 100-year floodplain FEMA map	☐ Yes ☐ No ☐ Yes ☐ No
	L res l No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plants a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe that the information submitted with the	
Signature: Date:	
e-mail address:Telephone:	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 7/14/2 Title: OCD Permit Number:	øH
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting to the closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not consection of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:4/22/2014	
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-loo ☐ If different from approved plan, please explain.	pp systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please ind mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits)	licate, by a check

Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirem	
Name (Print): Jeff Peace	Title: Area Environmental Advisor
Signature: Self Page	Date:June 24, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit 174E Tank A (95 bbl BGT) API No. 3004525202 Unit Letter E, Section 28, T28N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was sent. This work was done as part of the Gallup recompletion project and was not done through the current ongoing BGT replacement and removal project. Therefore, the BP personnel responsible for submitting the notice were not aware this BGT was going to be removed. BP personnel are aware of this issue and will work to make sure any BGT removal and closure is properly noticed.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was sent. This work was done as part of the Gallup recompletion project and was not done through the current and ongoing BGT replacement and removal project. Therefore, the BP personnel responsible for submitting the notice were not aware this BGT was going to be removed. BP personnel are aware of this issue and will work to make sure any BGT removal and closure is properly noticed.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
 - f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
 - g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
 - h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
 - i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
 - j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
 - k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT – Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total

petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that

cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following:
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District 1</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

* 1			Rele	ease Notific	atio	n and Co	orrective A	ction			- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1
						OPERA	ГOR	🗌 Initial Report 🛛 Final			Final Report
Name of Company: BP						Contact: Jeff Peace					
		Court, Farm					No.: 505-326-94				
Facility Nar	ne: Galleg	gos Canyon l	Jnit 174E	· ·		Facility Typ	e: Natural gas v	vell			
Surface Ow	ner: Feder	al		Mineral C	wner:	Federal		APIN	o. 30045252	202	
				LOCA	TIO	N OF REI	LEASE				
Unit Letter	Section	Township	Range	Feet from the	North	/South Line	Feet from the	East/West Line	County: S	an Juar	1
Е	28	28N	12W	1,450	North		410	West			
	I	Lat	itude3	6.63652	,	_ Longitud	e108.12438				
				NAT	URE	OF RELI			•		
Type of Rele							Release: N/A		Recovered: N		
Source of Re	lease: belov	w grade tank –	· 95 bbl, Ta	ank A		Date and H N/A	lour of Occurrenc	e: Date and	l Hour of Dis	covery	: N/A
Was Immedia	ite Notice (Yes 🗆	No ⊠ Not Re	anired	If YES, To	Whom?				
By Whom?				110 23 1101110		Date and H	our				
Was a Watero	course Read	ched?	Yes ⊠	No		If YES, Volume Impacting the Watercourse.					
If a Watercou	rse was Im					<u> </u>					
		,									
							the BGT was dor		to ensure no	soil im	pacts from
the BGT. So	il analysis r	esulted in TPI	н, втех а	and chlorides belo	w stanc	lards. Analys	is results are attac	hed.			
					noved a	and the area u	nderneath the BG	T was sampled.	The excavated	l area v	vas
backfilled and	d compacte	d and is still w	ithin the a	ctive well area.							:
I hereby certi	fy that the i	nformation gi	ven above	is true and compl	ete to t	he best of my	knowledge and ur	nderstand that pur	suant to NM	OCD rt	ıles and
regulations al	loperators	are required to	report an	d/or file certain re	elease n	otifications ar	nd perform correct	tive actions for re	leases which	may en	ndanger
							arked as "Final Re on that pose a thre				
							e the operator of r				
		ws and/or regu			eport a		e the operator of t	espendiening for	zomprianee vi		
1	^						OIL CONS	SERVATION	DIVISIO	N	
Signature:	all 1) saco									
(y // U					Approved by Environmental Specialist:					
Printed Name	. Jen Peace	<u> </u>									
Title: Area Ei	vironment	al Advisor			-	Approval Dat	e: ·	Expiration	Date:		
E-mail Addre	ss: peace.jo	effrey@bp.cor	n			Conditions of	Approval:		Attached		
Date: June 2	4, 2014		Phone: 50)5-326-9479							

Date: June 24, 2014

^{*} Attach Additional Sheets If Necessary

ВР		NGINEERING, INC.	7442	API#: 3004525202		
CLIENT:	i -	BLOOMFIELD, NM 87 05) 632-1199	413	TANK ID (if applicble):		
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTHER:		PAGE #:1 of1_		
SITE INFORMATION				DATE STARTED: 04/10/14		
	28N RNG: 12W PM			DATE FINISHED:		
1/4 -1/4/FOOTAGE: 1,450'N / 410 LEASE #: SF078828A		TYPE: FEDERAL STATE / FEE CROSSFIRE CONTRACTOR: MBF - C. PARK		ENMRONMENTAL SPECIALIST(S): JCB		
REFERENCE POINT	_	s coord.: 36.63662 X		GLELEV: 5.603'		
	GPS COORD.:			RING FROM W.H.: 114', S71E		
2) 21 bot (b) (3W/bb)	_			RING FROM W.H.:		
3)	GPS COORD.:		_ DISTANCE/BEA	RING FROM W.H.:		
4)	GPS COORD.:		_ DISTANCE/BEA			
SAMPLING DATA.	CHAIN OF CUSTODY RECORD(S) #	OR LAB USED: HALL		OVM READING (ppm)		
1) SAMPLEID: 95 BGT 5-pt. @	5' SAMPLE DATE: 04/10	0/14 SAMPLETIME: 0815 LAB ANA	LYSIS: 418.1/8	· · · · ·		
2) SAMPLEID: ZI DUI 3-pi.(U)	SAMPLEDATE: 64/16	3/14 SAMPLE TIME 3022 LAB AND	LYSIS: 416.1/6	615B/3321B/368.6 (OI) - 9.8		
3) SAMPLEID:	SAMPLE DATE:	SAMPLE TIME: LAB ANA	LYSIS:			
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANA	LYSIS:			
SOIL DESCRIPTION	SOIL TYPE: SAND / SILTY SAND	SILT / SILTY CLAY / CLAY / GRAVEL / OTI	HER			
SOIL COLOR: DARK YELLO				DHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC		
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS):		DENSITY (COHESIVE CLAYS & SILTS): HC ODOR DETECTED: YES NO EXPLA				
MOISTURE: DRY/SLIGHTLY MOIST MOIST W	ET / SATURATED / SUPER SATURATED					
SAMPLE TYPE: GRAB COMPOSITE # OF PTS. 5 ANY AREAS DISPLAYING WETNESS: YES / NO EXPLANATION - WATER FROM NAPI						
DISCOLORATION/STAINING OBSERVED: YES NO EXPLANATION- IRRIGATION. SITE OBSERVATIONS: LOST INTEGRITY OF EQUIPMENT: YES NO EXPLANATION-						
APPARENT EVIDENCE OF A RELEASE OBSERVE						
EQUIPMENT SET OVER RECLAIMED AREA:						
OTHER:				·		
SOIL IMPACT DIMENSION ESTIMATION:				IMATION (Cubic Yards) : NA		
	EAREST WATER SOURCE: >1,000		000' NMOC	D TPH CLOSURE STD: 100 ppm		
SITE SKETCH [BGT Located: off on si	te PLOT PLAN circle: a	ttached 0VM	CALIB. READ. = 100.4 ppm RF =1.00		
			1	CALIB. GAS = 100 ppm		
			N TIME			
		PROD. TANK	1	MISCELL. NOTES		
		/ IMM		O:		
		BERM	_	C: ZDCS01GEN1		
	CEDADATOD	~ \frac{1}{2}	<u>P</u>	J#: X5-005-MK		
W.H. ⊕	SEPARATOR —		1 -	ermit date(s): 06/14/10		
-		DEDM	O	CD Appr. date(s): 03/24/14		
	(95)	BERM	Tan ID	ppm = parts per million		
	PBGTL T.B. ~ 5'	* (x*x)/		BGT Sidewalls Visible: Y /N		
	B.G.	X - S	ס.א.ט <u>.</u> ן⊢≃	BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N		
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	JN DEPRESSION; B.G. = BELOW GRADE; B = E OW-GRADE TANK LOCATION; SPD = SAMPLE	BELOW; T.H. = TEST HOLE; ~ = APPROX.; W.H. = W POINT DESIGNATION; R.W. = RETAINING WALL; N	4 1/07	agnetic declination: 10° E		
APPLICABLE OR NOT AVAILABLE; SW - SINGLI		TTOM; DB - DOUBLE BOTTOM.	1	agnotic acompation. TO L		
NOTES:		ONSITE: 04/10/14				

revised: 11/26/13

BEI1005E-6.SKF

Analytical Report

Lab Order 1404592

Date Reported: 4/22/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT 5-pt @ 5'

Project: GCU 174E

Collection Date: 4/10/2014 8:15:00 AM

Lab ID: 1404592-001

Matrix: SOIL

Received Date: 4/12/2014 12:00:00 PM

Analyses	Result	RL Qı	ıal Units	DF	Date Analyzed	Batch	
EPA METHOD 8015D: DIESEL RANGE ORGANICS Analyst:							
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	4/15/2014 8:46:36 PM	12676	
Surr: DNOP	68.3	66-131	%REC	1	4/15/2014 8:46:36 PM	12676	
EPA METHOD 8015D: GASOLINE RANG	GE				Analyst	: RAA	
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	4/16/2014 1:31:02 AM	12692	
Surr: BFB	87.6	74.5-129	%REC	1	4/16/2014 1:31:02 AM	12692	
EPA METHOD 8021B: VOLATILES					Analyst	: RAA	
Benzene	ND	0.047	mg/Kg	1	4/16/2014 1:31:02 AM	12692	
Toluene	ND	0.047	mg/Kg	1	4/16/2014 1:31:02 AM	12692	
Ethylbenzene	ND	0.047	mg/Kg	1	4/16/2014 1:31:02 AM	12692	
Xylenes, Total	ND	0.094	mg/Kg	1	4/16/2014 1:31:02 AM	12692	
Surr: 4-Bromofluorobenzene	102	80-120	%REC	1	4/16/2014 1:31:02 AM	12692	
EPA METHOD 300.0: ANIONS					Analyst	JRR	
Chloride	ND	30	mg/Kg	20	4/15/2014 12:24:14 PM	12716	
EPA METHOD 418.1: TPH					Analyst	BCN	
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	4/15/2014	12673	

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level,
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404592

22-Apr-14

Client:

Blagg Engineering

Project:

GCU 174E

	715			
Sample ID MB-12673	SampType: MBLK	TestCode: EPA Method	418.1: TPH	
Client ID: PBS	Batch ID: 12673	RunNo: 17999		
Prep Date: 4/11/2014	Analysis Date: 4/15/2014	SeqNo: 519327	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	ND 20			
Sample ID LCS-12673	SampType: LCS	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS	Batch ID: 12673	RunNo: 17999		
Prep Date: 4/11/2014	Analysis Date: 4/15/2014	SeqNo: 519328	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	96 20 100.0	0 96.4 80	120	
Sample ID LCSD-12673	SampType: LCSD	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS02	Batch ID: 12673	RunNo: 17999		
Prep Date: 4/11/2014	Analysis Date: 4/15/2014	SeqNo: 519329	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	98 20 100.0	0 97.8 80	120 1.42	20

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 140

1404592 22-Apr-14

Client:

Blagg Engineering

Project:

GCU 174E

Project: GCU 1	74E 	
Sample ID MB-12676	SampType: MBLK	TestCode: EPA Method 8015D: Diesel Range Organics
Client ID: PBS	Batch ID: 12676	RunNo: 17956
Prep Date: 4/11/2014	Analysis Date: 4/14/2014	SeqNo: 518235 Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO)	ND 10	
Surr: DNOP	7.2 10.00	71.6 66 131
Sample ID LCS-12676	SampType: LCS	TestCode: EPA·Method 8015D: Diesel Range Organics
Client ID: LCSS	Batch ID: 12676	RunNo: 17956
Prep Date: 4/11/2014	Analysis Date: 4/14/2014	SeqNo: 518236 Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO)	45 10 50.00	0 89.1 60.8 145
Surr: DNOP	3.6 5.000	72.1 66 131
Sample ID MB-12726	SampType: MBLK	TestCode: EPA Method 8015D: Diesel Range Organics
Client ID: PBS	Batch ID: 12726	RunNo: 18017
Prep Date: 4/15/2014	Analysis Date: 4/17/2014	SeqNo: 521794 Units: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Surr: DNOP	8.4 10.00	84.4 57.9 140
Sample ID LCS-12726	SampType: LCS	TestCode: EPA Method 8015D: Diesel Range Organics
Client ID: LCSS	Batch ID: 12726	RunNo: 18017
Prep Date: 4/15/2014	Analysis Date: 4/17/2014	SeqNo: 521795 Units: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Surr: DNOP	4.3 5.000	86.4 57.9 140

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404592

22-Apr-14

Client:

Blagg Engineering

Project:

GCU 174E

Sample ID MB-12692 SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range Client ID: PBS Batch ID: 12692 RunNo: 17997 Prep Date: 4/14/2014 Analysis Date: 4/15/2014 SeqNo: 519538 Units: mg/Kg Analyte Result **PQL** SPK value SPK Ref Val %REC LowLimit HighLimit %RPD **RPDLimit** Qual Gasoline Range Organics (GRO) ND 5.0 Surr: BFB 870 1000 86.9 74.5 129

Sample ID LCS-12692 SampType: LCS TestCode: EPA Method 8015D: Gasoline Range Client ID: LCSS Batch ID: 12692 RunNo: 17997 Prep Date: 4/14/2014 Analysis Date: 4/15/2014 SeqNo: 519539 Units: mg/Kg %RPD Result **PQL** SPK value SPK Ref Val %REC LowLimit HighLimit **RPDLimit** Qual Analyte Gasoline Range Organics (GRO) 24 5.0 25.00 0 96.3 71.7 134 Surr: BFB 920 1000 91.9 74.5 129

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1404592

22-Apr-14

Client:

Blagg Engineering

Project: GCU 1	74E											
Sample ID MB-12692	SampType: MBLK Batch ID: 12692			Tes		, , , , ,						
Client ID: PBS				F	RunNo: 1	7997						
Prep Date: 4/14/2014	Analysis D	Date: 4/	15/2014	SeqNo: 519613		Units: mg/h	(g					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	ND	0.050										
Toluene	ND	0.050										
Ethylbenzene	ND	0.050										
Xylenes, Total	ND	0.10										
Surr: 4-Bromofluorobenzene	1.0		1.000		104	80	120					
Sample ID LCS-12692 SampType: LCS				TestCode: EPA Method 8021B: Volatiles								
Client ID: LCSS	Batch	n ID: 12	692	F	RunNo: 1	7997				,		
Prep Date: 4/14/2014	Analysis D	ate: 4/	15/2014	SeqNo: 519614			Units: mg/k	(g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	1.1	0.050	1.000	0	110	80	120					
Toluene	1.0	0.050	1.000	0	102	80	120					
Ethylbenzene	1.0	0.050	1.000	0	101	80	120					
Xylenes, Total	3.0	0.10	3.000	0	101	80	120					
Surr: 4-Bromofluorobenzene	1.1		1.000		110	80	120					

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits
- О RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- В Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2.

RLReporting Detection Limit Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Number: 14045	92		RcptN	lo: 1
Received by/date: AF	x1/12/14				
Logged By: Lindsay Mangin	4/12/2014 12:00:00 PM		Jacoby Hloriggo		
Completed By: Lindsay Mangin	4/14/2014 8:p3:35 AM		Juney Hope		
Reviewed By:	01/11/2014				
Chain of Custody	09/19/2019		•	•	
: 1. Custody seals intact on sample bottles?	Yes	:	No	Not Present >	•
2. Is Chain of Custody complete?	Yes	~	No	Not Present	
3. How was the sample delivered?	Couri	<u>er</u>			
<u>Log In</u>					
4. Was an attempt made to cool the samples	? Yes	~	No	NA	
5. Were all samples received at a temperatur	e of >0° C to 6.0°C Yes	Y	No	NA	
6. Sample(s) in proper container(s)?	Yes	Y .	No		
7. Sufficient sample volume for indicated test	(s)? Yes	y.	No		
8. Are samples (except VOA and ONG) prope		~	No		
9. Was preservative added to bottles?	Yes		No 🗸	NA	
10.VOA vials have zero headspace?	· Yes		No	No VOA Vials	,
i11. Were any sample containers received broken	ten? Yes		No 🗸		
	Yes	1.2°	No	# of preserved bottles checked for pH:	
12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)	res	×			2 or >12 unless noted)
13. Are matrices correctly identified on Chain of	f Custody? Yes	V	No	Adjusted?	
14. Is it clear what analyses were requested?	Yes	✓	No		
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes	√ ,	No	Checked by	y:
Special Handling (if applicable)					
16. Was client notified of all discrepancies with	this order?	:	No	NA N	•
Person Notified:	Date:	CONTRACTOR AND	TO DO SERVICE DE LA CONTRACTION DEL CONTRACTION DE LA CONTRACTION	,	
By Whom:	Via: eMa	il I	Phone Fax	In Person	
Regarding:					
Client Instructions:					
17. Additional remarks:					
18. Cooler Information					
Cooler No Temp °C Condition S	Seal Intact Seal No Seal Da	te	Signed By		
1 4.1 Good Ye	es : : : : : : : : : : : : : : : : : : :	. !			

BR America			Project Name: ANALYSIS LABORATORY									? `					
			Project Name:						-				-				
Mailing Address R:O: Box:87:		GCU 174E 4901 HawkinstNE - Albuquarque, NM, 87109.															
Bloomfield. NM :				Project#:				Tel 505-345-3975 Fax 505-345-4107 Analysis Request									
Phone #: (595)320-1/183			_				The Control of the Co		Ar	nalysi	siReq	uest	,				
email of Fax	d :	-		Project Mana	iger:		,	-		1						1	1
OAVOC Package: Standard Dilevel:4 (Full Validation)			Jeff Blagg:				ွ်						:	:			
☐ Other			······································	Sampler: Jeff/Blagg				(GRO/LDRO)									9
© EDD (Type)			On Ice Dayes D No. Sample Temperature: 17.4				180		- :							ō	
٦.			11	Sample: J.em	beigmie: A	V	= = =	9	اييا							:	S
Date?	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.) BTEX (802)	TPH B015B	TPH 418 1						Chloride	2010	Air Bubbles (Y or N)
04/10/2014	8,15	Soll	95 BGT-5-pt @ 5'	1x 4oz	cool	-001	:x·	×.			*		\prod		×	3 -	T
94/10/2014	0.22	Sen	21 SCT 6 pt @ 6	1× 10E	- söél -	-002			-ŝ			1					,
			1		<u> </u>								H		-	+	T
		4 = -			1		· -						1 1	+	- 		╁
1	<u>-1</u>			<u> </u>	!	[#	7 -		+		+-	1	十		+	+
		-1	:			<u> </u>	- 	· · ·			=	+-		\dashv	\dashv	1.	+
	1				' 	1						+	1- 1	+	-	+	-
		1			,		* ! *	- 1				•	1	\dashv	+	+	-
			1					·		. · ,		-	+	-+	- 1	- 	+
-		- ,	:		I ·							<u> </u>			+	+-	+
	1											+		+		-	+
	<u> </u>			<u> </u>		<u> </u>	:	1		 		<u>:1 .</u>	- 1			+	+
Date:	Time	Relinquist	ned by:	Received by:	<u> </u>	Date Time	Ren	narks: I	i 3∭.BF	<u>. </u>		<u>l.</u>		.	!	.]	<u>: </u>
Date:	930 Time:	Relinguished by Relinguished by		Received by:	u Litelen	Date Time											
Date:	Ĩ724	250	منعلق لماستلاقة		ÜL.	9/14/4 720	Pea *	ce} F	Please copy results to peace jeffrey@bp.com								om)
i kine		s stanlited to I	al Environmeral may be subcontract	ed to pitter accrediti	ed laboratories. This		ssibility, A	ny syp <u>-چې</u> ټر	iacted i	PV CIE	j oe des	ny notat	ed on th	o anāly	vicaj jes	on!	

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

May 7, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 174E API 30-045-25202 (G) Section 28 – T28N – R12W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close two 95 bbl BGT's that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



