

Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

5. Lease Serial No.

NMNM 112953 NMNM 109386

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter and the sum of abandoned well. Use Form 3160-3 (APD) for such proposals: 7. If Unit of CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE - Other instructions on page 2.1 N/A 1. Type of Well 8. Well Name and No. Lybrook P28-2306 01H Farmington Field O Oil Well Gas Well Other **Gureau of Land Manag** Name of Operator Encana Oil & Gas (USA) Inc. 9: API Well No. 10. Field and Pool or Exploratory Area 3b. Phone No. (include area code) 3a. Address 370 17th Street, Suite 1700 Denver, CO 80202: Lybrook Gallup 720-876-5867 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
8HL: 336' FSL and 1280' FEL Sec 28, T23N, R6W 11. Country or Parish, State Sandoval, New Mexico BHL: 2372 FNL and 1610' FEL Sec 4, T22N, R6W 12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Deepen Acidize Production (Start/Resume) Water Shut-Off Notice of Intent Alter Casing Fracture Treat Well Integrity Reclamation Other Conductor, Spud, New Construction Casing Repair Recomplete ✓ Subsequent Report Surface casing/cement ___ Change Plans Plug and Abandon Temporarily Abandon Plug Back Water Disposal Final Abandonment Notice Convert to Injection

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) JUL 0 3 2014

Set 20" 94# conductor at 120' on 3/23/14. 100sk Type I Neat cerrent, 16.6ppg. Cement to surface ✓

Well soud 6/24/2014 ✓

Set surface casing string 6/24/14. Gelled freshwater mud system.

Hole diameter: 12.25", casing diameter: 9.625", casing weight and grade: 36ppf J55 LTC. Depth of 12.25" hole from 0-505TVD/MD. Casing set from surface to 505 TVD/MD.

Pumped 320 sacks of Type III Halcern Cement + 2% bwoc CaCl + 0.125 lbs/sk Poly-E-Flake, yield 1.17 cuft/sk, mixed at 15.8 ppg on 6/23/14 . Circulated 33bbls to surface. WOC 13.5 hours for surface casing.

Float collar at 463'. TOC at surface and BOC at 505'.

ACCEPTED FOR RECORD

Tested BOP 6/25/14 to 3000# for 30minutes. Tested casing 6/25/14 to 1500# for 30 minutes. No pressure drop. 1 2014

Drilled out cement and float collar 6/26/14.

FARMINGTON FIELD OFFICE BY: William Tambelkon

Operations Technologist	
6/30/14	-
THIS SPACE FOR FEDERAL OR STATE OFFICE USE	
Title	Date
Office	`
	OR STATE OFFICE USE

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

