District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

#### State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

# Pit, Below-Grade Tank, or

Proposed Alternative Method Permit or Closure	Plan Application
Proposed Alternative Method Permit or Closure    Below grade tank registration   Permit of a pit or proposed alternative method   Closure of a pit, below-grade tank, or proposed alternation   Modification to an existing permit/or registration   Closure plan only submitted for an existing permitted or proposed alternative method	
Instructions: Please submit one application (Form C-144) per individual pit, below	v-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable g	
	770
Operator: BP America Production Company OGRID #:	OIL CONS. DIV DIST. 3
Address:200 Energy Court, Farmington, NM 87401	OIF OOIGO: DIA DIO!!
Facility or well name:Gallegos Canyon Unit 95E	JUL <b>3 0</b> 2014
API Number:3004525500 OCD Permit Number:	
U/L or Qtr/QtrP Section31 Township28N Range11W	County:San Juan
Center of Proposed Design: Latitude36.61433 Longitude108.04035_	NAD: □1927 🛛 1983
Surface Owner:  Federal  State  Private  Tribal Trust or Indian Allotment	
Pit: Subsection F, G or J of 19.15.17.11 NMAC     Temporary: Drilling Workover     Permanent Emergency Cavitation P&A Multi-Well Fluid Management Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC C   String-Reinforced     Liner Seams: Welded Factory Other Volume: bb	ther
3.    Below-grade tank: Subsection I of 19.15.17.11 NMAC   Tank A	
Volume:95.0bbl Type of fluid:Produced water	
Tank Construction material:Steel	
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic of	verflow shut-off
☐ Visible sidewalls and liner ☒ Visible sidewalls only ☐ Other _Single walled/double bott	omed
Liner type: Thicknessmil	
4.	

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

☐ Alternative Method:

5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church)	, hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC  12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
<ul> <li>Variances and Exceptions:</li> <li>Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.</li> </ul>	
Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
material are provided below. String effectia does not appry to drying pads of above-grade talks.	1
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
<u>Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.</u> NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks)  - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	!
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
<ul> <li>initial application.</li> <li>NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site</li> </ul>	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Naturations: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached.	
<ul> <li>□ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>□ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>□ A List of wells with approved application for permit to drill associated with the pit.</li> <li>□ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC</li> <li>□ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC</li> </ul>	.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### attached.  ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment	
<ul> <li>☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC</li> </ul>	·.
☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan	
<ul> <li>□ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>□ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>□ Nuisance or Hazardous Odors, including H₂S, Prevention Plan</li> <li>□ Emergency Response Plan</li> </ul>	•
Oil Field Waste Stream Characterization Monitoring and Inspection Plan	
☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.  Type:   Drilling: Workover: Emergency: Cavitation: P&A: Permanent Pit: Below-grade Tank: Multi-well F	luid Management Pit
Alternative  Proposed Closure Method: Waste Excavation and Removal	ruid Management ( it
<ul><li>☐ Waste Removal (Closed-loop systems only)</li><li>☐ On-site Closure Method (Only for temporary pits and closed-loop systems)</li></ul>	
☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	attached to the
closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	- ·
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sout provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 NMAC  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11.NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel	ief.
Name (Print): Title:	<u> </u>
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature: Approval Date: 8/21/  Title: OCD Permit Number:	2014
19.	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.    Closure Completion Date:5/30/2014	
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	t complete this

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirements.	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Pesce	Date:July 29, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

#### BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

# Gallegos Canyon Unit 95E API No. 3004525500 Unit Letter P, Section 31, T28N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

#### **General Closure Plan**

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
  - Notice to BLM is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

#### Notice to NMOCD is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.** 

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil. The area over the BGT is covered by the LPT and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

    Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

#### **Release Notification and Corrective Action**

			Itti	ase mount	auoi		rod		<b>.</b>	l D		C'ard Dans
N	DD					OPERATOR						
Name of Co			natan N	NA 97401		Contact: Jeff Peace Telephone No.: 505-326-9479						
Address: 20 Facility Nar				101 8 / 40 1			e: Natural gas v					
Facility Nai	ne. Ganego:	s Carryon C	IIII 93E			racility Typ	e. Naturai gas v	VC11	····	<del></del>		
Surface Ow	ner: Federal		Mineral C	wner: l	Federal		Al	PI No.	30045255	00		
				LOCA	TION	OF REI	LEASE					
Unit Letter P	1 1	Township 28N	Range 11W	Feet from the 1,020	North/ South	South Line	Feet from the 1,080	East/West I East	Line	County: Sa	n Juan	
		Lati	tude3	6.61433		_ Longitud	e108.04035_					
				NAT	URE	OF RELI	EASE					
Type of Relea	ase: none						Release: N/A	Vol	ume R	ecovered: N	/A	
Source of Re		grade tank –	95 bbl				lour of Occurrenc	e: Dat	e and F	lour of Disc	overy:	N/A
11/ I	( ) ( ) ( ) ( ) ( )					N/A	3371 0					
Was Immedia	ate Notice Gi		Yes [	No 🛛 Not Re	quired	If YES, To	wnom?					
By Whom?						Date and H						
Was a Water	course Reach		Yes 🛚	] No		If YES, Volume Impacting the Watercourse.						
If a Watercou	rse was Impa	acted Descri	he Fully *	*								
n a maiorea	noo was impe	10100, 5 00011		·								
							the BGT was don is results are attac		noval to	o ensure no	soil im	pacts from
					moved a	and the area u	nderneath the BG	T was samp!	ed. Th	e excavated	area w	'as
backimed and	i compacted	and is suit w	nunn ine a	active well area.								
	·											
L hereby certi	fy that the int	formation gi	ven above	is true and comn	lete to th	ne best of my	knowledge and u	nderstand the	nt nursi	ant to NMC	OCD ru	les and
							nd perform correc					
public health	or the enviro	nment. The	acceptanc	ce of a C-141 repo	rt by the	NMOCD m	arked as "Final Re	eport" does n	ot relie	eve the opera	ator of	liability
							on that pose a thre					
or the enviror federal, state,				tance of a C-141	report de	oes not reliev	e the operator of r	responsibility	for co	mpliance w	ith any	other
rederal, state,	or local laws	and/or regu	iations.				OIL CONS	CEDVAT	IONI I	DIVICIO	NI	
Signature: (	alf h	me					OIL CON	SERVAI.	<u>iON</u> .	<u>DI VISIO</u>	1/	
7110						Approved by Environmental Specialist:						
Title: Area E		Advisor				Approval Dat	e:	Expir	ation D	Date:		
E mail Add	sai nacaa laff	frau@hn ac	2					. 1 *				
E-mail Addre	ss. peace.jen	rey@op.con	1		<b></b>   '	Conditions of	Approvai:			Attached		
Date: July 2	9. 2014		Phone: 50	)5-326-9479								

<sup>\*</sup> Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, E	NGINEERING, INC. BLOOMFIELD, NM 8		API#: 3004	_
PICI O DEDADT.		D5) 632-1199 / RELEASE INVESTIGATION / OTHE	:R:	(if applicble):	
FIELD REPORT:				PAGE #:	of
SITE INFORMATION				DATE STARTED:	05/21/14
QUAD/UNIT: P SEC: 31 TWP:			ST: NM	DATE FINISHED:	
1/4-1/4/FOOTAGE: 1,020'S / 1,08		TYPE:  FEDERAL  STATE / FE ELKHORN CONTRACTOR: MBF - S. GLY		ENVIRONMENTAL SPECIALIST(S):	JCB
REFERENCE POINT					
		36.61433 X 108.04035	DISTANCE/BEA	RING FROM W.H.:	135', N75W
, , , ,				RING FROM W.H.:	
3)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) #	OR LAB USED: HALL		•	OVM READING (ppm)
1) SAMPLE ID: 5 BGT 5-pt. @	-				0 (CI) 0.0
2) SAMPLE ID:					
3) SAMPLE ID:					
4) SAMPLE ID:					
SOIL DESCRIPTION		SILT / SILTY CLAY / CLAY / GRAVEL / C	OTHER		
SOIL COLOR: DARK YELL  COHESION (ALL OTHERS): NON COHESIVE) SLIGHTLY		PLASTICITY (CLAYS): NON PLASTIC / SL DENSITY (COHESIVE CLAYS & SILT			
CONSISTENCY (NON COHESIVE SOILS): LC	OOSE FIRM / DENSE / VERY DENSE	The state of the s			
MOISTURE: DRY SLIGHTLY MOIST MOIST / W					
SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED: YES N		ANY AREAS DISPLAYING WETNESS:	YES NO EXPLAN	IATION -	
SITE OBSERVATION		T: YES NO EXPLANATION -	_		
APPARENT EVIDENCE OF A RELEASE OBSERVE	D AND/OR OCCURRED : YES NO EXP	LANATION:			
EQUIPMENT SET OVER RECLAIMED AREA: OTHER:	YES NO EXPLANATION - LPAG	TTO BE SET ATOP BGT POSITION	N.		
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <50' N	NA ft. X NA			IMATION (Cubic Yards	400
	EAREST WATER SOURCE: >1,000			D TPH CLOSURE STD: _	100 ppm
SHESKLICH	BGT Located: off lon si	te PLOT PLAN circle:		CALIB. READ. = <u>52.2</u>	Kr - 0.32
WOO				CALIB. GAS =	ppm
PBGTL T.B. ~ 6' (xxx) R.Y	N.		N TIME	<u> </u>	
B.G.	BERM			MISCELL. I	
SEP/	ARATOR			<u>/0: N1543973</u>	
	·	<b></b>	PI	0#: k: <b>ZEVH01B</b>	CT2
		<b>w</b> .н. ⊕	-	J#: Z2-006Q0	
	1		ı —		6/08/10
	BERM		O(		2/28/14
PROD. TANK	\		I ID	ppm = parts per n	nillion
	\		_   A	BGT Sidewalls Visible	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO	N DEDDESSION: D.C DELOWICHADE: D D	ELONATU - TEST DOLE - ADDDOV JAIL -	<u>S.P.D.</u>	BGT Sidewalls Visible	
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELC	DW-GRADE TANK LOCATION; SPD = SAMPLE I	POINT DESIGNATION: R.W. = RETAINING WALL		agnetic declination	
APPLICABLE OR NOT AVAILABLE; SW - SINGLE NOTES:	WALL; DW - DOUBLE WALL; SB - SINGLE BO	A = /A		J. J. J GOM IGHOL	
HOILO.		ONSITE: 05/21/1	4		•

#### **Analytical Report**

Lab Order 1405A92

Date Reported: 5/30/2014

#### Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Client Sample ID: 95 BGT 5-pt @ 6'

Project: GCU 95 E

Collection Date: 5/21/2014 11:55:00 AM

Lab ID: 1405A92-001

Matrix: SOIL

Received Date: 5/27/2014 9:55:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE	ORGANICS				Analyst	BCN
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	5/29/2014 3:45:46 AM	13356
Surr: DNOP	113	57.9-140	%REC	1	5/29/2014 3:45:46 AM	13356
EPA METHOD 8015D: GASOLINE RAN	GE				Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	5/29/2014 2:16:40 AM	13363
Surr: BFB	91.8	80-120	%REC	1	5/29/2014 2:16:40 AM	13363
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.047	mg/Kg	1	5/29/2014 2:16:40 AM	13363
Toluene	ND	0.047	mg/Kg	1	5/29/2014 2:16:40 AM	13363
Ethylbenzene	ND	0.047	mg/Kg	1	5/29/2014 2:16:40 AM	13363
Xylenes, Total	ND	0.093	mg/Kg	1	5/29/2014 2:16:40 AM	13363
Surr: 4-Bromofluorobenzene	107	80-120	%REC	1	5/29/2014 2:16:40 AM	13363
EPA METHOD 300.0: ANIONS					Analyst	SRM
Chloride	ND	30	mg/Kg	20	5/28/2014 2:55:57 PM	13380
EPA METHOD 418.1: TPH					Analyst	: JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	5/28/2014 12:00:00 PM	13358

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH greater than 2.
- RL Reporting Detection Limit

## Hall Environmental Analysis Laboratory, Inc.

WO#:

1405A92

30-May-14

Client:

Blagg Engineering

Project:

GCU 95 E

Sample ID MB-13380

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 13380

RunNo: 18897

Prep Date: 5/28/2014 Analysis Date: 5/28/2014

SeqNo: 545733

Units: mg/Kg

Analyte

Result PQL

HighLimit

**RPDLimit** %RPD Qual

Qual

Chloride

ND 1.5

Sample ID LCS-13380

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: **LCSS** 

5/28/2014

Batch ID: 13380

RunNo: 18897

Analysis Date: 5/28/2014

Units: mg/Kg

SeqNo: 545734

Analyte SPK value SPK Ref Val %REC 1.5

LowLimit

HighLimit %RPD

Prep Date:

SPK value SPK Ref Val %REC LowLimit

15.00

**RPDLimit** 

94.9

110

Chloride

Qualifiers:

Value exceeds Maximum Contaminant Level.

Е Value above quantitation range

Analyte detected below quantitation limits

Spike Recovery outside accepted recovery limits

0 RSD is greater than RSDlimit

RPD outside accepted recovery limits

Analyte detected in the associated Method Blank

Η Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit

P Reporting Detection Limit

Sample pH greater than 2.

Page 2 of 6

## Hall Environmental Analysis Laboratory, Inc.

Result

99

20

WO#: 1405A92

30-May-14

Client:

Analyte

Petroleum Hydrocarbons, TR

Blagg Engineering

Project:

GCU 95 E

Sample ID MB-13358	SampType: MBLK	TestCode: EPA Method	1418.1: TPH	
Client ID: PB\$	Batch ID: 13358	` RunNo: 18876		
Prep Date: 5/27/2014	Analysis Date: 5/28/2014	SeqNo: <b>545282</b>	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	ND 20			
Sample ID LCS-13358	SampType: LCS	TestCode: EPA Method	418.1: TPH	1 100
Client ID: LCSS	Batch ID: 13358	RunNo: 18876		
Prep Date: 5/27/2014	Analysis Date: 5/28/2014	SeqNo: <b>545283</b>	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	91 20 100.0	0 91.4 80	120	
Sample ID LCSD-13358	SampType: LCSD	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS02	Batch ID: 13358	RunNo: 18876		
Prep Date: 5/27/2014	Analysis Date: 5/28/2014	SeqNo: <b>545284</b>	Units: mg/Kg	

%REC

98.5

LowLimit

80

SPK value SPK Ref Val

100.0

#### Qualifiers

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded

HighLimit

120

**RPDLimit** 

Qual

%RPD

7.54

- ND Not Detected at the Reporting Limit
  - P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 6

## Hall Environmental Analysis Laboratory, Inc.

WO#:

1405A92

30-May-14

Client:

Blagg Engineering

Proiect:

GCU 95 E

Project: GCU 9	5 E	
Sample ID MB-13356	SampType: MBLK	TestCode: EPA Method 8015D: Diesel Range Organics
Client ID: PBS	Batch ID: 13356	RunNo: 18844
Prep Date: 5/27/2014	Analysis Date: 5/27/2014	SeqNo: 544526 Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO)	ND 10	
Surr: DNOP	7.0 10.00	70.2 57.9 140
Sample ID LCS-13356	SampType: LCS	TestCode: EPA Method 8015D: Diesel Range Organics
Client ID: LCSS	Batch ID: 13356	RunNo: 18844
Prep Date: 5/27/2014	Analysis Date: 5/27/2014	SeqNo: 544670 Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO)	51 10 50.00	0 102 60.8 145
Surr: DNOP	4.9 5.000	98.7 57.9 140
Sample ID MB-13336	SampType: MBLK	TestCode: EPA Method 8015D: Diesel Range Organics
Client ID: PBS	Batch ID: 13336	RunNo: 18882
Prep Date: 5/23/2014	Analysis Date: 5/28/2014	SeqNo: 545907 Units: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Surr: DNOP	8.7 10.00	87.1 57.9 140
Sample ID LCS-13336	SampType: <b>LCS</b>	TestCode: EPA Method 8015D: Diesel Range Organics
Client ID: LCSS	Batch ID: 13336	RunNo: 18882
Prep Date: 5/23/2014	Analysis Date: 5/28/2014	SeqNo: 545908 Units: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual
Surr: DNOP	4.8 5.000	95.4 57.9 140

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

## Hall Environmental Analysis Laboratory, Inc.

WO#: 1405A92

30-May-14

Client:

Blagg Engineering

Project:

GCU 95 E

Project: GCU 9.	) E		,						
Sample ID MB-13363	SampType: MI	BLK	Tes	tCode: El	PA Method	8015D: Gaso	oline Rang	e	
Client ID: PBS	Batch ID: 13	363	F	RunNo: 1	8887				
Prep Date: 5/27/2014	Analysis Date: 5/	28/2014	5	SeqNo: 5	45864	Units: mg/h	<b>(</b> g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND 5.0								
Surr: BFB	860	1000		85.8	80	120			
Sample ID LCS-13363	SampType: LCS TestCode: EPA Method 8015D: Gasoline Range								
Client ID: LCSS	Batch ID: 13	RunNo: 18887							
Prep Date: 5/27/2014	Analysis Date: <b>5</b> /	SeqNo: <b>545865</b>			Units: mg/Kg				
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	25 5.0	25.00	0	101	71.7	134			
Surr: BFB	880	1000		87.7	80	120			

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 6

## Hall Environmental Analysis Laboratory, Inc.

0.89

0.90

2.8

0.98

0.050

0.050

0.10

1.000

1.000

3.000

1.000

WO#:

1405A92

30-May-14

Client:

Toluene

Ethylbenzene

Xylenes, Total

Surr: 4-Bromofluorobenzene

Blagg Engineering

Project:

GCU 95 E

Sample ID MB-13363	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batcl	n ID: <b>13</b>	363	F	RunNo: 1	8887				
Prep Date: 5/27/2014	Analysis Date: 5/28/2014		SeqNo: <b>545900</b>			Units: mg/K	(g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.93		1.000		93.4	80	120			
Sample ID LCS-13363	SampType: LCS			TestCode: EPA Method 8021B: Volatiles						
Client ID: LCSS	Batch ID: 13363		RunNo: 18887			•				
Prep Date: 5/27/2014	Analysis Date: 5/28/2014		SeqNo: <b>545901</b>			Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.90	0.050	1.000	0	90.4	80	120			

0

0

88.9

89.7

94.6

97.5

80

80

80

80

120

120

120

120

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

### Sample Log-In Check List

RcptNo: 1 **BLAGG** Work Order Number: 1405A92 Client Name: Received by/date: 5/27/2014 9:55:00 AM Logged By: Lindsay Mangin Completed By: 5/27/2014 10:33:07 AM Lindsay Mangin Reviewed By: < Chain of Custody Yes 🗌 No 🗆 Not Present 1. Custody seals intact on sample bottles? No 🗀 Yes 🗸 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In No 🗆 NA 🗀 Yes 🗹 4. Was an attempt made to cool the samples? NA 🗌 No 🗌 5. Were all samples received at a temperature of >0° C to 6.0°C Yes 🔽 No 🗆 Yes 🗸 6. Sample(s) in proper container(s)? Yes 🗸 No  $\square$ 7. Sufficient sample volume for indicated test(s)? No 8. Are samples (except VOA and ONG) properly preserved? Yes NA 🔲 No 🗹 9. Was preservative added to bottles? Yes No 🗀 No VOA Vials 10.VOA vials have zero headspace? Yes No 🗹 Yes 11. Were any sample containers received broken? # of preserved bottles checked No 🗌 for pH: 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No 🗌 13. Are matrices correctly identified on Chain of Custody? No 🗆 ✓ 14, is it clear what analyses were requested? No 🗌 Checked by: Yes 🗸 15. Were all holding times able to be met? (If no, notify customer for authorization.) Special Handling (if applicable) Yes 🗌 No 🗌 NA 🔽 16. Was client notified of all discrepancies with this order? Person Notified: Date: eMail Phone Fax By Whom: Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No | Temp °C | Condition | Seal Intact | Seal No | Seal Date | Signed By 2.4 Good Yes

Standard	nental.com erque, NM 87109 505-345-4107
Mailing Address:  P.O. Box 87  Bloomfield, NM 87413  Project #:  (505)320-1183  email or Fax#:  QA/QC Package:  Standard  Cother  Date  Date  Time  Matrix  Sample Request ID  Container Type and #  Cothainer Type and #	erque, NM 87109 505-345-4107 Jest
Bloomfield, NM 87413  Project #:  End 505-345-3975  Fax 50  Analysis Request ID  Date  Time  Matrix  Project #:  Project #:  Project #:  Project #:  Project #:  Tel. 505-345-3975  Fax 50  Analysis Request ID  Container Type and #  Preservative Type and #  Preservative Type III	iest (2 Lo
Phone #: (505)320-1183  email or Fax#:  QA/QC Package:  Standard  Other  Date  Date  Time  Matrix  Sample Request ID  Container Type and #  Project Manager:  Jeff Blagg  On Ice:  Yes  No Sample Temperature  Preservative Type  HEAL No.  1 805-343-3973  Pax 30  Analysis Request ID  Odd  Odd  Odd  Odd  Odd  Odd  Odd  O	iest (N.JO.X.) Se
email or Fax#:  QA/QC Package:  Standard  □ Level 4 (Full Validation)  □ Other □ EDD (Type)  Date  Time  Matrix  Sample Request ID  Container Type and #  Project Manager:  Jeff Blagg  On Ice:  Sample:  Jeff Blagg  On Ice:  Type  HEAL No.  HEAL No.  LOS AO2  HEAL No.  LOS AO2  HEAL No.  LOS AO2  Preservative Type and #  Los AO2  HEAL No.  LOS AO2  Preservative Type and #	Se (Y or N)
Date   Time   Matrix   Sample Request ID   Sample Request ID   Container   Type   HEAL No.   HEAL No.   Level 4 (Full Validation)   Container   Type   Container   Type   Container   Type   Container   Type   Container	ride hithles (Y or N)
Date   Time   Matrix   Sample Request ID   Container   Type   APP   A	iride inhles (Y or N)
Date Time Matrix Sample Request ID Container Type and # Preservative Type HEAL No. 1205 AQ 2 IB WHEAL No. 1205 AQ 2 IB Type	iride
Date Time Matrix Sample Request ID Container Type and # Preservative Type HEAL No. 1205 AQ 2 IB WHEAL No. 1205 AQ 2 IB Type	iride inhles (Y or N)
Date Time Matrix Sample Request ID Container Type and # Preservative Type HEAL No. 1205 AQ 2 IB WHEAL No. 1205 AQ 2 IB Type	ride lubbles (V or P
Date Time Matrix Sample Request ID Container Type and # Preservative Type HEAL No. 1205 AQ 2 IB WHEAL No. 1205 AQ 2 IB Type	iride Inhloc (V
	ıride
	1   원   발
	<del></del>
	<del></del>
Date: Time: Relinquished by: Received by: Date Time Remarks: Bill BP    123/2014	
Date: Time: Relinquished by: Date Time peace.jeffrey@bp.com	e copy results to:
137/14 145 V Thu + Walk 15/14/14/1955  If necessary, samples submitted to Hall Environmental may be subcontracted to other accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated	

ಳಿ





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

May 5, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

#### VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: GALLEGOS CANYON UNIT 095E

API#: 3004525500

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 22, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9DULIA

Surface Land Negotiator

**BP America Production Company** 

#### **BP America Production Company**

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

#### SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

May 7, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 095E API 30-045-25500 (G) Section 31 – T28N – R11W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



