District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division

1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.
For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application Type of action: Below grade tank registration Permit of a pit or proposed alternative method

☐ Closure of a pit, below-grade tank, or proposed alternative method
☐ Modification to an existing permit/or registration
☐ Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.

Operator: BP America Production Company OGRID #:778	OIL CONS. DIV DIST. 3
Address:200 Energy Court, Farmington, NM 87401	
Facility or well name:Florance C 8R	JUL 3 0 2014
API Number:3004525591OCD Permit Number:	
U/L or Qtr/QtrKSection19Township28NRange8WCounty:	San Juan
Center of Proposed Design: Latitude36.64383 Longitude107.72615	NAD: □1927 ⊠ 1983
Surface Owner: X Federal X State Private Tribal Trust or Indian Allotment	
☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: ☐ Drilling ☐ Workover ☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride ☐ Lined ☐ Unlined Liner type: Thickness mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other ☐ String-Reinforced	<u> </u>
Liner Seams: Welded Factory Other Volume: bbl Dimension	ns: L x W x D
3. Selow-grade tank: Subsection I of 19.15.17.11 NMAC	off
4.	
Alternative Method:	

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

s. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital,
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
 □ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. □ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptant are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.	Yes No
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	∐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,	
or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	
	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do	
attached.	camenis ure
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do	cuments are
attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit.	
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19	.15.17.9 NMAC
and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
or rountertainout.	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
13. Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Falternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	Fluid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland.	L TOS LI NO
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: S/5 Title: OCD Permit Number:	72014
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 6/10/2014	the closure report. complete this
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo ☐ If different from approved plan, please explain.	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation	dicate, by a check
Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude 36.64383 Longitude -107.72615 NAD:	927 🛛 1983

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure r belief. I also certify that the closure complies with all applicable closure requirem	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: St Poace	Date:July 29, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Florance C 8R API No. 3004525591 Unit Letter K, Section 19, T28N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice to BLM is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice to NMOCD is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil. The area over the BGT is covered by the LPT and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notifi	catio	on and Co	rrective A	ction				
						OPERA?	ГOR		Initia	al Report	\boxtimes	Final Repor
			ington, N	M 87401								
Facility Na	me: Florar	ice C 8R				Facility Typ	e: Natural gas v	well				
Surface Ow	ner: Feder	al		Mineral (Owner:	Federal		Α	API No	. 3004525	591	
				LOC	ATIO	N OF REI	LEASE					
Unit Letter K	Section 19	Township 28N	Range 8W	Feet from the 1,450	1		Feet from the 1,380	East/West West	t Line	County: S	an Juar	n
		Lati	itude3	6.64383		Longitud	e107.72615_		· · · ·			
Name of Company: BP Contact: Leff Peace Feacher Address: 200 Energy Court, Farmington, NM 87401 Telephone No.: 505-326-9479 Facility Type: Natural gas well												
Source of Re	elease: belov	w grade tank –	- 95 bbl				lour of Occurrenc	ee: Da	ate and	Hour of Dis	covery	: N/A
Was Immedi	ate Notice (Yes [No ⊠ Not R	equired		Whom?					
By Whom?				·		Date and H	our					
Was a Water	course Read		Yes 🛚	No		If YES, Vo	lume Impacting t	he Waterco	urse.			
If a Watercon	urse was Im	pacted, Descri	ibe Fully.*			—I						
									moval t	o ensure no	soil im	ipacts from
					emoved	and the area un	nderneath the BG	T was samp	oled. Tl	ne excavate	d area v	was
regulations a public health should their or or the environ	Il operators or the envir operations h nment. In a	are required to ronment. The ave failed to a ddition, NMO	o report an acceptance dequately CD accep	d/or file certain to e of a C-141 repo investigate and r	release rort by the emedia	notifications ar ne NMOCD ma te contamination	nd perform correctarked as "Final Room that pose a three	tive actions eport" does : eat to ground	for rele not reli d water	eases which eve the ope , surface wa	may er rator of ater, hu	ndanger f liability man health
Signature:	aff	Peace					OIL CONS	SERVAT	TION	DIVISIO	<u>)N</u>	
Printed Name	e: Jeff Peace	2				Approved by	Environmental Sp	pecialist:				
Title: Area E	nvironment	al Advisor				Approval Date	ə:	Expi	ration I	Date:		
E-mail Addre	Yes No Yes No No No No No No No No					Conditions of	Approval:			Attached		
Date: July 2	9, 2014	•	Phone: 50	5-326-9479								

^{*} Attach Additional Sheets If Necessary

client: BP	Ī	ENGINEERING, IN BLOOMFIELD, NA		API #: 3004	_
	(5	05) 632-1199		(if applicble):	A
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / O	OTHER:	PAGE #:	of 1 _
SITE INFORMATION	I: SITE NAME: FLORA	NCE C # 8R		DATE STARTED:	05/29/14
QUAD/UNIT: K SEC: 19 TWP:	28N RNG: 8W PN	1: NM CNTY: SJ	st: NM	DATE FINISHED:	
		EL KUODA		ENVIRONMENTAL SPECIALIST(S):	JCB
				GLELEV:	
,					
1					
					CVM READING
	J			.015B/8021B/300 (0.0 (CI) (ppm)
					2(01)
		1			
		1			
		ANY AREAS DISPLAYING WETNES	SS: YES NO EXPLAN	IATION -	
		IT: YES NO EXPLANATION -			
APPARENT EVIDENCE OF A RELEASE OBSERVE	D AND/OR OCCURRED : YES NO EXP	PLANATION:			
EQUIPMENT SET OVER RECLAIMED AREA:	YES NO EXPLANATION - LPAG	T TO BE SET ATOP BGT POSIT	ION.	D DV DDECIDITATION	
OTHER: BOTTOM PORTION OF BUT COV	ERED BY SOIL, POSSIBLY FROM	I WIND BLOWN OR GRAVITION	IAL PROCESS AIDE	D BY PRECIPITATION.	
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA ft.		IMATION (Cubic Yards): NA
	EAREST WATER SOURCE:>1,00	O' NEAREST SURFACE WATER:	<1,000' NMOC	D TPH CLOSURE STD:	100 ppm
SITE SKETCH.	BGT Located: off on si	te PLOT PLAN circ	le: attached 0\/M	CALIB. READ. = 52.0	_ppm _pr =0.50
			↑ ovm	CALIB. GAS =	ppm
		DEDM	N TIME:	_ 6:55	05/29/14
		DERIVI		MISCELL N	VOTES
PBGTL			l w		
T.B. ~ 6' → (x x x) B.G.					
			Pi	K: ZEVH01B	GT2
	\.		P.	#: Z2-006Q0	
SEPARATOR	BERM		Pe		
		PROD. TANK		CD Appr. date(s): 0	2/27/14
			ID.	ppm = parts per m	illion
			<u> </u>	`	
, <u> </u>		X TOTAL TOTA	- S.P.D.		
LEASE #: NM03549 PROD FORMATION DK CONTRACTOR MISE S. GENTRY REFERENCE POINT: WELL HEAD (WH.) GPS COORD. 36.64363 X 107.72611 DISTRICT CONTRACTOR MISE S. GENTRY PS BGT (SW/DB) GPS COORD. 36.64383 X 107.72615 DISTRICT CONTRACTOR MISE S. GENTRY 1111, NBE 37.564 38.64366 X 107.72615 DISTRICT CONTRACTOR MISE S. GENTRY 1111, NBE 38.64366 X 107.72621 DISTRICT CONTRACTOR MISE S. GENTRY 1111, NBE 1111					
		TTOM; DB - DOUBLE BOTTOM.	IVI	agnetic declination	. IU E.
NOTES:		ONSITE: 05/29	9/14		

Analytical Report

Lab Order 1406097

Date Reported: 6/10/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT 5-pt @ 4'

Project: FLORANCE C 8R

Collection Date: 5/29/2014 12:57:00 PM

Lab ID: 1406097-001

Received Date: 6/3/2014 10:13:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE	ORGANICS				Analyst	BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	6/4/2014 10:13:27 AM	13493
Surr: DNOP	96.6	57.9-140	%REC	1	6/4/2014 10:13:27 AM	13493
EPA METHOD 8015D: GASOLINE RAN	IGE				Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	6/4/2014 6:16:14 PM	13489
Surr: BFB	88.0	80-120	%REC	1	6/4/2014 6:16:14 PM	13489
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.048	mg/Kg	1	6/4/2014 6:16:14 PM	13489
Toluene	ND	0.048	mg/Kg	1	6/4/2014 6:16:14 PM	13489
Ethylbenzene	ND	0.048	mg/Kg	1	6/4/2014 6:16:14 PM	13489
Xylenes, Total	ND	0.096	mg/Kg	1	6/4/2014 6:16:14 PM	13489
Surr: 4-Bromofluorobenzene	105	80-120	%REC	1	6/4/2014 6:16:14 PM	13489
EPA METHOD 300.0: ANIONS					Analyst	: JRR
Chloride	ND	30	mg/Kg	20	6/4/2014 11:32:13 AM	13512
EPA METHOD 418.1: TPH					Analyst	BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	6/4/2014	13465

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1406097 10-Jun-14

Client:

Blagg Engineering

Project:

FLORANCE C 8R

Sample ID MB-13512

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Sample ID LCS-13512

Batch ID: 13512

PQL

1.5

RunNo: 19055

Prep Date:

6/4/2014

Analysis Date: 6/4/2014

SeqNo: 550654

Units: mg/Kg

HighLimit

%RPD **RPDLimit**

Qual

Analyte Chloride

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Batch ID: 13512

RunNo: 19055

Units: mg/Kg

Analyte

Prep Date:

Analysis Date: 6/4/2014

Result

ND

SeqNo: 550655 SPK value SPK Ref Val %REC

SPK value SPK Ref Val %REC LowLimit

RPDLimit Qual

Chloride

6/4/2014

1.5

94.9

%RPD

14

15.00

90

110

HighLimit

Qualifiers:

Value exceeds Maximum Contaminant Level.

Ε Value above quantitation range

Analyte detected below quantitation limits RSD is greater than RSDlimit

R RPD outside accepted recovery limits

Spike Recovery outside accepted recovery limits

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded ND Not Detected at the Reporting Limit

Sample pH greater than 2.

Reporting Detection Limit

RL

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1406097

10-Jun-14

Client: Project: Blagg Engineering FLORANCE C 8R

Sample ID MB-13465

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 13465

PQL

20

RunNo: 19032

Prep Date: 6/2/2014 Analysis Date: 6/4/2014

SeqNo: 550010

Units: mg/Kg HighLimit

%RPD **RPDLimit**

Qual

Analyte Petroleum Hydrocarbons, TR

ND

Result

SampType: LCS

TestCode: EPA Method 418.1: TPH

Sample ID LCS-13465 Client ID: LCSS

Batch ID: 13465

RunNo: 19032

Units: mg/Kg

Prep Date: Analyte

Analysis Date: 6/4/2014

Result

96

SeqNo: 550011 SPK value SPK Ref Val %REC

LowLimit 80

HighLimit %RPD

Petroleum Hydrocarbons, TR

PQL 20

100.0 96.3

SPK value SPK Ref Val %REC LowLimit

120

RPDLimit

Qual

Sample ID LCSD-13465 Client ID:

LCSS02

6/2/2014

SampType: LCSD

Batch ID: 13465

RunNo: 19032

SeqNo: 550012

Units: mg/Kg

Qual

Analyte

Prep Date:

6/2/2014

Analysis Date: 6/4/2014 Result

99

SPK value SPK Ref Val

%REC 99.2

LowLimit

TestCode: EPA Method 418.1: TPH

HighLimit 120 %RPD 2.91

RPDLimit

20

Petroleum Hydrocarbons, TR

20

100.0

0

80

Qualifiers:

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

E Value above quantitation range

Analyte detected below quantitation limits

0 RSD is greater than RSDlimit

R RPD outside accepted recovery limits

Analyte detected in the associated Method Blank В

ND Not Detected at the Reporting Limit

Sample pH greater than 2.

Reporting Detection Limit

Holding times for preparation or analysis exceeded

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1

1406097 10-Jun-14

Client:

Blagg Engineering

Project:

FLORANCE C 8R

Sample ID MB-13493	SampType: MBLK			TestCode: EPA Method 8015D: Diesel Range Organics						
Client ID: PBS	Batcl	n ID: 13	493	F	RunNo: 1	9030				
Prep Date: 6/3/2014	Analysis D	oate: 6/	4/2014	SeqNo: 550021 Uni			Units: mg/F	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Surr: DNOP	8.5		10.00		84.7	57.9	140			
Sample ID LCS-13493	SampT	ype: LC	s	Tes	tCode: El	PA Method	8015D: Dies	el Range (Organics	
Client ID: LCSS	Batch	n ID: 13	493	F	RunNo: 1	9030			1	
Prep Date: 6/3/2014	Analysis Date: 6/4/2014			SeqNo: 550108			Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	49	10	50.00	0	98.0	60.8	145			

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

P Sample pH greater than 2.

RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1406097

10-Jun-14

Client: Project: Blagg Engineering FLORANCE C 8R

Sample ID MB-13489

SampType: MBLK

TestCode: EPÀ Method 8015D: Gasoline Range

Client ID: **PBS** Batch ID: 13489

RunNo: 19040

Analysis Date: 6/4/2014

Prep Date:

6/3/2014

SeqNo: 550220

Units: mg/Kg

Analyte Gasoline Range Organics (GRO) PQL

5.0

%REC

ND

SPK value SPK Ref Val

LowLimit HighLimit

RPDLimit

Surr: BFB

870

1000

86.6

80

%RPD

Sample ID LCS-13489

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

120

Client ID: LCSS

6/3/2014

Batch ID: 13489

RunNo: 19040 SeqNo: 550221

Units: mg/Kg

%RPD

Analyte Gasoline Range Organics (GRO) Analysis Date: 6/4/2014 Result PQL

SPK value SPK Ref Val 25.00

%REC LowLimit 103

71.7

HighLimit 134

RPDLimit Qual

Surr: BFB

26 1000

120

Prep Date:

1000

100 80

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range Ε
- Analyte detected below quantitation limits RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits . R
- Spike Recovery outside accepted recovery limits
- В Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2. Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1406097

10-Jun-14

Client:

Blagg Engineering

Project:

FLORANCE C 8R

Sample ID MB-13489	SampType: MBLK			Tes	TestCode: EPA Method 8021B: Volatiles					
Client ID: PBS	Batch ID: 13489			F	RunNo: 1	9040				
Prep Date: 6/3/2014	Analysis [Date: 6/	4/2014	5	SeqNo: 550239 Units:					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.1		1.000		106	80	120			
Sample ID LCS-13489	Samp	SampType: LCS TestCode: EPA Method 8021B: Volatiles								
Client ID: LCSS	Batc	h ID: 13	489	F	RunNo: 1	9040				
Prep Date: 6/3/2014	Analysis [Date: 6/	4/2014	5	SeqNo: 5	50240	Units: mg/F	(g		

Sample ID LCS-13489	TestCode: EPA Method 8021B: Volatiles												
Client ID: LCSS	RunNo: 19040												
Prep Date: 6/3/2014	Analysis [Date: 6/	4/2014	SeqNo: 550240			Units: mg/F						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	1.2	0.050	1.000	0	118	80	120						
Toluene	1.1	0.050	1.000	0	108	80	120						
Ethylbenzene	1.1	0.050	1.000	0	106	80	120						
Xylenes, Total	3.1	0.10	3.000	0	104	80	120						
Surr: 4-Bromofluorobenzene	1.2		1.000		116	80	120						

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDImit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE

Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Number:	1406097		1	
Received by/date:	Ole/03/14				
Logged By: Michelle Garcia		Michiel Gan Michiel Gan	eia		
Completed By: Michelle Garcia				ue)	
Reviewed By:	06/03/14		, ,		
Chain of Custody	0.10011	-			
1. Custody seals intact on sample bott	Yes 🗌	No 🗆	Not Present 🗹		
2. Is Chain of Custody complete?		Yes 🗹	No 🗌	Not Present	
3. How was the sample delivered?		Courier			
<u>Log In</u>					
4. Was an attempt made to cool the sa	amples?	Yes 🗹	No 🗆	na 🗆	
5. Were all samples received at a temp	perature of >0° C to 6.0°C	Yes 🗹	No 🗌	na 🗆	
6. Sample(s) in proper container(s)?		Yes 🗹	No 🗌		
7. Sufficient sample volume for indicate	ed test(s)?	Yes 🗹	No 🗆		
8. Are samples (except VOA and ONG) properly preserved?	Yes 🗹	No 🗆 -		
9. Was preservative added to bottles?	Yes 🗌	No 🗹	NA 🗆		
10.VOA vials have zero headspace?		Yes 🗌	No 🗆	No VOA Vials 🗹	
11. Were any sample containers receive	ed broken?	Yes □	No 🗹 🛚	# of preserved	
42 0	•	٧ [4]	No 🗆	bottles checked for pH:	•
12. Does paperwork match bottle labels (Note discrepancies on chain of cus		Yes 🗹	INO 🗀		>12 unless noted)
13. Are matrices correctly identified on 0		Yes 🗹	No 🗆	Adjusted?	
14. Is it clear what analyses were reque	sted?	Yes 🗹	No 🗆		
15. Were all holding times able to be me (If no, notify customer for authorizati		Yes 🗹	No 🗌	Checked by:	
(ii iio, iiomy ouotoiioi io, addioiizad	on.,				
Special Handling (if applicable)				•	
16. Was client notified of all discrepanci	es with this order?	Yes 🗌	No 🗹	NA 🗆	
Person Notified:	Date:				
By Whom:	Via: [eMail 🔲 I	Phone Fax	☐ In Person	
Regarding:					
Client Instructions:					
17. Additional remarks:			,	······································	1
18. Cooler Information Cooler No Temp C Condition 1 1.0 Good	on Seal-Intact Seal No S	Seal Date	Signed By		

Chain-of-Custody Record Client: BLAGG ENGINEERING INC. BP AMERICA			Standard □ Rush_				HALL ENVIRONMENTAL ANALYSIS LABORATORY														
																			www.hallenvironmental.com		
							Mailing Address: P.O. Box 87			FLORANCE C 8R			4901 Hawkins NE - Albuquerque, NM 87109								
BLOOMFIELD NM 87413			Project #:				Tel. 505-345-3975 Fax 505-345-4107														
Phone #: 505-632-1199			1				- A				nalysis Request								r-A-wal		
email or Fax#:			Project Manager:				ly)										-				
QA/QC Package:							s on	(里)			<u>~</u>		S,	B's			il	.]			
Standard			J. BLAGG				Ga	30 /	ļ		M		PO	PC							
Accreditation			Sampler: J. BLAGG				- TPH (Gas onl	님	_		0.5		o²,	082							
□ NELAP □ Other			On ice and the second of the s				=	30	18.1	8	827		7°°C	8/8		A		.		ᅵ짇	
□ EDD (Type)		On Ice (Control of the Control of th				빎	(GF	d 4	d 5	Ö	tals	Ž,	ges	<u>ہ</u> ا	٠٠	M			ک		
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAPNOR	EX +	BTEX + MTBE + TPH (Gas only)	ТРН 8015В (GRO / DRO / MBG)	TPH (Method 418.1)	EDB (Method 504.1)	PAH's (8310 or 8270 SIMS)	RCRA 8 Me	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082 PCB'	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE			Air Bubbles (Y or N)
12/2014	1257	SOIL	95 BGT / 5-pt @ 4	402 ×1		-001	X		×	X		_	144			٣	3	X			
	•		1 2 PS 0 1	,,,,,,	<u> </u>		1									<u> </u>				_	
							_											$\vdash\vdash$	- +	-	
			·	4			-	<u> </u>											\longrightarrow		
										,									,		
			·																		
-																T					
	<u> </u>						_														
														<u> </u>							_
									 					 	 					\dashv	
Date:	Time:	Relinquish All Relinquish	Blegg	Received by:	alt	Date Time Column 130 Date Time	Rei	mark	F	3 ru Ark	Er	: 2			_		と	1	I I		
42/4 1744 Christulado		Celin Some 06/03/14 10:13				contact: Jeff Perce															

If necessary, samples submitted to Hall Environmental may be subcontracted to other accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report.





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

April 7, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: FLORANCE C 008R

API#: 3004525591

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 15, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9D Vanker

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

April 10, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

FLORANCE C 008R API 30-045-25591 (G) Section 19 – T28N – R08W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



