District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

	Pit, Below-Grade Tank, or							
Proposed Alternative Method Permit or Closure Plan Application								
Type of action: Below grade tank registration								
Permit of a pit or proposed alternative method								
	Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration							
9090	Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank							
4529030	or proposed alternative method	,						
	Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request							
Please be advised	ed that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water o for does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or	or the						
	to does approval reneve the operator of its responsibility to compry with any other appreadie governmental authority's rules, regulations or	ordinances.						
Operator: BP /	P America Production Company OGRID #:778							
	00 Energy Court, Farmington, NM 87401 OIL CONS. DIV DIST. 3							
	Ul name:Sellers Federal LS 2MJUN 0 9 2014							
	OCD Permit Number:							
U/L or Qtr/Qtr	trO Section30 Township30N Range10W County:San Juan							
Center of Propo	posed Design: Latitude36.77889 Longitude107.92117 NAD: □1927 ⊠	1983						
Surface Owner:	er: 🛛 Federal 🗌 State 🔲 Private 🔲 Tribal Trust or Indian Allotment							
2.								
	section F, G or J of 19.15.17.11 NMAC							
	t Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no							
	Unlined Liner type: Thickness mil 🗋 LLDPE 🗋 HDPE 📄 PVC 🗋 Other							
String-Reinf								
	Welded Factory Other Volume: bbl Dimensions: L x W x D							
3.								
Below-grad	ade tank: Subsection I of 19.15.17.11 NMAC Tank B							
	18.0bbl Type of fluid:Produced water							
Tank Constructi	ction material:Steel							
Secondary of	y containment with leak detection 🔲 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off							
Visible side	dewalls and liner 🗌 Visible sidewalls only 🛛 Other _Single walled/single bottomed - side walls not visible							
Liner type: Thi	hicknessmil 🔲 HDPE 🗌 PVC 🛄 Other							
4.								
Alternative	<u>e Method</u> :							

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)						
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital,						
institution or church)						
 Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify 						
6.						
^{o.} <u>Netting</u> : Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)						
Screen Netting Other						
Monthly inspections (If netting or screening is not physically feasible)						
7. Signs: Subsection C of 19.15.17.11 NMAC						
[] 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers						
Signed in compliance with 19.15.16.8 NMAC						
8.						
<u>Variances and Exceptions</u> : Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.						
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.						
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.						
9. <u>Siting Criteria (regarding permitting)</u> : 19.15.17.10 NMAC						
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source					
<u>General siting</u>						
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. -	□ Yes □ No □ NA					
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA					
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	🗌 Yes 🗌 No					
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality						
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	🗌 Yes 🗌 No					
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗋 Yes 🗋 No					
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗋 Yes 🗌 No					
Below Grade Tanks						
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	🗌 Yes 🗌 No					
 from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 						
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No					
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)						
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No					

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes 🗋 No
<u>Temporary Pit Non-low chloride drilling fluid</u>	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗍 No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application	
 initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
^{10.} Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N	MAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	
 attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 	NMAC
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	<u> </u>
11.	
<u>Multi-Well Fluid Management Pit Checklist</u> : Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are
 Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. 	
 Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC 	15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

12.	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	documents are
 Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment 	
 Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan 	
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan 	
Emergency Response Plan Oil Field Waste Stream Characterization Manitoring and Ingragation Plan	
 Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19 15 17 9 NMAC and 19 15 17 13 NMAC 	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: 🗌 Drilling 🔲 Workover 🔲 Emergency 🛄 Cavitation 🗌 P&A 🛄 Permanent Pit 🛄 Below-grade Tank 🛄 Multi-well Fl	uid Management Pit
Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)	
On-site Closure Method (Only for temporary pits and closed-loop systems)	
Alternative Closure Method	
 Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC	
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗋 Yes 🗌 No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	Yes 🗌 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

(

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 						
	🗌 Yes 🗌 No					
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes 🗌 No					
Within an unstable area.						
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes 🗌 No					
Within a 100-year floodplain. - FEMA map	Yes 🗌 No					
16						
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 						
17. Operator Application Certification:						
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and be	lief.					
Name (Print):						
Signature: Date:						
e-mail address: Telephone:						
e-mail address: Telephone: I8. OCD Approval: Permit Application (including closure plan) Glosure Plan (only) OCD Conditions (see attachment)						
18. OCD Approval: Permit Application (including closure plan) OCD Approval: OCD Conditions (see attachment)						
18. OCD Approval: Permit Application (including closure plan) Image: Signature: Image: OCD Conditions (see attachment) OCD Representative Signature: Image: S						
18. OCD Approval: Permit Application (including closure plan) Image: Second seco						
18. OCD Approval: Permit Application (including closure plan) Image: Signature: Image: OCD Conditions (see attachment) OCD Representative Signature: Image: S	g the closure report.					
18. OCD Approval: Permit Application (including cloture plan) Isoure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:	g the closure report.					
18. OCD Approval: Permit Application (including cloture plan) folosure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:	g the closure report. t complete this					
18. OCD Approval: Permit Application (including cloture plan) Glosure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:	g the closure report. t complete this					

22. Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature:	Date:June 5, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

.

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Sellers Federal LS 2M BGT Tank B (18 bbl)</u> <u>API No. 3004529080</u> <u>Unit Letter O, Section 30, T30N, R10W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B. D. or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. **Notice is attached.**
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number. **Notice is attached.**
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	18 bbl BGT, Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	950
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and BTEX and chloride levels were below the stated limits. TPH was 950 mg/kg by Method 418.1 and 140 mg/kg by Method 8015D at 2 feet below the surface. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicates a very minor release occurred. The release was addressed under the spill and release guidelines. Attached C-141 has details.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Fra	1220 S. St. Francis Dr., Santa Fe, NM 87505 Santa Fe, NM 87505										
Release Notification and Corrective Action											
						OPERA	ГOR		[] Initi	al Report	🛛 Final Report
Name of Company: BP						Contact: Jef	f Peace				
Address: 200 Energy Court, Farmington, NM 87401						Telephone N	No.: 505-326-94	79			
Facility Name: Sellers Federal LS 2M						Facility Typ	e: Natural gas v	vell			
Surface Ow	vner: Fede	ral		Mineral	Owner [.]	Federal	·		APINO	0. 30045290	80
Surface Ow	viler. I ede			k						5. 500-5290	
The star	Section	Township	Danaa	LOC Feet from the		N OF REI	EASE Feet from the	East/W	Vest Line	Country So	
Unit Letter O	30	30N	Range 10W	1,170	South		1,460	East		County: Sa	in Juan
		Lat	titude_3	6.77889		_ Longitud	e_107.92117_	-			
				NA	FURE	OF RELI	EASE				
Type of Rele	ease: conde	nsate/oil					Release: unknow	'n	Volume I	Recovered: u	nknown
		w grade tank -	- 18 bbl, T	ank B			lour of Occurrenc	e:	Date and	Hour of Disc	covery: April 30,
Weeler	into NI-ti					unknown	W/h =		2013; 12	:57 PM	
Was Immedi	iate Notice]Yes 🛛	No 🗌 Not R	Required	If YES, To	Whom?				
By Whom?						Date and H	our				
Was a Water	rcourse Rea	ched?]Yes 🛛	No		If YES, Vo	lume Impacting t	he Wate	rcourse.		
If a Waterco	urce was In	pacted, Descr	ibe Fully	<u>د </u>					<u> </u>		
by Method 8 was below the Describe Are	015D. Thio ne limits for	ckness of the i TPH, BTEX	mpacted se and chlorid Action Tak	oil was 2-4 inche des. Analysis re en.* BGT was re	es and les sults are	attached.	yards in volume.	. Soil sa T was sa	ample take	n at 3.5 feet b	of impacted soil
Describe Area Affected and Cleanup Action Taken.* BGT was removed and the area underneath the BGT was sampled. The thin layer of impacted soil found was churned with the backhoe and aerated in place before backfilling. The area under the BGT was backfilled and compacted and is still within the active well area.											
regulations a public health should their o or the enviro	Il operators or the envi operations l onment. In a	are required t ronment. The nave failed to a	o report an acceptanc adequately DCD accep	d/or file certain e of a C-141 rep investigate and	release no ort by the remediate	otifications ar e NMOCD ma e contaminatio	knowledge and u ad perform correc arked as "Final Re on that pose a thre e the operator of r	tive acti- eport" de eat to gre	ons for rel bes not rel bund wate	eases which i ieve the opera r, surface wat	may endanger ator of liability er, human health
0	OIL CONSERVATION DIVISION					N					
Signature: Jose Printed Name: Jeff Peace Approved by Environmental Specialist:											
Title: Area E				<u></u>		Approval Dat	e:	Ē	Expiration	Date:	
		effrey@bp.co	m			Conditions of			E	Attached	
_			-	204 0470						/ mached	
Date: June 5	, 2014		Phone: 505	-326-9479							

* Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, BLOC	NEERING, INC. DMFIELD, NM 8741 32-1199	13	API #: 3004529080 TANK ID (if applicble): A;B;C;D			
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELE 95 SW/DB REPLAC			PAGE #: <u>1</u> of <u>1</u>			
SITE INFORMATION QUAD/UNIT: 0 SEC: 30 TWP: 1/4 -1/4/FOOTAGE: 1,170'S / 1,460	30N RNG: 10W PM: N		NM DIAN	DATE STARTED: 04/30/13 DATE FINISHED: ENVIRONMENTAL			
	PROD. FORMATION: MV/DK CONTRA		I	SPECIALIST(S): NJV GL ELEV.: 6,065'			
1)		78 X 407.02457		RING FROM W.H.: 92', S33E			
3)	GPS COORD.: 30.773	20 X 107.92101		RING FROM WH.: 113', N75 W			
SAMPLING DATA: 1) SAMPLE ID: <u>5PC-TB@2'(18)-</u> 2) ONMELE ID: <u>5PC-TB@6'(21)</u>-	CHAIN OF CUSTODY RECORD(S) # OR LAB I B SAMPLE DATE: OW/12 OW/12		<u>448,4/8</u>	READING (ppm) 015B/8021B/300.0(CI) NA 045B/90⊒4B/300.9(CI) NA			
3) 57/11/1210. 5PC TB @ 6' (21) 4) 67/11/1210: CS @ 7' (95) A	DOWNELEDATEO4/30/13	OVVIT LE TIRIL. 1000 EPO NVELTOD.		845B/8024B/388.9(SI) - 114 845B/8924B/399.9(GI) - 114			
SOIL DESCRIPTION: SOIL TYPE: SAND / SILTY SAND SILT / SILTY CLAY / CLAY / GRAVEL / OTHER SOIL COLOR: MOSTLY MODERATE BROWN TO DARK YELLOWISH ORANGE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / SILTY / STIFF / VERY STIFF / HARD MOISTURE: DRY SLIGHTLY MOIST MOIST / WET / SATURATED / SUPER SATURATED HC ODOR DETECTED: YES/ NO EXPLANATION - DISCOLORED SOILS SAMPLE TYPE: GRAB / COMPOSITE # OF PTS. 5 ONLY. DISCOLORATION/STAINING OBSERVED: YES NO EXPLANATION - BENEATH 18 BGT & 95 BGT (2 - 4 INCHES IN THICKNESS).							
ADDITIONAL COMMENTS: <u>ADDITIONAL</u> <u>CUSTODY RECORD).</u> SOIL IMPACT DIMENSION ESTIMATION:	BSERVED AND/OR OCCURRED : YES N SAMPLE COLLECTED FROM IMPACTE	X 1/3 ft. EXCAVA	BGT FOR	T INTEGRITY; OVERFLOW(S)? LAB ANALYSES (SEE CHAIN-OF- MATION (Cubic Yards) : D TPH CLOSURE STD: 100 ppm			
SITE SKETCH		PLOT PLAN circle: attacl	hed OVM (CALIB. READ. = <u>NA</u> ppm CALIB. GAS = <u>NA</u> ppm NA am/pm DATE: <u>NA</u>			
	W.H.	-	Pł	D#: 79132			
	GS (TIME	18 (B) PBGTL PBGTL 7.B. ~ 2' 8.G.	Pe	Immit date(s): 06/14/10 CD Appr. date(s): 05/16/12 K OVM = Organic Vapor Meter			
	X – S.P.D. DN DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H OW-GRADE TANK LOCATION; SPD = SAMPLE POINT DE: WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DB	SIGNATION; R.W. = RETAINING WALL; NA - NO	LLS IBLE. IEAD; C	BGT Sidewalls Visible: Y (N) BGT Sidewalls Visible: Y (N) agnetic declination: 10° E			
TRAVEL NOTES: CALLOUT:		ONSITE: 04/30/13					

Analytical Report Lab Order 1305091

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Project: Sellers Federal LS #2M

Date Reported: 5/9/2013 Client Sample ID: 5PC-TB @ 2' (18)-B Collection Date: 4/30/2013 12:57:00 PM

· · · J · · · · · · · · · · · · · · · ·						
Lab ID: 1305091-001	091-001 Matrix: SOIL		Received Date: 5/2/2013 10:00:00 AM			
Analyses	Result	RL Qu	al Units	DF	Date Analyzed	
EPA METHOD 8015D: DIESEL RANGI	E ORGANICS				Analyst: JME	
Diesel Range Organics (DRO)	140	10	mg/Kg	1	5/6/2013 10:46:21 PM	
Surr: DNOP	116	63-147	%REC	1	5/6/2013 10:46:21 PM	
EPA METHOD 8015D: GASOLINE RA	NGE				Analyst: NSB	
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	5/4/2013 9:16:18 AM	
Surr: BFB	117	80-120	%REC	1	5/4/2013 9:16:18 AM	
EPA METHOD 8021B: VOLATILES					Analyst: NSB	
Benzene	ND	0.047	mg/Kg	1	5/4/2013 9:16:18 AM	
Toluene	ND	0.047	mg/Kg	1	5/4/2013 9:16:18 AM	
Ethylbenzene	ND	0.047	mg/Kg	1	5/4/2013 9:16:18 AM	
Xylenes, Total	ND	0.094	mg/Kg	1	5/4/2013 9:16:18 AM	
Surr: 4-Bromofluorobenzene	108	80-120	%REC	1	5/4/2013 9:16:18 AM	
EPA METHOD 300.0: ANIONS					Analyst: JRR	
Chloride	ND	7.5	mg/Kg	5	5/7/2013 10:09:17 AM	
EPA METHOD 418.1: TPH					Analyst: LRW	
Petroleum Hydrocarbons, TR	950	20	mg/Kg	1	5/7/2013	

Qualifiers:

*

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

Р Sample pH greater than 2

RL Reporting Detection Limit

- В Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

Spike Recovery outside accepted recovery limits S

Analytical Report

Analyst: NSB

Analyst: JRR

5/4/2013 10:42:23 AM

5/7/2013 12:25:45 PM

Hall Environmental Analysis Laboratory, Inc.

Gasoline Range Organics (GRO)

EPA METHOD 8021B: VOLATILES

Surr: 4-Bromofluorobenzene

EPA METHOD 300.0: ANIONS

Surr: BFB

Benzene

Toluene

Chloride

Ethylbenzene

Xylenes, Total

Lab Order 1305091 Date Reported: 5/9/2013

CLIENT:Blagg EngineeringProject:Sellers Federal LS #2MLab ID:1305091-004	Client Sample ID: GS @ 3.5' (18)-B Collection Date: 4/30/2013 1:01:00 PM Matrix: SOIL Received Date: 5/2/2013 10:00:00 AM				
Analyses	Result	RL Qu	al Units	DF	Date Analyzed
EPA METHOD 8015D: DIESEL RANG	E ORGANICS		· · · · · · · · · · · · · · · · · · ·		Analyst: JME
Diesel Range Organics (DRO)	29	10	mg/Kg	1	5/7/2013 12:07:47 AM
Surr: DNOP	120	63-147	%REC	1	5/7/2013 12:07:47 AM
EPA METHOD 8015D: GASOLINE RA	NGE				Analyst: NSB

4.8

80-120

0.048

0.048

0.048

0.095

80-120

7.5

mg/Kg

%REC

mg/Kg

mg/Kg

mg/Kg

mg/Kg

%REC

mg/Kg

1

1

1

1

1

1

1

5

ND

95.5

ND

ND

ND

ND

104

ND

Oua	lifiers:
Qua	miller 5.

- * Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits J
- Р Sample pH greater than 2
- RL Reporting Detection Limit

Analyte detected in the associated Method Blank В

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

RPD outside accepted recovery limits R

Spike Recovery outside accepted recovery limits S

QC SUMMARY REPORT

WO#: 1305091

09-May-13

Client: Project:	Blagg Engineering Sellers Federal LS									
Sample ID: MB-7	317 Samı	оТуре: МІ	BLK	Tes	tCode: El	PA Method	300.0: Anion	s		
Client ID: PBS	Bat	ch ID: 73	17	F	RunNo: 1	0464				
Prep Date: 5/7/2	2013 Analysis	Date: 5/	7/2013	5	SeqNo: 2	95832	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Chloride	ND	1.5								
Sample ID: LCS-7	7 317 Samı	Type: LC	s	Tes	tCode: El	PA Method	300.0: Anion	s	-	
Client ID: LCSS	Bat	ch ID: 73	17	F	RunNo: 1	0464				
Prep Date: 5/7/2	013 Analysis	Date: 5/	7/2013	S	SeqNo: 2	95833	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Chloride	15	1.5	15.00	0	98.9	90	110			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2
- RL Reporting Detection Limit

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits

WO#: 1305091

09-May-13

Client: Bla	agg Engineering					
Project: Sel	lers Federal LS #2M					
Sample ID: MB-7307	SampType: MBLK	TestCode: EPA Method	1 418.1: TPH			
Client ID: PBS	Batch ID: 7307	RunNo: 10453				
Prep Date: 5/6/2013	Analysis Date: 5/7/2013	SeqNo: 295385	Units: mg/Kg			
Analyte	Result PQL SPK va	ue SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual	
Petroleum Hydrocarbons, TR	ND 20					
Sample ID: LCS-7307 SampType: LCS TestCode: EPA Method 418.1: TPH						
Client ID: LCSS	Batch ID: 7307	RunNo: 10453				
Prep Date: 5/6/2013	Analysis Date: 5/7/2013	SeqNo: 295386	Units: mg/Kg			
Analyte	Result PQL SPK va	ue SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual	
Petroleum Hydrocarbons, TR	94 20 10	0.0 0 93.7 80	120			
Sample ID: LCSD-7307	SampType: LCSD	TestCode: EPA Method	418.1: TPH			
Client ID: LCSS02	Batch ID: 7307	RunNo: 10453				
Prep Date: 5/6/2013	Analysis Date: 5/7/2013	SeqNo: 295388	Units: mg/Kg			
Analyte	Result PQL SPK va	ue SPK Ref Val %REC LowLimit	HighLimit%RPD	RPDLimit	Qual	
Petroleum Hydrocarbons, TR	92 20 10	0.0 0 92.3 80	120 1.51	20		

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2
- RL Reporting Detection Limit

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits

Page 8 of 11

WO#: 1305091

09-May-13

Client: Project:		ngineering Federal LS #	2M								
Sample ID: N	MB-7278	SampTy	ype: ME	BLK	Tes	tCode: E	PA Method	8015D: Dies	el Range C	Drganics	
Client ID: F	PBS	Batch	ID: 72	78	F	RunNo: 1	0338				
Prep Date:	5/3/2013	Analysis Da	ate: 5 /	6/2013	S	SeqNo: 2	94806	Units: %RE	C		
Analyte Surr: DNOP		Result 9.8	PQL	SPK value 10.00	SPK Ref Val	%REC 98.2	LowLimit 63	HighLimit 147	%RPD	RPDLimit	Qual
Sample ID: N	MB-7280	SampTy	ype: ME	3LK	Tes	tCode: E	 PA Method	8015D: Dies	el Range C	 Drganics	
Client ID: F	PBS	Batch	ID: 72	80	F	RunNo: 1	0338				
Prep Date:	5/3/2013	Analysis Da	ate: 5 /	6/2013	S	SeqNo: 2	94807	Units: mg/l	<g< td=""><td></td><td></td></g<>		
Analyte Diesel Range Or	manics (DRO)	Result	PQL 10	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP	30,000 (2000)	9.8		10.00		98.3	63	147			
Sample ID: L	_CS-7278	SampTy	pe: LC	S	Tes	tCode: El	PA Method	8015D: Dies	el Range C)rganics	
Client ID: L	CSS	Batch	ID: 72	78	F	RunNo: 1	0338				
Prep Date:	5/3/2013	Analysis Da	ate: 5 /	6/2013	5	SeqNo: 2	94808	Units: %RE	C		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		5.4	· · · · · · · · · · · · · · · · · · ·	5.000		107	63	147			
Sample ID: L	_CS-7280	SampTy	pe: LC	s	Tes	tCode: El	PA Method	8015D: Dies	el Range C)rganics	
Client ID: L	_CSS	Batch	ID: 72	80	F	RunNo: 1	0338				
Prep Date:	5/3/2013	Analysis Da	ate: 5/	6/2013	S	SeqNo: 2	94809	Units: mg/ł	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Or Surr: DNOP	ganics (DRO)	50 4.7	10	50.00 5.000	0	99.9 94.6	47.4 63	122 147			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2
- RL Reporting Detection Limit

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits

Page 9 of 11

WO#: 1305091

09-May-13

	Engineering Federal LS #2M								
Sample ID: MB-7269	SampType: N	IBLK	Tes	tCode: El	PA Method	8015D: Gasol	ine Rang	e	
Client ID: PBS	Batch ID: 7	269	F	RunNo: 1	0318				
Prep Date: 5/2/2013	Analysis Date:	5/4/2013	S	SeqNo: 2	94116	Units: mg/K	3		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND 5.					100			
Surr: BFB	930	1000		93.3	80	120			
Sample ID: LCS-7269	SampType: L	cs	Tes	tCode: El	PA Method	8015D: Gasol	ine Rang	e	
Client ID: LCSS	Batch ID: 7	269	F	RunNo: 1	0318				
Prep Date: 5/2/2013	Analysis Date:	5/4/2013	S	SeqNo: 2	94117	Units: mg/Kg	9		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	23 5.) 25.00	0	90.7	62.6	136			
Surr: BFB	990	1000		99.0	80	120			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2
- RL Reporting Detection Limit

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits

Page 10 of 11

Client:Blagg EngineeringProject:Sellers Federal LS #2M

Sample ID: MB-7269	SampType: MBLK TestCode: EPA Method 802						8021B: Volat	iles		
Client ID: PBS	Batc	h ID: 72	69	RunNo: 10318						
Prep Date: 5/2/2013	Analysis [Date: 5 /	4/2013	S	eqNo: 2	94162	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.1		1.000		106	80	120			
Sample ID: LCS-7269	Samp	Гуре: LC	S	Tes	tCode: El	PA Method	8021B: Volat	iles		
Client ID: LCSS	Batc	h ID: 72	69	F	lunNo: 1	0318				
Prep Date: 5/2/2013	Analysis [Date: 5/	4/2013	S	eqNo: 2	94163	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.0	0.050	1.000	0	103	80	120			
		0.050	1.000	0	100	80	120			
Toluene	1.0	0.050	1.000	•						
	1.0 0.99	0.050	1.000	0	98.6	80	120			
Toluene Ethylbenzene Xylenes, Total					98.6 97.8	80 80	120 120			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2
- RL Reporting Detection Limit

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits

Page 11 of 11

WO#: 1305091

09-May-13

Cł	nain-c	of-Cus	tody Record	Turn-Around T	ime:		Ι.			L		11		NN	9т с	2			NT	A 1	
Client:	BLAG	G ENGR.	/ BP AMERICA	Standard Standard	🗌 Rush _						N	Al	Y	SIS	5 L	A	30	R/	ATO		
Mailing Ac	Idress:	P.O. BO	K 87	SELLERS FEDERAL LS # 2M				49	01 F	ławł					nme Ierqi				9		
— <u> </u>			FIELD, NM 87413	Project #:)5-3					505				5		
Phone #:		(505) 63					1								Rec					39° - 63 M	2 2 1 1
email or Fa	ax#:			Project Manag	ier:				ħU							.**		Â			
QA/QC Pac	-		Level 4 (Full Validation)	NELSON VELEZ				+ TPH (Gas only)	(ONIN)			1S)		PO4,SO4	PCB's			er - 300.1)			
Accreditati		<u>.</u>		Sampler:	NELSON VE	ELEZ AV	B's (8021B)	(Gas	DRO /	नि	(न	OSIN		V0 ₂ ,I	8082			/ water			aidilips
		D Other		and the second second second second	Yes			HdT	1	418.1)	504	827(S	03, N	ss /		(YC	0.00	i I	5	
	ype)			Sample Tempe	efature: 1, V	2			(GRO	por	por	l 2	etal	U U U	icid	(A)	ν-iι	oit - 3		Sei O	
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO:	BTEX + -MT H	BTEX + MTBE	TPH 8015B	TPH (Method	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /		Grad sample	
4/30/13	1257	SOIL	5РС-ТВ @ 2' (18)-В	4 oz 2	Cool	100	۷		۷	V								۷		1	1
										Ì											
-4/30/13-	-1305-			401.2-		-002	V		4									4		-+-	H
																					Т
4/30/12	-1308-		FPG_TB-@-6 ¹ (21) D	402-3-	Geol	-003	*		-~	-			-					~			Ā
									t	1.		<u> </u>	1-							╈	╈
4/30/13	1301	SOIL	GS @ 3.5' (18)-B	4 oz 1	Cool	-004	٧		۷									۷		V	+
-4/39/13-	-1315-		CS @ 7! (05) A			-005			~									~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		6	
																			\square		Τ
	1319				-693	- cole	4		-4									÷.	$\square \downarrow $	₩-	-
·															1						Τ
Date:	Time: 811: Time:	Relinquish	un Vf	Received by:	Marta	Date Time 5/1/13 811 Pate Time	в		REC	FLY T 200			ourt,	Farn	ningt	on, N	IM 8	7401	i		
5/1/13	1724	In	intere Walters	MA		5 021B 100				r: _									01BG1		-

fice This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report.

HALL ENVIRONMENTAL ANALYSIS LABORATORY

Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Number: 1305091		RcptNo:	1
Received by/date: LM 05/0	2/13			
Logged By: Anne Thorne	5/2/2013 10:00:00 AM	anne Han	_	
Completed By: Anne Thorne	5/2/2013	anne Im		
Reviewed By:	15 02 13	//		
Chain of Custody	1 1			
1. Custody seals intact on sample bottles?	Yes 🗌	No 🗌	Not Present 🗹	
2. Is Chain of Custody complete?	Yes 🗹	No 🗌	Not Present	
3. How was the sample delivered?	<u>Courier</u>			
Log In				
4. Was an attempt made to cool the samples?	Yes 🗹	No 🗆	na 🗆	
5. Were all samples received at a temperature	of >0° C to 6.0°C Yes ☑	No 🗆	NA 🗔	
6. Sample(s) in proper container(s)?	Yes 🔽	No 🗌		
7. Sufficient sample volume for indicated test(s)? Yes 🗹	No 🗌		
8. Are samples (except VOA and ONG) proper	y preserved? Yes 🗹	No 🗌		
9. Was preservative added to bottles?	Yes	No 🗹	na 🗂	
10.VOA vials have zero headspace?	Yes	No 🗌	No VOA Vials 🗹	
11. Were any sample containers received broke	n? Yes 🗆	No 🗹	# of preserved	
12. Does paperwork match bottle labels?	Yes 🗹	No 🗌	bottles checked for pH:	
(Note discrepancies on chain of custody)		No 🗆	(<2 c Adjusted?	r >12 unless noted)
13. Are matrices correctly identified on Chain of14. Is it clear what analyses were requested?	Custody? Yes 🗹 Yes 🗹			
15. Were all holding times able to be met?	Yes 🗹	No 🗌	Checked by:	<u> </u>
(If no, notify customer for authorization.)		1	L	
Special Handling (if applicable)				
16. Was client notified of all discrepancies with t	his order? Yes	No 🗌	NA 🗹	
Person Notified:	Date] .
By Whom:	Via: 🗌 eMail 🗌] Phone 🗌 Fax	In Person	
Regarding:		an a	······································	
Client Instructions:	and the second		ا المراجع من المراجع الم المراجع المراجع]
17. Additional remarks:				
18. <u>Cooler Information</u>				
Cooler No Temp C Condition Se	al Intact Seal No Seal Date	Signed By		

Page 1 of 1



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

January 17, 2013

Bureau of Land Management Mark Kelly 1235 La Plata Hwy Farmington, NM 87401

VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: Sellers Federal LS 002M

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about February 18, 2013. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper Surface Land Negotiator BP America Production Company

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

January 18, 2013

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

SELLERS FEDERAL LS 002M API 30-045-29080 (M) Section 30 – T30N – R10W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close two 21 bbl. BGT's and a 18 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401



