District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method
Closure of a pit, below-grade tank, or proposed alternative method
☐ Modification to an existing permit/or registration☐ Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
5-2390 Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1.
Operator: BP America Production CompanyOGRID #:778OIL CONS. DIV DIST. 3 Address:200 Energy Court, Farmington, NM 87401 Facility or well name:Gallegos Canyon Unit 242EJUL 2 1 2014
Address: _200 Energy Court, Farmington, NM 87401
Facility or well name:Gallegos Canyon Unit 242E
API Number:3004523901OCD Permit Number:
U/L or Qtr/QtrK Section24 Township28N Range12W County:San Juan
Center of Proposed Design: Latitude36.64487 Longitude108.06735 NAD: □1927 ☑ 1983
Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined Liner type: Thickness mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. ■ Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank B
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Single walled/Double bottomed, side walls not visible
Liner type: Thicknessmil
4.



Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	, hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	·
Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
<u>Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.</u> NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
visual hispection (certification) of the proposed site, Aeriai photo, Satemie image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,	
or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock	
watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
10. Tampagan Pita Emarganar Pita and Palary grada Tanka Parmit Application Attachment Charliste. Subsection P. of 10.15.17.0 N	IMAC
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	15 17 9 NMAC
and 19.15.17.13 NMAC	13.17.9 NIVIAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are
☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit.	
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC	.15.17.9 NMAC
Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

12.	
<u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	·
13. Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sout provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	1.62 [1NO

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.	
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. □ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC □ Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC □ Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. □ Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC □ Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17.	
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	of.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (Including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: OCD Permit Number:	5/14
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:5/9/2014	
20.	
Closure Method:	on eveteme only)
Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo ☐ If different from approved plan, please explain.	

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirements.	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Poses	Date:July 18, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit 242E – Tank B (95 bbl) API No. 3004523901 Unit Letter K, Section 24, T28N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows:

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT – Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	40

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride were below the stated limit. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area.

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT was backfilled with clean soil and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT was backfilled with clean soil and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT was backfilled with clean soil and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District 1</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	catio	n and Co	orrective A	ction	1			
						OPERA'	ГOR		☐ Initi	al Report	\bowtie	Final Report
Name of Co	ompany: B	SP.				Contact: Jef						<u>.</u>
		Court, Farmi	ngton, N	M 87401		Telephone 1	No.: 505-326-94	79				
Facility Na	me: Galleg	gos Canyon U	Jnit 242E	}		Facility Typ	e: Natural gas v	vell				
Surface Ow	ner: Feder	ral	· · · · · · · · · · · · · · · · · · ·	Mineral (Owner:	Federal			API No	. 3004523	901	
				LOC	ATIO	N OF RE	LEASE					
Unit Letter K	Section 24	Township 28N	Range 12W	Feet from the 1,600		n/South Line	Feet from the 1,455	East/\ West	West Line	ine County: San Juan		
	•	Lati	tude3	6.64487		Longitud	e108.06735_					
				NAT	rure	OF REL	EASE					
Type of Rele						Volume of	Release: N/A			Recovered: 1		
Source of Re	lease: belov	w grade tank –	95 bbl, T	ank B		Date and F N/A	lour of Occurrenc	e:	Date and	Hour of Dis	covery:	N/A
Was Immedi	ate Notice (If YES, To	Whom?					
			Yes _	No Not R	equired							
By Whom? Was a Water	n	1 10				Date and H		1 337				
was a water	course Kea		Yes 🗵	No		II YES, VO	lume Impacting t	ne wate	ercourse.			
Describe Cau	ise of Probl		dial Action	n Taken.* Sampli			the BGT was do		g removal	to ensure no	soil im	pacts from
				en.* BGT was reactive well area.	·moved	and the area u	nderneath the BG	1 was s	ampied. Ti	ne excavated	i area w	'as
regulations a public health should their c or the environ	Il operators or the envi operations l nment. In a	are required to ronment. The nave failed to a	report ar acceptance dequately CD accep	nd/or file certain rece of a C-141 reporting and received investigate a	elease r ort by the emedia	notifications ar ne NMOCD m te contaminati	knowledge and und perform correctarked as "Final Roon that pose a threather of the operator of the control of the operator operator of the operator ope	tive acti eport" d eat to gr	ions for rele oes not reli ound water	eases which eve the oper surface wa	may end rator of iter, hun	danger liability nan health
Signature:	off 1	Pesia					OIL CONS	<u>SERV</u>	ATION	DIVISIO	<u>)N</u>	
Printed Name	e: Jeff Peac	e ·				Approved by	Environmental S _I	pecialist	i:			
Title: Area E	nvironment	al Advisor				Approval Dat	e:]	Expiration l	Date:		
E-mail Addre	ess: peace.j	effrey@bp.cor	n			Conditions of	Approval:			Attached		
Date: July 1	8 2014		Phone: 50)5-326-9479								

^{*} Attach Additional Sheets If Necessary

FIELD REPORT: Conditional EST CONFRWATION RELEASE INVESTIGATION / OTHER: PAGE # 1 of 1	CLIENT: BP		ENGINEERING, IN		API#: 300	4523901
SITE INFORMATION: SITEME GCU# 242E MAINDAMIN K SEC 24 TAP 28N RNS. 12W PM MM CNTY SJ ST NM MAINDAMIN K SEC 24 TAP 28N RNS. 12W PM MM CNTY SS NM MM CNTY S	OCICITI.	· ·		WI 07-713		A&B
CALADIANT K Sec 24 TMP 28N RNS 12W PM NM CATY S.J. T NM DATE FIRSTED	FIELD REPORT:	(circle one): BGT CONFIRMATION] / RELEASE INVESTIGATION /	OTHER:	PAGE#:	1 of 1
LEASE & SF078904 PROD FORMATION DK CONTRACTOR MEY S.	SITE INFORMATION		242E		DATE STARTED:	05/01/14
LEASE # \$F078904 PROD PORIANTION DK CONTRACTON BELKHONN SPECIALST(S) NUV REFERENCE POINT: WELL HEAD (WH.) GPS COORD: 36,64493 X 108,06717 GL BLEV: 5,3851 1	QUAD/UNIT: K SEC: 24 TWP:	28N RNG: 12W PA	M: NM CNTY: SJ	st: NM	DATE FINISHED:	
REFERENCE POINT: WELL HEAD (WHI) GPS COORD: 36,6449X 108.06717 GL ELEV: 5,851*	1/4-1/4/FOOTAGE: 1,600'S / 1,45	55'W NE/SW LEASE			ENVIRONMENTAL	
19 SS BGT (SWVDB) - B GPS COORD. 36.64487 X 108.06735 DEFENDENTIAL WITH SET OF	LEASE #: SF078904	PROD. FORMATION: DK	CONTRACTOR: MBF - S.	GLYNN	SPECIALIST(S):	NJV
2) 95 BGT (SW/DB) - B GPS COORD: 36.64487 X 108.06735 DESTAUGEBEARING FROM WH: 68.5', \$64.5W PROD. TANK GPS COORD: 36.644844 X 108.067497 DESTAUGEBEARING FROM WH: 99', \$68W 99'	REFERENCE POINT		PS COORD.: 36.644	93 X 108.06717	GL ELE	v.: 5,851'
99 S68W S68W S68		GPS COOKD	36.64407 X 408.0675 8	DISTANCEBEA	RING FROM W.H.	427', NS4W
A) GPS COORD: DESIGNED MATERIAL CHANGE CUSTODY RECORDS # OR LAB USED HALL 1) SPOT TROOPS (SS) A SAMPLEID HALL 2) SAMPLEID SPCTB @ 6' (95) - B SUREDRE OS/01/14 SHEET 1155 L-3 ANALYS 418.1/801507362157300.0 (CI) TAX- 2) SAMPLEID: SAMPLE	,					· · · ·
SAMPLING DATA: CHANGE CUSTODY RECORDS # OR LAB USED HALL 1) SPORTS STORE STORES STORED STORES STORES STORED STORE STORED STORES STORED STORES STORED STORE STORED STORES STORED STORES STORED STORES STORED STORES STORED STORE STORED STORES STORED STORE STORED STORES STORED ST	3) PROD. TANK	GPS COORD.: 3	<u>6.644844 X 108.06749</u>	7 DISTANCE/BEA	RING FROM W.H.:	99', S68W
SAMPLETING DATA: INVANOR COLORS & CALL BUSED HALL 1) SPC-TB & C (95) A SAMPLE DE SOUND A SOUND SPC-TABLE SECTION SPC-TB & C (95) B SAMPLED BY SUPPLEMENT STORES SPC-TB & C (95) B SAMPLED BY SAMPLED BY SAMPLED BY SAMPLED BY SAMPLED BY SAMPLED BY SAMPLED SAMPLED BY	4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
2) SAMPLEID 5 PC-TB @ 6' (95) - B SAMPLEIDE SA	SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) #	OR LAB USED: HA	LL		READING
3) SAMPLE ID: SAMPLE ID: SAMPLE DIE SAMPLE ID: SAMPLE ID: SAMPLE ID: SAMPLE DIE SAMPLE ID: SAMPLE ID: SAMPLE ID: SAMPLE DIE SOIL COLOR: SAMPLE ID: SAMPLE DIE SOIL COLOR: MODERATE BROWN PLASTICITY CLAY / CLAY / CLAY / CLAY / CRAY / CLAY		,				
A) SAMPLETO: SOIL DESCRIPTION: SOIL TYPE: SAND / SILTY SAND SOIL COLORS: MODERATE BROWN COMESION (ALL OTHERS) (EXCLUSESIVE SIGNITY COMESIVE / HIGHLY COMESIVE / CLAY'S CLAY'S ROND PLASTIC / SIGNITY PLASTIC / COMESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC PLASTIC / HI	2) SAMPLE ID: 5 PC-TB @ 6' (95) - B SAMPLE DATE: 05/0	1/14 SAMPLETIME: 1155	LAB ANALYSIS: 418.1/8	8015B/8021B/300).0 (CI) NA
SOIL COLOR: MODERATE BROWN CORRESTOR MODERATE CREATER CORRESTOR MODERATE M	3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
SOIL COLOR MODERATE BROWN PLASTICITY (CLAYS), NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDICAL COMESION / MALORISTING/MODES/MS MODERATE / MEDICAL COMESION / MALORISTING/MODES/MS MODERATE / MEDICAL COMESION / MALORISTING/MODES/MS MODERATE / MO						
SITE SKETCH BGT Located: off on site PLOT PLAN circle: attached OMCALIB.READ. = NA ppm RE=0.52 OMCALIB.GAS = NA ppm RE=0.5	COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY SLIGHTLY MOIST MOIST / W. SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED: YES N SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE	Y COHESIVE / COHESIVE / HIGHLY COHESIVE OOSE / FIRM! DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED OF PTS. 5 O EXPLANATION - LOST INTEGRITY OF EQUIPMEN D AND/OR OCCURRED : YES NO EXF	DENSITY (COHESIVE CLAYS 8 HC ODOR DETECTED: YES NO ANY AREAS DISPLAYING WETNE NT: YES NO EXPLANATION - PLANATION:	SILTS): SOFT/FIRM/ EXPLANATION- SS: YES NO EXPLAI	STIFF / VERY STIFF / F	
SITE SKETCH BGT Located: off on site PLOT PLAN circle: attached OWN CALIB. READ. = NA ppm NA OWN CALIB. READ. = NA ppm NA NA METER RUN MISCELL. NOTES WO: N15386440 PO #: PK: ZEVH01BGT2 PJ #: Z2-006Q0 Permit date(s): 06/08/10 OCD Appr. date(s): 11/25/13 Tank OVM = Organic Vapor Meter ID. ppm = parts per million A BGT Sidewalls Visible: Y (N) B BGT Sidewalls Visible: Y (N)					,	400
METER RUN METER RUN METER RUN METER RUN METER RUN MISCELL. NOTES WO: N15386440 PO #: PK: ZEVH01BGT2 PJ #: Z2-006Q0 Permit date(s): 06/08/10 OCD Appr. date(s): 11/25/13 Tank; OVM OCALIB. GAS = NA ppm MISCELL. NOTES WO: N15386440 PO #: PK: ZEVH01BGT2 PJ #: Z2-006Q0 Permit date(s): 06/08/10 OCD Appr. date(s): 11/25/13 Tank; OVM OCALIB. GAS = NA ppm MISCELL. NOTES WO: N15386440 PO #: PK: ZEVH01BGT2 PJ #: Z2-006Q0 Permit date(s): 06/08/10 OCD Appr. date(s): 11/25/13 Tank; OVM OCALIB. GAS = NA ppm MISCELL. NOTES WO: N15386440 PO #: PK: ZEVH01BGT2 PJ #: Z2-006Q0 Permit date(s): 06/08/10 OCD Appr. date(s): 11/25/13 Tank; OVM OCALIB. GAS = NA ppm METER WO: N15386440 PO #: PK: ZEVH01BGT2 PJ #: Z2-006Q0 Permit date(s): 06/08/10 OCD Appr. date(s): 11/25/13 Tank; OVM OCALIB. GAS = NA ppm METER WO: N15386440 PO #: PK: ZEVH01BGT2 PJ #: Z2-006Q0 Permit date(s): 06/08/10 OCD Appr. date(s): 1/25/13 Tank; OVM OCALIB. GAS = NA ppm METER WO: N15386440 PO #: PK: ZEVH01BGT2 PJ #: Z2-006Q0 Permit date(s): 06/08/10 OCD Appr. date(s): 1/25/13 Tank; OVM OCALIB. GAS = NA ppm METER WO: N15386440 PO #: PK: ZEVH01BGT2 PJ #: Z2-006Q0 Permit date(s): 06/08/10 OCD Appr. date(s): 1/25/13 Tank; OVM OCALIB. CAN ppm ABGT Sidewalls Visible: Y (N) BGT Sidewalls Visible: Y / N Magnetic declination: 10 ° E						
## W.H. ## W.H. ## W.H. ## W.H. ## ZEVH01BGT2 ## Z2-006Q0 ## Permit date(s): 06/08/10 ## OCD Appr. date(s): 11/25/13 ## OVM = Organic Vapor Meter DOCD Appr. date(s): 11/25/13 ## OVM = Organic Vapor Meter DOCD Appr. date(s): 11/25/13 ## OVM = Organic Vapor Meter DOCD Appr. date(s): 11/25/13 ## OVM = Organic Vapor Meter DOCD Appr. date(s): 11/25/13 ## OVM = Organic Vapor Meter DOCD Appr. date(s): 11/25/13 ## BGT Sidewalls Visible: Y (N) ## BGT Sidewalls Visible: Y (N) ## BGT Sidewalls Visible: Y / N		METER	ioj [<u> Lot Lat</u> di	N TIME	CALIB. GAS = NA am/pm D/	A ppm RE = 0.32 ATE: NA NOTES
PROD. TANK NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD; APPLICABLE OR NOT AVAILABLE; SW- SINGLE WALL; DW- DOUBLE WALL; SB - SINGLE BOTTOM; DB- DOUBLE BOTTOM. PROD. TANK X - S.P.D. PK: ZEVH01BG12 PJ #: Z2-006Q0 Permit date(s): 06/08/10 OCD Appr. date(s): 11/25/13 Tank OVM = Organic Vapor Meter ppm = parts per million A BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N Magnetic declination: 10° E	SEPAR	RATOR	⊕ wh.	<u>P</u>		
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELOW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; NA - NOT APPLICABLE OR NOT AVAILABLE; SW - SINGLE WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM.	PROD.	│ PBGTL	· ·	P P O Tai	J#: Z2-006Q ermit date(s): CD Appr. date(s): OVM = Organic ppm = parts per A BGT Sidewalls Visit BGT Sidewalls Visit	00 06/08/10 11/25/13 Vapor Meter r.million ole: Y (N)
APPLICABLE OR NOT AVAILABLE; SW - SINGLE WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM, UB - DOUBLE BOTTOM.				; W.H. = WELL HEAD;		
	APPLICABLE OR NOT AVAILABLE; SW - SINGLE	E WALL; DW - DOUBLE WALL; SB - SINGLE BO	OTTOM; DB - DOUBLE BOTTOM.	Ш	iagnesic decimalio	<u>ль. IV Ц</u>

Analytical Report

Lab Order 1405109

Date Reported: 5/9/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 6' (95)-B

Project: GCU # 242E

Collection Date: 5/1/2014 11:55:00 AM

Lab ID: 1405109-002

Received Date: 5/3/2014 10:20:00 AM

Analyses	Result	RL Q	ual Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RAN	GE ORGANICS				Analys	t: BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	5/6/2014 6:54:03 PM	12995
Surr: DNOP	98.3	57.9-140	%REC	1	5/6/2014 6:54:03 PM	12995
EPA METHOD 8015D: GASOLINE R	ANGE				Analys	t: NSB
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	5/8/2014 12:07:34 AM	12999
Surr: BFB	88.5	74.5-129	%REC	1	5/8/2014 12:07:34 AM	12999
EPA METHOD 8021B: VOLATILES					Analys	t: NSB
Benzene	ND .	0.048	mg/Kg	1	5/8/2014 12:07:34 AM	12999
Toluene	ND	0.048	mg/Kg	1	5/8/2014 12:07:34 AM	12999
Ethylbenzene	ND	0.048	mg/Kg	1	5/8/2014 12:07:34 AM	12999
Xylenes, Total	ND	0.095	mg/Kg	1	5/8/2014 12:07:34 AM	12999
Surr: 4-Bromofluorobenzene	104	80-120	%REC	1	5/8/2014 12:07:34 AM	12999
EPA METHOD 300.0: ANIONS					Analyst	: JRR
Chloride	40	30	mg/Kg	20	5/7/2014 3:31:51 PM	13053
EPA METHOD 418.1: TPH	•				Analyst	BCN
Petroleum Hydrocarbons, TR	, ND	20	mg/Kg	1	5/6/2014	12981

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 2 of 7

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1405109

09-May-14

Client:

Blagg Engineering

Project:

GCU # 242E

Sample ID MB-13053

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 13053

RunNo: 18482

Prep Date: 5/7/2014

Analysis Date: 5/7/2014

Units: mg/Kg

SeqNo: 533533

RPDLimit

Analyte

Client ID:

Prep Date:

Result

PQL 1.5

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD

Qual

Qual

Chloride

ND

Sample ID LCS-13053 LCSS

5/7/2014

SampType: LCS

TestCode: EPA Method 300.0: Anions

RunNo: 18482

Batch ID: 13053 Analysis Date: 5/7/2014

SeqNo: 533534

Units: mg/Kg

LowLimit

HighLimit %RPD **RPDLimit**

Result

PQL SPK value SPK Ref Val %REC

91.7

Chloride

Analyte

14

1.5

15.00

90

110

Qualifiers:

Value exceeds Maximum Contaminant Level.

Ε Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDlimit

R RPD outside accepted recovery limits

S Spike Recovery outside accepted recovery limits Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

P Sample pH greater than 2.

RLReporting Detection Limit Page 3 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#:

5.72

120

1405109

09-May-14

20

Client:

Blagg Engineering

Project:

Petroleum Hydrocarbons, TR

GCU # 242E

Sample ID MB-12981	SampType: MBLK	TestCode: EPA Method	418.1: TPH	
Client ID: PBS	Batch ID: 12981	RunNo: 18411		
Prep Date: 5/2/2014	Analysis Date: 5/6/2014	SeqNo: 531748	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	ND 20			
Sample ID LCS-12981	SampType: LCS	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS	Batch ID: 12981	RunNo: 18411		•
Prep Date: 5/2/2014	Analysis Date: 5/6/2014	SeqNo: 531749	Units: mg/Kg	
Analyte .	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	100 20 100.0	0 104 80	120	
Sample ID LCSD-12981	SampType: LCSD	TestCode: EPA Method	418.1: TPH	<u> </u>
Client ID: LCSS02	Batch ID: 12981	RunNo: 18411		
Prep Date: 5/2/2014	Analysis Date: 5/6/2014	SeqNo: 531751	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual

100.0

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Ε

Analyte detected below quantitation limits J

О RSD is greater than RSDlimit

R RPD outside accepted recovery limits

Spike Recovery outside accepted recovery limits

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Sample pH greater than 2.

RL Reporting Detection Limit Page 4 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#:

1405109

09-May-14

Client:

Blagg Engineering

Project:

GCU # 242E

Sample ID MB-12995	SampT	ype: ME	BLK	Tes	tCode: El	PA Method	8015D: Dies	el Range C	Organics	
Client ID: PBS	Batch	1D: 12	995	F	RunNo: 1	8374				
Prep Date: 5/5/2014	Analysis D	ate: 5/	/5/2014	S	SeqNo: 5	30743	Units: mg/F	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Surr: DNOP	8.2		10.00		81.9	57.9	140			

Sample ID LCS-12995	SampT	ype: LC	s	TestCode: EPA Method 8015D: Diesel Range Organics										
Client ID: LCSS	Batcl	n ID: 12	995	F	RunNo: 1	8374								
Prep Date: 5/5/2014	Analysis Date: 5/5/2014			SeqNo: 530744			Units: mg/h	(g						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Diesel Range Organics (DRO)	44	10	50.00	0	88.0	60.8	145							
Surr: DNOP	3.9		5.000		78.0	57.9	140							

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits

S Spike Recovery outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

P Sample pH greater than 2.

RL Reporting Detection Limit

Page 5 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#:

1405109

09-May-14

Client:

Blagg Engineering

Project:

GCU # 242E

Sample ID MB-12999 MK

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

PBS

Batch ID: R18443

PQL

RunNo: 18443

Analysis Date: 5/6/2014

SeqNo: 532561

Units: %REC

Prep Date:

%REC

Analyte

Result

129

SPK value SPK Ref Val

HighLimit

Qual

Surr: BFB

880

1000

88.4

RPDLimit

Sample ID LCS-12999 MK

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

%RPD

Client ID:

LCSS

Batch ID: R18443

RunNo: 18443

Prep Date:

Analysis Date: 5/6/2014

PQL

SeqNo: 532562

Units: %REC

Analyte

Result 990

SPK value SPK Ref Val %REC

LowLimit

HighLimit %RPD

Surr: BFB

Batch ID: 12999

1000 98.5 74.5

RPDLimit

Qual

Sample ID MB-12999 PBS

129

Client ID:

Prep Date:

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

RunNo: 18443

Lowl imit

74.5

129

Analyte

5/5/2014

Analysis Date: 5/6/2014

SeqNo: 532566

Units: mg/Kg

Result **PQL**

SPK value SPK Ref Val

%REC LowLimit

HighLimit

%RPD

Gasoline Range Organics (GRO)

ND 5.0 880

1000

88.4

74.5

RPDLimit

Qual

Surr: BFB

Sample ID LCS-12999

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

%RPD

Prep Date:

Client ID:

5/5/2014

LCSS

Batch ID: 12999

Analysis Date: 5/6/2014

PQL

RunNo: 18443

SeqNo: 532567

Units: mg/Kg

RPDLimit Qual

Analyte Gasoline Range Organics (GRO) Result

SPK value SPK Ref Val

%REC LowLimit 91.0

71.7

HighLimit 134

Surr: BFB

23 5.0 990

25.00 1000

98.5

74.5

129

Е

S

Qualifiers:

Spike Recovery outside accepted recovery limits

- Analyte detected below quantitation limits
- RPD outside accepted recovery limits
- Value exceeds Maximum Contaminant Level.
- RSD is greater than RSDlimit 0

Value above quantitation range

- Analyte detected in the associated Method Blank
- Н ND
- Not Detected at the Reporting Limit Sample pH greater than 2.
- RL Reporting Detection Limit

Holding times for preparation or analysis exceeded

Page 6 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#: 1405109

09-May-14

Client:

Blagg Engineering

Project:

GCU # 242E

Sample ID MB-12999	SampType: MBLK Batch ID: 12999			Tes						
Client ID: PBS				, F						
Prep Date: 5/5/2014	Analysis Date: 5/6/2014		S	SeqNo: 5	32595	Units: mg/h	(g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050		•						
Toluene .	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	. ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		105	80	1,20	···		
Sample ID LCS-12999	SampType: LCS			Tes	tiles					
Client ID: LCSS	Batch ID: 12999			RunNo: 18443						
Prep Date: 5/5/2014	Analysis [Date: 5 /	6/2014	S	eqNo: 5	32596	Units: mg/F	(q		

Sample ID LCS-12999	Samp	Type: LC	ss	Tes						
Client ID: LCSS	Batc	h ID: 12	999	F	RunNo: 1					
Prep Date: 5/5/2014	Analysis [Date: 5 /	6/2014	5	SeqNo: 5	32596	Units: mg/F	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	114	80	120			
Toluene	1.1	0.050	1.000	0	107	80	120			
Ethylbenzene	1.1	0.050	1.000	0	107	80	120			
Xylenes, Total	3.1	0.10	3.000	0	105	80	120			
Surr: 4-Bromofluorobenzene	1.1		1.000		113	80	120			

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 7 of 7



Page 1 of 1

trail Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: **BLAGG** Work Order Number: 1405109 RcptNo: 1 Received by/date: Logged By: Lindsay Mangin 5/3/2014 10:20:00 AM Completed By: Lindsay Mangin 5/5/2014 7:39:16 AM Reviewed By: Chain of Custody Yes 🛄 1 Custody seals intact on sample bottles? No ._ Not Present . 2. Is Chain of Custody complete? Yes 🔽 No 🗌 Not Present i... !3. How was the sample delivered? Courier Log In 4. Was an attempt made to cool the samples? No 5. Were all samples received at a temperature of >0° C to 6.0°C No 1 1 NA : 6. Sample(s) in proper container(s)? No 🗔 7. Sufficient sample volume for indicated test(s)? 8. Are samples (except VOA and ONG) properly preserved? :9. Was preservative added to bottles? Yes No NA No 10.VOA vials have zero headspace? No VOA Vials 🗸 Yes 11. Were any sample containers received broken? # of preserved bottles checked 12. Does paperwork match bottle labels? No 🗔 for pH: Yes (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No [.. 13. Are matrices correctly identified on Chain of Custody? Yes No 🛄 14. Is it clear what analyses were requested? Checked by: 15. Were all holding times able to be met? No (If no, notify customer for authorization.) Special Handling (if applicable) 16. Was client notified of all discrepancies with this order? Yes ... Nο Person Notified: Date: By Whom: Via: eMail Phone Fax In Person Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No Temp °C | Condition | Seal Intact | Seal No 1.0 Good

Client:	BLAGG ENGR. / BP AMERICA			Standard Project Name	HALL ENVIRONMENTAL ANALYSIS LABORATORY www.hallenvironmental.com																
Mailing Ad	ddress:	P.O. BO	X 87	GCU # 242E Project #:				www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109 Tel. 505-345-3975 Fax 505-345-4107													
		BLOOM	FIELD, NM 87413																		
Phone #:		(505) 63	2-1199	1													Į.			7.7	2. 9
email or F	ax#:			Project Manag	ger:				911												
QA/QC Pad Standa	-		Level 4 (Full Validation)		NELSON V	ELEZ)21B)	only)	MINO			(S)		204,50,	PCB's			er - 300.1)			ω l
Accreditat		☐ Other		Sampler: On ice	NELSON V		MB5 (8021B)	TPH (Gas	/DRO/	18.1)	04.1)	270SIN		3,NO ₂ ,6	, / 8082		(A)	0.0 / wat			sample
□ EDD (1				Sample Temp	ectional more or man house of one of the Course	d .		+ 1	GRO	od 4	od 5	or 8	tals	J,NC	ides	ित	-70	1-30		<u>.</u>	osite
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX + MITE	BTEX + MTBE	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 82705IMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soll - 300.0 / water		Grab sample	5 pt. composite
-5/1/14	1450	-3 0 1L		4-02:1	Gool	001	V		*	4								4		4	4
				·																	
5/1/14	1155	SOIL	5PC - TB @ 6' (95)-B	4 oz 1	Cool	-002	٧		٧	٧								٧			٧
				<u> </u>	<u> </u>			_													
	· 			<u> </u>	<u> </u>			_		_										_	
				ļ				_	_											_	
*	Tima	Dalin aviah	od bus	Received by:	<u> </u>	Date Time															
2/14 :e:	Time:	Relinquish	n V J	Received by:	Hally	5/2/14 815 Date Time	I	. DIF	RECT	LY T (urt, i	Farm	ingto	on, N	IM 81	7401	,		
2/14	11,44	Ch	it I have	Y / //	10	5/03/4/1020	Wo	rk O	rder	:	N15	3864	140		Pay	key:	<u>Z</u>	EVH	01BG	T2	





YBP: America Production Company 1200 Energy Court Farmington, NM 87401 IPhone: (505) 326-9200

January 30, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a bellow grade tank Well Name: GALLEGOS CANYON UNIT 242E

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Ranagraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/semove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about March 3, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

January 30, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 242E API 30-045-23901 (G) Section 24 - T28N - R12W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close two 95 \mathbb{B} \mathbb{B} \mathbb{B} \mathbb{C} \mathbb{F} is that will no longer be operational at this well site.

Should you have any questions, please feel free to contact IBP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



