. Ъ

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

۲

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan	Application
Proposed Alternative Method Permit or Closure Plan 12056 145-07 145-07 145-07 145-07 150 150 150 150 150 150 150 150	ethod
Instructions: Please submit one application (Form C-144) per individual pit, below-grade	a tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollice environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable government.	ution of surface water, ground water or the
Operator: BP America Production Company OGRID #:	778
Operator: BP America Production Company OGRID #:         Address:200 Energy Court, Farmington, NM	OIL CONS. DIV DIST. 3
Facility or well name:Hardie LS 3	
API Number:	
U/L or Qtr/QtrASection25Township29NRange8W	County:San Juan
Center of Proposed Design: Latitude36.70147Longitude107.62289	NAD: 🗌 1927 🛛 1983
Surface Owner: 🖾 Federal 🗌 State 🗋 Private 🗌 Tribal Trust or Indian Allotment	
2.     Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover     Permanent Emergency Cavitation P&A Multi-Well Fluid Management     Low Ch     Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory OtherVolume:bbl Dim	· · · · · · · · · · · · · · · · · · ·
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank B	
Below-grade tank:       Subsection I of 19.15.17.11 NMAC       Tank B         Volume:      21.0      bbl       Type of fluid:      Produced water	
Tank Construction material:Steel	
Secondary containment with leak detection 🗌 Visible sidewalls, liner, 6-inch lift and automatic overflow	v shut-off
□ Visible sidewalls and liner ⊠ Visible sidewalls only □ Other _Single walled/Double bottom	ned
Liner type: Thickness mil 🗌 HDPE 🗌 PVC 🗋 Other	
<ul> <li>Alternative Method:</li> <li>Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental B</li> </ul>	ureau office for consideration of approval.



.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

**Netting:** Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other\_

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	
<u>Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.</u> - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
<ul> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul>	🗌 Yes 🗌 No
<ul> <li>Within the area overlying a subsurface mine. (Does not apply to below grade tanks)</li> <li>Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division</li> </ul>	Yes 🗌 No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	🗌 Yes 🗌 No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
<ul> <li>Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No
<ul> <li>Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.</li> <li>NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site</li> </ul>	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
<ul> <li>Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	Yes 🗌 No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	📙 Yes 📙 No
<ul> <li>application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
<ul> <li>Within 100 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
<ul> <li>Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No
<ul> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	Yes No
<ul> <li>Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;</li> <li>NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No
<ul> <li>Within 300 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
<ul> <li>Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No
<ul> <li>Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	🗌 Yes 🗌 No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
<ul> <li>Within 500 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	Yes No
<sup>10.</sup> <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 N <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc</i> <i>attached.</i>	
<ul> <li>Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC</li> <li>Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9</li> <li>Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC</li> <li>Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC</li> <li>Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1</li> <li>and 19.15.17.13 NMAC</li> </ul>	
Previously Approved Design (attach copy of design) API Number: or Permit Number: _	
II.         Multi-Well Fluid Management Pit Checklist:       Subsection B of 19.15.17.9 NMAC         Instructions:       Each of the following items must be attached to the application.         Please indicate, by a check mark in the box, that the doc attached.         Design Plan, based upon the appropriate requirements of 10.15.17.11 NMAC	uments are
<ul> <li>Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>A List of wells with approved application for permit to drill associated with the pit.</li> <li>Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC</li> </ul>	15.17.9 NMAC
<ul> <li>Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC</li> <li>Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC</li> </ul>	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

۰

12. <u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the a attached.	locuments are
<ul> <li>Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC</li> <li>Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC</li> <li>Climatological Factors Assessment</li> </ul>	
<ul> <li>Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC</li> </ul>	
<ul> <li>Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>Quality Control/Quality Assurance Construction and Installation Plan</li> </ul>	
<ul> <li>Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> </ul>	
<ul> <li>Nuisance or Hazardous Odors, including H<sub>2</sub>S, Prevention Plan</li> <li>Emergency Response Plan</li> </ul>	
<ul> <li>Oil Field Waste Stream Characterization</li> <li>Monitoring and Inspection Plan</li> </ul>	
<ul> <li>Erosion Control Plan</li> <li>Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC</li> </ul>	
<sup>13.</sup> Proposed <u>Closure</u> : 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fl	uid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)	
<ul> <li>On-site Closure Method (Only for temporary pits and closed-loop systems)</li> <li>In-place Burial</li> <li>On-site Trench Burial</li> </ul>	
Alternative Closure Method	
<u>Waste Excavation and Removal Closure Plan Checklist</u> : (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached.	nttached to the
<ul> <li>Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC</li> <li>Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC</li> </ul>	
<ul> <li>Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)</li> <li>Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC</li> </ul>	
<ul> <li>Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC</li> <li>Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC</li> </ul>	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC	
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Put 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
<ul> <li>Ground water is more than 100 feet below the bottom of the buried waste.</li> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells</li> </ul>	□ Yes □ No □ NA
<ul> <li>Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗍 No
<ul> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	🗌 Yes 🗌 No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.	🗌 Yes 🗍 No
- NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinanceForm C-144Oil Conservation DivisionPage 4 of	<sup>2</sup> 6

.

<ul> <li>adopted pursuant to NMSA 1978, Section 3-27-3, as amended.</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul>	
	Yes No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	🗌 Yes 🗌 No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	🗌 Yes 🗍 No
Within a 100-year floodplain. - FEMA map	🗌 Yes 🗍 No
1	
On-Site Closure Plan Checklist:       (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plate by a check mark in the box, that the documents are attached.         Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC         Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC         Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.1         Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC         Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC         Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC         Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC         Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canned Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC         Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed and be	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Cosure Plan (only) OCD Conditions (see attachment)	_/
OCD Representative Signature: Approval Date: Approval Date: S	
Approvar Date: Approvar Date:	
Title: <u>Ervironental</u> Spec OCD Permit Number:	
Title: <u>Every sonerdal</u> <u>Spec</u> <u>19.</u> <u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not a section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.
Title: <u>First someword</u> Spec       OCD Permit Number:         19. <u>Closure Report (required within 60 days of closure completion)</u> :       19.15.17.13 NMAC         Instructions:       Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report is required to be submitted to the division within 60 days of the completion of the closure activities.	the closure report.
Title: <u>Every sonerdal</u> <u>Spec</u> <u>19.</u> <u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not a section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this

.

22. Operator Closure Certification:	
	his closure report is true, accurate and complete to the best of my knowledge and ure requirements and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Name (Print):      Jeff Peace         Signature:	Date: July 28, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

•

# BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

## <u>Hardie LS 3 Tank B (21 bbl)</u> <u>API No. 3004507892</u> <u>Unit Letter A, Section 25, T29N, R8W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B. D. or E of 19.15.17.17 NMAC.

### **General Closure Plan**

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

## Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT – Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	32
Chlorides	US EPA Method 300.0 or 4500B	250 or background	92

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
   Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area under the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area under the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area under the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

## BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

•

## State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Frar	icis Dr., Sant	a Fe, NM 8750	>	S	anta F	e, NM 875	505		· · · · · · · · · · · · · · · · · · ·
			Rel	ease Notifi	catio	n and Co	orrective A	ction	
				·		<b>OPERA</b> '	ГOR	. [] Initia	al Report 🛛 🛛 Final Report
Name of Co	ompany: B	Р				Contact: Jef			
	Address: 200 Energy Court, Farmington, NM 87401						No.: 505-326-94	79	
Facility Nat						·	e: Natural gas v		· · · · · · · · · · · · · · · · · · ·
		-							
Surface Ow	ner: Feder	al	·	Mineral (	Owner:	Federal		API No	. 3004507892
					ATIO	N OF RE	LEASE		
Unit Letter A	Section 25	Township 29N	Range 8W	Feet from the 990	North North	n/South Line 1	Feet from the 990	East/West Line East	County: San Juan
	I	Lat	itude3	6.70147		Longitud	e107.62289_		
				NAT	TURE	OF REL	EASE		
Type of Rele							Release: N/A		Recovered: N/A
		w grade tank –	- 21 bbl, T	ank B		N/A	lour of Occurrenc	ce: Date and	Hour of Discovery: N/A
Was Immedi	ate Notice (		Yes 🗌	] No 🛛 Not R	equired	If YES, To	Whom?		
By Whom?						Date and H	lour		
Was a Water	course Read		Yes 🗵	No			olume Impacting	the Watercourse.	
If a Watercou	urse was Im	pacted, Descr	ibe Fully.	k			<u></u>		
		r,	····)·						
Dereziler der	Duch1	D					I DOT		·····
							sis results are atta		o ensure no soil impacts from
	in unaryono .		., 0151		on stan	dards. Thirdy	···	ioned.	
					moved	and the area u	nderneath the BG	T was sampled. Th	ne excavated area was
backfilled an	a compacte	d and is still v	ithin the	active well area.					
									uant to NMOCD rules and
									eases which may endanger
									eve the operator of liability
									, surface water, human health
		ws and/or regu		tance of a C-141	report	loes not reliev	e the operator of	responsibility for co	ompliance with any other
Tederal, state,	, 01 10cai 1a						OIL CON	SEDVATION	DIVISION
٥	-DA 11	/					<u>OIL CON</u>	SERVATION	DIVISION
Signature:	9KK V	ave							
				Approved by Environmental Specialist:					
Printed Name: Jeff Peace									
Title: Area Environmental Advisor						Approval Da	al Date: Expiration Date:		Date:
						u			
E-mail Addre	ess: peace.je	effrey@bp.coi	n			Conditions of Approval:		Attached	
Date: July 2	Date: July 28, 2014 Phone: 505-326-9479								

\* Attach Additional Sheets If Necessary

	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413	API #: 3004507892
	(505) 632-1199	(if applicble):B
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:	PAGE #:1 of1
SITE INFORMATION	SITE NAME: HARDIE LS # 3	DATE STARTED: 05/20/14
QUAD/UNIT: A SEC: 25 TWP:	29N RNG: 8W PM: NM CNTY: SJ ST: N	ATE FINISHED:
1/4 -1/4/FOOTAGE: 990'N / 990'E		
LEASE #: SF078416A	PROD. FORMATION: MV CONTRACTOR: MBF - C. KENNETH	SPECIALIST(S): JCB
REFERENCE POINT	WELL HEAD (W.H.) GPS COORD.: 36.70131 X 107.62	264 GL ELEV.: 6.737'
1) 21 BGT (SW/DB)	GPS COORD.: 36.70147 X 107.62289 DISTAN	CE/BEARING FROM W.H.: 99', N47W
2)	GPS COORD.: DISTAN	CE/BEARING FROM W.H.:
3)	GPS COORD.: DISTAN	CE/BEARING FROM W.H.:
4)	GPS COORD.: DISTAN	CE/BEARING FROM W.H.:
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	OVM READING (ppm)
1) SAMPLE ID: 21 BGT 5pt. @	6'SAMPLE DATE:05/20/14SAMPLE TIME:0645LAB ANALYSIS: 41	
2) SAMPLE ID:	SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:	
3) SAMPLE ID:	SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:	
4) SAMPLE ID:	SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:	
SOIL DESCRIPTION	SOIL TYPE: SAND / SILTY SAND SILT / SILTY CLAY / CLAY / GRAVEL / OTHER	
SOIL COLOR: DARK YE COHESION (ALL OTHERS): NON COHESIVE (SLIGHTL) CONSISTENCY (NON COHESIVE SOILS): LC	COHESIVE / COHESIVE / HIGHLY COHESIVE       DENSITY (COHESIVE CLAYS & SILTS): SOFT / F         XXXE       FIRM / DENSE / VERY DENSE       HC ODOR DETECTED: YES / NO EXPLANATION -	IRM / STIFF / VERY STIFF / HARD
MOISTURE: DRY SLIGHTLY MOIST / MOIST / WA SAMPLE TYPE: GRAB COMPOSITE #		
DISCOLORATION/STAINING OBSERVED: YES N		XPLANATION
SITE OBSERVATION	IS: LOST INTEGRITY OF EQUIPMENT: YES NO EXPLANATION -	
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER:	D AND/OR OCCURRED : YES NO EXPLANATION:	
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA ft. X NA ft. EXCAVATION	NESTIMATION (Cubic Yards) : NA
		NMOCD TPH CLOSURE STD: ppm
SITE SKETCH	BGT Located : off on site PLOT PLAN circle: attached	OVM CALIB. READ. = <b>52.1</b> ppm pr _ 0.5
	PBGTL TO T.B.~6' B.G. BGT N	OVM CALIB. GAS =         100         ppm         RF = 0.52           TIME:         _5:40         ampm         DATE:         _05/20/14
ZOOMED		MISCELL. NOTES
$I \cap I$	WOODEN R.W.	WO:
	R. W.	PO #: PK: USE ZEVH01BGT2
	DEDM	PJ#: Z2-006Q0
PROD. TANK	BERM W.H.	Permit date(s): 06/14/10
	$\oplus$	OCD Appr. date(s): 05/20/14
		Tank OVM = Organic Vapor Meter ID ppm = parts per million
	TO METER /	B BGT Sidewalls Visible: Y/ N
	$\xrightarrow{\text{RUN}} \checkmark X - S.P.D.$	BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	DN DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~ = APPROX.; W.H. = WELL HEAD; OW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; NA - NOT E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM.	Magnetic declination: 10° E
NOTES:	ONSITE: 05/20/14	

•

#### Analytical Report Lab Order 1405989

Date Reported: 5/29/2014

# Hall Environmental Analysis Laboratory, Inc.

-

Lab ID:

CLIENT: Blagg Engineering Project: Hardie LS 3

1405989-001

# Client Sample ID: 21 BGT 5-pt @ 6' Collection Date: 5/20/2014 6:45:00 AM Matrix: SOIL Received Date: 5/22/2014 10:00:00 AM

Result	RL QI	ial Units	DF	Date Analyzed	Batch
E ORGANICS				Analyst	BCN
ND	9.9	mg/Kg	1	5/23/2014 7:57:16 PM	13321
90.3	57.9-140	%REC	1	5/23/2014 7:57:16 PM	13321
NGE				Analyst	: NSB
ND	4.7	mg/Kg	1	5/23/2014 11:34:48 PM	13319
86.5	80-120	%REC	1	5/23/2014 11:34:48 PM	13319
				Analyst	NSB
ND	0.047	mg/Kg	1	5/23/2014 11:34:48 PM	13319
ND	0.047	mg/Kg	1	5/23/2014 11:34:48 PM	13319
ND	0.047	mg/Kg	1	5/23/2014 11:34:48 PM	13319
ND	0.093	mg/Kg	1	5/23/2014 11:34:48 PM	13319
102	80-120	%REC	1	5/23/2014 11:34:48 PM	13319
				Analyst	: JRR
92	30	mg/Kg	20	5/23/2014 6:09:45 PM	13335
				Analyst	JME
32	20	mg/Kg	1	5/27/2014 12:00:00 PM	13322
	E ORGANICS ND 90.3 NGE ND 86.5 ND ND ND ND ND 102 92	E ORGANICS ND 9.9 90.3 57.9-140 NGE ND 4.7 86.5 80-120 ND 0.047 ND 0.047 ND 0.047 ND 0.047 ND 0.047 ND 0.043 102 80-120 92 30	E ORGANICS ND 9.9 mg/Kg 90.3 57.9-140 %REC NGE ND 4.7 mg/Kg 86.5 80-120 %REC ND 0.047 mg/Kg ND 0.047 mg/Kg	E ORGANICS ND 9.9 mg/Kg 1 90.3 57.9-140 %REC 1 NGE ND 4.7 mg/Kg 1 86.5 80-120 %REC 1 ND 0.047 mg/Kg 1 ND 0.093 mg/Kg 1 102 80-120 %REC 1 92 30 mg/Kg 20	E ORGANICS         Analysi           ND         9.9         mg/Kg         1         5/23/2014 7:57:16 PM         90.3         57.9-140         %REC         1         5/23/2014 7:57:16 PM         MGE         Analysi           NGE         Analysi         Analysi         Analysi         MGE         Analysi           ND         4.7         mg/Kg         1         5/23/2014 11:34:48 PM         86.5         80-120         %REC         1         5/23/2014 11:34:48 PM         Analysi           ND         0.047         mg/Kg         1         5/23/2014 11:34:48 PM         ND         0.093         mg/Kg         1         5/23/2014 11:34:48 PM         MD         0.093         mg/Kg         1         5/23/2014 11:34:48 PM         MAalyst           102         80-120         %REC         1         5/23/2014 11:34:48 PM         Maalyst           92         30         mg/Kg         20         5/23/2014 6:09:45 PM<

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Metho	od Blank
	Е	Value above quantitation range	Н	Holding times for preparation or analysis	s exceeded
		Analyte detected below quantitation limits ND Not Detected at the R		Not Detected at the Reporting Limit	Page 1 of 6
	0	RSD is greater than RSDlimit	Р	Sample pH greater than 2.	
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit	
	S	Spike Recovery outside accepted recovery limits			

WO#: 1405989

29-May-14

Client: Project:		Engineering e LS 3										
Sample ID MI	B-13335	SampTy	pe: MI	3LK	Tes	tCode: El	PA Method	300.0: Anion	s			
Client ID: PE	PBS Batch ID: 13335 RunNo: 18847											
Prep Date: 5	5/23/2014	Analysis Da	ite: 5/	23/2014	SeqNo: 544228			Units: <b>mg/Kg</b>				
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Chloride		ND	1.5	······································								
Sample ID LC	CS-13335	SampTy	pe: LC	s	Tes	tCode: El	PA Method	300.0: Anion	s			
Client ID: LC	CSS	Batch	ID: <b>13</b>	335	F	RunNo: 1	8847					
Prep Date: 5	5/23/2014	Analysis Da	te: 5/	23/2014	SeqNo: 544229			Units: mg/K	(g			
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Chloride		14	1.5	15.00	0	95.2	90	110				

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 2 of 6

WO#: 1405989

29-May-14

Client: Blagg I Project: Hardie	Engineering LS 3								
Sample ID MB-13322	SampType: MBLK	TestCode: EPA Method	418.1: TPH						
Client ID: PBS	Batch ID: 13322	RunNo: 18817							
Prep Date: 5/22/2014	Analysis Date: 5/23/2014	SeqNo: 543363	Units: <b>mg/Kg</b>						
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual				
Petroleum Hydrocarbons, TR	ND 20								
Sample ID LCS-13322	D LCS-13322 SampType: LCS TestCode: EPA Method 418.1: TPH								
Client ID: LCSS	Batch ID: 13322	RunNo: 18817							
Prep Date: 5/22/2014	Analysis Date: 5/23/2014	SeqNo: 543364	Units: <b>mg/Kg</b>						
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual				
Petroleum Hydrocarbons, TR	97 20 100.0	0 96.9 80	120						
Sample ID LCSD-13322	SampType: LCSD	TestCode: EPA Method	418.1: TPH						
Client ID: LCSS02	Batch ID: 13322	RunNo: 18817							
Prep Date: 5/22/2014	Analysis Date: 5/23/2014	SeqNo: 543365	Units: mg/Kg						
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual				
Petroleum Hydrocarbons, TR	110 20 100.0	0 110 80	120 12.4	20					

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 6

WO#: 1405989

29-May-14

Client: Blagg Project: Hardie	Engineering LS 3													
Sample ID MB-13321	SampT	Гуре: <b>МЕ</b>	BLK	TestCode: EPA Method 8015D: Diesel Range Organics										
Client ID: PBS	nt ID: PBS Batch ID: 13321			F	RunNo: 1	8820								
Prep Date: 5/22/2014	Analysis Date: 5/23/2014			SeqNo: 543460			Units: mg/k							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Diesel Range Organics (DRO)	ND	10												
Surr: DNOP	9.5	_	10.00		95.1	57.9	140							
Sample ID LCS-13321	SampT	ype: LC	s	Tes	tCode: El	PA Method	8015D: Dies	el Range (	Drganics					
Client ID: LCSS	Batch	h ID: 13	321	F	RunNo: 1	8820								
Prep Date: 5/22/2014	Analysis D	)ate: <b>5</b> /	23/2014	S	SeqNo: 5	43509	Units: mg/k	(g						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Diesel Range Organics (DRO)	47	10	50.00	0	93.6	60.8	145							
Surr: DNOP	4.7		5.000		94.3	57.9	140							

Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

Client: Blagg Engineering

Project: Hardie LS 3

-

Sample ID MB-13319	Samp	Гуре: МЕ	BLK	TestCode: EPA Method 8015D: Gasoline Range									
Client ID: PBS	Batc	h ID: 13	319	F	8829								
Prep Date: 5/22/2014	Analysis [	Date: 5/	23/2014	SeqNo: <b>543975</b> U			Units: <b>mg/H</b>	٩					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Gasoline Range Organics (GRO)	ND	5.0											
Surr: BFB	810		1000		81.3	80	120						
Sample ID LCS-13319	Samp	Гуре: LC	s	Tes	tCode: El	PA Method	8015D: Gase	oline Rang	le	<u></u>			
Client ID: LCSS	Batc	h ID: 13	319	F	RunNo: 1	8829							
Prep Date: 5/22/2014	Analysis [	Date: <b>5</b> /	23/2014	SeqNo: 543976			Units: mg/F	٢g					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
	20	5.0	25.00	0	80.0	71.7	134						
Gasoline Range Organics (GRO)	20	5.0	20.00	0	00.0	11.1	104						

Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 6

1405989

WO#:

29-May-14

\_\_\_\_\_

Client: Blagg Engineering

Project: Hardie LS 3

Sample ID MB-13319	SampT	Гуре: МЕ	BLK	Tes	TestCode: EPA Method 8021B: Volatiles										
Client ID: PBS	Batcl	h ID: 13	319	F	RunNo: 1	8829	,								
Prep Date: 5/22/2014	Analysis E	Date: 5/	23/2014	S	SeqNo: <b>544018</b> Un			Units: mg/Kg							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	ND	0.050													
Toluene	ND	0.050													
Ethylbenzene	ND	0.050													
Xylenes, Total	ND	0.10													
Surr: 4-Bromofluorobenzene	0.95		1.000		94.8	80	120								
Sample ID LCS-13319	Samp1	 Гуре: LC	s	Tes	tCode: El	PA Method	8021B: Vola	tiles							
Client ID: LCSS	Batcl	h ID: 13	319	F	RunNo: 1	8829									
Prep Date: 5/22/2014	Analysis E	Date: 5/	23/2014	S	SeqNo: 5	44019	Units: mg/M	(g							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	1.1	0.050	1.000	0	109	80	120								
Toluene	1.0	0.050	1.000	0	99.5	80	120								
Ethylbenzene	0.99	0.050	1.000	0	99.1	80	120								
Xylenes, Total	2.9	0.10	3.000	0	95.8	80	120								
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120								
Guilt. 4-Dromolidorobolizenc	1.0		1.000		102	00	120								

Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6

WO#: 1405989

29-May-14

## HALL ENVIRONMENTAL ANALYSIS LABORATORY

#### Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

# Sample Log-In Check List

Clier	nt Name:	BLAGG		Work Order Num	ber: 1405989		RcptNo:	1
Rece	ived by/dat	e:	2	ES IZ KI				
Logg	ed By:	Lindsay I	Mangin	5/22/2014 10:00:00	АМ	Juniy Hongo		
Com	pleted By:	Lindsay <b>F</b>	langin	5/22/2014 2:10:40 I	PM	Junkiy Horizo		
Revie	ewed By:		Ĉs	ostzzliy				
<u>Chai</u>	n of Cus	tody		• • •				
1. C	Custody sea	uls intact on a	sample bott	es?	Yes 🗌	No 🗆	Not Present 🗹	
<b>2</b> . Is	s Chain of (	Custody com	plete?		Yes 🗹	No 🗌	Not Present	
<b>3</b> . H	low was the	e sample del	ivered?		Client			
Log	In							
4. v	Vas an atte	empt made to	o cool the se	amples?	Yes 🔽	No 🗌	NA 🗌	
5. V	Vere all sar	nples receiv	ed at a temp	perature of >0° C to 6.0°C	Yes 🗹	No 🗌	NA 🗖	
6. s	Sample(s) i	n proper con	tainer(s)?		Yes 🗹	No 🗌		
7. S	ufficient sa	mple volume	e for indicate	ed test(s)?	Yes 🗹	No 🗌		
8. A	re samples	(except VO	A and ONG	properly preserved?	Yes 🗹	No 🗌	•	
9. v	Vas preserv	ative added	to bottles?		Yes 🗌	No 🗹	NA 🗌	
10.v	'OA vials ha	ave zero hea	dspace?		Yes	No 🗆	No VOA Vials 🗹	
11.V	Vere any s	ample contai	ners receive	ed broken?	Yes 🗌	No 🗹	# of preserved	
		vork match b pancies on c			Yes 🗹	No 🗌	bottles checked for pH:	r >12 unless noted)
				hain of Custody?	Yes 🗹	No 🗌	Adjusted?	
14. ls	s it clear wh	at analyses	were reques	ited?	Yes 🗹	No 🗌		
		ding times al customer for			Yes 🗹	No 🗌	Checked by:	
		ling (if ap						
				es with this order?	Yes 🗌	No 🗌		_
ſ	Persor	n Notified:		Date	:			
	By Wh	iom:		Via:	eMail [] I	Phone 🗌 Fax	In Person	
	Regard	ding:				in an The second to a state of as boots to		
	Client	Instructions:		······································				

17. Additional remarks:

#### 18. Cooler Information

1	Cooler No	Temp °C	Condition	Seal Intact	Seal No	Seal Date	Signed By
	1	1.1	Good	Not Present			

Client:	Blagg Engi		с.	X Standard		<u> </u>											ENT AT(		
	BP America	a		Project Name	<b>B</b> :			Section of the sectio	in the second		w	ww.h	allen	vironi	ment	al.co	m		
Mailing Addr	ess:	P.O. Bo	K 87		Hardie LS 3			4901 Hawkins NE - Albuquerque, NM 87109											
<u> </u>		Bloomfie	eld, NM 87413	Project #:		<u> </u>	<u> </u>	Tel. 505-345-3975 Fax 505-345-4107 Analysis Request											
Phone #:	,· ·	(505)320	D-1183					مينينين آفيزي			eren er	Āna	lysis	Req	uest	ng with grains	ي مير بي مير بي در مير مير مير	5 R.	
email or Fax	;#:		·····	Project Mana	iger:														Τ
QA/QC Packa	-		Level 4 (Full Validation	)	Jeff Blagg					ĝ									
Other				Sampler:	Jeff Blagg					ē									19
🗆 EDD (Typ	□ EDD (Type)				perature: (					(GRO / DRO)									(Y or M
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	14051		BTEX (8021)		TPH 8015B	TPH 418.1							Chloride	Air Bubbles (Y or N)
05/20/2014	6:45	Soil	21 BGT 5-pt @ 6'	1x 4oz	cool	00	<u>u</u>	x	-+	x	x		-			-		x	╧
		-								+				+		-+	+	-+	+-
									-+	┽				+		-+		+	+
								┼──┼			_			+		-+			
<u></u>			· · · · · · · · · · · · · · · · · · ·					┝╶┼						+		-+	+		
·								┝╼╋	-+-							-+		+	+
		_				<u> </u>		┝╌╂		_			_			$\rightarrow$			
						<u> </u>		┨━╾┽			_						$\rightarrow$		<u> </u>
			· ·							$\rightarrow$				<b> </b>		$\rightarrow$		<u> </u>	<u> </u>
				<u> </u>					$\rightarrow$										<u> </u>
·	<u> </u>					<u> </u>				<u> </u> ,	$\rightarrow$			<u> </u>		$\rightarrow$			┿
				[			····												
<u></u>		Relinquist	and hut	Received by:		Date	Time												
Date: 5/21/2014	Time: 820		14 Blegg	Mistal	Jaeler	Shu/	1111e 820		g Co	des	Avail		-No		0.001		eulte		No
Date:	Time:	Relinquist	the Walter	Received by:	X	- 11	Time	BP Contact: Jeff Peace Please copy results to: peace.jeffrey@bp.com     Y											
lf ne	the second s		Hall Environmental may be subcontract	ed to other accredite	d laboratories. Thi	والمراجع والمراجع والمراجع والمراجع والمراجع والمحاد والمحاد والمحاد والمحاد والمحاد والمحاد والمحاد والمحاد و			y sub-c	ontrai	xed dat	a will b	e clearly	y notate	ed on th	e anali	<b>Algebre</b>	port.	

.



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

May 20, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

#### **VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED**

Re: Notification of plans to close/remove a below grade tank Well Name: HARDIE LS 003 API #: 3004507892

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 20, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

7D Jakin

Jerry Van Riper Surface Land Negotiator BP America Production Company

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

#### SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

May 20, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

#### RE: Notice of Proposed Below-Grade Tank (BGT) Closure

HARDIE LS 003 API 30-045-07892 (G) Section 25 – T29N – R08W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21 bbl BGT and a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

lace

Jeff Peace BP Field Environmental Advisor

(505) 326-9479

