District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: RP America Production Company
Operator: BP America Production Company OGRID#: 778
Address: _200 Energy Court, Farmington, NM
Facility or well name:Florance J 48A
API Number:3004522146 OCD Permit Number:
U/L or Qtr/Qtr O Section 23 Township 30N Range 8W County: San Juan
Center of Proposed Design: Latitude36.79281 Longitude107.64183 NAD: □1927 ⊠ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2. Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank C
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/double bottomed
Liner type: Thicknessmil
4.

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)					
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital,				
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet	•				
Alternate. Please specify					
6					
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)					
Screen Netting Other					
☐ Monthly inspections (If netting or screening is not physically feasible)					
7.					
Signs: Subsection C of 19.15.17.11 NMAC					
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers					
Signed in compliance with 19.15.16.8 NMAC					
8. Variances and Exceptions:					
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.					
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.					
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.					
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC					
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate in a provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source				
material the provided below. Sitting criteria does not apply to drying pads of above-grade tanks.					
General siting					
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	Yes No				
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	NA NA				
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.	☐ Yes ☐ No				
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	∐ NA				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No				
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality					
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)					
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No				
Within an unstable area. (Does not apply to below grade tanks)	☐ Yes ☐ No				
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 					
Within a 100-year floodplain. (Does not apply to below grade tanks)					
- FEMA map					
Below Grade Tanks					
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).	☐ Yes ☐ No				
- Topographic map; Visual inspection (certification) of the proposed site					
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;	☐ Yes ☐ No				
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site					
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)					
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole,					
or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No				

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NInstructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9	cuments are
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	: 15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	- <u>,,</u>
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	cuments are
□ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC	.15.17.9 NMAC
☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions Facility of the following items were benefit at the detailed by the following items were benefit at the detail of the d	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC	
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	,
☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC	
☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan	
☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization	
Monitoring and Inspection Plan	
Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
☐ Alternative	raid management in
Proposed Closure Method: Waste Excavation and Removal	·
Waste Removal (Closed-loop systems only)On-site Closure Method (Only for temporary pits and closed-loop systems)	
In-place Burial On-site Trench Burial	
Alternative Closure Method	
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. ` - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	
- Written confirmation or verification from the municipality, Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.	
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain.	
- FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste.Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believes	ef.
Name (Print):	
	
Signature: Date:	
Signature: Date: e-mail address: Telephone:	
Signature:	
Signature:	
Signature:	
Signature:	284 the closure report.
Signature:	the closure report.

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this c belief. I also certify that the closure complies with all applicable closure r	losure report is true, accurate and complete to the best of my knowledge and equirements and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: St Peace	Date:July 18, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Florance J 48A, Tank C (95 bbl) API No. 3004522146 Unit Letter O, Section 23, T30N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank C	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	41
Chlorides	US EPA Method 300.0 or 4500B	250 or background	180

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV

State of New Mexico Energy Minerals and Natural Resources

Form C-141.
Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Fran	icis Dr., Sant	a Fe, NM 87505	5	S	anta Fe	e, NM 875	05				
	<u> </u>		Rel	ease Notifi	cation	and Co	rrective A	ction			
						OPERA	ΓOR	☐ In	tial Report	\boxtimes	Final Report
Name of Co	mpany: B	P				Contact: Jef	f Peace				
L					No.: 505-326-94	179					
						e: Natural gas v					
Surface Ow	ner: Feder	al		Mineral (Owner: I	Federal		API1	No. 3004522	146	
L				LOC	ATION	V OF REI	FASE				
Unit Letter O	Section 23	Township 30N	Range 8W	Feet from the 1,060				East/West Line East	County: S	an Juar	า
		Lat	itude3	6.79281		Longitud	e107.64183_				
				NAT	TURE	OF REL	EASE				
Type of Rele	ase: none					Volume of	Release: N/A	Volum	Recovered:	N/A	
		v grade tank –	95 bbl, T	ank C		Date and F N/A	lour of Occurrence		d Hour of Dis		: N/A
Was Immedi	ate Notice (Yes [] No ⊠ Not R	equired	If YES, To	Whom?				
By Whom?						Date and F	lour				
Was a Water	course Read	ched?	Yes 🗵] No		If YES, Vo	lume Impacting t	the Watercourse.			
If a Watercou	ırse was Im	pacted, Descr	ibe Fully.	*					-		
							the BGT was do		al to ensure no	soil in	ipacts from
				cen.* BGT was reactive well area.	emoved a	nd the area u	nderneath the BG	T was sampled.	The excavate	d area v	vas
regulations al public health should their cor the environ	If operators or the environment. In a	are required to ronment. The ave failed to a	o report an acceptand idequately OCD accep	nd/or file certain in the certain in	release no ort by the remediate	otifications are NMOCD m contaminati	knowledge and und perform correctarked as "Final Roon that pose a three the operator of the correction	tive actions for r eport" does not r eat to ground wa	eleases which elieve the ope er, surface wa	may er rator of iter, hu	ndanger f liability man health
Signature:	off i	Peace					OIL CONS	SERVATIO)	V DIVISIO	<u>N</u>	
Printed Name	e: Jeff Peace	e				Approved by	Environmental S	pecialist:			
Title: Area E	nvironment	al Advisor			1	Approval Dat	e:	Expiratio	n Date:		
E-mail Address: peace.jeffrey@bp.com				Conditions of	Approval:		Attached				

Phone: 505-326-9479

Date: July 18, 2014

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	API #: 3004522146 TANK ID (if applicble):
FIELD REPORT:	(circle one): BGT CONFIRMATION RELEASE INVESTIGATION OTHER:	PAGE #: 1 of 1
SITE INFORMATION QUAD/UNIT: 0 SEC: 23 TWP: 1/4-1/4/FOOTAGE: 1,060'S / 1,68 LEASE #: SF078385	30N RNG: 8W PM: NM CNTY: SJ ST: N	LITVINOITIVILITIAL
REFERENCE POINT	WELL HEAD (W.H.) GPS COORD.: 36.79280 X 107.6	4201 GL ELEV: 6,172'
1)	GPS COORD.: 36.79281 X 107.64183 DIST	ANCE/BEARING FROM W.H.: 55', S68E
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	OVM READING (ppm)
2) SAMPLE ID: 5 PC-TB @ 6' (95) 3) SAMPLE ID:	B SAMPLE DATE 95/97/14 SAMPLE TIME 1253 LAB ANALYSIS 4 - C SAMPLE DATE: 05/07/14 SAMPLE TIME: 1300 LAB ANALYSIS: LAB ANALYSIS: SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS: LAB ANALYSIS:	18.1/8015B/8021B/300.0 (CI) NA
SOIL COLOR: MOSTLY GRA COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LO MOISTURE: DRY SLIGHTLY MOIST MOIST / WE SAMPLE TYPE: GRAB COMPOSITE #	COHESIVE / COHESIVE / HIGHLY COHESIVE DENSITY (COHESIVE CLAYS & SILTS): SOFT OSE FIRM DENSE / VERY DENSE HC ODOR DETECTED: YES NO EXPLANATION OF TAXABLE PROPERTY OF THE PROPE	ASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC / FIRM / STIFF / VERY STIFF / HARD - DISCOLORED SOIL @ 18 BGT ONLY.
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: BEDROCK SANDSTONE OUTCF INTO BEDROCK. IMPACTED SOIL VE SOIL IMPACT DIMENSION ESTIMATION:	ROP @ GROUND SURFACE THROUGHOUT NORTHERN HALF OF WELL P RY MINIMAL. WILL LEAVE IN PLACE.	PAD. 18 BGT INSTALLED BY CARVING ON ESTIMATION (Cubic Yards): <1 NMOCD TPH CLOSURE STD: 5,000 ppm
X - S.P.D. NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELC	BGT Located: off on site PLOT PLAN circle: attached N W.H. ⊕ BERM WOODEN N DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~ = APPROX.; W.H. = WELL HEAD WGRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; NA-NOT WALL; DW-DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM.	OVM CALIB. GAS = NA ppm TIME: NA am/pm DATE: NA MISCELL. NOTES WO: N15182573 PO #: 4300261710 PK: PJ #: Permit date(s): 06/14/10 OCD Appr. date(s): 05/14/14 Tank OVM = Organic Vapor Meter ppm = parts per million B BGT Sidewalls Visible: (Y) N C BGT Sidewalls Visible: (Y) N

revised: 11/26/13

BEI1005E-6.SKF

Analytical Report

Lab Order 1405369

Date Reported: 5/15/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 2' (95)-C

Project: Florance J #48A

Collection Date: 5/7/2014 1:00:00 PM

Lab ID: 1405369-002

Matrix: SOIL Received Date: 5/8/2014 3:00:00 PM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	E ORGANICS		<u> </u>	·	Analyst	: BCN
Diesel Range Organics (DRO)	21	10	mg/Kg	1	5/13/2014 11:26:40 AM	13082
Surr: DNOP	99.3	57.9-140	%REC	1	5/13/2014 11:26:40 AM	13082
EPA METHOD 8015D: GASOLINE RA	NGE		•		Analyst	NSB
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	5/12/2014 1:41:02 PM	13090
Surr: BFB	87.1	74.5-129	%REC	1	5/12/2014 1:41:02 PM	13090
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.048	mg/Kg	1	5/12/2014 1:41:02 PM	13090
Toluene	ND	0.048	mg/Kg	1	5/12/2014 1:41:02 PM	13090
Ethylbenzene	ND	0.048	mg/Kg	1	5/12/2014 1:41:02 PM	13090
Xylenes, Total	ND	0.096	mg/Kg	1	5/12/2014 1:41:02 PM	13090
Surr: 4-Bromofluorobenzene	101	80-120	%REC	1	5/12/2014 1:41:02 PM	13090
EPA METHOD 300.0: ANIONS					Analyst	JRR
Chloride	180	30	mg/Kg	20	5/13/2014 2:27:15 PM	13142
EPA METHOD 418.1: TPH					Analyst	JME
Petroleum Hydrocarbons, TR	41	20	mg/Kg	1	5/13/2014 12:00:00 PM	13084

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 2 of 8

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1405369

15-May-14

Client:

Blagg Engineering

Project:

Florance J #48A

Sample ID MB-13142

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 13142

RunNo: 18590

Prep Date: 5/13/2014 Analysis Date: 5/13/2014

SegNo: 536900

Units: mg/Kg

HighLimit

RPDLimit Qual

Analyte Chloride

Result **PQL** ND 1.5

SampType: LCS

TestCode: EPA Method 300.0: Anions

SPK value SPK Ref Val %REC LowLimit

%RPD

Sample ID LCS-13142

Client ID:

LCSS

Batch ID: 13142

RunNo: 18590

Prep Date: 5/13/2014

SeqNo: 536901

Units: mg/Kg

Analysis Date: 5/13/2014

HighLimit

RPDLimit Qual

Analyte

PQL

Result

15.00

96.1

Chloride

1.5

SPK value SPK Ref Val %REC

110

%RPD

14

LowLimit

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

Spike Recovery outside accepted recovery limits

O RSD is greater than RSDlimit

RPD outside accepted recovery limits R

Analyte detected in the associated Method Blank

Η Holding times for preparation or analysis exceeded

P Sample pH greater than 2.

RL Reporting Detection Limit

Not Detected at the Reporting Limit Page 3 of 8

Hall Environmental Analysis Laboratory, Inc.

WO#:

1405369

15-May-14

Client:

Blagg Engineering

Project:

Florance J #48A

Sample ID MB-13084

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 13084

PQL

20

20

RunNo: 18548

Prep Date: 5/9/2014 Analysis Date: 5/13/2014

SeqNo: 535923

LowLimit

Units: mg/Kg

Result Analyte

ND

HighLimit

RPDLimit

Qual

Petroleum Hydrocarbons, TR

SampType: LCS

TestCode: EPA Method 418.1: TPH

SeqNo: 535924

%RPD

Sample ID LCS-13084

5/9/2014

Client ID:

LCSS

Batch ID: 13084

RunNo: 18548

Units: mg/Kg

Prep Date: Analyte

Client ID:

Prep Date:

Analysis Date: 5/13/2014

LowLimit

HighLimit

%RPD

Petroleum Hydrocarbons, TR

Result **PQL** 91

SPK value SPK Ref Val 100.0

%REC 91.2

80

120

RPDLimit

Qual

Sample ID LCSD-13084

LCSS02

5/9/2014

SampType: LCSD Batch ID: 13084

0

SPK value SPK Ref Val %REC

RunNo: 18548 SeqNo: 535925

Units: mg/Kg

Qual

Analyte Petroleum Hydrocarbons, TR Result

96

Analysis Date: 5/13/2014

SPK value SPK Ref Val 100.0

%REC 95.5

LowLimit

TestCode: EPA Method 418.1; TPH

HighLimit 120 %RPD 4.58 **RPDLimit**

20

Qualifiers:

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

Value above quantitation range Ε

Analyte detected below quantitation limits RSD is greater than RSDlimit 0

RPD outside accepted recovery limits R

Analyte detected in the associated Method Blank

Н Not Detected at the Reporting Limit

Sample pH greater than 2.

Reporting Detection Limit

Holding times for preparation or analysis exceeded

Page 4 of 8

Hall Environmental Analysis Laboratory, Inc.

WO#:

1405369

15-May-14

Client:

Blagg Engineering

Project:

Florance J #48A

Project: Floran	ce J #48A		<u></u>	
Sample ID MB-13082	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Org	ganics
Client ID: PBS	Batch ID: 13082	RunNo: 18502		
Prep Date: 5/9/2014	Analysis Date: 5/9/2014	SeqNo: 534127	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD I	RPDLimit Qual
Diesel Range Organics (DRO) Surr: DNOP	ND 10 8.2 10.00	81.9 57.9	140	
Sample ID LCS-13082	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Org	ganics
Client ID: LCSS	Batch ID: 13082	RunNo: 18502		
Prep Date: 5/9/2014	Analysis Date: 5/9/2014	SeqNo: 534128	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD I	RPDLimit Qual
Diesel Range Organics (DRO)	48 10 50.00	0 96.5 60.8	145	
Surr: DNOP	4.3 5.000	85.5 57.9	140	
Sample ID MB-13132	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Orç	ganics
Client ID: PBS	Batch ID: 13132	RunNo: 18557		•
Prep Date: 5/13/2014	Analysis Date: 5/13/2014	SeqNo: 536327	Units: %REC	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD F	RPDLimit Qual
Surr: DNOP	8.3 10.00	83.4 57.9	140	
Sample ID LCS-13132	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Org	janics
Client ID: LCSS	Batch ID: 13132	RunNo: 18557	*	
Prep Date: 5/13/2014	Analysis Date: 5/13/2014	SeqNo: 536328	Units: %REC	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD F	RPDLimit Qual
Surr: DNOP	4.0 5.000	79.7 57.9	140	
Sample ID MB-13112	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Org	janics
Client ID: PBS	Batch ID: 13112	RunNo: 18557		
Prep Date: 5/12/2014	Analysis Date: 5/13/2014	SeqNo: 536644	Units: %REC	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD F	RPDLimit Qual
Surr: DNOP	8.9 10.00	88.8 57.9	140	
Sample ID LCS-13112	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Org	ganics
Client ID: LCSS	Batch ID: 13112	RunNo: 18557		
Prep Date: 5/12/2014	Analysis Date: 5/13/2014	SeqNo: 536647	Units: %REC	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD F	RPDLimit Qual
Surr: DNOP	4.7 5.000	93.5 57.9	140	

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 5 of 8

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1405369

15-May-14

Client:

Blagg Engineering

Project:

Florance J #48A

Sample ID	MB-13119

SampType: MBLK

TestCode: EPA Method 8015D: Diesel Range Organics

Client ID: PBS

Batch ID: 13119

RunNo: 18557

Prep Date: 5/12/2014 Analysis Date: 5/13/2014

SeqNo: 536743

Units: %REC

Analyte

140

Result SPK value SPK Ref Val

%REC LowLimit

Surr: DNOP

9.3 10.00

HighLimit 93.0 57.9

57.9

LowLimit

%RPD **RPDLimit**

Qual

Sample ID LCS-13119

SampType: LCS Batch ID: 13119

RunNo: 18557

TestCode: EPA Method 8015D: Diesel Range Organics

%RPD

%RPD

Client ID: Prep Date:

LCSS

5/12/2014

Analysis Date: 5/13/2014

PQL

SeqNo: 536744

Units: %REC

Qual

Analyte Surr: DNOP Result

SPK value SPK Ref Val

%REC LowLimit HighLimit

RPDLimit

4.7

5.000

94.4

140

Sample ID MB-13097

SampType: MBLK

TestCode: EPA Method 8015D: Diesel Range Organics

Client ID:

PBS

Batch ID: 13097

SPK value SPK Ref Val

RunNo: 18557

Prep Date: Analyte

5/9/2014

Analysis Date: 5/14/2014

Result

SeqNo: 536755 %REC

89.3

Units: %REC HighLimit

140

RPDLimit

Qual

Surr: DNOP

8.9

PQL

TestCode: EPA Method 8015D: Diesel Range Organics

Sample ID LCS-13097 Client ID:

LCSS

SampType: LCS Batch ID: 13097

RunNo: 18557

Prep Date:

5/9/2014

Analysis Date: 5/14/2014

SeqNo: 536756

Units: %REC

Analyte

Result

SPK value SPK Ref Val

10.00

%REC

LowLimit

Qual

Surr: DNOP

4.6

5.000

92.4

57.9

HighLimit 140

%RPD **RPDLimit**

Qualifiers:

Ε

0

- Value exceeds Maximum Contaminant Level.
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit

Value above quantitation range

- RPD outside accepted recovery limits R Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND P Sample pH greater than 2.
- RL Reporting Detection Limit

Not Detected at the Reporting Limit Page 6 of 8

Hall Environmental Analysis Laboratory, Inc.

WO#:

1405369

15-May-14

Client:

Blagg Engineering

Project: Florance	e J #48A										
Sample ID MB-13090	SampType: MBLK	SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range									
Client ID: PBS	Batch ID: 13090	RunNo: 18552									
Prep Date: 5/9/2014	Analysis Date: 5/12/2014	SeqNo: 535973	Units: mg/Kg								
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit C	Qual							
Gasoline Range Organics (GRO)	ND 5.0										
Surr: BFB	850 1000	85.0 74.5	129								
Sample ID LCS-13090	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Range								
Client ID: LCSS	Batch ID: 13090	RunNo: 18552									
Prep Date: 5/9/2014	Analysis Date: 5/12/2014	SeqNo: 535974	Units: mg/Kg								
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit C	Qual							
Gasoline Range Organics (GRO)	23 5.0 25.00	0 91.1 71.7	134								
Surr: BFB	930 1000	93.4 74.5	129								
Sample ID MB-13090 MK	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Range								
Client ID: PBS	Batch ID: R18552	RunNo: 18552									
Prep Date:	Analysis Date: 5/12/2014	SeqNo: 535984	Units: %REC								
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit C	Qual							
Surr: BFB	850 1000	85.0 74.5	129								
Sample ID LCS-13090 MK	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Range								
Client ID: LCSS	Batch ID: R18552	RunNo: 18552									
Prep Date:	Analysis Date: 5/12/2014	SeqNo: 535985	Units: %REC								
Analyte .	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit C	Qual							
Surr: BFB	930 1000	93.4 74.5	. 129								

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 7 of 8

Hall Environmental Analysis Laboratory, Inc.

WO#: **1405369**

15-May-14

Client: Project:

Blagg Engineering

Florance J #48A

Sample ID MB-13090	Samp ¹	Гуре: М	BLK	Tes	tCode: E									
Client ID: PB\$	Batc	Batch ID: 13090 RunNo: 18552												
Prep Date: 5/9/2014	Analysis Date: 5/12/2014		SeqNo: 536001			Units: mg/F	ζg							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Benzene	ND	0.050					<u> </u>							
Toluene	ND	0.050												
Ethylbenzene	ND	0.050												
Xylenes, Total	ND	0.10												
Surr: A-Bromofluorobenzene	1.0		1.000		101	80	120							

Sample ID LCS-13090	SampT	ype: LC	s	Tes						
Client ID: LCSS	Batcl	n ID: 13	090	F	RunNo: 1	8552				
Prep Date: 5/9/2014	Analysis D	oate: 5/	12/2014	SeqNo: 536002			Units: mg/k			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	107	80	120			
Toluene	1.0	0.050	1.000	0	101	80	120			
Ethylbenzene	0.99	0.050	1.000	0	98.7	80	120			
Xylenes, Total	2.9	0.10	3.000	0 97.4 80			120			
Surr: 4-Bromofluorobenzene	r: 4-Bromofluorobenzene 1.1 1.000 108 80		120							

Sample ID 1405369-002AMS SampType: MS TestCode: EPA Method 8021B: Volatiles											
Client ID: 5PC-TB @ 2' (95	5)-C Batcl	h ID: 13 6	090	F	RunNo: 18552						
Prep Date: 5/9/2014	Analysis [Analysis Date: 5/12/2014			SeqNo: 5	36007	Units: mg/k	(g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	0.91	0.048	0.9625	0	94.4	67.4	135				
Toluene	0.86	0.048	0.9625	0.009048	88.6	72.6	135				
Ethylbenzene	0.87	0.048	0.9625	0	90.5	69.4	143				
Xylenes, Total	2.5	0.096	2.887	7 0.01380 86.1 70.8			144				
Surr: 4-Bromofluorobenzene	1.0		0.9625		104	80	120				

Sample ID 1405369-002AMS	MSD SampType: MSD TestCode: EPA Method 8021B: Volatiles									
Client ID: 5PC-TB @ 2' (95)-	-C Batch	090	F	RunNo: 1	8552					
Prep Date: 5/9/2014	Analysis Date: 5/12/2014			SeqNo: 536008 Units: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.94	0.048	0.9606	0	98.3	67.4	135	3.90	20	
Toluene	0.88	0.048	0.9606	0.009048	90.7	72.6	135	2.14	20	
Ethylbenzene	0.89	0.048	0.9606	0 92.2 69.4		143	1.62	20		
Xylenes, Total	2.6	0.096	2.882	0.01380 88.9 70.8		144	2.95	20		
Surr: 4-Bromofluorobenzene	0.98		0.9606		102	80	120	0	0	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 8 of 8



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG Work Ord	er Number: 1405369		RcptNo:	1
Received by/date: 05 08 12				
Logged By: Lindsay Mangin 5/8/2014 3:	00:00 PM	Streeky Hlafige	ı	· : :
Completed By: Lindsay Mangin 5/9/2014 6:	36:19 AM	Jamby Hlyngo	1	:
Reviewed By:		000		
Chain of Custody				
1. Custody seals intact on sample bottles?	Yes	No □	Not Present ❤	
2. Is Chain of Custody complete?	Yes ✓	No 🗀	Not Present	
3. How was the sample delivered?	Courier			
Log In				
4. Was an attempt made to cool the samples?	Yes 🗹	No 🗀	NA [":	
5. Were all samples received at a temperature of >0° C to	6.0°C Yes 🗹	No 🛄	NA 13	
6. Sample(s) in proper container(s)?	Yes 🔽	No 🗆		
7. Sufficient sample volume for indicated test(s)?	Yes 🗹	No 🗌		
8. Are samples (except VOA and ONG) properly preserved	? Yes 🗹	No 🗌		
9. Was preservative added to bottles?	Yes 🗌	No 🔽	NA 🗌	
10.VOA vials have zero headspace?	Yes 🗀	No 🛄	No VOA Vials	
11. Were any sample containers received broken?	Yes	No 🗹		
	r>	rith	# of preserved bottles checked	
12.Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes 🗹	No 🗔	for pH: (<2 o	r >12 unless noted)
13. Are matrices correctly identified on Chain of Custody?	Yes 🗹	No 🗔	Adjusted?	
14. Is it clear what analyses were requested?	Yes 🗹	No 🗀		
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes 🗹	No 🗆	Checked by:	
Special Handling (if applicable)			***	
16. Was client notified of all discrepancies with this order?	Yes 🗀	No 🗔	NA 🖍	
Person Notified:	Date:	The state of the s		
By Whom:	Via: [] eMail []	Phone [] Fax	In Person	
Regarding:			AND THE PROPERTY OF THE PARTY O	1
Client Instructions:				
17. Additional remarks:				
18. Cooler Information				
Cooler No. Temp °C Condition Seal Intact S	Seal No. Seal Date	Signed By		
1 1.0 Good Yes				

Onam-or-oustody Necord]				_	\Box	1	HΑ		F	NI	/T	5 C)	ıNı	ME	N	ГА	_		
Client: BLAGG ENGR. / BP AMERICA			✓ Standard		<u> </u>		F									R/					
		···		Project Name					F. F. E.	_							.com				
Mailing Ad	ddress:	P.O. BO	X 87	FLORANCE J # 48A				4901 Hawkins NE - Albuquerque, NM 87109													
		BLOOM	FIELD, NM 87413	Project #:							45-3						-410				
Phone #: (505) 632-1199								194	,	and s	1	Ånal	ysis	Red	Įuė:	i (
email or F	ax#:			Project Manaç	ger:				71 V					(4)				ਜ਼			T
QA/QC Package: Standard Level 4 (Full Validation)			NELSON VI	ELEZ	8021B)	only)	(Outro)			(S)		PO4,50	2 PCB's			ter - 300.1)			e e		
Accreditation:		Sampler: On ice:	NELSON VI		% fay	+ MTBE + TPH (Gas only)	/ DRO	18.1)	04.1)	8270SIMS))3,NO ₂ ,	s / 8082		(A)	10.0 / water			samb		
.□ EDD (1	уре)			Sample Temp	erature: [C		1	E + T	GRO	od 4	od 5	៦	tals	N.	cide	F	V	-30		<u>e</u>	osite
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALING THEALING	BTEX + MFB	BTEX + MTB	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /		Grab sample	5 pt. composite sample
3/1/14	1250	301L	3PC - TD @ 2' (16) - D	4 Oz 1	Cool	- 001	4		4	-				_				4			*
																					\Box
5/7/14	1300	SOIL	5PC - TB @ 2' (95) - C	4 oz 1	Cool	-002	7		7	√								٧			V
															-						\perp
				,																	\perp
																			\dashv	_	\dashv
			\			 				L				<u> </u>					$ \bot $		
Date: //4	Time: 807	Relinquish	in VJ	Ghristaliacia 5/8/14 807		Remarks: Send invoice to : Blagg Engineering, Inc.															
Date: Time: Relinquished by: 0		Received by:		Daté Time	P.O. Box 87																
U	If necessa	ary samples s	ubmitted to Hall Environmental may be s	ubcontracted to other	accredited laboratorie	s. This serves as notice of	this p	ossibil	ity. Ar	ny sub	-contr	acted	data v	vill be	clearly	notat	ed on	the ana	alytical	l report	Ł.





IBP/America Production Company 2000/Energy Court Framington, NM 87401 IPhone: (505) 326-9200

April 7, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade trank

Well Name: FLORANCE J 048A

API#: 3004522146

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closume Requirements, Paragraph J. BP America Production Company (BP) is required to notify the sunface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about April 22, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well sate will continue to operate.

Unless you have questions about this notice, there is no meed to mespond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

Surface Land Negotiator

92 Va Rai

BP America Production Company

BP America Production Company

200 Energy Court Earmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON POWELL @STATE INM.US

April 10, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

FLORANCE J 048A API 30-045-22146 (G) Section 23 - T30N - R08W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



