District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Operator: BP America Production Company OGRID#:778		<u> </u>		rational and the contract of t	
Type of action: Below grade tank registration Permit of a pit of a price of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank or afternative request sease be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the vivronnent. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinant proval of the properties. Part of the operator of the permitted proval operators are provaled permitted permitted provaled permitted provaled permitted provaled permitted provaled permitted provaled permitted provaled permitted permitted provaled permitted provaled permitted provaled permitted permitted provaled permitted permitted permitted provaled permitted					
Type of action: below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permit/or registration Closure plan only submitted for an existing permit/or registration Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request ease he advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the vironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinan Operator: BP America Production Company OGRID #:778 Operator: BP America Production Company OGRID #:778 Address:200 Energy Court, Farmington, NM Oll CONS, DIV DIST, 3 Facility or well name:Jaquez Gas Com B 1A JUL 2 1 2014 API Number:3004522281 OCD Permit Number:	051	Proposed Alternative M	lethod Permit or Cle	osure Plan Application	
ease be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the vironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinand. Operator: BP America Production Company OGRID#:778		☐ Permit of a pit or pro ☐ Closure of a pit, belo ☐ Modification to an e ☐ Closure plan only su	oposed alternative method ow-grade tank, or proposed existing permit/or registrati	d alternative method ion	
Address:200 Energy Court, Farmington, NM	18666-	Instructions: Please submit one application	(Form C-144) per individual	pit, below-grade tank or alternative request	•
Deperator: BP America Production CompanyOGRID #:778	lease be advised	I that approval of this request does not relieve the ope or does approval relieve the operator of its responsibil	erator of liability should operati-	ions result in pollution of surface water, ground water or	the
Address:200 Energy Court, Farmington, NM	1.				-
Facility or well name:Jaquez Gas Com B 1A	Operator: BP	America Production Company		OGRID #:778	
Facility or well name:Jaquez Gas Com B 1A	Address:20	00 Energy Court, Farmington, NM		OIL CONS. DIV DIS	I. 3
API Number:3004522281OCD Permit Number:	Facility or well	I name:Jaquez Gas Com B 1A			
D Section 4 Township 29N Range 9W County: San Juan					_
Center of Proposed Design: Latitude36.75788					
Surface Owner: Federal State Private Tribal Trust or Indian Allotment					
Pit: Subsection F, G or J of 19.15.17.11 NMAC Cremporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced String-Reinforced Welded Factory Other Volume: bbl Dimensions: L x W x D Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other Available Dimensions: L x W x D Dimension				'9096 NAD: □1927 🖾 1983	
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D Note	Surface Owner	:	or Indian Allotment		
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D Management Subsection 1 of 19.15.17.11 NMAC Tank A Volume: 95.0 bbl Type of fluid: Produced water Tank Construction material: Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Single walled/Double bottomed, side walls not visible Liner type: Thickness mil HDPE PVC Other Liner type: Thickness mil LLDPE PVC Dther LLDPE PVC Dther Liner type: Thickness mil LLDPE PVC Dther LLDPE PVC Dther Liner type: Thickness mil LLDPE PVC Dther LLDPE PVC Dther Liner type: Thick	2.	ection E. C. on L. of 10.15.17.11 NIMAC			
Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management ☐ Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined ☐ Liner type: Thickness ☐ mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other ☐ String-Reinforced ☐ Liner Seams: ☐ Welded ☐ Factory ☐ Other ☐ Volume: ☐ bbl Dimensions: ☐ x W x D		•			
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D			i-Well Fluid Management	Low Chloride Drilling Fluid ☐ yes ☐ no	
Welded Factory Other Volume: bbl Dimensions: L x W x D			-	-	
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A Volume:95.0bbl Type of fluid:Produced water Tank Construction material:Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only \(\triangle \) OtherSingle walled/Double bottomed, side walls not visible Liner type: Thickness mil HDPE PVC Other	String-Rein	nforced			
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A Volume:95.0	iner Seams: [☐ Welded ☐ Factory ☐ Other	Volume:	bbl Dimensions: L x W x D	
Volume:95.0bbl Type of fluid:Produced water	i.				
Tank Construction material:Steel	⊠ <u>Below-grad</u>	de tank: Subsection 1 of 19.15.17.11 NMAC	Tank A		
Tank Construction material:Steel	/olume:	95.0 bbl Type of fluid:	Produced water		
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other _Single walled/Double bottomed, side walls not visible					
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _Single walled/Double bottomed, side walls not visible Liner type: Thicknessmil ☐ HDPE ☐ PVC ☐ Other				utomatic overflow shut-off	
iner type: Thicknessmil	☐ Visible sid	lewalls and liner 🔲 Visible sidewalls only 🕅 (Other Single walled/Do	ouble bottomed, side walls not visible	
			_ -		
	Submittal of an	exception request is required. Exceptions must	be submitted to the Santa Fe F	Environmental Bureau office for consideration of appr	roval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution on abuseh)	hospital,
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	•
Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
involuting inspections (it netting or selecting is not physically reasible)	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions</u> : Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	•
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acce, material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
	T .
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)	☐ Yes ☐ No
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks)	☐ Yes ☐ No
- FEMA map	
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	O NMAC 15.17.9 NMAC
Treviously Approved Design (attach copy of design) Att Trumber.	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	Iuid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes No
Within a 100-year floodplain. FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
17.	
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel	iof
Name (Print): Title:	<u> </u>
Signature: Date:	
Signature: Date: e-mail address: Telephone:	
e-mail address:	
e-mail address:	12014
e-mail address:	12014
e-mail address:	the closure report.
e-mail address: Telephone:	the closure report.
e-mail address: Telephone:	the closure report.

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure requi	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Joff Poses	Date:July 18, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Jaquez Gas Com B 1A API No. 3004522281 Unit Letter D, Section 4, T29N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids) a.
 - JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge) b.
 - Basin Disposal, Permit NM-01-0005 (Liquids) c.
 - Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and d. Sludge)
 - BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids) e.

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	24
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	cation	and Co	rrective A	ction	ı	•		,
						OPERATOR Initial Report _ Final F						Final Report
Name of Co						Contact: Jeff Peace						
		Court, Farm		M 87401			No.: 505-326-94				·	
Facility Nai	ne: Jaquez	Z Gas Com B	i IA			Facility Typ	e: Natural gas v	vell				
Surface Ow	ner: Priva	te		Mineral ()wner:	Private			API No	. 3004522	281	
				LOCA	OITA	N OF REI	LEASE					
Unit Letter D	Section 4	Township 29N	Range 9W	Feet from the 1,070	North/ North	South Line	Feet from the 1,070	East/\ West	West Line	County: S	an Juan	
		Lat	itude3	6.75788		_ Longitud	e107.79096					
				NAT	URE	OF REL						
Type of Rele		1 . 1	05111				Release: N/A			Recovered: 1		77/4
Source of Re	lease: belov	w grade tank –	- 95 bbi,			Date and F	lour of Occurrenc	e:	Date and	Hour of Dis	covery:	N/A
Was Immedi	ate Notice (Yes [No Not R	equired	If YES, To	Whom?					
By Whom?						Date and I-	lour					
Was a Water	course Read		Yes 🗵] No		If YES, Vo	lume Impacting t	he Wate	ercourse.			
		pacted, Descr										
				n Taken.* Sampli and chlorides belo					g removal	to ensure no	soil im	pacts from
				cen.* BGT was re active well area.	moved a	ınd the area u	nderneath the BG	T was s	ampled. Ti	ne excavated	l area w	as
regulations al public health should their or or the environ	I operators or the envi- perations hament. In a	are required to ronment. The lave failed to a	o report ar acceptance adequately OCD accep	e is true and comp nd/or file certain r ce of a C-141 repo investigate and r otance of a C-141	elease no ort by the emediate	otifications ar e NMOCD m e contaminati	nd perform correctarked as "Final Room that pose a thre	tive acti eport" d eat to gr	ons for rele oes not reli ound water	eases which eve the oper surface wa	may end ator of ter, hun	danger liability nan health
Signature:	SAR 1	2002					OIL CONS	SERV	ATION	DIVISIO	<u>N</u>	
Printed Name: Jeff Peace						Approved by Environmental Specialist:						
Title: Area E	nvironment	al Advisor				Approval Date:			Expiration Date:			
E-mail Addre	ss: peace.je	effrey@bp.cor	n			Conditions of Approval:						
Date: July 18	3, 2014		Phone: 50	5-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP		NGINEERING, INC. BLOOMFIELD, NM 87	7413	API#: 3004522281
	(50	05) 632-1199		(if applicble):
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTHER	:	PAGE#: 1 of 1
SITE INFORMATION	I: SITE NAME: JAQUE	Z GC B # 1A		DATE STARTED: 05/14/14
QUAD/UNIT: D SEC: 4 TWP:	29N RNG: 9W PM	: NM CNTY: SJ s	T. NM	DATE FINISHED:
1/4-1/4/FOOTAGE: 1,070'N / 1,07		EL KHODNI		ENVIRONMENTAL SPECIALIST(S): JCB
	_	ONTRACTOR: MBF - S. PERE		
REFERENCE POINT 1) 95 BGT (SW/DB)		36.75823 X 6.75788 X 107.79096	107.79096 DISTANCE/BEAF	GL ELEV.: 5,639' RING FROM W.H.: 138', S1W
2)	GPS COORD.:		DISTANCE/BEAF	RING FROM W.H.:
3)				
4)	GPS COORD.:		DISTANCE/BEAF	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # 0	OR LAB USED: HALL	···	OVM READING (ppm)
1) SAMPLE ID:	5' SAMPLE DATE:05/14	1/14 SAMPLE TIME: 1108 LAB AN	alysis: 418.1/8	015B/8021B/300.0 (CI) 0.0
2) SAMPLE ID:				
3) SAMPLE ID:				
4) SAMPLE ID:SOIL DESCRIPTION				
SOIL COLOR: MODER COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY SLIGHTLY MOIST MOIST / WE SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED: YES N	COHESIVE COHESIVE/HIGHLY COHESIVE COHESIVE COHESIVE / VERY DENSE ET / SATURATED / SUPER SATURATED OF PTS. 5	PLASTICITY (CLAYS): NON PLASTIC / SLIG DENSITY (COHESIVE CLAYS & SILTS)	HTLY PLASTIC / CO : SOFT / FIRM / S ANATION -	
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: BGT SITTING ON PEA GRAVELE	LOST INTEGRITY OF EQUIPMENT D AND/OR OCCURRED: YES NO EXPL YES NO EXPLANATION - LPAGT	ANATION:		
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA ft. EXC		IMATION (Cubic Yards) : NA
	EAREST WATER SOURCE: <1,000		0001	D TPH CLOSURE STD: 100 ppm
SITE SKETCH	BGT Located: off on sit	e PLOT PLAN circle: a	attached O\M	CALIB. READ. = 51.9 ppm pc =0.50
	↑ TO W.H.		_ A OVM	CALIB. GAS = 100 ppm RF = 0.52 6:20 ampm DATE: 05/14/14
		BERM	<u> </u>	MISCELL. NOTES 0: N15464175 0#:
SEPA 100 BBL PROD.TANK	ARATOR (X X X X X X X X X X X X X X X X X X X	PBGTL T.B. ~ 5' B.G.	PM PJ Pe OC Tanil ID	C: ZEVH01BGT2 I #: Z2-006Q0 rmit date(s): 06/14/10 CD Appr. date(s): 04/28/14 R OVM = Organic Vapor Meter ppm = parts per million
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO	IN DEDRESSION: B.C BELOWINGDADE: D D.		S.P.D.	BGT Sidewalls Visible: Y / N
	OW-GRADE TANK LOCATION; SPD = SAMPLE F	POINT DESIGNATION; R.W. = RETAINING WALL; N		agnetic declination: 10° E
NOTES:	•	ONSITE: 05/14/14		



Project Name:

Jaquez GC B 1A

PO Box 22024

Tulsa OK, 74121-2024

Project Number:

03143-0424

Project Manager:

Jeff Blagg

Reported: 16-May-14 13:46

Analyical Report for Samples

Client Sample ID	Lab Sample ID	Matrix	Sampled	Received	Container
95 BGT 5-pt @ 5'	P405030-01A	Soil	05/14/14	05/14/14	Glass Jar, 4 oz.

Partial or incomplete reproduction of this report is prohibited, unless approved by Envirotech, Inc.

5796 US Highway 64, Farmington, NM 87401

Ph (505) 632-0615 Fx (505) 632-1865

envirotech-inc.com laboratory@envirotech-inc.com



Project Name:

Jaquez GC B 1A

PO Box 22024

Project Number:

03143-0424

Tulsa OK, 74121-2024

Project Manager: Jeff Blagg

Reported:

16-May-14 13:46

95 BGT 5-pt @ 5' P405030-01 (Solid)

		Reporting							
Analyte	Result	Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
Volatile Organics by EPA 8021									
Benzenc	ND	0.05	mg/kg	1	1420027	05/15/14	05/15/14	EPA 8021B	
Toluene	ND	0.05	mg/kg	1	1420027	05/15/14	05/15/14	EPA 8021B	
Ethylbenzene	ND	0.05	mg/kg	1	1420027	05/15/14	05/15/14	EPA 8021B	
p,m-Xylene	ND	0.05	mg/kg	1	1420027	05/15/14	05/15/14	EPA 8021B	
o-Xylene	ND	0.05	mg/kg	1	1420027	05/15/14	05/15/14	EPA 8021B	
Total Xylenes	ND	0.05	mg/kg	1	1420027	05/15/14	05/15/14	EPA 8021B	
Total BTEX	ND	0.05	mg/kg	1	1420027	05/15/14	05/15/14	EPA 8021B	
Surrogate: Bromochlorobenzene		97.6 %	80-	-120	1420027	05/15/14	05/15/14	EPA 8021B	
Surrogate: 1,3-Dichlorobenzene		92.9 %	80-	-120	1420027	05/15/14	05/15/14	EPA 8021B	
Nonhalogenated Organics by 8015									
Gasoline Range Organics (C6-C10)	ND	5.00	mg/kg	1	1420027	05/15/14	05/15/14	EPA 8015D	
Diesel Range Organics (C10-C28)	ND	29.9	mg/kg	1	1420028	05/15/14	05/15/14	EPA 8015D	
Total Petroleum Hydrocarbons by 418.1									
Total Petroleum Hydrocarbons	24.0	20.0	mg/kg	1	1420032	05/15/14	05/15/14	EPA 418.1	
Cation/Anion Analysis									
Chloride	ND	9.93	mg/kg	1	1420024	05/14/14	05/14/14	EPA 300.0	

Partial or incomplete reproduction of this report is prohibited, unless approved by Envirotech, Inc.

5796 US Highway 64, Farmington, NM 87401

Ph (505) 632-0615 Fx (505) 632-1865

envirotech-inc.com

Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301

Ph (970) 259-0615 Fr (800) 362-1879

laboratory@envirotech-inc.com



Project Name:

Jaquez GC B 1A

Spike

Source

PO Box 22024 Tulsa OK, 74121-2024 Project Number: Project Manager:

Reporting

03143-0424 Jeff Blagg

16-1

%REC

Reported: 16-May-14 13:46

RPD

Volatile Organics by EPA 8021 - Quality Control

Envirotech Analytical Laboratory

Analyte .	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1420027 - Purge and Trap EPA 503	30A									
Blank (1420027-BLK1)				Prepared &	Analyzed:	: 15-May-1	1	_		_
Benzene	ND	0.05	mg/kg					-		
Toluene	ND	0.05	11							
Ethylbenzene	ND	0.05	**							
p,m-Xylene	ND	0.05	ü							
o-Xylene	ND	0.05	11							
Total Xylenes	ND	0.05	11		•					
Total BTEX	ND	0.05	"							
Surrogate: 1,3-Dichlorobenzene	50.7		ug/L	50.0		101	80-120			
Surrogate: Bromochlorobenzene	- 52.9		"	50.0		106	80-120			
Ouplicate (1420027-DUP1)	Sour	ce: P405030-	01	Prepared &	. Analyzed:	15-May-14	1			
Benzene	ND	0.05	mg/kg		ND				30	
Foluene Foluene	ND	0.05	**		ND				30	
Ethylbenzene	ND	0.05	II .		ND				30	
p,m-Xylene	ND	0.05	n		ND				30	
o-Xylene	ND	0.05	**		ND				30 ·	
Surrogate: 1,3-Dichlorobenzene	49.7		ug/L	50.0		99.5	80-120			
Surrogate: Bromochlorobenzene	52.7		"	50.0		105	80-120			
Matrix Spike (1420027-MS1)	Sour	ce: P405030-	01	Prepared &	•					
Benzene	46.9		ug/L	50.0	ND	93.8	39-150			
Гоlиепе	47.1		п	50.0	ND	94.1	46-148			
Ethylbenzene	47.1		н	50.0	ND .	94.1	32-160			
o,m-Xylene	94.4		11	100	ND	94.4	46-148			
o-Xylene	47.6 .		11	50.0	ND	95.2	46-148			
Surrogate: 1,3-Dichlorobenzene	50.7		"	50.0		101	80-120			
Surrogate: Bromochlorobenzene	54.3		"	50.0		109	80-120		•	

Partial or incomplete reproduction of this report is prohibited, unless approved by Envirotech, Inc.

5796 US Highway 64, Farmington, NM 87401

Ph (505) 632-0615 Fx (505) 632-1865

envirotech-inc.com



Project Name:

Jaquez GC B 1A

Spike

Source

PO Box 22024

Project Number:

03143-0424

Reported:

Tulsa OK, 74121-2024

Project Manager: Jeff Blagg

Reporting

16-May-14 13:46

RPD

%REC

Nonhalogenated Organics by 8015 - Quality Control

Envirotech Analytical Laboratory

Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1420027 - Purge and Trap EPA 5030A					· · · · · · · · · · · · · · · · · · ·					
Blank (1420027-BLK1)		_		Prepared &	Analyzed:	15-May-14	1			
Gasoline Range Organics (C6-C10)	ND	5.00	mg/kg							
Duplicate (1420027-DUP1)	Sourc	Source: P405030-01 Pr			Analyzed:	15-May-14	ļ			
Gasoline Range Organics (C6-C10)	ND	4.99	mg/kg		ND				30	
Matrix Spike (1420027-MS1)	Sourc	e: P405030-	01	Prepared &	Analyzed:	15-May-14	ļ			
Gasoline Range Organics (C6-C10)	0.43		mg/L	0.450	ND	95.6	75-125			

Partial or incomplete reproduction of this report is prohibited, unless approved by Envirotech, Inc.



Project Name:

Jaquez GC B 1A

Spike

Level

Source

Result

%REC

PO Box 22024

Analyte

Tulsa OK, 74121-2024

Project Number: Project Manager:

Reporting

Limit

Result

03143-0424

Jeff Blagg

Reported:

16-May-14 13:46

Notes

RPD

Limit

%REC

Limits

RPD

Nonhalogenated Organics by 8015 - Quality Control

Envirotech Analytical Laboratory

Units

Blank (1420028-BLK1)				Prepared &	Analyzed:	15-May-14	1 .						
Diesel Range Organics (C10-C28)	ND	30.0	mg/kg	•									
Duplicate (1420028-DUP1)	Sour	Source: P405030-01 P				Prepared & Analyzed: 15-May-14							
Diesel Range Orgánics (C10-C28)	ND	30.0	mg/kg		ND				30				
Matrix Spike (1420028-MS1)	Source	e: P405030-0	11	Prepared &	Analyzed:	15-May-14	Į.						

Partial or incomplete reproduction of this report is prohibited, unless approved by Envirotech, Inc.



PO Box 22024

Project Name:

Jaquez GC B 1A

Project Number:

03143-0424

16-May-14 13:46

Reported:

Tulsa OK, 74121-2024

Project Manager:

Jeff Blagg

Total Petroleum Hydrocarbons by 418.1 - Quality Control

Envirotech Analytical Laboratory

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch 1420032 - 418 Freon Extraction										
Blank (1420032-BLK1)										
Total Petroleum Hydrocarbons	ND	20.0	mg/kg						*	
Duplicate (1420032-DUP1)	Sour	e: P405030-	01	Prepared &	: Analyzed:	15-May-14	ļ			
Total Petroleum Hydrocarbons	27.9	20.0	mg/kg		24.0			15.2	30	
Matrix Spike (1420032-MS1)	Sour	ee: P405030-	01	Prepared &	: Analyzed:	15-May-14	Ļ			
Total Petroleum Hydrocarbons	1760	20.0	mg/kg	2020	24.0	86.0	80-120			

Partial or incomplete reproduction of this report is prohibited, unless approved by Envirotech, Inc.



Project Name:

Jaquez GC B 1A

PO Box 22024

Tulsa OK, 74121-2024

Project Number:

03143-0424

Reported:

Project Manager:

Jeff Blagg

16-May-14 13:46

Cation/Anion Analysis - Quality Control

Envirotech Analytical Laboratory

		Reporting		Spike	Source		%REC		RPD			
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes		
Batch 1420024 - Anion Extraction EPA 300.0												
Blank (1420024-BLK1)				Prepared &	k Analyzed:	14-May-14	4					
Chloride	ND	9.84	mg/kg						-			
LCS (1420024-BS1)				Prepared &	Analyzed:	14-May-14	4					
Chloride	486	9.93	mg/kg	497		97.9	90-110		·			
Matrix Spike (1420024-MS1)	Sou	rce: P405029-	-01	Prepared & Analyzed: 14-May-14								
Chloride	15000	9.89	mg/kg	495	14800	30.2	80-120			SPK I		
Matrix Spike Dup (1420024-MSD1)	Sou	rce: P405029-	01	Prepared &	Analyzed:	14-May-14	1					
Chloride	16200	9.90	mg/kg	495	14800	276	80-120	7.81	20	SPKI		

Partial or incomplete reproduction of this report is prohibited, unless approved by Envirotech, Inc.

5796 US Highway 64, Farmington, NM 87401

Ph (505) 632-0615 Fx (505) 632-1865

envirotech-inc.com

Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301

Ph (970) 259-0615 Fr (800) 362-1879

laboratory@envirotech-inc.com



Project Name:

Jaquez GC B 1A

PO Box 22024

Project Number:

03143-0424

Reported:

Tulsa OK, 74121-2024

Project Manager: Jeff Blagg

16-May-14 13:46

Notes and Definitions

SPK1 The spike recovery for this QC sample is outside of control limits.

DET Analyte DETECTED

ND Analyte NOT DETECTED at or above the reporting limit

NR Not Reported

dry Sample results reported on a dry weight basis

RPD Relative Percent Difference

Partial or incomplete reproduction of this report is prohibited, unless approved by Envirotech, Inc.

Page 9 of 10

CHAIN OF CUSTODY RECORD

16966

Client:	Fadas	Р	roject Name / Locatio		- f A				ANALYSIS / PARAMETERS															
BP AMERICA BLAGE Email results to: jeff cblage	e Aul.	Em S	ampler Name:						15)	(021)	(09													
Peace jeffrey @ BP. Client Phone No.:		C	JEFF BUAGE Client No.: 03143-0424					thod 80	lethod 8	thod 82	Metals	Metals	Vetals	Metals	Anion		th H/P	910-1	3.1)	出			Cool	ntact
505 - 320 - 1123 Sample No./ Identification	Sample Date	Sample Time	- 	No./Vo	olume	Pr HNO ₃	eservati HCI	ive	TPH (Method 8015)	BTEX (Method 8021)	VOC (Method 8260)	RCRA 8 Metals	Cation / Anion	RCI	TCLP with H/P	CO Table 910-1	TPH (418.1)	CHLORIDE			Sample (Sample Intact		
95 BGT 5-pt @ 5	5/14/2014		P405030-01	[XL	t 02			_	X	×	_	41)			<u> </u>	×	X			Y	Ty		
,																								
						<u> </u>											,					_		
									R	US	SH	/-	15,	ДP	•									
		_							B	u	B	Ρ:												
										P	1-/-k	E	•	7	EV	140	91	BG	7-7	2_				
										CO	nta	.ct		تنتظ	F-	to	rc. (7						
Relinquished by: (Signature) Relinquished by: (Signature)	<u> </u>			Date 5/14/14	Time	Recei	ved b	y: (S	Signature)									Da 5.	1	Time 12-43				
Relinquished by: (Signature)						Rece	ved to	ý. (S	ignati	ure)														
Sample Matrix Soil Solid ☐ Sludge ☐	Aqueous 🗆] Other[
☐ Sample(s) dropped off after	hours to see	cure drop	off area.	う e	nv And	ire	o t	e	:r	1				g,	10	<u> </u>				-				
5795 IIS Highway 6	.4 • Farminati	on. NM 87	401 • 505-632-0615 • 1								uran.	70 C	O 81	301 •	laho	raton	v@en	virote	-ch-ind					





(BP/America Production Company 1200 (Energy Court (Farmington, NM 87401 (Phone: (505) 326-9200

May 12, 2014

Loraine Gurule 17 Road 5457 Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: JAQUEZ GC B 001A

Dear Mrs. Gurule,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 13, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade rank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to mespond to this letter. If you do have any questions or concerns, please contact me at \$05-326-9214

Sincerely,

Jerry Van Riper

40 Valer

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON POWELL@STATE.NM.US

May 7, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

JAQUEZ GC B 001A API 30-045-22281 (G) Section 4 – T29N – R09W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



