State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

12060	<u>Pit, Below-Grade Tank, or</u> Proposed Alternative Method Permit or Closure Plan Ap	plication				
	Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-perm or proposed alternative method		ade tank,			
	Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank that approval of this request does not relieve the operator of liability should operations result in pollution of does approval relieve the operator of its responsibility to comply with any other applicable governmental	of surface water, grour	nd water or the			
1. Operator: BP 4	America Production Company OGRID #:778	OIL CONS. DIV	DIST. 3			
Address:20) Energy Court, Farmington, NM 87401 name:Navajo Allotted Gas Com B 1	JUL 24-2	2014			
	OCD Permit Number:					
U/L or Qtr/Qtr	HSection36Township28NRange9WCounty:	San Juan	_			
	sed Design: Latitude36.62056Longitude107.73501	NAD: □1	927 🔀 1983			
Temporary: Permanent [Lined 1	ction F, G or J of 19.15.17.11 NMAC Drilling Workover Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Inlined Liner type: Thicknessmil LLDPE HDPE PVC Other Forced Welded Factory OtherVolume:bbl Dimensio					
3.						
Below-grad	e tank: Subsection I of 19.15.17.11 NMAC Tank A					
Volume:	_45.0bbl Type of fluid:Produced water		_			
Tank Construction material:Steel						
	containment with leak detection 🗌 Visible sidewalls, liner, 6-inch lift and automatic overflow shut					
	walls and liner 🛛 Visible sidewalls only 🗌 Other _Single walled/double bottomed ckness mil 🔲 HDPE 🗌 PVC 🗍 Other					
4.	Method:					

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.



Fencing:	Subsection D of 19.15.1	7.11 NMAC	(Applies to pe	ermanent pits,	temporary pits,	and below-grade tanks)
----------	-------------------------	-----------	----------------	----------------	-----------------	------------------------

Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify_

Netting: Subsection E of 19.15.17.11 NMAC (*Applies to permanent pits and permanent open top tanks*)

Screen Netting Other_

Monthly inspections (If netting or screening is not physically feasible)

7.

5

Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

- Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.
- Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting					
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank					
Ground water is less than 50 feet below the bottom of a remotrary bit, bermanent bit, or withti-wen rund management bit, $=$	Yes 🗌 No NA				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes 🗌 No				
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes 🗌 No				
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes 🗌 No				
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes 🗌 No				
Below Grade Tanks					
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site	Yes 🗌 No				
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes 🗌 No				
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)					
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	Yes 🗌 No				

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗋 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	📋 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes 🗋 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗍 No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
<u>Permanent Pit or Multi-Well Fluid Management Pit</u>	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes 🗌 No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
 initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
^{10.} <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do	
 attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. 	
and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	cuments are
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC 	.15.17.9 NMAC
 Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

12.				
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the sattached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	documents are			
^{13.} Proposed Closure: 19.15.17.13 NMAC				
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well FI Alternative Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit			
14.	<u></u>			
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the			
15.				
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.				
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA			
 Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA			
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells				
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No			
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No			
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No			
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No			
Written confirmation of verification from the multicipanty, written approval obtained from the multicipanty Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance				

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological 	
Society; Topographic map	🗌 Yes 🗌 No
Within a 100-year floodplain. - FEMA map	Yes No
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plane by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canned Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed and be	ef.
Name (Print): Title:	·
Signature: Date:	
Signature: Date: e-mail address: Telephone:	
e-mail address: Telephone:	2014 the closure report.
e-mail address:	2014 the closure report. complete this

22. Operator Closure Certification:

.

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.					
Name (Print):Jeff Peace	Title: Area Environmental Advisor				
Signature: Joff Peace	Date:July 23, 2014				
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479				

.

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Navajo Allotted Gas Com B 1- Tank A (45 bbl)</u> <u>API No. 3004506991</u> <u>Unit Letter M, Section 1, T30N, R9W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

No notice was sent due to misunderstanding of BGT notice requirements at the time.

2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

No notice was sent due to misunderstanding of BGT notice requirements at the time.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)

- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

- 5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.All equipment associated with the BGT has been removed.
- 6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	45 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

200 C St Francis Dr. Conto Fr. MM 97505				
Santa	Fe, NM 87505			
Release Notificati	ion and Correct	ive Action		
	OPERATOR		Initial Report 🛛 🛛 Final Repo	
Name of Company: BP	Contact: Jeff Peace			
Address: 200 Energy Court, Farmington, NM 87401	Telephone No.: 505	-326-9479		
Facility Name: Navajo Allotted Gas Com B 1	Facility Type: Natu	al gas well		
Surface Owner: Tribal Mineral Owne		A D	1 No. 3004506991	
			1110. 5004500991	
	ON OF RELEAS		ine County: San Juan	
A 36 28N 9W 1,845 No		East West L		
Latitude 36.62056	Longitude 107.	73501		
	E OF RELEASE			
Type of Release: none	Volume of Release:		ime Recovered: N/A	
Source of Release: below grade tank – 45 bbl, Tank A	Date and Hour of O	ccurrence: Date	and Hour of Discovery:	
Was Immediate Notice Given?	If YES, To Whom?			
By Whom?	Date and Hour			
Vas a Watercourse Reached?		pacting the Watercours	se.	
🗌 Yes 🖾 No		_		
Describe Cause of Problem and Remedial Action Taken.* Sampling of he BGT. Soil analysis resulted in TPH, BTEX and chloride below sta			oval to ensure no soil impacts from	
Describe Area Affected and Cleanup Action Taken.* BGT was remove backfilled and compacted and is still within the active well area.	ed and the area underneat	n the BGT was sample	d. The area under the BGT was	
hereby certify that the information given above is true and complete the egulations all operators are required to report and/or file certain release bublic health or the environment. The acceptance of a C-141 report by hould their operations have failed to adequately investigate and remed or the environment. In addition, NMOCD acceptance of a C-141 report ederal, state, or local laws and/or regulations.	e notifications and perfor the NMOCD marked as liate contamination that p	n corrective actions fo 'Final Report" does no ose a threat to ground v	r releases which may endanger at relieve the operator of liability water, surface water, human health	
A ag ()	OIL	CONSERVATIO	ON DIVISION	
ignature: 96 Vare				
Printed Name: Jeff Peace Approved by Environmental Specialist:				
itle: Area Environmental Advisor	Approval Date:	Expira	tion Date:	
-mail Address: peace.jeffrey@bp.com	Conditions of Approva	ıl:	Attached	

* Attach Additional Sheets If Necessary

	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	API #:
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:	PAGE #: <u>1</u> of <u>1</u>
QUAD/UNIT: H SEC: 36 TWP:		DATE STARTED: 12/12/13 DATE FINISHED:
	ELKHORN PROD. FORMATION: MV/CHA CONTRACTOR: MBF - S. GENTRY	ENVIRONMENTAL SPECIALIST(S): JCB
REFERENCE POINT 1) 45 BGT (SW/DB) - A 2) 21 BGT (SW/DB) - B	GPS COORD.: 36.62056 X 107.73501 DISTANCE/BEA	ARING FROM W.H.: 99', S42W
3)	GPS COORD.: DISTANCE/BEA	ARING FROM W.H.:
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL 7'	ÖVM READING (ppm)
2) SAMPLEID: 21 BGT 5-pt. (2) 3) SAMPLEID:	TSAMPLE DATE: TSAMPLE DATE: TSAMPLE DATE: TSAMPLE DATE: G924 Dab ANALYSIS: 410.1/4 SAMPLE DATE: SAMPLE TIME: SAMPLE DATE: SAMPLE DATE:	89155/99215/999.0(El)
SOIL COLOR: PALE YE COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY (SLIGHTLY MOIST / MOIST) W SAMPLE TYPE: GRAB (COMPOSITE # DISCOLORATION/STAINING OBSERVED: YES (SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE	OOSE/ FIRM / DENSE / VERY DENSE HC ODOR DETECTED: YES (NO EXPLANATION - ET / SATURATED / SUPER SATURATED ANY AREAS DISPLAYING WETNESS: YES (NO EXPLANATION - O EXPLANATION -	STIFF / VERY STIFF / HARD
OTHER:		TIMATION (Cubic Yards) : <u>NA</u>
SITE SKETCH	BGT Located : off on site PLOT PLAN circle: attached OW W.H. N (45) PBGTL T.B. ~ 7' B.G. X - S.P.D. WDEPRESSION: B.G. = BELOW GRADE: B = BELOW TH. = TEST HOLE: ~= APPROX: WH. = WELL HEAD.	ICALIB. READ. = 100.1 ppm ICALIB. GAS = 100.0 ppm VO: N15113601 0 VO: ZEVH01BGT2 0 VI: Z2-006L3 0 ermit date(s): (A)06/10/10 (B) 10/23/12 0 CD Appr. date(s): (A)11/01/12(B)10/26/12 0 OVM = Organic Vapor Meter 0 0 PID Expression Premillion N A
NOTES:	ONSITE: 12/12/13	

Analytical Report Lab Order 1312643

Date Reported: 12/20/2013

Hall Environmental Analysis Laboratory, Inc.

 CLIENT:
 Blagg Engineering
 Client Sample ID: 45 BGT 5-pt @ 7'

 Project:
 NAVAJO ALLOTEED GC B#1
 Collection Date: 12/12/2013 9:15:00 AM

 Lab ID:
 1312643-002
 Matrix: SOIL
 Received Date: 12/14/2013 10:30:00 AM

 Analyses
 Result
 RL Qual Units
 DF Date Analyzed
 Batch

					5		
EPA METHOD 8015D: DIESEL RANGI	E ORGANICS					Analyst	JME
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	12/18/2013	11:35:13 PN	A 10815
Surr: DNOP	111	66-131	%REC	1	12/18/2013	11:35:13 PN	/ 10815
EPA METHOD 8015D: GASOLINE RA	NGE				•	Analyst	NSB
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	12/18/2013 3	3:57:26 PM	10837
Surr: BFB	93.0	74.5-129	%REC	1	12/18/2013 3	8:57:26 PM	10837
EPA METHOD 8021B: VOLATILES						Analyst:	NSB
Benzene	ND	0.047	mg/Kg	1	12/18/2013 3	3:57:26 PM	10837
Toluene	ND	0.047	mg/Kg	1	12/18/2013 3	8:57:26 PM	10837
Ethylbenzene	ND	0.047	mg/Kg	1	12/18/2013 3	3:57:26 PM	10837
Xylenes, Total	ND	0.093	mg/Kg	1	12/18/2013 3	8:57:26 PM	10837
Surr: 4-Bromofluorobenzene	105	80-120	%REC	1	12/18/2013 3	8:57:26 PM	10837
EPA METHOD 300.0: ANIONS						Analyst:	JRR
Chloride	ND	30	mg/Kg	20	12/18/2013 1	2:54:59 PN	1 10863
EPA METHOD 418.1: TPH						Analyst:	JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	12/18/2013		10802

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method Blank
	E	Value above quantitation range	Н	Holding times for preparation or analysis exceeded
	J	Analyte detected below quantitation limits	ND	Not Detected at the Reporting Limit Page 2 of 6
	0	RSD is greater than RSDlimit	Р	Sample pH greater than 2 for VOA and TOC only.
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit
	S	Spike Recovery outside accepted recovery limits		

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

WO#: 1312643

20-Dec-13

Client: Blagg Engineering Project: NAVAIO ALL OTEED GC B#1

Project:	NAVA	JO ALLOTEE	ED GC	C B#1							
Sample ID	MB-10802	SampTy	pe: ME	3LK	Tes	tCode: El	PA Method	418.1: TPH			
Client ID:	PBS	Batch I	ID: 10	802	F	RunNo: 1	5588				
Prep Date:	12/16/2013	Analysis Da	te: 12	2/18/2013	5	eqNo: 4	48814	Units: mg/H	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hyd	rocarbons, TR	ND	20								
Sample ID	LCS-10802	SampTy	pe: LC	S	Tes	tCode: El	PA Method	418.1: TPH			
Client ID:	LCSS	Batch I	D: 10	802	F	unNo: 1	5588				
Prep Date:	12/16/2013	Analysis Dat	te: 12	2/18/2013	S	eqNo: 4	48821	Units: mg/K	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hyd	rocarbons, TR	95	20	100.0	0	95.3	80	120			
Sample ID	LCSD-10802	SampTyp	pe: LC	SD	Tes	Code: El	PA Method	418.1: TPH		<u> </u>	
Client ID:	LCSS02	Batch I	D: 10	802	R	unNo: 1	5588				
Prep Date:	12/16/2013	Analysis Dat	te: 12	2/18/2013	S	eqNo: 4	48826	Units: mg/K	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hyd	rocarbons, TR	96	20	100.0	0	96.5	80	120	1.27	20	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 3 of 6

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering

_

Project: NAVAJO ALLOTEED GC B#1

Sample ID MB-10815	SampType: MBLK			TestCode: EPA Method 8015D: Diesel Range Organics						
Client ID: PBS	Batch ID: 10815			RunNo: 15536						
Prep Date: 12/16/2013	Analysis [Date: 12	2/17/2013	5	SeqNo: 4	48012	Units: mg/K	٢g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
					a- <i>i</i>	00	101			
Surr: DNOP	8.5		10.00		85.1	66	131			
Surr: DNOP Sample ID LCS-10815		Гуре: LC		Tes			8015D: Diese	el Range C	Drganics	
	Samp1	Гуре: LC h ID: 10	s			PA Method		el Range (Drganics	
Sample ID LCS-10815	Samp1	h ID: 10	s	F	tCode: EF	PA Method 5536		5	Drganics	
Sample ID LCS-10815 Client ID: LCSS	Samp1 Batcl	h ID: 10	S 815 2/17/2013	F	tCode: EF	PA Method 5536	8015D: Diese	5	Drganics RPDLimit	Qual
Sample ID LCS-10815 Client ID: LCSS Prep Date: 12/16/2013	Samp] Batcl Analysis [h ID: 10 Date: 12	S 815 2/17/2013	٦ S	tCode: EF RunNo: 1 SeqNo: 44	PA Method 5536 48013	8015D: Diese Units: mg/K	(g	5	Qual

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Е Value above quantitation range
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits S
- В Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2 for VOA and TOC only. Р
- RL **Reporting Detection Limit**

Page 4 of 6

WO#: 1312643 20-Dec-13

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

WO#:	1312643
WOT.	1314043

				20-Del-1
	Engineering JO ALLOTEED GC B#1			
Sample ID MB-10837	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Range	
Client ID: PBS	Batch ID: 10837	RunNo: 15586		
Prep Date: 12/17/2013	Analysis Date: 12/18/2013	SeqNo: 449046	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit	Qual
Gasoline Range Organics (GRO) Surr: BFB	ND 5.0 920 1000	92.0 74.5	129	
Sample ID LCS-10837	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Range	
Client ID: LCSS	Batch ID: 10837	RunNo: 15586	,	
Prep Date: 12/17/2013	Analysis Date: 12/18/2013	SeqNo: 449047	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit	Qual
Gasoline Range Organics (GRO) Surr: BFB	27 5.0 25.00 980 1000	0 107 74.5 98.2 74.5	126 129	
Sample ID MB-10837 MK	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Range	
Client ID: PBS	Batch ID: R15586	RunNo: 15586		
Prep Date:	Analysis Date: 12/18/2013	SeqNo: 449123	Units: %REC	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit	Qual
Surr: BFB	920 1000	92.0 74.5	129	
Sample ID LCS-10837 MK	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Range	
Client ID: LCSS	Batch ID: R15586	RunNo: 15586		
Prep Date:	Analysis Date: 12/18/2013	SeqNo: 449124	Units: %REC	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit	Qual
Surr: BFB	980 1000	98.2 74.5	129	

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Е Value above quantitation range
- Analyte detected below quantitation limits 1
- RSD is greater than RSDlimit Ο
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2 for VOA and TOC only. Р
- RL Reporting Detection Limit

Page 5 of 6

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#: 1312643

20-Dec-13

Client: Blagg Engineering Project: NAVAJO ALLOTEED GC B#1

Project: NAVAJ	O ALLOTEED GC	B#1							
Sample ID MB-10837 MK	SampType: MB	LK	Tes	tCode: EF	PA Method	8021B: Volat	iles		
Client ID: PBS	Batch ID: R15	586	F	RunNo: 18	5586				
Prep Date:	Analysis Date: 12/	/18/2013	S	SeqNo: 44	49140	Units: %RE	с		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	1.0	1.000		105	80	120			
Sample ID LCS-10837 MK	SampType: LCS	3	Test	tCode: EF	PA Method	8021B: Volat	iles		· · ·
Client ID: LCSS	Batch ID: R15	586	R	RunNo: 1	5586				
Prep Date:	Analysis Date: 12/	18/2013	S	eqNo: 44	19141	Units: %RE	С		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	1.1	1.000		111	80	120			
Sample ID MB-10837	SampType: MBI	 LK	Test	tCode: EF	PA Method	8021B: Volat	iles		
Client ID: PBS	Batch ID: 108	37	R	unNo: 15	5586				
Prep Date: 12/17/2013	Analysis Date: 12/	18/2013	S	eqNo: 44	49145	Units: mg/K	g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND 0.050								
Toluene	ND 0.050								
Ethylbenzene	ND 0.050								
Xylenes, Total	ND 0.10								
Surr: 4-Bromofluorobenzene	1.0	1.000		105	80	120			
Sample ID LCS-10837	SampType: LCS		Test	Code: EF	A Method	8021B: Volat	iles		
Client ID: LCSS	Batch ID: 108	37	R	unNo: 15	5586				
Prep Date: 12/17/2013	Analysis Date: 12/	18/2013	S	eqNo: 44	9146	Units: mg/K	g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.0 0.050	1.000	0	104	80	120			
Toluene	1.0 0.050	1.000	0	102	80	120			
Ethylbenzene	1.0 0.050	1.000	0	104	80	120			
Xylenes, Total	3.1 0.10	3.000	0	102	80	120			
Surr: 4-Bromofluorobenzene	1.1	1.000		111	80	120			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.

RL Reporting Detection Limit

Page 6 of 6

e pH greater than 2 for VOA and the pH greater than 2 for VOA and the time the phase of the phas

ENVIRONMENTAL ANALYSIS LABORATORY

Tuu: Environmental Anatysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Nork Order Number: 1312643		RcptNo:	1
Received by/date: AF 12/14/10		·		
Logged By: Anne Thorne 12/	/14/2013 10:30:00 AM	anne Hr		3
Completed By: Anne Thorne 12/	/16/2013	Arne Hr. Arne Hr.		
Reviewed By: IC 12	117/13	Cana Ji-		
Chain of Custody	/··/	······································		
1. Custody seals intact on sample bottles?	Yes	No 🗌	Not Present 🗹	
2, Is Chain of Custody complete?	Yes 🔽	No 🗌	Not Present	-
3. How was the sample delivered?	Courier			
Log In				
4. Was an attempt made to cool the samples?	Yes 🔽] No 🗌	na 🗀	
5. Were all samples received at a temperature of	>0° C to 6.0°C Yes 🗹	No 🗍	na 🗆	
6. Sample(s) in proper container(s)?	Yes 🔽] No 🗌		
7 Sufficient sample volume for indicated test(s)?	Yes 🔽	No 🗌		
8. Are samples (except VOA and ONG) properly pr	reserved? Yes 🗹	No 🗋		
9. Was preservative added to bottles?	Yes	No 🗹	NA 🗌	
10, VOA vials have zero headspace?	Yes	No 🗌	No VOA Vials 🗹	
11. Were any sample containers received broken?	Yes	No 🗹	# of preserved	
12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes 🗹	No 🗌	bottles checked for pH:	r >12 unless noted
13. Are matrices correctly identified on Chain of Cus	itody? Yes 🗹	No 🗔	Adjusted?	
14. Is it clear what analyses were requested?	Yes 🗹	No 🗌		
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes 🗹	No 🗌	Checked by:	
· · · · ·				
Special Handling (if applicable)				
16. Was client notified of all discrepancies with this of	order? Yes 🗌	No 🗌	NA 🗹	-
Person Notified:	Date			
By Whom:	Via: 🗌 eMail	Phone 🗌 Fax	In Person	
Regarding:		<u></u>		

17. Additional remarks:

18. Cooler Information

Client Instructions:

Ī	Cooler No	Temp °C	Condition	Seal Intact	Seal No	Seal Date	Signed By
ĺ	1	1.0	Good	Yes			

Chain-of-Custody Record	Turn-Around Time:	
Client: BLAGG ENGLIEERNG INC.	Standard	HALL ENVIRONMENTAL
BP AMERICA	Project Name: NAVAJO ALLOTTES	www.hallenvironmental.com
Mailing Address: R.O. Box 87	<u>GC B #1</u>	4901 Hawkins NE - Albuquerque, NM 87109
BLOOMFIELD, NM 87413	Project #:	Tel. 505-345-3975 Fax 505-345-4107
Phone #: 505-632-U99		Analysis Request
email or Fax#:	Project Manager:	Later (1975) (19
QA/QC Package:	J- BLAGS	(802) (80) (802) (
Standard D Level 4 (Full Validatio	n)	L (Gas (802) (1 (Gas (1 (Gas (802) (1 (Gas (1))))))))))))))))))))))))))))))))))))
Accreditation	Sampler: J-BLA66 Onlice No. 20 Yes No. 20 No.	
EDD (Type)	Sangle Jemperature: 100 //	
Date Time Matrix Sample Request I	Container Type and # Preservative Type 73/2//43	BTEX + MTBE + TMBs (8021) BTEX + MTBE + TPH (Gas only) TPH 8015B (GRO / DRO / MTED) TPH (Method 418.1) EDB (Method 504.1) PAH's (8310 or 8270 SIMS) PAH's (8310 or 8270 SIMS) RCRA 8 Metals Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄) RCRA 8 Metals Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄) 8081 Pesticides / 8082 PCB's 8260B (VOA) 8270 (Semi-VOA) CULOR (DE
12/2/13 0121 3012 21 BGT		
13 0915 SOIL 5-PE @ 1 12/12/13 0915 SOIL 5-PE C 7	11 11	
12/13 0415 DOIL 5-PE P. 7		
·		
		┼─┼╍┤╶╃╾┼╴┝╼╃╍╎╼┼╶┼╶┽╺╂╺╋╴┼╶┼╶┼┝
		┼┼┽┥┽┼╴┼╌╎╶┥╴┼╶┼╸┼╶┼╴┼╴┾
		┼╌┼╌┥╞╾┾╴╞╼┾╴┼╶┤╌┥╾┢╴┾╴┾╼┿
Date: Time: Relinquished by: 12/13/13 1126 AM Blogy	Received by: Date Time $\frac{12}{13}$, $\frac{12}{13}$ 1126	Remarks: BILL BP DATHER J PEVLI OI BUTZ
Date: Time: Remonstrated by:	Received by Date Time	- PATKET: ZEVHOLBGTZ Controt: JEFF REACE

If necessary, samples submitted to Hall Environmental may be subcontracted to other accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report.

