District 1
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application										
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method										
5-101 (S Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the										
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.										
Operator: BP America Production CompanyOGRID #:778										
Address: _200 Energy Court, Farmington, NM 87401 OIL CONS. DIV DIST. 3										
Facility or well name:Pritchard B 2										
API Number:3004510165 OCD Permit Number:										
U/L or Qtr/QtrB Section34 Township31N Range9W County:San Juan										
Center of Proposed Design: Latitude36.85851 Longitude107.76575 NAD: ☐1927 ☒ 1983										
Surface Owner: X Federal X State Private Tribal Trust or Indian Allotment										
2. Pit: Subsection F, G or J of 19:15.17.11 NMAC Temporary:										
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D										
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A										
Volume: 95.0 bbl Type of fluid: Produced water										
Tank Construction material: Steel										
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off										
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/single bottomed										
Liner type: Thickness mil										

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.1 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school	, hospital,								
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet									
Alternate. Please specify									
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other									
Monthly inspections (If netting or screening is not physically feasible)									
7. Signs: Subsection C of 19.15.17.11 NMAC ☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers									
Signed in compliance with 19.15.16.8 NMAC									
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.									
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source								
General siting									
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA								
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No								
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No								
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No								
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No								
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map									
Below Grade Tanks									
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)									
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No								

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No						
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image							
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Temporary Pit Non-low chloride drilling fluid	,						
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site							
	Yes No						
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No						
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site							
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Permanent Pit or Multi-Well Fluid Management Pit							
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No						
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No						
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of							
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.							
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC							
Préviously Approved Design (attach copy of design) API Number: or Permit Number:							
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do	cuments are						
attached. □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC □ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	.15.17.9 NMAC						
Previously Approved Design (attach copy of design) API Number: or Permit Number:							

12.	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
 Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization 	
 ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	
13. Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial	'luid Management Pit
Alternative Closure Method	
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	,
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sout provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa ake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. JS Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal houndaries or within a defined municipal fresh water wall field covered under a municipal ordinance	

Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain.	I NMAC 5.17.11 NMAC
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain. - FEMA map 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	Yes No Yes No N
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain. - FEMA map 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plans by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	Yes No Yes No N
Within a 100-year floodplain. FEMA map 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plant by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	Nes No Nes No Nes indicate, NMAC NMAC NMAC
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15 Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	n. Please indicate, I NMAC 5.17.11 NMAC
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15 Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	I NMAC 5.17.11 NMAC
Operator Appreciation Certification.	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.	
Name (Print): Title:	
Signature: Date:	
e-mail address:	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
OCD Representative Signature: Approval Date: 8/5/2	2014
Title: Comphance Office OCD Permit Number:	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting th The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not co section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
•	
☐ Closure Completion Date:5/9/2014	
Closure Completion Date:5/9/2014	o systems only)

	· · · · · · · · · · · · · · · · · · ·
Operator Closure Certification:	
	nd attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and omplies with all applicable closure requirements and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: If Peace	Date:July 18, 2014
e-mail address:peace.jeffrey@bp	p.com Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Pritchard B 2 API No. 3004510165 Unit Letter B, Section 34, T31N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

- 5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.
 - All equipment associated with the BGT has been removed.
- 6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	160

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and BTEX, TPH and chloride were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

						OPERA'	ГOR		☐ Initi	al Report	\boxtimes	Final Report
Name of Company: BP						Contact: Jeff Peace						
		Court, Farmi	ngton, N	M 87401		Telephone No.: 505-326-9479						
Facility Na	ne: Pritch	ard B 2				Facility Typ	e: Natural gas v	vell				
Surface Ow	ner: Feder	al		Mineral (Owner: I	Federal			API No	. 30045101	65	
				LOC	ATION	OF RE	LEASE					
Unit Letter B	Section 34	Township 31N	Range 9W	Feet from the 1,180		North/South Line Feet from the East/West Line County: San Juan					1	
, , , , , , , , ,	Latitude36.85851Longitude107.76575											
				NAT	URE	OF REL	EASE	,				
Type of Rele							Release: N/A			Recovered: N		
Source of Re	lease: belov	w grade tank –	95 bbl			Date and I N/A	Iour of Occurrenc	e:	Date and	Hour of Dis	covery:	: N/A
Was Immedi	ate Notice (Yes [No Not R	equired	If YES, To	Whom?					
By Whom?						Date and I						
Was a Watercourse Reached? ☐ Yes ☑ No If YES, Volume Impacting the Watercourse.												
If a Watercou	irse was Im	pacted, Descri	be Fully.*	,		.1	1					
Describe Cause of Problem and Remedial Action Taken.* Sampling of the soil beneath the BGT was done during removal to ensure no soil impacts from the BGT. Soil analysis resulted in TPH, BTEX and chlorides below standards. Analysis results are attached.									pacts from			
Describe Are backfilled and	a Affected a	and Cleanup A	Action Tak within the a	en.* BGT was re active well area.	moved a	nd the area u	nderneath the BG	T was s	ampled. Th	ne excavated	area w	/as
		i										
regulations al public health should their of or the environ	I operators or the envir perations h nment. In a	are required to ronment. The ave failed to a	report ar acceptanc dequately CD accep	d/or file certain ree of a C-141 repo investigate and r	elease no ort by the emediate	otifications are NMOCD me contaminati	knowledge and und perform correct arked as "Final Roon that pose a three the operator of roon the contract of the operator of roon that pose a three the operator of roon that pose a three the operator of roon that pose a three operator of roon that pose and under the p	tive acti eport" d eat to gr	ions for rele oes not reli ound water	eases which a eve the opera , surface was	may en ator of er, hur	danger liability nan health
Signature: OIL CONSERVATION DIVISION												
	Approved by Environmental Specialist:											
Title: Area E	nvironment	al Advisor			A	Approval Dat	e:		Expiration I	Date:		
E-mail Addre	ss: peace.je	effrey@bp.com	n			Conditions of	Approval:			Attached		ļ
Date: July 1	8, 2014	,	Phone: 50	5-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, E	NGINEERING, INC BLOOMFIELD, NM 05) 632-1199		API #: 3004510165 TANK ID (if applicble): A & B					
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OT	HER:	PAGE#: 1 of 1					
1/4-1/4/FOOTAGE: 1,180'N / 1,85	31N RNG: 9W PM	NM CNTY: SJ	FEE / INDIAN	DATE STARTED: 05/01/14 DATE FINISHED: ENVIRONMENTAL SPECIALIST(S): JCB					
REFERENCE POINT 1) 95 BGT (SW/DB) 2) 3)	WELL HEAD (W.H.) GPS GPS COORD.: 3	s coord.: 36.85872 6.85851 X 107.76575	2 X 107.76546 DISTANCE/BEA DISTANCE/BEA DISTANCE/BEA	RING FROM W.H.:					
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # 0	OR LAB USED: HALL	<u> </u>	OVM READING (ppm)					
 SAMPLE ID: 95 BGT 5-pt. (SAMPLE ID: 3) SAMPLE ID: 4 SAMPLE ID: 4 	SAMPLE DATE: SAMPLE DATE:	SAMPLE TIME: L	AB ANALYSIS:	` '					
SOIL COLOR: DARK YEL COHESION (ALL OTHERS): NON COHESIVE (SLIGHTLY	SOIL DESCRIPTION: SOIL TYPE: SAND / SILTY SAND SILTY CLAY / CLAY / GRAVEL / OTHER SOIL COLOR: DARK YELLOWISH ORANGE COHESION (ALL OTHERS): NON COHESIVE SUIGHTLY COHESIVE CHESIVE / HIGHLY COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD CONSISTENCY (NON COHESIVE SOILS): LOOSE FIRM / DENSE / VERY DENS								
MOISTURE: DRY (SLIGHTLY MOIST) MOIST / W SAMPLE TYPE: GRAB (COMPOSITE) # DISCOLORATION/STAINING OBSERVED: YES N	OF PTS 5	ANY AREAS DISPLAYING WETNESS	: YES NO EXPLAN	NATION -					
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: BGT SET ON PVC LINER. SAM	DAND/OR OCCURRED: YES NO EXPL YES NO EXPLANATION - T-BLOX	LANATION:CK LIFT TO BE SET ATOP BGT	POSITION.	,					
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <50' N		ft. X <u>NA</u> ft. NEAREST SURFACE WATER:		TIMATION (Cubic Yards) : NA					
SITE SKETCH STEEL CONATINMENT RING 300 BBL	BGT Located: off on sit		OVM	CALIB. READ. = 51.9 ppm CALIB. GAS = 100 ppm CALIB. GAS = 05/01/14					
PROD. TANK PBGTL T.B. ~ 6' B.G. WOODEN R.W. BERM	SOUND WALLS COMPRESSO SEPARATOR	DR	<u>W</u> P P P P	MISCELL. NOTES WO: N15445971 O#: K: ZEVH01BGT2 J#: Z2-006Q0 ermit date(s): 06/14/10 CD Appr. date(s): 03/24/14 OVM = Organic Vapor Meter ppm = parts per million A BGT Sidewalls Visible Y/ N					
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGLE	OW-GRADE TANK LOCATION; SPD = SAMPLE	BELOW; T.H. = TEST HOLE; ~ = APPROX.; W. POINT DESIGNATION; R.W. = RETAINING W	- S.P.D. (H. = WELL HEAD; /ALL; NA - NOT	BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N Magnetic declination: 10° E					
NOTES:		ONSITE: 05/01	111						

revised: 11/26/13

Analytical Report

Lab Order 1405107

Date Reported: 5/9/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT 5-pt @ 6'

Project: Pritchard B 2

Collection Date: 5/1/2014 2:55:00 PM

Lab ID: 1405107-001

Matrix: SOIL

Received Date: 5/3/2014 10:20:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	E ORGANICS				Analys	t: BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	5/6/2014 4:49:34 PM	12995
Surr: DNOP	87.9	57.9-140	%REC	1	5/6/2014 4:49:34 PM	12995
EPA METHOD 8015D: GASOLINE RA	NGE				Analyst	t: NSB
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	5/7/2014 10:41:47 PM	12999
Surr: BFB	88.2	74.5-129	%REC	1	5/7/2014 10:41:47 PM	12999
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.047	mg/Kg	1	5/7/2014 10:41:47 PM	12999
Toluene	ND	0.047	mg/Kg	1	5/7/2014 10:41:47 PM	12999
Ethylbenzene	ND	0.047	mg/Kg	1	5/7/2014 10:41:47 PM	12999
Xylenes, Total	ND	0.094	mg/Kg	1	5/7/2014 10:41:47 PM	12999
Surr: 4-Bromofluorobenzene	105	80-120	%REC	1	5/7/2014 10:41:47 PM	12999
EPA METHOD 300.0: ANIONS					Analyst	:: JRR
Chloride	160	30	mg/Kg	20	5/7/2014 2:42:13 PM	13053
EPA METHOD 418.1: TPH					Analyst	:: BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	5/6/2014	12981

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDImit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1405107 09-May-14

Client:

Blagg Engineering

Project:

Pritchard B 2

Sample ID MB-13053

Sample ID LCS-13053

LCSS

5/7/2014

5/7/2014

SampType: MBLK

TestCode: EPA Method 300.0: Anions

LowLimit

Client ID: PBS Batch ID: 13053

RunNo: 18482

SeqNo: 533533

Units: mg/Kg

Analyte

Prep Date:

Client ID:

Prep Date:

Analysis Date: 5/7/2014

%REC

HighLimit

%RPD **RPDLimit**

Qual

Chloride

ND

SampType: LCS

Batch ID: 13053

Analysis Date: 5/7/2014

PQL 1.5

TestCode: EPA Method 300.0: Anions

RunNo: 18482

SeqNo: 533534

LowLimit

Units: mg/Kg HighLimit

%RPD

Analyte

Result

Result

SPK value SPK Ref Val **PQL**

1.5

SPK value SPK Ref Val

%REC 91.7

110

RPDLimit Qual

Chloride

14

15.00

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range E

Analyte detected below quantitation limits

RSD is greater than RSDlimit O

RPD outside accepted recovery limits R

Spike Recovery outside accepted recovery limits S

В Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Η

ND Not Detected at the Reporting Limit

Sample pH greater than 2.

RL Reporting Detection Limit Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1405107

09-May-14

Client:

Blagg Engineering

Project:

Analyte

Analyte

Pritchard B 2

Sample ID MB-12981

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID: PBS Batch ID: 12981

RunNo: 18411

Prep Date: 5/2/2014 Analysis Date: 5/6/2014

Result

SeqNo: 531748

Units: mg/Kg

HighLimit

%RPD

RPDLimit

Qual

Petroleum Hydrocarbons, TR

Sample iD LCS-12981

ND 20

TestCode: EPA Method 418.1: TPH

SPK value SPK Ref Val %REC LowLimit

0

LCSS Client ID:

SampType: LCS Batch ID: 12981

RunNo: 18411

Prep Date: 5/2/2014

PQL

Units: mg/Kg

Analysis Date: 5/6/2014

SeqNo: 531749 SPK value SPK Ref Val %REC

HighLimit

Qual

Petroleum Hydrocarbons, TR

100

100.0

104

80 120 %RPD **RPDLimit**

Sample ID LCSD-12981

Client ID: LCSS02

Result

SampType: LCSD

PQL

20

TestCode: EPA Method 418.1: TPH

LowLimit

Prep Date: 5/2/2014

Batch ID: 12981

Result

99

RunNo: 18411 SeqNo: 531751

Units: mg/Kg

Analysis Date: 5/6/2014 PQL

20

SPK value SPK Ref Val

%REC LowLimit

%RPD HighLimit 120

RPDLimit Qual

20

Analyte Petroleum Hydrocarbons, TR

100.0

0

98.6

80

5.72

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range E
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0 RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2. Reporting Detection Limit RL
- Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

44

3.9

10

50.00

5.000

WO#:

145

140

1405107

09-May-14

Client:

Blagg Engineering

Project:

Diesel Range Organics (DRO)

Surr: DNOP

Pritchard B 2

Sample ID MB-12995	SampType: MI	TestCode: EPA Method 8015D: Diesel Range Organics					Organics		
Client ID: PBS	Batch ID: 12	995	F	RunNo: 1	8374				
Prep Date: 5/5/2014	Analysis Date: 5	/5/2014	S	SeqNo: 5	30743	Units: mg/k	(g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND 10					***			
Surr: DNOP	8.2	10.00		81.9	57.9	140			
Sample ID LCS-12995	SampType: LC	s	Test	Code: EF	PA Method	8015D: Dies	el Range (Organics	
Client ID: LCSS	Batch ID: 12	995	R	lunNo: 1 8	8374				
Prep Date: 5/5/2014	Analysis Date: 5/	5/2014	S	eqNo: 5	30744	Units: mg/K	(g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HiahLimit	%RPD	RPDLimit	Qual

88.0

78.0

60.8

57.9

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1405107

09-May-14

Client:

Blagg Engineering

Project:

Pritchard B 2

Sample ID	MB-12999	MK
Client ID:	PBS	

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Batch ID: R18443

RunNo: 18443

Prep Date:

Analysis Date: 5/6/2014

SeqNo: 532561

Units: %REC

129

HighLimit

Analyte

Result **PQL** SPK value SPK Ref Val %REC

LowLimit 88.4 74.5 %RPD

RPDLimit Qual

Surr: BFB 880 1000

TestCode: EPA Method 8015D: Gasoline Range

Sample ID LCS-12999 MK

LCSS

SampType: LCS Batch ID: R18443

PQL

RunNo: 18443

Client ID: Prep Date:

Analysis Date: 5/6/2014

SeqNo: 532562

Units: %REC

129

Analyte Surr: BFB

Prep Date:

Result 990

Result

ND

880

23

990

SPK value SPK Ref Val 1000

%REC LowLimit 98.5

HighLimit 74.5

%RPD

RPDLimit

Qual

Sample ID MB-12999

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID: **PBS**

Batch ID: 12999

Analysis Date: 5/6/2014

RunNo: 18443

%REC

Units: mg/Kg

HighLimit

Analyte Gasoline Range Organics (GRO)

5/5/2014

5.0

PQL

1000

88.4

SeqNo: 532566

74.5

LowLimit

%RPD **RPDLimit** Qual

Surr: BFB Sample ID LCS-12999

SampType: LCS

SPK value SPK Ref Val

TestCode: EPA Method 8015D: Gasoline Range

Client ID: Prep Date:

LCSS

5/5/2014

Batch ID: 12999

RunNo: 18443

Units: mg/Kg

129

Analyte

Analysis Date: 5/6/2014 Result

SPK value SPK Ref Val

SeqNo: 532567 %REC

LowLimit 71.7

HighLimit 134

%RPD **RPDLimit** Qual

Surr: BFB

Gasoline Range Organics (GRO)

PQL 5.0 25.00

1000

91.0 98.5

74.5

129

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits j
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded Н Not Detected at the Reporting Limit
- Sample pH greater than 2.

ND

Reporting Detection Limit

Page 5 of 6

	·				
		•			
			,		
· ·					
	·				

Hall Environmental Analysis Laboratory, Inc.

1.1

1.000

WO#:

1405107

09-May-14

Client:

Blagg Engineering

Project:

Surr: 4-Bromofluorobenzene

Pritchard B 2

Sample ID MB-12999	SampType: MBLK TestCode: EPA Method 8021B: Volatiles									
Client ID: PBS	Batch	Batch ID: 12999 RunNo: 18443								
Prep Date: 5/5/2014	Analysis Da	ate: 5 /	6/2014	SeqNo: 532595			Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		105	80	120			
Sample ID LCS-12999	SampTy	pe: LC	S	Tes	tCode: El	PA Method	8021B: Volat	tiles		
Client ID: LCSS	Batch	ID: 12	999	F	RunNo: 1	8443				
Prep Date: 5/5/2014	Analysis Da	ate: 5/	6/2014	SeqNo: 532596			Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	114	80	120			
Toluene	1.1	0.050	1.000	0	107	80	120			
Ethylbenzene	1.1	0.050	1.000	0	107	80	120			
Xylenes, Total	3.1	0.10	3.000	0	105	80	120			
,										

113

80

120

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6

HALL ENVIRONMENTAL ANALYSIS LABORATORY

Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG	Work Order Number	: 1405	107		RcptN	RcptNo: 1						
Received by/date:	05/02/14											
Logged By: Lindsay Mangin	5/3/2014 10:20:00 AM			Judy Hope)							
Completed By: Lindsay Mangin	5/5/2014 7:33:09 AM			Sincher Harris)							
Reviewed By:	05/05/14			0 500								
Chain of Custody	0 100/12											
1. Custody seals intact on sample bottles?		Yes		No 🗔	Not Present ⊻	ii.						
2. Is Chain of Custody complete?		Yes		No 🗔	Not Present							
3. How was the sample delivered?		Cour										
Log In												
4. Was an attempt made to cool the sample	es?	Yes	V	No	NA							
5. Were all samples received at a temperate	ure of >0° C to 6.0°C	Yes	∀	No 🎞	NA 🗀							
6. Sample(s) in proper container(s)?		Yes	V	No 🗌								
7. Sufficient sample volume for indicated tes	st(s)?	Yes	¥	No 🗔								
8. Are samples (except VOA and ONG) pro		Yes	V	No 🗔								
9. Was preservative added to bottles?		Yes	i. i	No 🗸	NA							
10.VOA vials have zero headspace?		Yes		No !	No VOA Vials .✔							
11. Were any sample containers received bro	oken?	Yes		No 💉	# of preserved bottles checked							
12.Does paperwork match bottle labels?		Yes	Z	No 📋	for pH:							
(Note discrepancies on chain of custody)			r 120	ر سار ا	(<2 Adjusted?	or >12 unless noted						
3. Are matrices correctly identified on Chain			⊻ ! : 31	No 🗔	Adjusted							
4. Is it clear what analyses were requested?				No []	Checked by:							
15. Were all holding times able to be met? (If no, notify customer for authorization.)		Yes	 V	No :	i							
pecial Handling (if applicable)												
6. Was client notified of all discrepancies with	th this order?	Yes	li	No []	NA 😾							
Person Notified:	Date:	*********										
By Whom:	Via:]] eMa	I []	Phone 📋 Fax	n Person	* *						
Regarding:			CONTRACTOR CONTRACTOR		THE RESERVE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TW	:						
Client Instructions:												
17. Additional remarks:												
8. Cooler Information												
		Seal Da	le	Signed By								
1 1.0 Good	'es		i	រ								

	BP America			Standard]		_					ENT		_			
				Project Name:															
Mailing Address: P.O. Box 87		Pritchard B 2				www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109													
		Bloomfie	eld, NM 87413	Project #:				Tel. 505-345-3975 Fax 505-345-4107											
Phone #: (505)320-1183						7.A.													
email or Fax	#:			Project Mana	iger:													T	
QA/QC Package: Standard □ Level 4 (Full Validation)			<u> </u> 	Jeff Blagg				Q											
				Sampler:	Jeff Blagg				(DRO)			1						=	
□ EDD (Typ	oe)			On Ice:	XYes .	□No			(GRO									ō	
			<u> </u>	Sample Tem	perature: /	6	\mathfrak{S}		9)									\ <u>\</u>	
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	J HEAL NO.	BTEX (8021)		TPH 8015B	TPH 418.1							Chloride	Air Bubbles (Y or N)	
05/01/2014	14:55	Soil	95 BGT 5-pt @ 6'	1x 4oz	cool	-001	×		x	x		1					x	1	
				 							1	1	 		+	_		+	
		 		<u> </u>						_	_	1	\dagger			-	┪	+-	
		_						-			\dashv		╁					+-	
		 		 					-	_	╅		 		-+			+-	
		+	<u> </u>					\vdash		\dashv	\dashv	+-	┼	-	-+	\dashv		+	
	·	-											╁—	-				+	
<u></u>		-		·				\vdash	\dashv				-		-+			+-	
								\vdash		-	+	+	├		-+		+	+	
								-+		-+	-		-			\dashv	-}-	+-	
		 						 					┼		-+	\dashv		+-	
											-	+-	├			-+		+-	
Date:	Time:	Relinguish	ed hv:	Received by:		Date Time	Rer	narke	· Ri	II RD			ــــــــــــــــــــــــــــــــــــــ						
12/2014 Date:	SIS	Relinquished by: Relinquished by:		Christophaesa 5/2/14 815 Regeived by: Date Time			Pay BP	Remarks: Bill BP Paykey: ZEVH01BGT2 BP Contact: Jeff Peace Please copy results to: peace.jeffrey@bp.com											
5/2/14	1644	Phri	tu lace	ted to other accredited laboratories. This serves as notice of this possible															





IBP:America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

April 7, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: PRITCHARD B 002

API#: 3004510165

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about April 29, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper Surface Land Negotiator

92 VarRen

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON POWELL @STATE.NM.US

April 10, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

PRITCHARD B 002 API 30-045-10165 (G) Section 34 – T31N – R09W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

If leave

(505) 326-9479



